

The Complexity Class NP and NP-Completeness

valentinpi

15. Dezember 2020 (neueste Version)

Proseminar Theoretische Informatik WiSe 2020-21

Institut für Informatik

Freie Universität Berlin

Remark

The *nondeterministic* definition of the Turing machine mainly differs in the state transitioning function

$$\delta: Q \times \Gamma \rightarrow \mathcal{P}(Q \times \Gamma \times \{ L, N, R \}).$$

Remark

The *nondeterministic* definition of the Turing machine mainly differs in the state transitioning function

$$\delta: Q \times \Gamma \rightarrow \mathcal{P}(Q \times \Gamma \times \{ L, N, R \}).$$

Definition

In analogy to the class TIME, the class *NTIME* of $f: \mathbb{N} \rightarrow \mathbb{R}^+$ is defined as:

$$\text{NTIME}(f(n)) := \{ L \mid \text{There is a nondeterministic TM that decides } L \text{ in } \mathcal{O}(f(n)) \text{ time for an input of size } n \}$$

Definition

An algorithm V is called a *verifier* for a language L , if:

$$L = \{ w \mid \exists c \in \Sigma^* : V \text{ accepts } \langle w, c \rangle \}$$

V is called a *polynomial verifier*, if it runs in polynomial time in terms of $|w|$. L is called *polynomially verifiable*, if such a polynomial verifier exists. c is called *certificate*.

Definition

An algorithm V is called a *verifier* for a language L , if:

$$L = \{ w \mid \exists c \in \Sigma^* : V \text{ accepts } \langle w, c \rangle \}$$

V is called a *polynomial verifier*, if it runs in polynomial time in terms of $|w|$. L is called *polynomially verifiable*, if such a polynomial verifier exists. c is called *certificate*.


Example: Path for the PATH problem


Machines and Verifiers

Machines

Verifiers

Machines and Verifiers





NP and Equivalence of Concepts

NP and Equivalence of Concepts

Definition

The class NP is the class of languages computable by nondeterministic turing machines in polynomial time.

$$NP := \bigcup_{k \in \mathbb{N}} \text{NTIME}(n^k)$$

NP and Equivalence of Concepts

Definition

The class NP is the class of languages computable by nondeterministic turing machines in polynomial time.


$$NP := \bigcup_{k \in \mathbb{N}} \text{NTIME}(n^k)$$

Corollary

$NP = \{ L \mid L \text{ has a polynomial time verifier} \}$


The HAMPATH Problem

$\text{HAMPATH} := \{ \langle G, s, t \rangle \mid \text{There is a hamiltonian path between } s \text{ and } t \}$



The HAMPATH Problem

$\text{HAMPATH} := \{ \langle G, s, t \rangle \mid \text{There is a hamiltonian path between } s \text{ and } t \}$



HAMPATH \in NP

Theorem
HAMPATH \in NP

HAMPATH \in NP

Theorem

HAMPATH \in NP

Proof.

Input: $\langle G, s, t \rangle$, where $G = (V, E)$ is a directed graph with nodes s, t .

Function:

- 1: Index the nodes from 1 to $m := |V|$ (number of nodes).
Nondeterministically write a list of m numbers p_1, \dots, p_m ,
where $p_i \in \{1, \dots, m\}$.
- 2: Check for repetitions. If any are found, reject.
- 3: Check if p_1, p_m correspond to the node indices of s, t . If
not, reject.
- 4: **for** each $1 \leq i \leq m - 1$ **do**
- 5: Check if $(p_i, p_{i+1}) \in E$. If not, reject.
- 6: Accept.



The SUBSET-SUM Problem

$$\text{SUBSET-SUM} := \{ \langle S, t \rangle \mid S = \{x_1, \dots, x_n\} \wedge \\ \exists \{y_1, \dots, y_k\} \subseteq S: \sum y_i = t \}$$

SUBSET-SUM \in NP

Theorem

SUBSET-SUM \in NP

SUBSET-SUM \in NP

Theorem

SUBSET-SUM \in NP

Proof.

Construct a polynomial time verifier.

SUBSET-SUM \in NP

Theorem

SUBSET-SUM \in NP

Proof.

Construct a polynomial time verifier.

Input: $\langle \langle S, t \rangle, C \rangle$ with S, C finite set of numbers and c number.

Function:

- 1: Test if $\sum c_i = t$ with $C = \{c_1, \dots, c_k\}$.
- 2: Test if $C \subseteq S$.
- 3: Accept if both pass, otherwise reject at one stage.



Additional NP Problems

$$\text{COMPOSITES} = \{ \langle n \rangle \mid n = pq \text{ with } p, q > 1 \text{ natural numbers} \}$$

Additional NP Problems

COMPOSITES = $\{ \langle n \rangle \mid n = pq \text{ with } p, q > 1 \text{ natural numbers} \}$

CLIQUE = $\{ \langle G, k \rangle \mid G \text{ is an undirected graph with a } k\text{-clique} \}$

Polynomial Time Reducibility

Definition

A language A is *polynomial time reducible* to a language B , written $A \leq_p B$, if there is a polynomial time computable function $f: \Sigma^* \rightarrow \Sigma^*$, where for every $w \in \Sigma^*$:

$$w \in A \leftrightarrow f(w) \in B$$

$$\text{SAT} = \{ \langle \phi \rangle \mid \phi \text{ has a satisfying assignment} \}$$

$$\text{SAT} = \{ \langle \phi \rangle \mid \phi \text{ has a satisfying assignment} \}$$

$$\text{3SAT} = \{ \langle \phi \rangle \mid \phi \text{ is a satisfiable 3cnf-formula} \}$$

3SAT \leq_p CLIQUE

Theorem

3SAT \leq_p CLIQUE

3SAT \leq_p CLIQUE

Theorem

3SAT \leq_p CLIQUE

Proof.

Present reduction as function f : Generate an undirected graph G out from the input 3cnf-formula ϕ given. Let ϕ have k clauses.

- Organize clauses in triples t_1, \dots, t_k
- Connect nodes if not from the same triple
- Or if not contradicting (e.g. x and $\neg x$ are not connected)



Example for the Construction

$$\phi = (x_1 \vee \overline{x_1} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_2}) \wedge (\overline{x_2} \vee x_1 \vee \overline{x_2})$$

Example for the Construction

$$\phi = (x_1 \vee \overline{x_1} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_2}) \wedge (\overline{x_2} \vee x_1 \vee \overline{x_2})$$

$$\overline{x_1}$$

$$x_2$$

$$\overline{x_2}$$

$$\overline{x_2}$$

$$\overline{x_2}$$

$$\overline{x_1}$$


$$x_1$$

$$x_1$$

$$\overline{x_2}$$


Example for the Construction

$$\phi = (x_1 \vee \overline{x_1} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_2}) \wedge (\overline{x_2} \vee x_1 \vee \overline{x_2})$$




Example for the Construction

$$\phi = (x_1 \vee \overline{x_1} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_2}) \wedge (\overline{x_2} \vee x_1 \vee \overline{x_2})$$




Example for the Construction

$$\phi = (x_1 \vee \overline{x_1} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_2}) \wedge (\overline{x_2} \vee x_1 \vee \overline{x_2})$$



Example for the Construction

$$\phi = (x_1 \vee \overline{x_1} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee \overline{x_2}) \wedge (\overline{x_2} \vee x_1 \vee \overline{x_2})$$



Observation: There is some kind of link between the complexities of problems.

Observation: There is some kind of link between the complexities of problems.

Definition

A language B is called *NP-complete*, if it satisfies two conditions:

1. $B \in \text{NP}$
2. $A \leq_p B$ for every language $A \in \text{NP}$, also called *NP-hard*

$$\text{SAT} = \{ \langle \phi \rangle \mid \phi \text{ has a satisfying assignment} \}$$

$$\text{SAT} = \{ \langle \phi \rangle \mid \phi \text{ has a satisfying assignment} \}$$

Fact (Cook-Levin Theorem)

SAT is NP-complete

Proof idea.

Corollary

If B is NP-complete and $B \in P$, then $P = NP$.

Corollary

If B is NP-complete and $B \in P$, then $P = NP$.

Corollary

If B is NP-complete and $B \leq_p C$ for $C \in NP$, then C is NP-complete.

Corollary

If B is NP-complete and $B \in P$, then $P = NP$.

Corollary

If B is NP-complete and $B \leq_p C$ for $C \in NP$, then C is NP-complete.

Corollary

CLIQUE is NP-complete.




Michael Sipser.

Introduction to the Theory of Computation, Third Edition.


Cengage Learning, 2012.

The New Landscape


The New Landscape



The New Landscape



The New Landscape



Questions?