

# Abstract

This thesis presents the development and characterization of the experimental system required for the preparation, optical trapping, and controlled transport of cold  $^{87}\text{Rb}$  atoms toward a Hollow-Core Photonic Crystal Fiber (HCPCF).

First, the atomic sample preparation was optimized: the optical molasses reached a minimum temperature of  $T = (8.4 \pm 0.2) \mu\text{K}$ . Loading into the Optical Dipole Trap (ODT) yielded a loading efficiency of  $(0.161 \pm 0.005)\%$  and an estimated trapped population of  $(1.0 \pm 0.1) \times 10^5$  atoms.

To implement the optical conveyor belt, a second counter-propagating 1064 nm field was established using a polarization-maintaining single-mode fiber. Characterization of the transmitted field showed fractional power and angular Allan deviations reaching minima of  $8 \times 10^{-4}$  at 0.1 s and  $7 \times 10^{-5}$  rad at 3 s, respectively, before degrading at longer times from low-frequency drifts.

To counteract potential heating during optical transport, Electromagnetically Induced Transparency (EIT) cooling was investigated numerically via a quantum master-equation model in QuTiP. Multilevel simulations of the  $^{87}\text{Rb}$   $D_2$  transition, with an active repump field preventing optical pumping into uncoupled states, reached a final  $\langle n \rangle \approx 0.08$  in approximately 18 ms.

These results establish the main experimental and numerical prerequisites for a future implementation of conveyor-belt transport and sub-Doppler cooling of cold atoms inside the HCPCF.