

Introduction

The work presented in this thesis was conducted in the cold atoms laboratory of Professors Francesco Minardi and Marco Prevedelli at the Department of Physics and Astronomy "A. Righi" of the University of Bologna. The primary objective of the experiment is to study a quantum system consisting of a cold rubidium-87 (^{87}Rb) gas loaded into the core of a Hollow-Core Photonic Crystal Fiber (HCPCF). By confining atoms directly within their hollow core, HCPCFs enable tight spatial confinement and strong atom-light interactions over macroscopic distances, establishing a highly versatile platform for advanced quantum technologies. Potential applications for the fiber-atoms system include the realization of highly sensitive, miniaturized quantum sensors (such as atomic magnetometers and interferometers), as well as the realization of quantum memories, which constitute the fundamental building blocks for future quantum networks.

Loading cold atoms into an HCPCF requires an efficient intermediate trapping and transfer mechanism. As a starting point, the source of these cold atoms is provided by a pre-existing setup utilizing a Magneto-Optical Trap (MOT) followed by an optical molasses phase, preparing a cold, sub-Doppler atomic sample. To efficiently load the atoms into the HCPCF, an optical conveyor belt is required. This system is realized by using two counter-propagating Optical Dipole Trap (ODT) beams that interfere to create a standing wave. Tuning the relative frequency of the two branches allows the standing wave to become dynamic, enabling the controlled transport of the cold atoms. Furthermore, the standing wave provides the necessary axial confinement inside the optical fiber's core. This thesis details the implementation and optimization of the first 1064 nm ODT beam, which represents the starting point for the implementation of the complete transfer mechanism.

The thesis is structured as follows:

Chapter 1 establishes the theoretical framework underpinning the experiment. It begins with the physics of optical waveguides, deriving the Linearly Polarized (LP) modes for standard step-index fibers in the weakly guiding approximation. It then introduces HCPCFs, contrasting the Photonic Band Gap (PBG) and Inhibited Coupling (IC) guiding mechanisms. Finally, it reviews the semiclassical theory of the optical dipole force, deriving the conservative trapping potential and scattering rates for multi-level alkali atoms.

Chapter 2 details the experimental apparatus and the analytical methodologies. Following an overview of the vacuum chamber, the MOT, and the laser frequency stabilization systems, it describes the implementation of the 1064 nm ODT setup. This includes the spatial characterization of the ODT laser beam, the design of the optical injection line, and the development of a custom horizontal microscope to monitor the near-field mode to optimize the coupling into the HCPCF. It also describes two theoretical models to calculate a reference ODT capture efficiency in shallow and non-shallow trap regimes. Finally, this chapter outlines the experimental and analytical procedure employed for obtaining the results summarized in the last chapter.

Chapter 3 presents the experimental results and their discussion. It first reports the systematic minimization of the optical molasses temperature. Subsequently, it details the tuning of the compensation magnetic fields required to maximize the spatial overlap between the atomic cloud and the ODT beam, ultimately optimizing the capture efficiency and comparing the experimental results with the theoretical predictions.