



MAT OPAL

Mat Opal privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film filters out most natural light creating subtle ambient lighting conditions.



Warranty

5 YEARS



Fire-resistance rating



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:

122 cm

152 cm

183 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| Ultraviolet transmission | 5 % |
|--------------------------------------|--------|
| Visible light transmission | 60 % |
| Reflection of external visible light | 27 % |
| Reflection of internal visible light | 20 % |
| Total solar energy rejected | 30 % |
| Total solar energy rejected 2* | 30 % |
| Solar ratio: | |
| Solar energy reflection | 21 % |
| Solar energy absorption | 18 % |
| Solar energy transmission | 61 % |
| Reduction in Solar Glare | 27 % |
| g-value | 0.71 |
| u-value | 5.6 |
| Shading coefficient | 0.8 |
| Installation type: Interior | |
| Roll length | 30,5 m |
| Film composition | PET |
| Thickness | 60 μ |
| | |

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

| Clear single pane | ~ |
|--------------------------------|---|
| Tinted single pane | ~ |
| Reflective tinted single pane | ~ |
| Clear double pane | ~ |
| Tinted double pane | ~ |
| Reflective tinted double pane | ~ |
| Gas-filled double pane - Low E | ~ |
| STADIP EXT. clear double pane | ~ |
| STADIP INT. clear double pane | ~ |
| | |

∨ Yes Caution X Not recommended


*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

CONSTRUCTION

1. Frosted polyester with satin surface

Colour from the outside: WHITE

- 2. Bonding adhesive
 3. High optical quality polyester
 4. PS adhesive, glass polymerization within 15 days
 5. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.