



SAFE 4 XC

Safer 4 XC solvent resistant films provide highly effective protection against tags and graffiti. The film's protective qualities are not limited to solvents, it will also shield a window's surface from other acts of vandalism involving scratching or acid etching. An easy film to install and replace, it is also classed as a security film, providing protection by holding shattered glass in place in the event of an explosion or serious impact.



Warranty See the notice



Fire-resistance rating



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:

→ 122 cm

→ 152 cm

←→ 183 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	5 %
Visible light transmission	85 %
Reflection of external visible light	11 %
Reflection of internal visible light	11 %
Total solar energy rejected	19 %
Total solar energy rejected 2*	19 %
Solar ratio:	
Solar energy reflection	9 %
Solar energy absorption	14 %
Solar energy transmission	77 %
Reduction in Solar Glare	14 %
g-value	0.83
u-value	5.7
Shading coefficient	0.9
Tensile strength (kg/cm ²)	28
Elongation at break	125%
Installation type: Exterior	
Roll length	30,5 m
Film composition	PET
Thickness	120 μ

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

Clear single pane	~
Tinted single pane	V
Reflective tinted single pane	V
Clear double pane	V
Tinted double pane	V
Reflective tinted double pane	~
Gas-filled double pane - Low E	V
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	V

✓ Yes Caution XNot recommended


*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

CONSTRUCTION

TRANSPARENT

Colour from the outside:

- 1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. High optical quality polyester
- 3. Bonding adhesive
- 4. High optical quality polyester
- 5. Reinforced PS Adhesive to accompany the elasticity of the film
- in case of impact, glass polymerization within 30 days
- **6.** Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.