



VITRA

The self-adhesive Vitra film is decorated with a repeating polygonal pattern, providing a modern touch of elegance to your windows and glass partitions.



Warranty **5 YEARS**



Fire-resistance rating





Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:



152 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	0 %
Reflection of external visible light	0 %
Reflection of internal visible light	0 %
Total solar energy rejected	%
Total solar energy rejected 2*	%
Solar ratio:	
Solar energy reflection	0 %
Solar energy absorption	0 %
Solar energy transmission	0 %
Reduction in Solar Glare	0 %
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type: Interior	
Roll length	30,5 m
Film composition	PET
Thickness	$40~\mu$
Colour from the outside: FROSTED	

INSTALLATION ADVICE

Vertical installation and on standard glass surface*


Clear single pane	~
Tinted single pane	~
Reflective tinted single pane	~
Clear double pane	~
Tinted double pane	~
Reflective tinted double pane	~
Gas-filled double pane - Low E	~
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	~



*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

CONSTRUCTION

- 1. High optical quality polyester with printed design
- 2. PS adhesive, glass polymerization within 15 days3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.