



MAT ACID-X

Mat Acid-X privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.



Warranty
See the notice



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **122 cm**

↔ **152 cm**

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	> 25 %
Visible light transmission	60 %
Reflection of external visible light	18 %
Reflection of internal visible light	18 %
Total solar energy rejected	28 %
Total solar energy rejected 2*	29 %
Solar ratio :	
Solar energy reflection	18 %
Solar energy absorption	15 %
Solar energy transmission	67 %
Reduction in Solar Glare	40 %
g-value	0.71
u-value	5.6
Shading coefficient	NC
Installation type : Exterior	
Roll length	50 m
Film composition	PVC
Thickness	75 µ

Colour from the outside : FROSTED

CONSTRUCTION

1. 75µ "cast" polymer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Paper release liner allowing digital cutting



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.