

AJAX with Fetch


fetch API

- Fetch
 - promise-based API for Ajax requests
 - replace **XMLHttpRequest**
 - now supported in all modern browsers

```
function doWebRequest() {
  const url = "..."; // put url string here
  fetch(url); // returns a Promise!
}
```

<https://www.digitalocean.com/community/tutorials/js-fetch-api>

The Promise Pipeline



Esempio GET

```
fetch('https://jsonplaceholder.typicode.com/users')
  .then(res => res.json())
  .then(res => res.map(user => user.username))
  .then(userNames => console.log(userNames));
```

Nota: sulla console funziona solo sulla pagina: <https://jsonplaceholder.typicode.com/>

Esempio POST

```
const myPost = {
  title: 'A post about true facts',
  body: '42',
  userId: 2
}

const options = {
  method: 'POST',
  body: JSON.stringify(myPost),
  headers: {
    'Content-Type': 'application/json'
  }
};

fetch('https://jsonplaceholder.typicode.com/posts', options)
  .then(res => res.json())
  .then(res => console.log(res));
```

Gestione dell'Errore

```
fetch('https://jsonplaceholder.typicode.com/postsZZZ', options)
  .then(res => {
    if (res.ok) {
      return res.json();
    } else {
      return Promise.reject({ status: res.status, statusText: res.statusText });
    }
  })
  .then(res => console.log(res))
  .catch(err => console.log('Error, with message:', err.statusText));
```

Esempio GitHub

```
const url = `http://pw.netgroup.uniroma2.it/docenti/${docente}.json`
console.log(url)
fetch(url)
  .then(res => res.json())
  .then(json_data => {
    const url_user = `https://api.github.com/users/${json_data.name}`
    console.log(url_user)
    return fetch(url_user)
  })
  .then(res=>res.json())
  .then(user_data=>{
```

ASYNC AWAIT

async

```
async function f() {  
  return 1;  
}
```

- **async** before a function means that a function **always** returns a **promise**

async

```
async function f() {
  return 1;
}
```

- **async** before a function means that a function **always** returns a **promise**

```
async function f() {
  return 1;
}

f().then(alert); // 1
```

async

```
async function f() {
  return 1;
}
```

- **async** before a function means that a function **always** returns a **promise**

```
async function f() {
  return 1;
}

f().then(alert); // 1
```

```
async function f() {
  return Promise.resolve(1);
}

f().then(alert); // 1
```

await

- Rende il codice asincrono ed aspetta la risposta

```
// works only inside async functions  
let value = await promise;
```

await

- Rende il codice asincrono ed aspetta la risposta futura

```
// works only inside async functions
let value = await promise;
```

```
async function f() {

    let promise = new Promise((resolve, reject) => {
        setTimeout(() => resolve("done!"), 1000)
    });

    let result = await promise; // wait until the promise resolves (*)

    alert(result); // "done!"
}

f();
```

error handling: try catch

- in the case of a **rejection** a promise throws the error
 - as if there were a throw statement at that line

error handling: try catch

- in the case of a **rejection** a promise throws the error
 - as if there were a throw statement at that line
- can catch that error using try..catch

```
async function f() {

  try {
    let response = await fetch('http://no-such-url');
  } catch(err) {
    alert(err); // TypeError: failed to fetch
  }
}

f();
```

Fetch with Async/Await

GET

```
async function fetchUsers(endpoint) {  
  const res = await fetch(endpoint);  
  let data = await res.json();  
  
  data = data.map(user => user.username);  
  
  console.log(data);  
}  
  
fetchUsers('https://jsonplaceholder.typicode.com/users');
```

GET V2

```

async function fetchUsers(endpoint) {
  const res = await fetch(endpoint);
  const data = await res.json();

  return data;
}

fetchUsers('https://jsonplaceholder.typicode.com/users')
  .then(data => {
    console.log(data.map(user => user.username));
  });

```

Errors

```

async function fetchUsers(endpoint) {
  const res = await fetch(endpoint);

  if (!res.ok) {
    throw new Error(res.status); // 404
  }

  const data = await res.json();
  return data;
}

fetchUsers('https://jsonplaceholder.typicode.com/usersZZZ')
  .then(data => {
    console.log(data.map(user => user.website));
  })
  .catch(err => console.log('Ooops, error', err.message));

```

Errors V2

```

async function fetchUsers(endpoint) {
  try {
    const res = await fetch(endpoint);
    if (!res.ok) {
      throw new Error(res.status); // 404
    }
    const data = await res.json();
    data = data.map(user => user.username);
    console.log(data);
  } catch (error) {
    // do something
  }
}

fetchUsers('https://jsonplaceholder.typicode.com/usersZZZ')

```

Esempio GitHub con async/await

```
const getInfoProf = async function(docente){
  try {

    const url = `http://pw.netgroup.uniroma2.it/docenti/${docente}.json`

    const res = await fetch(url);
    const json_data = await res.json()
    const url_user = `https://api.github.com/users/${json_data.name}`

    const res_gh = await fetch(url_user)
    const user_data = await res_gh.json()
```

CORS

CORS: cross-origin HTTP request

- un client richiede una risorsa di un differente dominio, protocollo o porta.
- Esempio
 - una web application con dominio X non può richiedere una risorsa ad un dominio Y tramite AJAX request se Y non ha abilitato il CORS.

<https://italiancoders.it/cors-in-dettaglio/>

<https://developer.mozilla.org/en-US/docs/Web/HTTP/CORS>

Same origin policy

- Un browser permette agli script contenuti in una pagina web di accedere ai dati contenuti in un'altra risorsa web (altra pagina web, json ecc) **solo se entrambe le pagine hanno la stessa origine**


✖ ▶ XMLHttpRequest cannot load json.html:8
<http://urls.api.twitter.com/1/urls/count.json?>
[url=http://www.uniroma2.it](http://www.uniroma2.it). No 'Access-Control-Allow-Origin' header is present on the requested resource. Origin 'null' is therefore not allowed access.

Live reload enabled.

✖ Access to fetch at '<https://api.twitter.com/2/tweets/counts/all>' from origin '<http://127.0.0.1:5500>' has been blocked by CORS policy: No 'Access-Control-Allow-Origin' header is present on the requested resource. If an opaque response serves your needs, set the request's mode to 'no-cors' to fetch the resource with CORS disabled. test.html:1

✖ Failed to load resource: net::ERR_FAILED api.twitter.com/2/tweets/counts/all:1 ↕

✖ Uncaught (in promise) TypeError: Failed to fetch
 at test.html:11:5 test.html:11 ↕ ✖



Cross Origin Resource Sharing

- Come fare se vogliamo espressamente permettere il resource sharing tra due siti diversi? → CORS
 - Standard W3C per condividere risorse tra domini diversi
 - Prevede richiesta di autorizzazione (client) e autorizzazione (server)
- Viene implementato inviando degli header HTTP in req/resp
 - Richieste Semplici
 - Richieste Preflight

Simple request

- Metodi Ammessi
 - GET
 - HEAD
 - POST
- Header ammessi
 - Accept
 - Accept-Language
 - Content-Language
 - Content-Type (but note the additional requirements below)
 - ...
- Valori ammessi per header Content-Type:
 - application/x-www-form-urlencoded
 - multipart/form-data
 - text/plain


Simple request

```
const xhr = new XMLHttpRequest();
const url = 'https://bar.other/resources/public-data/';

xhr.open('GET', url);
xhr.onreadystatechange = someHandler;
xhr.send();
```

Client

Server



Access-Control-Allow-Origin: * means that the resource can be accessed by **any** origin.

Pre-flight request

```
const xhr = new XMLHttpRequest();
xhr.open('POST', 'https://bar.other/resources/post-here/');
xhr.setRequestHeader('X-PINGOTHER', 'pingpong');
xhr.setRequestHeader('Content-Type', 'application/xml');
xhr.onreadystatechange = handler;
xhr.send('<person><name>Arun</name></person>');
```

Client

Server

Preflight request

OPTIONS /doc HTTP/1.1
Origin: http://foo.example
Access-Control-Request-Method: POST
Access-Control-Request-Headers: X-PINGOTHER, Content-type
...

HTTP/1.1 204 No Content
Access-Control-Allow-Origin: http://foo.example
Access-Control-Allow-Methods: POST, GET, OPTIONS
Access-Control-Allow-Headers: X-PINGOTHER, Content-Type
Access-Control-Max-Age: 86400
...

Pre-flight request

```
re | Access-Control-Request-Headers: X-PINGOTHER, Content-type  
  
const xhr = new XMLHttpRequest();  
xhr.open('POST', 'https://bar.other/resources/post-here/');  
xhr.setRequestHeader('X-PINGOTHER', 'pingpong');  
xhr.setRequestHeader('Content-Type', 'application/xml');  
xhr.onreadystatechange = handler;  
xhr.send('<person><name>Arun</name></person>');
```

```
..1 204 No Content  
http://foo.example  
POST, GET, OPTIONS  
OTHER, Content-Type  
col-Max-Age: 86400  
...
```

Main request

```
POST /doc HTTP/1.1  
X-PINGOTHER: pingpong  
Content-Type: text/xml; charset=UTF-8  
Origin: http://foo.example  
...
```

```
HTTP/1.1 200 OK  
Access-Control-Allow-Origin: http://foo.example  
Vary: Accept-Encoding, Origin  
Content-Encoding: gzip  
Content-Length: 235
```