```
score of A = 11, score of B : 8
Player B, enter row1 col1 row2 col2: 4 4 4 5
Good turn player B

  0 1 2 3 4 5
0 .-.-.-.-.-.
  |A|A|A|A|A|
1 .-.-.-.-.-.
  |A|B|A|A|A|
2 .-.-.-.-.-.
  |B|B|B|B|A|
3 .-.-.-.-.-.
  |B|A|B|B|B|
4 .-.-.-.-.-.
score of A = 11, score of B : 9
Final Score - Player A: 11 | Player B: 9
The winner is A
==2999==
==2999== HEAP SUMMARY:
==2999==     in use at exit: 0 bytes in 0 blocks
==2999==   total heap usage: 2 allocs, 2 frees, 2,048 bytes allocated
==2999==
==2999== All heap blocks were freed -- no leaks are possible
==2999==
==2999== For lists of detected and suppressed errors, rerun with: -s
==2999== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

```
┌──(kali㉿kali)-[~/ActiveProject]
└─$ gdb ./test
GNU gdb (Debian 17.1-3) 17.1
Copyright (C) 2025 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
    <http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from ./test...
(gdb) help
List of classes of commands:

aliases -- User-defined aliases of other commands.
breakpoints -- Making program stop at certain points.
data -- Examining data.
files -- Specifying and examining files.
internals -- Maintenance commands.
obscure -- Obscure features.
running -- Running the program.
stack -- Examining the stack.
status -- Status inquiries.
support -- Support facilities.
```

kali@kali: ~/ActiveProject

Session Actions Edit View Help

```
score of A = 11, score of B : 8
Player B, enter row1 col1 row2 col2: 4 4 4 5
Good turn player B

  0 1 2 3 4 5
0 .-.-.-.-.-.
  |A|A|A|A|A|
1 .-.-.-.-.-.
  |A|B|A|A|A|
2 .-.-.-.-.-.
  |B|B|B|B|A|
3 .-.-.-.-.-.
  |B|A|B|B|B|
4 .-.-.-.-.-.
score of A = 11, score of B : 9
Final Score - Player A: 11 | Player B: 9
The winner is A
==2999==
==2999== HEAP SUMMARY:
==2999==     in use at exit: 0 bytes in 0 blocks
==2999==   total heap usage: 2 allocs, 2 frees, 2,048 bytes allocated
==2999==
==2999== All heap blocks were freed -- no leaks are possible
==2999==
==2999== For lists of detected and suppressed errors, rerun with: -s
==2999== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)

┌──(kali㉿kali)-[~/ActiveProject]
└─$

┌──(kali㉿kali)-[~/ActiveProject]
└─$ Students: Mohamad Barakeh and Mohamad Alaa AlDeen Al Hamwi
```

kali@kali: ~/ActiveProject

Session Actions Edit View Help

```
support -- Support facilities.
text-user-interface -- TUI is the GDB text based interface.
tracepoints -- Tracing of program execution without stopping the program.
user-defined -- User-defined commands.

Type "help" followed by a class name for a list of commands in that class.
Type "help all" for the list of all commands.
Type "help" followed by command name for full documentation.
Type "apropos word" to search for commands related to "word".
Type "apropos -v word" for full documentation of commands related to "word".
Command name abbreviations are allowed if unambiguous.
(gdb) break
❌ No default breakpoint address now.
(gdb) break main
Breakpoint 1 at 0x1184: file main.c, line 8.
(gdb) run
Starting program: /home/kali/ActiveProject/test
[Thread debugging using libthread_db enabled]
Using host libthread_db library "/usr/lib/x86_64-linux-gnu/libthread_db.so.1".

Breakpoint 1, main () at main.c:8
8           for (int i = 0; i < 5; i++) {
(gdb) continue
Continuing.

Player A, enter row1 col1 row2 col2: 0 0 0 1
  0 1 2 3 4 5
0 .-. . . . .

1 . . . . . .

2 . . . . . .
```

kali@kali: ~/ActiveProject

Session Actions Edit View Help

```
1 .-.-.-.-.-.
  |A|A|A|A|B|
2 .-.-.-.-.-.
  |A|A|A|A|B|
3 .-.-.-.-.-.
  |B|A|B|A| |
4 .-.-.-.-. .
score of A = 11, score of B : 8
Player B, enter row1 col1 row2 col2: 4 4 4 5
Good turn player B

  0 1 2 3 4 5
0 .-.-.-.-.-.
  |B|A|B|B|B|
1 .-.-.-.-.-.
  |A|A|A|A|B|
2 .-.-.-.-.-.
  |A|A|A|A|B|
3 .-.-.-.-.-.
  |B|A|B|A|B|
4 .-.-.-.-.-.
score of A = 11, score of B : 9
Final Score - Player A: 11 | Player B: 9
The winner is A
[Inferior 1 (process 3508) exited normally]
(gdb) print score_A
❌ No symbol "score_A" in current context.
(gdb) exit

┌──(kali㉿kali)-[~/ActiveProject]
└─$ Students: Mohamad Barakeh and Mohamad Alaa AlDeen Al Hamwi
```

kali@kali: ~/ActiveProject

Session Actions Edit View Help

```
┌──(kali㉿kali)-[~/ActiveProject]
└─$ ls
main.c  main.o  Makefile  playgame.c  playgame.h  playgame.o  test

┌──(kali㉿kali)-[~/ActiveProject]
└─$ valgrind ./test
==2999== Memcheck, a memory error detector
==2999== Copyright (C) 2002-2024, and GNU GPL'd, by Julian Seward et al.
==2999== Using Valgrind-3.25.1 and LibVEX; rerun with -h for copyright info
==2999== Command: ./test
==2999==

Player A, enter row1 col1 row2 col2: 0 0 0 1
  0 1 2 3 4 5
0 .-. . . . .

1 . . . . . .

2 . . . . . .

3 . . . . . .

4 . . . . . .
```