

BRP Event API

0.0.1 OAS 3.1

This documentation describes the API for registration of webhooks and to how to receive webhook calls. The registration endpoints follows the REST principles and the webhook calls are done as HTTP **POST** requests.

Go through the following sections to get an understanding of how to use the API:

- The events that are available to register webhooks for
- How to register, update and list webhooks
- How to specify the data to be included in the webhook call (data projection)
- How to filter on data for specific events (data filter)

Events

The following events are available to register webhooks for.

Event	Description
BOOKED_FROM_WAITING_LIST	A user has been booked from a waiting list
BOOKED_ON_CLASS	A user has been booked on a class
ENTRY_BOOKING_DEBITED	An entry booking has been debited
EVENT_BOOKING_DEBITED	An event booking has been debited
GROUP_ACTIVITY_ARRIVED	A participant arrives to a group activity
GROUP_ACTIVITY_BOOKING_DEBITED	A group activity booking has been debited
ITEM_BOOKING_DEBITED	An item booking has been debited
MEMBER	A member has been created
NO_SHOW_STATUS	A no show has changed status
PASSAGE_TRY	A user tried to pass a reader
PERSON_CREATED	A user has been created
PERSON_GROUP_CHANGED	A users person groups have been changed
PERSON_INFORMATION_CHANGED	A persons information has been changed
SERVICE_BOOKING_DEBITED	A service booking has been debited
SUBSCRIPTION_BOOKING_DEBITED	A subscription booking has been debited
SUBSCRIPTION_CREATED	A valid subscription has been created
SUBSCRIPTION_DEBITED_UNTIL_CHANGED	An existing subscription's debited until has been changed

Event	Description
SUBSCRIPTION_REFERRED_FROM_A_FRIEND	A new user purchases a subscription that was referred by a friend
SUBSCRIPTION_TERMINATED	A subscription has been terminated
USER_ACTIVITY	A user has made an interaction
VALUE_CARD_BOOKING_DEBITED	A value card booking has been debited
WORKOUT	A work out has been created

Webhook data projection

This part is a work in progress and is subject to change. Data available for events may change until the API is stable.

A webhook shall be registered with a data projection. The data projection selects the fields that should be included in the webhook call.

Data projections are specified as a [GraphQL query string](#) (without arguments, aliases, etc.). Look at the [Receive an event](#) section to see the data structure for each event. Then "transform" the data structure to a GraphQL query string.

These steps describes how the data projection works:

1. Available data for an event

```
{
  "id": 1,
  "name": "John",
  "products": [
    { "id": 2, "name": "Can", "amount": 375 },
    { "id": 3, "name": "Fruit", "amount": 500 }
  ]
}
```

2. Data projection

```
{ id, items { id, amount } }
```

3. Data that will be included in the webhook call

```
{
  "id": 1,
  "items": [
    { "id": 2, "amount": 375 },
    { "id": 3, "amount": 500 }
  ]
}
```

Examples

- Receive only the id and time of a workout: `{ id, time }`

- Receive id and participant properties of a group activity booking: `{ id, participants { id, arrived, person { id } } }`

Webhook data filter

A webhook can be registered with a filter. The filter will be matched with the data of the event before the event is sent to the webhook url. Only events that matches the filter will be sent to the webhook. The filter can't be applied on array items.

The filter will be used after the data projection is done. That means that it's only possible to filter on fields that are specified in the data projection.

Type	Description	Format
field	Selects a field in the data structure	<code>{ "type": "field", "path": <string> }</code>
equals	Match if field value equals value	<code>{ "type": "equals", "value": <string\ number> }</code>
equalsAny	Match if field value equals any of values	<code>{ "type": "equalsAny", "values": [<string\ number>] }</code>
equalsNone	Match if field value equals none of values	<code>{ "type": "equalsNone", "values": [<string\ number>] }</code>
notEquals	Match if field value doesn't equal value	<code>{ "type": "notEquals", "value": <string\ number> }</code>
notNull	Match if field value isn't null	<code>{ "type": "notNull" }</code>
containsText	Match if field value contains a text	<code>{ "type": "equals", "text": <string> }</code>
and	All filters should match	<code>{ "type": "and", "filters": [<filter>] }</code>
or	At least on filter should match	<code>{ "type": "or", "filters": [<filter>] }</code>

Examples

- Receive events for a specific business unit

```
{
  "type": "field",
  "path": "businessUnit.id",
  "filter": {
    "type": "equals",
    "value": 1
  }
}
```

- Receive events for a specific status, only for some business units

```
{
  "type": "and",
  "filters": [
    {
      "type": "field",
      "path": "status",

```

```
{
  "filter": {
    "type": "equals",
    "value": "active"
  },
  {
    "type": "field",
    "path": "businessUnit.id",
    "filter": {
      "type": "equalsAny",
      "values": [1, 2, 3, 4]
    }
  }
]
```

Authentication

No authentication as the registration api is not publicly available.

Register a webhook

Register a webhook to receive events. See [Register a webhook](#) endpoint.

Receive a webhook

The registered webhook url will be called with a HTTP **POST** request. See [Receive an webhook](#).

Order of events

The order of events is not guaranteed. The events can be received in any order.

Retry policy

If anything other than a **200** response code is returned the webhook will be retried. The retry policy is as follows:

- Exponential backoff with a base of 2 and an initial first delay of 1 second.
- The first retry will be after 1 second, the second after 2 seconds, the third after 4 seconds and so on.
- Currently no number of maximum retries is set. This will be added later.

Error response

A request might not be performed by the Event API server. The request might not be valid, request object don't exist, authorization not provided, etc.

Field validation error

Is an error which occurs when a request has failed the validation. The detail field includes a more detailed summary of the issue.


```
{
  "type": "about:blank",
  "title": "Field validation error",
  "status": 400,
  "detail": "The following fields are not valid. 'secret': must not be null, 'data': must not be null, 'event': must not be null.",
  "instance": "/api/v1/webhook"
}
```

webhook

GET /api/v1/webhook List all webhooks

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK	No links

Media type

application/json

Examples

List of webhooks

Controls Accept header.

Example Value Schema

```
[
  {
    "id": 1,
    "licenseId": "1234560",
    "url": "https://mywebhookservice:1234/webhook/workout",
    "event": "WORKOUT",
    "data": "{ id, timePoint }",
    "dataFilter": null
  },
  {
    "id": 2,
    "licenseId": "1234560",
    "url": "https://mywebhookservice:1234/webhook/member",
    "event": "MEMBER",
    "data": "{ id, firstName, lastName }",
    "dataFilter": null
  }
]
```

Example Description

All webhooks for a client

Code	Description	Links
400	Bad request error. Media type application/json+problem Example Value Schema <pre>{ "type": "about:blank", "title": "Field validation error", "status": 400, "detail": "The following fields ...", "instance": "/api/v1/webhook" }</pre>	No links

POST /api/v1/webhook Register a webhook ^

Parameters

Try it out

No parameters

Request body

application/json

Examples:

Booked from waiting list

Example Value Schema

```
{
  "licenseId": "1234560",
  "url": "https://mywebhookservice:1234/webhook/member",
  "event": "BOOKED_FROM_WAITING_LIST",
  "secret": "my-secret",
  "data": "{ id, participants { id, arrived, person { id } } }",
  "dataFilter": null
}
```

Example Description

Webhook for **BOOKED_FROM_WAITING_LIST** events

Responses

Code

Description

Links

201

Webhook registered

No links

Media type

application/json

Examples

Booked from waiting list

Controls Accept header.

Example Value Schema

```
{
  "id": 1,
  "licenseId": "1234560",
  "url": "https://mywebhookservice:1234/webhook/member",
  "event": "BOOKED_FROM_WAITING_LIST",
  "secret": "my-secret",
  "data": "{ id, participants { id, arrived, person { id } } }",
  "dataFilter": null
}
```

Example Description

Webhook for BOOKED_FROM_WAITING_LIST events

400

Bad request error.

No links

Media type

application/json+problem

Example Value Schema

```
{
  "type": "about:blank",
  "title": "Field validation error",
  "status": 400,
  "detail": "The following fields ...",
  "instance": "/api/v1/webhook"
}
```

GET

/api/v1/webhook/{id} Get a webhook



Parameters

Try it out

Name

Description

id * required
integer
(path)

id

Responses

Code

Description

Links

200

OK

No links

Media type

application/json

Examples

Booked from waiting list

Controls Accept header.

Example Value Schema

```
{
  "id": 1,
  "licenseId": "1234560",
  "url": "https://mywebhookservice:1234/webhook/member",
  "event": "BOOKED_FROM_WAITING_LIST",
  "secret": "my-secret",
  "data": "{ id, participants { id, arrived, person { id } } }",
  "dataFilter": null
}
```

Example Description

Webhook for BOOKED_FROM_WAITING_LIST events

400

Bad request error.

No links

Media type

application/json+problem

Example Value Schema

```
{
  "type": "about:blank",
  "title": "Field validation error",
  "status": 400,
  "detail": "The following fields ...",
  "instance": "/api/v1/webhook"
}
```

PUT

/api/v1/webhook/{id} Update a webhook



Parameters

Try it out

Name

Description

id * required
integer
(path)

id

Request body

application/json

Examples:

Booked from waiting list

Example Value Schema

```
{
  "licenseId": "1234560",
  "url": "https://mywebhookservice:1234/webhook/member",
  "event": "BOOKED_FROM_WAITING_LIST",
  "secret": "my-secret",
  "data": "{ id, participants { id, arrived, person { id } } }",
  "dataFilter": null
}
```

Example Description

Webhook for **BOOKED_FROM_WAITING_LIST** events

Responses

Code	Description	Links
200	OK	No links

Media type

application/json

Examples

Booked from waiting list

Controls Accept header.

Example Value Schema

```
{
  "id": 1,
  "licenseId": "1234560",
  "url": "https://mywebhookservice:1234/webhook/member",
  "event": "BOOKED_FROM_WAITING_LIST",
  "secret": "my-secret",
  "data": "{ id, participants { id, arrived, person { id } } }",
  "dataFilter": null
}
```

Example Description

Webhook for **BOOKED_FROM_WAITING_LIST** events

400	Bad request error.	No links
-----	--------------------	----------

Media type

Code	Description	Links
	application/json+problem	
	Example ValueSchema <pre>{ "type": "about:blank", "title": "Field validation error", "status": 400, "detail": "The following fields ...", "instance": "/api/v1/webhook" }</pre>	

DELETE

/api/v1/webhook/{id} Delete a webhook

⌵

Parameters

Try it out

Name	Description
id * required integer (path)	id

Responses

Code	Description	Links
204	No Content Example Value "string"	No links
400	Bad request error. Media type application/json+problem Example Value Schema { "type": "about:blank", "title": "Field validation error", "status": 400, "detail": "The following fields ...", }	No links

Code	Description	Links
<pre>"instance": "/api/v1/webhook" }</pre>		

Webhooks

POST

receive-event

Receive an event

^

The url that is registered with the webhook will be called with a HTTP **POST** call. The request body is a JSON object with the data for the event. Look at the different schemas and examples to see the data structure for each event.

Parameters

Name	Description
brp-signature string (header)	Calculated signature of the body. Uses the secret of the webhook and the body to calculate the signature using HMAC SHA256. The body is canonicalized json that conforms with RFC-8785 .
brp-signature	
brp-license-id string (header)	The BRP license id from which the event is originated
brp-license-id	

Request body

application/json

Examples:

Booked from waiting list

Example Value

Schema

```
"staff": false,
"personGroups": [
  {
    "id": 1,
    "name": "Group 1"
  },
  {
    "id": 2,
    "name": "Group 2"
  }
],
"organization": [
  {
    "id": 1,
    "name": "My Organization"
  }
],
}
```

Responses

Code	Description	Links
200	Return a 200 status to indicate that the data was received successfully. Example Value string	No links

Schemas

EventType ^ Collapse all string

Event type

Allowed values

"BOOKED_FROM_WAITING_LIST"	"ENTRY_BOOKING_DEBITED"	"EVENT_BOOKING_DEBITED"		
"GROUP_ACTIVITY_ARRIVED"	"GROUP_ACTIVITY_BOOKING_DEBITED"	"ITEM_BOOKING_DEBITED"		
"MEMBER"	"NO_SHOW_STATUS"	"PASSAGE_TRY"	"PERSON_CREATED"	"PERSON_GROUP_CHANGED"
"PERSON_INFORMATION_CHANGED"	"SERVICE_BOOKING_DEBITED"	"SUBSCRIPTION_BOOKING_DEBITED"		
"SUBSCRIPTION_CREATED"	"SUBSCRIPTION_DEBITED_UNTIL_CHANGED"			
"SUBSCRIPTION_REFERRED_FROM_A_FRIEND"	"SUBSCRIPTION_TERMINATED"	"USER_ACTIVITY"		
"VALUE_CARD_BOOKING_DEBITED"	"WORKOUT"			

TimePoint ^ Collapse all string date-time

The date-time notation as defined by RFC 3339, section 5.6. E.g. **2017-07-21T17:32:28Z**

WebhookDataFilter ^ Collapse all object

Filter for the webhook

type* ^ Collapse all string

Type of filter. [Read about the filters.](#)

Allowed values

"field"	"equals"	"equalsAny"	"equalsNone"	"notEquals"	"notNull"
"containsText"	"and"	"or"			

Additional properties any

Discriminator ^ Collapse all type object

and=WebhookFilterAnd

or=WebhookFilterOr

WebhookDataProjection ^ Collapse all string

A data projection for data to include in the webhook call

WebhookIn ^ Collapse all object

Webhook to register

licenseId* ^ Collapse all string

The BRP license id the webhook will be registered to

url* ^ Collapse all string

Url which will be called when an event is received

event* ^ Collapse all string

The event the webhook is listening to

Allowed values

"BOOKED_FROM_WAITING_LIST"	"ENTRY_BOOKING_DEBITED"	"EVENT_BOOKING_DEBITED"	
"GROUP_ACTIVITY_ARRIVED"	"GROUP_ACTIVITY_BOOKING_DEBITED"	"ITEM_BOOKING_DEBITED"	
"MEMBER"	"NO_SHOW_STATUS"	"PASSAGE_TRY"	"PERSON_CREATED"
"PERSON_GROUP_CHANGED"	"PERSON_INFORMATION_CHANGED"	"SERVICE_BOOKING_DEBITED"	
"SUBSCRIPTION_BOOKING_DEBITED"	"SUBSCRIPTION_CREATED"		
"SUBSCRIPTION_DEBITED_UNTIL_CHANGED"	"SUBSCRIPTION_REFERRED_FROM_A_FRIEND"		
"SUBSCRIPTION_TERMINATED"	"USER_ACTIVITY"	"VALUE_CARD_BOOKING_DEBITED"	
"WORKOUT"			

secret* ^ Collapse all string

Secret which will be used when calculating the signature

data* ^ Collapse all string

A data projection for data to include in the webhook call

dataFilter ^ Collapse all object

Filter for the webhook

type* ^ Collapse all string

Type of filter. [Read about the filters.](#)

Allowed values

"field" "equals" "equalsAny" "equalsNone" "notEquals" "notNull"
"containsText" "and" "or"

Additional properties any

Discriminator ^ Collapse all type object

and=WebhookFilterAnd

or=WebhookFilterOr

WebhookOut ^ Collapse all object

A registered webhook

id ^ Collapse all integer

The id of the webhook

licenseId ^ Collapse all string

The BRP license id the webhook is registered to

url ^ Collapse all string

The url of the webhook

event ^ Collapse all string

The event the webhook is listening to

Allowed values

"BOOKED_FROM_WAITING_LIST" "ENTRY_BOOKING_DEBITED" "EVENT_BOOKING_DEBITED"
"GROUP_ACTIVITY_ARRIVED" "GROUP_ACTIVITY_BOOKING_DEBITED" "ITEM_BOOKING_DEBITED"
"MEMBER" "NO_SHOW_STATUS" "PASSAGE_TRY" "PERSON_CREATED"
"PERSON_GROUP_CHANGED" "PERSON_INFORMATION_CHANGED" "SERVICE_BOOKING_DEBITED"
"SUBSCRIPTION_BOOKING_DEBITED" "SUBSCRIPTION_CREATED"
"SUBSCRIPTION_DEBITED_UNTIL_CHANGED" "SUBSCRIPTION_REferred_FROM_A_FRIEND"
"SUBSCRIPTION_TERMINATED" "USER_ACTIVITY" "VALUE_CARD_BOOKING_DEBITED"
"WORKOUT"

secret ^ Collapse all string

Secret which will be used when calculating the signature

data ^ Collapse all string

A data projection for data to include in the webhook call

dataFilter ^ Collapse all object

Filter for the webhook

type* ^ Collapse all string

Type of filter. [Read about the filters.](#)

Allowed values

"field" "equals" "equalsAny" "equalsNone" "notEquals" "notNull"
"containsText" "and" "or"

Additional properties any

Discriminator ^ Collapse all type object

and=WebhookFilterAnd

or=WebhookFilterOr

DataBooking ^ Collapse all object

Generic booking object

id* ^ Collapse all integer

Unique ID

product* ^ Collapse all object

Product that was booked

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items > Expand all object

givesMembership* ^ Collapse all integer

Type of membership this product gives

businessUnit ^ Collapse all object

Business unit that the booking belongs to

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. **Europe/Stockholm**

orderedBy ^ Collapse all object

Person who made the booking

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

givesMembership* ^ Collapse all integer

Type of membership this product gives

debited ^ Collapse all boolean

Whether the booking was debited or not

numberOfProducts ^ Collapse all integer

Number of products of the booking

DataBusinessUnit ^ Collapse all object

Business unit

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. **Europe/Stockholm**

DataGroupActivity ^ Collapse all object

Group activity

id* ^ Collapse all integer

Unique ID

product* ^ Collapse all object

Product that was booked

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all `array<object>`

Product labels the product belongs to

Items ^ Collapse all `object`

Product label

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

description* ^ Collapse all `string`

Description

availableFor ^ Collapse all `integer`

Available for

givesMembership* ^ Collapse all `integer`

Type of membership this product gives

businessUnit* ^ Collapse all `object`

Business unit where the group activity is held

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

timeZone* ^ Collapse all `string`

Time zone. E.g. **Europe/Stockholm**

DataGroupActivityBooking ^ Collapse all `object`

Group activity booking for a person

id* ^ Collapse all `integer`

Unique ID

start* ^ Collapse all `string` `date-time`

Time point when the booking was made

businessUnit* ^ Collapse all `object`

Business unit where the group activity is held

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

timeZone* ^ Collapse all `string`

Time zone. E.g. **Europe/Stockholm**

participants* ^ Collapse all `array<object>`

Participants of the group activity booking

Items ^ Collapse all `object`

Participant of a group activity

id* ^ Collapse all integer

Unique ID

arrived ^ Collapse all string date-time

Time point when the participant checked in to the activity

groupActivity* ^ Collapse all object

The group activity that the participant is attending

id* ^ Collapse all integer

Unique ID

product* ^ Collapse all object

Product that was booked

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

givesMembership* ^ Collapse all integer

Type of membership this product gives

businessUnit* ^ Collapse all object

Business unit where the group activity is held

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. [Europe/Stockholm](#)

firstName* ^ Collapse all [string](#)

First name

lastName* ^ Collapse all [string](#)

Last name

person ^ Collapse all [object](#)

Person that is the participant

id* ^ Collapse all [integer](#)

Unique ID

firstName* ^ Collapse all [string](#)

First name

lastName* ^ Collapse all [string](#)

Last name

ssn* ^ Collapse all [string](#)

Person number (national identification number)

personGroups ^ Collapse all [array<object>](#)

Person groups the person belongs to

Items ^ Collapse all [object](#)

Person group

id* ^ Collapse all [integer](#)

Unique ID

name* ^ Collapse all [string](#)

Name

email ^ Collapse all [string](#)

Email address

gender ^ Collapse all [integer](#)

Gender, 0-male, 1-Female, 3-Other

memberJoin ^ Collapse all [string](#)

Date when the person joined membership

memberEnd ^ Collapse all [string](#)

Date when the person's membership is ending

staff ^ Collapse all [boolean](#)

If the person is a staff member

businessUnit ^ Collapse all [object](#)

The facility the person belongs to

id* ^ Collapse all [integer](#)

Unique ID

name* ^ Collapse all [string](#)

Name

timeZone* ^ Collapse all [string](#)

Time zone. E.g. [Europe/Stockholm](#)

mobilePhone ^ Collapse all [object](#)

Mobile phone information

countryCode ^ Collapse all [string](#)

Country code. One to three digits. Example: 46

number ^ Collapse all [string](#)

Number in national format. Example: 0701234567

address ^ Collapse all [object](#)

Address

city ^ Collapse all [string](#)

City

street ^ Collapse all [string](#)

Street

postalCode [string](#)

careOf [string](#)

country ^ Collapse all [object](#)

alpha3 ^ Collapse all [string](#)

Country code in alpha-3 format. Example: SWE

organization ^ Collapse all [object](#)

Organization the person belongs to

id* ^ Collapse all [integer](#)

Unique ID

name* ^ Collapse all [string](#)

Name

Example

```
{ "id": 1, "firstName": "John", "lastName": "Doe", "ssn": "991231-1234", "staff": false, "personGroups": [ { "id": 1, "name": "Group 1" }, { "id": 2, "name": "Group 2" } ], "organization": [ { "id": 1, "name": "My Organization" } ] }
```

DataGroupActivityParticipant ^ Collapse all [object](#)

Participant of a group activity

id* ^ Collapse all [integer](#)

Unique ID

arrived ^ Collapse all [string](#) [date-time](#)

Time point when the participant checked in to the activity

groupActivity* ^ Collapse all [object](#)

The group activity that the participant is attending

id* ^ Collapse all [integer](#)

Unique ID

product* ^ Collapse all [object](#)

Product that was booked

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

givesMembership* ^ Collapse all integer

Type of membership this product gives

businessUnit* ^ Collapse all object

Business unit where the group activity is held

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. **Europe/Stockholm**

firstName* ^ Collapse all string

First name

lastName* ^ Collapse all string

Last name

person ^ Collapse all object

Person that is the participant

id* ^ Collapse all integer

Unique ID

firstName* ^ Collapse all string

First name

lastName* ^ Collapse all `string`

Last name

ssn* ^ Collapse all `string`

Person number (national identification number)

personGroups ^ Collapse all `array<object>`

Person groups the person belongs to

Items ^ Collapse all `object`

Person group

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

email ^ Collapse all `string`

Email address

gender ^ Collapse all `integer`

Gender, 0-male, 1-Female, 3-Other

memberJoin ^ Collapse all `string`

Date when the person joined membership

memberEnd ^ Collapse all `string`

Date when the person's membership is ending

staff ^ Collapse all `boolean`

If the person is a staff member

businessUnit ^ Collapse all `object`

The facility the person belongs to

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

timeZone* ^ Collapse all `string`

Time zone. E.g. **Europe/Stockholm**

mobilePhone ^ Collapse all `object`

Mobile phone information

countryCode ^ Collapse all `string`

Country code. One to three digits. Example: 46

number ^ Collapse all `string`

Number in national format. Example: 0701234567

address ^ Collapse all `object`

Address

city ^ Collapse all `string`

City

street ^ Collapse all string

Street

postalCode string

careOf string

country ^ Collapse all object

alpha3 ^ Collapse all string

Country code in alpha-3 format. Example: SWE

organization ^ Collapse all object

Organization the person belongs to

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

Example

```
{
  "id": 1,
  "firstName": "John",
  "lastName": "Doe",
  "ssn": "991231-1234",
  "staff": false,
  "personGroups": [
    {
      "id": 1,
      "name": "Group 1"
    },
    {
      "id": 2,
      "name": "Group 2"
    }
  ],
  "organization": [
    {
      "id": 1,
      "name": "My Organization"
    }
  ]
}
```

DataNoShow ^ Collapse all object

No show

id* ^ Collapse all integer

Unique ID

status* ^ Collapse all integer

The status of the no show

Allowed values 0 1 2 3 4 5

start* ^ Collapse all string date-time

Time point when the booking started

person* ^ Collapse all object

Person for the no show

id* ^ Collapse all integer

Unique ID

firstName* ^ Collapse all string

First name

lastName* ^ Collapse all string

Last name

ssn* ^ Collapse all string

Person number (national identification number)

personGroups ^ Collapse all array<object>

Person groups the person belongs to

Items ^ Collapse all object

Person group

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

`email` ^ Collapse all `string`

Email address

`gender` ^ Collapse all `integer`

Gender, 0-male, 1-Female, 3-Other

`memberJoin` ^ Collapse all `string`

Date when the person joined membership

`memberEnd` ^ Collapse all `string`

Date when the person's membership is ending

`staff` ^ Collapse all `boolean`

If the person is a staff member

`businessUnit` ^ Collapse all `object`

The facility the person belongs to

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

`timeZone*` ^ Collapse all `string`

Time zone. E.g. [Europe/Stockholm](#)

`mobilePhone` ^ Collapse all `object`

Mobile phone information

`countryCode` ^ Collapse all `string`

Country code. One to three digits. Example: 46

`number` ^ Collapse all `string`

Number in national format. Example: 0701234567

`address` ^ Collapse all `object`

Address

`city` ^ Collapse all `string`

City

`street` ^ Collapse all `string`

Street

`postalCode` `string`

`careOf` `string`

`country` ^ Collapse all `object`

`alpha3` ^ Collapse all `string`

Country code in alpha-3 format. Example: SWE

organization ^ Collapse all **object**

Organization the person belongs to

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

Example

```
{"id":1,"firstName":"John","lastName":"Doe","ssn":"991231-1234","staff":false,"personGroups":[{"id":1,"name":"Group 1"}, {"id":2,"name":"Group 2"}], "organization":[{"id":1,"name":"My Organization"}]}
```

businessUnit* ^ Collapse all **object**

The facility where the activity was held

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

timeZone* ^ Collapse all **string**

Time zone. E.g. **Europe/Stockholm**

booking* ^ Collapse all **object**

The booking that the person got a no show on

id* ^ Collapse all **integer**

Unique ID

product* ^ Collapse all **object**

Product that was booked

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

productSubtype* ^ Collapse all **integer**

Product subtype

noCheckOnDebitedUntil ^ Collapse all **boolean**

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all **array<object>**

Product labels the product belongs to

Items ^ Collapse all **object**

Product label

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

description* ^ Collapse all **string**

Description

`availableFor` ^ Collapse all `integer`

Available for

`givesMembership*` ^ Collapse all `integer`

Type of membership this product gives

`businessUnit` ^ Collapse all `object`

Business unit that the booking belongs to

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

`timeZone*` ^ Collapse all `string`

Time zone. E.g. [Europe/Stockholm](#)

`orderBy` ^ Collapse all `object`

Person who made the booking

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

`productSubtype*` ^ Collapse all `integer`

Product subtype

`noCheckOnDebitedUntil` ^ Collapse all `boolean`

If true, no need to verify debitedUntil when entering

`productLabels` ^ Collapse all `array<object>`

Product labels the product belongs to

Items ^ Collapse all `object`

Product label

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

`description*` ^ Collapse all `string`

Description

`availableFor` ^ Collapse all `integer`

Available for

`givesMembership*` ^ Collapse all `integer`

Type of membership this product gives

`debited` ^ Collapse all `boolean`

Whether the booking was debited or not

`numberOfProducts` ^ Collapse all `integer`

Number of products of the booking

Example `{"id":1,"status":0,"start":"2024-02-28T13:56:00Z"}`

DataOrganization ^ Collapse all object

Organization

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

DataPassageTry ^ Collapse all object

Passage try event data

id* ^ Collapse all integer

Id of the passage-try

time* ^ Collapse all string date-time

When the passage try occurred

result* ^ Collapse all integer

Result of the passage-try. Non-zero value means it was unsuccessful

newVisit* ^ Collapse all boolean

True if BRP counted this as a new visit

message ^ Collapse all string

A descriptive message of the passage-try

person ^ Collapse all object

The person who tried to pass

id* ^ Collapse all integer

Unique ID

firstName* ^ Collapse all string

First name

lastName* ^ Collapse all string

Last name

ssn* ^ Collapse all string

Person number (national identification number)

personGroups ^ Collapse all array<object>

Person groups the person belongs to

Items ^ Collapse all object

Person group

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

`email` ^ Collapse all `string`
Email address

`gender` ^ Collapse all `integer`
Gender, 0-male, 1-Female, 3-Other

`memberJoin` ^ Collapse all `string`
Date when the person joined membership

`memberEnd` ^ Collapse all `string`
Date when the person's membership is ending

`staff` ^ Collapse all `boolean`
If the person is a staff member

`businessUnit` ^ Collapse all `object`
The facility the person belongs to

`id*` ^ Collapse all `integer`
Unique ID

`name*` ^ Collapse all `string`
Name

`timeZone*` ^ Collapse all `string`
Time zone. E.g. **Europe/Stockholm**

`mobilePhone` ^ Collapse all `object`
Mobile phone information

`countryCode` ^ Collapse all `string`
Country code. One to three digits. Example: 46

`number` ^ Collapse all `string`
Number in national format. Example: 0701234567

`address` ^ Collapse all `object`
Address

`city` ^ Collapse all `string`
City

`street` ^ Collapse all `string`
Street

`postalCode` `string`

`careOf` `string`

`country` ^ Collapse all `object`

`alpha3` ^ Collapse all `string`
Country code in alpha-3 format. Example: SWE

`organization` ^ Collapse all `object`
Organization the person belongs to

`id*` ^ Collapse all `integer`
Unique ID

`name*` ^ Collapse all `string`

Name

Example

```
{ "id":1, "firstName":"John", "lastName":"Doe", "ssn":"991231-1234", "staff":false, "personGroups":[{"id":1, "name":"Group 1"}, {"id":2, "name":"Group 2"}], "organization":[{"id":1, "name":"My Organization"}]}
```

businessUnit* ^ Collapse all **object**

The business unit where the passage-try occurred

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

timeZone* ^ Collapse all **string**

Time zone. E.g. **Europe/Stockholm**

reader* ^ Collapse all **object**

The reader that handled the passage-try

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

Example

```
{ "id":1, "time":"2023-12-31T23:59:59Z", "result":0, "newVisit":true, "message":"Passage try successful", "person":{"id":1, "firstName":"John", "lastName":"Doe"}, "businessUnit":{"id":1, "name":"My business unit", "timeZone":"Europe/Stockholm"}, "reader":{"id":1, "name":"Entrance door"}}
```

DataPerson ^ Collapse all **object**

Person

id* ^ Collapse all **integer**

Unique ID

firstName* ^ Collapse all **string**

First name

lastName* ^ Collapse all **string**

Last name

ssn* ^ Collapse all **string**

Person number (national identification number)

personGroups ^ Collapse all **array<object>**

Person groups the person belongs to

Items ^ Collapse all **object**

Person group

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

email ^ Collapse all string

Email address

gender ^ Collapse all integer

Gender, 0-male, 1-Female, 3-Other

memberJoin ^ Collapse all string

Date when the person joined membership

memberEnd ^ Collapse all string

Date when the person's membership is ending

staff ^ Collapse all boolean

If the person is a staff member

businessUnit ^ Collapse all object

The facility the person belongs to

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. [Europe/Stockholm](#)

mobilePhone ^ Collapse all object

Mobile phone information

countryCode ^ Collapse all string

Country code. One to three digits. Example: 46

number ^ Collapse all string

Number in national format. Example: 0701234567

address ^ Collapse all object

Address

city ^ Collapse all string

City

street ^ Collapse all string

Street

postalCode string

careOf string

country ^ Collapse all object

alpha3 ^ Collapse all string

Country code in alpha-3 format. Example: SWE

organization ^ Collapse all object

Organization the person belongs to

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

Example

```
{"id":1,"firstName":"John","lastName":"Doe","ssn":"991231-1234","staff":false,"personGroups":[{"id":1,"name":"Group 1"}, {"id":2,"name":"Group 2"}], "organization":[{"id":1,"name":"My Organization"}]}
```

DataProduct ^ Collapse all object

Product

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

givesMembership* ^ Collapse all integer

Type of membership this product gives

DataReader ^ Collapse all object

Reader

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

DataPersonGroup ^ Collapse all object

Person group

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

DataProductLabel ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

DataWorkOut ^ Collapse all object

Work out

id* ^ Collapse all integer

Unique ID

timePoint* ^ Collapse all string date-time

When the work out was created

person* ^ Collapse all object

Person that performed the work out

id* ^ Collapse all integer

Unique ID

firstName* ^ Collapse all string

First name

lastName* ^ Collapse all string

Last name

ssn* ^ Collapse all string

Person number (national identification number)

personGroups ^ Collapse all array<object>

Person groups the person belongs to

Items ^ Collapse all object

Person group

id* ^ Collapse all integer

Unique ID

`name*` ^ Collapse all `string`
Name

`email` ^ Collapse all `string`
Email address

`gender` ^ Collapse all `integer`
Gender, 0-male, 1-Female, 3-Other

`memberJoin` ^ Collapse all `string`
Date when the person joined membership

`memberEnd` ^ Collapse all `string`
Date when the person's membership is ending

`staff` ^ Collapse all `boolean`
If the person is a staff member

`businessUnit` ^ Collapse all `object`
The facility the person belongs to

`id*` ^ Collapse all `integer`
Unique ID

`name*` ^ Collapse all `string`
Name

`timeZone*` ^ Collapse all `string`
Time zone. E.g. [Europe/Stockholm](#)

`mobilePhone` ^ Collapse all `object`
Mobile phone information

`countryCode` ^ Collapse all `string`
Country code. One to three digits. Example: 46

`number` ^ Collapse all `string`
Number in national format. Example: 0701234567

`address` ^ Collapse all `object`
Address

`city` ^ Collapse all `string`
City

`street` ^ Collapse all `string`
Street

`postalCode` `string`

`careOf` `string`

`country` ^ Collapse all `object`

`alpha3` ^ Collapse all `string`
Country code in alpha-3 format. Example: SWE

`organization` ^ Collapse all `object`
Organization the person belongs to

`id*` ^ Collapse all `integer`

Unique ID

name* ^ Collapse all string

Name

Example

```
{"id":1,"firstName":"John","lastName":"Doe","ssn":"991231-1234","staff":false,"personGroups":[{"id":1,"name":"Group 1"}, {"id":2,"name":"Group 2"}], "organization":[{"id":1,"name":"My Organization"}]}
```

businessUnit* ^ Collapse all object

The facility where the work out was performed

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. [Europe/Stockholm](#)

booking ^ Collapse all object

A booking that the work out is connected to

id* ^ Collapse all integer

Unique ID

product* ^ Collapse all object

Product that was booked

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

givesMembership* ^ Collapse all integer

Type of membership this product gives

businessUnit ^ Collapse all object

Business unit that the booking belongs to

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. [Europe/Stockholm](#)

orderBy ^ Collapse all object

Person who made the booking

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

productSubtype* ^ Collapse all integer

Product subtype

noCheckOnDebitedUntil ^ Collapse all boolean

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all array<object>

Product labels the product belongs to

Items ^ Collapse all object

Product label

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

description* ^ Collapse all string

Description

availableFor ^ Collapse all integer

Available for

givesMembership* ^ Collapse all integer

Type of membership this product gives

debited ^ Collapse all boolean

Whether the booking was debited or not

numberOfProducts ^ Collapse all integer

Number of products of the booking

DataSubscription ^ Collapse all object

Subscription

id* ^ Collapse all integer

Unique ID

recruitedBy* ^ Collapse all object

The person that the user of the subscription was referred by

id* ^ Collapse all integer

Unique ID

firstName* ^ Collapse all string

First name

lastName* ^ Collapse all string

Last name

ssn* ^ Collapse all string

Person number (national identification number)

personGroups ^ Collapse all array<object>

Person groups the person belongs to

Items ^ Collapse all object

Person group

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

email ^ Collapse all string

Email address

gender ^ Collapse all integer

Gender, 0-male, 1-Female, 3-Other

memberJoin ^ Collapse all string

Date when the person joined membership

memberEnd ^ Collapse all string

Date when the person's membership is ending

staff ^ Collapse all boolean

If the person is a staff member

businessUnit ^ Collapse all object

The facility the person belongs to

id* ^ Collapse all integer

Unique ID

name* ^ Collapse all string

Name

timeZone* ^ Collapse all string

Time zone. E.g. **Europe/Stockholm**

mobilePhone ^ Collapse all object

Mobile phone information

`countryCode` ^ Collapse all `string`

Country code. One to three digits. Example: 46

`number` ^ Collapse all `string`

Number in national format. Example: 0701234567

`address` ^ Collapse all `object`

Address

`city` ^ Collapse all `string`

City

`street` ^ Collapse all `string`

Street

`postalCode` `string`

`careOf` `string`

`country` ^ Collapse all `object`

`alpha3` ^ Collapse all `string`

Country code in alpha-3 format. Example: SWE

`organization` ^ Collapse all `object`

Organization the person belongs to

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

Example

```
{ "id": 1, "firstName": "John", "lastName": "Doe", "ssn": "991231-1234", "staff": false, "personGroups": [ { "id": 1, "name": "Group 1" }, { "id": 2, "name": "Group 2" } ], "organization": [ { "id": 1, "name": "My Organization" } ] }
```

`created*` ^ Collapse all `string` `date-time`

When the subscription was created

`start` ^ Collapse all `string` `date-time`

Start time point of the subscription

`end` ^ Collapse all `string` `date-time`

End time point of the subscription

`debitedUntil` ^ Collapse all `string` `date-time`

Time point that the subscription is debited until

`product` ^ Collapse all `object`

Product of the subscription

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

`productSubtype*` ^ Collapse all `integer`

Product subtype

noCheckOnDebitedUntil ^ Collapse all `boolean`

If true, no need to verify debitedUntil when entering

productLabels ^ Collapse all `array<object>`

Product labels the product belongs to

Items ^ Collapse all `object`

Product label

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

description* ^ Collapse all `string`

Description

availableFor ^ Collapse all `integer`

Available for

givesMembership* ^ Collapse all `integer`

Type of membership this product gives

users ^ Collapse all `array<object>`

Users of the subscription

Items ^ Collapse all `object`

Person

id* ^ Collapse all `integer`

Unique ID

firstName* ^ Collapse all `string`

First name

lastName* ^ Collapse all `string`

Last name

ssn* ^ Collapse all `string`

Person number (national identification number)

personGroups ^ Collapse all `array<object>`

Person groups the person belongs to

Items ^ Collapse all `object`

Person group

id* ^ Collapse all `integer`

Unique ID

name* ^ Collapse all `string`

Name

email ^ Collapse all `string`

Email address

gender ^ Collapse all `integer`

Gender, 0-male, 1-Female, 3-Other

`memberJoin` ^ Collapse all `string`
Date when the person joined membership

`memberEnd` ^ Collapse all `string`
Date when the person's membership is ending

`staff` ^ Collapse all `boolean`
If the person is a staff member

`businessUnit` ^ Collapse all `object`
The facility the person belongs to

`id*` ^ Collapse all `integer`
Unique ID

`name*` ^ Collapse all `string`
Name

`timeZone*` ^ Collapse all `string`
Time zone. E.g. `Europe/Stockholm`

`mobilePhone` ^ Collapse all `object`
Mobile phone information

`countryCode` ^ Collapse all `string`
Country code. One to three digits. Example: 46

`number` ^ Collapse all `string`
Number in national format. Example: 0701234567

`address` ^ Collapse all `object`
Address

`city` ^ Collapse all `string`
City

`street` ^ Collapse all `string`
Street

`postalCode` `string`

`careOf` `string`

`country` ^ Collapse all `object`
`alpha3` ^ Collapse all `string`
Country code in alpha-3 format. Example: SWE

`organization` ^ Collapse all `object`
Organization the person belongs to

`id*` ^ Collapse all `integer`
Unique ID

`name*` ^ Collapse all `string`
Name

Example

```
{
  "id": 1,
  "firstName": "John",
  "lastName": "Doe",
  "ssn": "991231-1234",
  "staff": false,
  "personGroups": [
    {
      "id": 1,
      "name": "Group 1"
    },
    {
      "id": 2,
      "name": "Group 2"
    }
  ],
  "organization": [
    {
      "id": 1,
      "name": "My Organization"
    }
  ]
}
```

businessUnit* ^ Collapse all **object**
The facility where the subscription was purchased

id* ^ Collapse all **integer**
Unique ID

name* ^ Collapse all **string**
Name

timeZone* ^ Collapse all **string**
Time zone. E.g. **Europe/Stockholm**

payer ^ Collapse all **object**
The payer of the subscription

id* ^ Collapse all **integer**
Unique ID

firstName* ^ Collapse all **string**
First name

lastName* ^ Collapse all **string**
Last name

ssn* ^ Collapse all **string**
Person number (national identification number)

personGroups ^ Collapse all **array<object>**
Person groups the person belongs to

Items ^ Collapse all **object**
Person group

id* ^ Collapse all **integer**
Unique ID

name* ^ Collapse all **string**
Name

email ^ Collapse all **string**
Email address

gender ^ Collapse all **integer**
Gender, 0-male, 1-Female, 3-Other

memberJoin ^ Collapse all **string**
Date when the person joined membership

memberEnd ^ Collapse all **string**
Date when the person's membership is ending

staff ^ Collapse all **boolean**
If the person is a staff member

businessUnit ^ Collapse all **object**
The facility the person belongs to

id* ^ Collapse all **integer**
Unique ID

name* ^ Collapse all **string**

Name

timeZone* ^ Collapse all **string**

Time zone. E.g. **Europe/Stockholm**

mobilePhone ^ Collapse all **object**

Mobile phone information

countryCode ^ Collapse all **string**

Country code. One to three digits. Example: 46

number ^ Collapse all **string**

Number in national format. Example: 0701234567

address ^ Collapse all **object**

Address

city ^ Collapse all **string**

City

street ^ Collapse all **string**

Street

postalCode **string**

careOf **string**

country ^ Collapse all **object**

alpha3 ^ Collapse all **string**

Country code in alpha-3 format. Example: SWE

organization ^ Collapse all **object**

Organization the person belongs to

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

Example

```
{ "id": 1, "firstName": "John", "lastName": "Doe", "ssn": "991231-1234", "staff": false, "personGroups": [ { "id": 1, "name": "Group 1" }, { "id": 2, "name": "Group 2" } ], "organization": [ { "id": 1, "name": "My Organization" } ] }
```

contractCancelDay ^ Collapse all **string** **date-time**

The day when the termination is done.

terminationReason ^ Collapse all **object**

If the subscription is terminated, the reason for the termination

id* ^ Collapse all **integer**

Unique ID

name* ^ Collapse all **string**

Name

DataTerminationReason ^ Collapse all **object**

Termination reason

`id*` ^ Collapse all `integer`

Unique ID

`name*` ^ Collapse all `string`

Name

DataPhone ^ Collapse all `object`

Phone

`countryCode` ^ Collapse all `string`

Country code. One to three digits. Example: 46

`number` ^ Collapse all `string`

Number in national format. Example: 0701234567

DataAddress ^ Collapse all `object`

Address

`city` ^ Collapse all `string`

City

`street` ^ Collapse all `string`

Street

`postalCode` `string`

`careOf` `string`

`country` ^ Collapse all `object`

`alpha3` ^ Collapse all `string`

Country code in alpha-3 format. Example: SWE