2025 International Conference on Future Telecommunications and Artificial Intelligence (IC-FTAI), Alexandria, Egypt

Unveiling the Quantum Realm: A Comprehensive Analysis of Quantum Computing

Salma Mostafa A. Helmy
Software Engineering Department,
Faculty of Computer and Information Science,
Ain Shams University,
Cairo, Egypt,
salma.mostafa@cis.asu.edu.eg

Salsabil A. El-Regaily
Basic Sciences Department,
Faculty of Computer and Information Sciences,
Ain Shams University
Cairo, Egypt,
salsabil_amin@cis.asu.edu.eg

Abeer M. Mahmoud
Computer Science Department,
Faculty of Computer and Information Sciences,
Ain Shams University,
Cairo, Egypt,
abeer.mahmoud@cis.asu.edu.eg

El-Sayed M. El-Horbaty
Computer Science Department,
Faculty of Computer and Information Sciences,
Ain Shams University,
Cairo, Egypt,
shorbaty@cis.asu.edu.eg

***Abstract*—Quantum computing represents a paradigm shift from classical computation, harnessing the principles of quantum mechanics to process information in fundamentally new ways. This paper provides a comprehensive analysis of the field, beginning with its theoretical underpinnings. It elucidates the core concepts of qubits, superposition, and entanglement, which collectively enable quantum computers to perform computations that are intractable for even the most powerful classical supercomputers. The discussion then transitions to the physical architecture of these machines, exploring various hardware implementations, the role of quantum gates and circuits, and the significance of landmark quantum algorithms. The concept of quantum advantage is examined as a critical milestone in the field's development. Subsequently, the paper surveys the potential applications of quantum computing across diverse industries, including drug discovery, materials science, cryptography, and financial modeling, highlighting its transformative potential. Finally, it addresses the significant challenges and limitations that currently impede the realization of large-scale, fault-tolerant quantum computers, such as decoherence, scalability, and algorithm development. By synthesizing the theoretical foundations, current technological state, future applications, and prevailing challenges, this paper offers a holistic overview of quantum computing, charting its trajectory from a theoretical curiosity to a disruptive technology poised to redefine the boundaries of science and industry.**

Keywords— Quantum Computing ,Qubits ,Superposition ,Entanglement ,Quantum Algorithms ,Decoherence ,Quantum Error Correction ,Quantum Advantage,NISQ (Noisy Intermediate-Scale Quantum) ,Shor's Algorithm ,Grover's Algorithm .

I. INTRODUCTION

The quest to solve computationally intractable problems, such as simulating complex molecular interactions or breaking modern cryptographic standards, signals that classical computation[24][26] is approaching its fundamental limits. This boundary necessitates a paradigm shift to quantum computing, a revolutionary domain that harnesses the laws of quantum mechanics specifically superposition and entanglement to process information in radically new ways. This technology is quickly evolving from a theoretical concept into a disruptive engineering endeavor, demanding a single, cohesive analysis that synthesizes its foundational principles, current technological state, and long-term roadmap. The purpose of this paper is to bridge the gap between this foundational theory and the practical reality of building and utilizing quantum machines, offering a complete picture of the field's immense potential and the significant hurdles that must be overcome.

While many excellent papers have explored specific facets of quantum computing, from the theoretical underpinnings to a single hardware modality or application, this work provides a comprehensive and holistic analysis that synthesizes these disparate areas into a single, cohesive overview. Our key contribution lies in providing a unified lens to assess the entire ecosystem. We first synthesize the theoretical concepts with current physical architectures, such as the Ion-Trap systems [12], before charting the technological state by examining the critical milestone of quantum advantage [13]. Furthermore, we detail the applications—from factoring large numbers using Shor's Algorithm [9] to accelerating drug discovery—while simultaneously providing a deep dive into the most pressing engineering challenge: achieving fault-tolerance. This is addressed by detailing the necessity of robust quantum error correction, including the concepts behind Surface Codes [8] and the general theory of error-correcting codes [10], which are crucial steps toward realizing a universal quantum computer [11].

To logically present this complex ecosystem, the paper is organized into a progression that moves from theory to application and challenge. We begin in **Section 2** by establishing the theoretical foundations rooted in quantum mechanics, detailing the essential concepts of qubits, superposition, and entanglement. **Section 3** then transitions to the physical architecture and operation of quantum machines, examining various hardware implementations, quantum circuits, and landmark algorithms. Subsequently, **Section 4** surveys the transformative applications across diverse industries, from drug discovery to cybersecurity. Finally, **Section 5** addresses the significant challenges—such as decoherence, scalability, and quantum error correction—that must be overcome to realize the full potential of this technology, leading into the summary and future outlook provided in the Conclusion (**Section 6**).

979-8-3315-5842-0/25/$31.00 ©2025 IEEE

2025 International Conference on Future Telecommunications and Artificial Intelligence (IC-FTAI) | 979-8-3315-5842-0/25/$31.00 ©2025 IEEE | DOI: 10.1109/IC-FTAI67960.2025.11384159

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:35:03 UTC from IEEE Xplore. Restrictions apply.

II. Theoretical Foundations of Quantum Computing

The extraordinary capability of quantum computing derives not from improved transistors or enhanced classical logic but from a departure into the principles of quantum mechanics. Developed in the early twentieth century, quantum mechanics describes atomic and subatomic phenomena that behave probabilistically rather than deterministically. Quantum computing harnesses these principles, embedding them into computation through concepts such as qubits, superposition, entanglement, and measurement. These theoretical foundations establish the framework for how information can be encoded and manipulated in a fundamentally new way[19][20].

A. The Quantum Mechanical Postulates

Quantum computing relies directly on the postulates of quantum mechanics, which provide the mathematical framework for describing quantum systems. The first postulate states that the state of an isolated quantum system can be represented by a vector in a Hilbert space. For a qubit, this space is two-dimensional with basis vectors $|0\rangle$ and $|1\rangle$. The second postulate specifies that the evolution of a closed system is described by a unitary transformation, meaning quantum operations are reversible and probability-preserving. In practice, these transformations correspond to quantum gates, which manipulate qubit states to perform computations.

The third and fourth postulates concern measurement. Each measurable property corresponds to an operator whose eigenvalues represent possible outcomes. Measurement collapses a quantum state to one of these outcomes with a probability determined by its amplitude. This collapse is probabilistic, distinguishing quantum computation from classical models[25][27], and introduces challenges in designing algorithms that can extract useful results reliably.

B. The Qubit: Beyond the Classical Bit

The qubit generalizes the binary classical bit. While a bit exists only as 0 or 1, a qubit can be in either state or in a linear combination (superposition) of both. Mathematically, the state is expressed as

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle, \quad (1)$$

where α and β are complex amplitudes with

$$|\alpha|^2 + |\beta|^2 = 1 \quad (2)$$

Upon measurement, the qubit collapses to $|0\rangle$ or $|1\rangle$ with probabilities determined by these amplitudes [1].

This property allows quantum registers to represent an exponential number of states. Whereas N classical bits encode one binary string at a time, N qubits can represent 2^N states simultaneously. This exponential scaling underpins the potential of quantum computing to solve problems otherwise intractable on classical machines as illustrate in table 1.

TABLE 1: COMPARISON OF CLASSICAL AND QUANTUM COMPUTING PARADIGMS

Feature	Classical Computing	Quantum Computing
Fundamental Unit	Bit (0 or 1)	Qubit (0, 1, or a superposition of both)
State	Definite; can only be in one state at a time.	Can exist in a superposition of multiple states simultaneously.
Processing	Operations are performed on one state at a time.	Operations are performed on all possible states simultaneously (due to superposition).
Logic Gates	Based on classical logic (AND, OR, NOT).	Based on quantum gates (Hadamard, CNOT, etc.).
Memory	Stored in physical devices like transistors and capacitors.	Stored in quantum systems like trapped ions or superconducting circuits.
Mathematical Basis	Boolean algebra and binary arithmetic.	Linear algebra and complex vector spaces.
Key Principle	Operates on the principles of classical physics.	Operates on the principles of quantum mechanics (superposition and entanglement).
Parallelism	Achieved through multiple processors.	Achieved inherently through superposition.
Error Correction	Redundancy and simple bit flips.	More complex due to fragile states; requires advanced quantum error correction codes.
Problem Solving	Excellent for most tasks; struggles with complex optimization and factorization.	Potentially revolutionary for specific, complex problems (e.g., drug discovery, cryptography).

C. Superposition: A Multi-State Existence

Superposition allows qubits to exist in multiple states until measured, akin to a spinning coin that represents both heads and tails before it lands. With N qubits, a quantum system can occupy a superposition of 2^N possible states. Algorithms exploit this property through quantum parallelism, applying operations across all states simultaneously.

However, quantum algorithms must ensure that when the system is measured, the probability distribution favors correct results. This is achieved by interference: undesired outcomes destructively interfere while correct outcomes constructively reinforce [3]. Thus, algorithm design requires carefully orchestrating superpositions to maximize useful results[23].

D. Entanglement: "Spooky Action at a Distance"

Entanglement, described by Einstein as "spooky action at a distance," is a unique quantum phenomenon where two or more qubits share correlations regardless of spatial separation. For example, in the Bell state $(|00\rangle + |11\rangle)/\sqrt{2}$, (1) neither qubit has a definite state, but their outcomes are perfectly correlated.

Entanglement enables non-classical correlations vital for quantum information processing. Multi-qubit gates such as the CNOT generate entanglement and form the backbone of quantum circuits. This phenomenon is central to the efficiency of Shor's factoring algorithm and Grover's search algorithm, which rely on such correlations for computational speedups[21].

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:35:03 UTC from IEEE Xplore. Restrictions apply.

E. Quantum Measurement and Decoherence

Measurement collapses a qubit into a definite classical outcome, eliminating superposition. Since full quantum states cannot be directly observed, algorithms must be repeated to sample probability distributions.

Decoherence represents a major challenge. Environmental interactions act as unintended measurements, destroying fragile superposition and entanglement [1]. Coherence time defines how long a qubit can resist decoherence. Engineering progress focuses on extending coherence times and implementing error correction techniques to protect qubits from environmental noise. Without overcoming decoherence, the theoretical power of quantum computing remains unattainable[22].

III. Architecture and Operation of Quantum Computers

Quantum computers embody these theoretical principles in hardware and operational frameworks. Their architecture requires novel implementations for qubits, control mechanisms, and error mitigation. Central aspects include physical realization of qubits, quantum gates, algorithms, and milestones like quantum advantage.

A. Comparative Analysis of Quantum Hardware Vendors

The commercial landscape is defined by key vendors leveraging different physical platforms, leading to a trade-off in performance metrics such as qubit count and coherence time. For example, major players like IBM (Superconducting), IonQ (Trapped Ions), and Rigetti (Superconducting) are at the forefront of development, each emphasizing a different strength in their architecture , as illustrate in table 2.

TABLE 2: COMPARATIVE ANALYSIS OF LEADING QUANTUM HARDWARE PLATFORMS

Vendor	Qubit Implementation	Representative Qubit Count	Representative Coherence Time (T1)	Gate Fidelity (Typical 2-Qubit)	Key Advantage	Recent Road Map Goal
IBM	Superconducting Circuits	>1,000	~100 µs	~99.0%	Highest Qubit Count, Scalability	Fault-tolerant Quantum-Centric Supercomputer (2029) [16]
IonQ	Trapped Ions	~32 (Algorithmic Qubits)	~seconds	>99.9%	Highest Gate Fidelity, Longest Coherence	Modular, Networked Systems with High AQ (2025+) [17]
Rigetti	Superconducting Circuits	~80	~10 µs	~98.5%	Cloud Access, Interconnect Research	100+ Qubit System with improved 2Q Fidelity (2025) [18]

These benchmarks illustrate the physical trade-offs: Superconducting platforms like IBM prioritize large-scale integration (high qubit count) but struggle with coherence time, while Trapped-Ion systems like IonQ offer superior fidelity and coherence but currently lag in raw qubit numbers. The race is to find the optimal balance among these metrics to achieve fault tolerance.

B. Physical Implementations of Qubits

Unlike standardized silicon transistors, qubits can be realized in multiple physical forms. Common approaches include superconducting circuits, trapped ions, and photonic systems, each with strengths and weaknesses.

Superconducting qubits, fabricated from materials like aluminum or niobium and cooled to cryogenic temperatures, represent one of the most mature platforms. They benefit from fast gate operations and compatibility with semiconductor manufacturing, making them scalable. However, coherence times remain short due to sensitivity to noise [3].

Trapped-ion qubits exploit the stable electronic energy levels of ions suspended in electromagnetic traps. They achieve exceptionally long coherence times and high-fidelity gates [6]. Their limitation lies in slower gate speeds and the difficulty of scaling up large arrays of ions.

Photonic qubits encode information in properties of photons such as polarization. They are robust against decoherence and suitable for quantum communication. However, challenges include reliable single-photon sources and efficient two-photon interactions.

Other platforms, including neutral atoms and quantum dots, are also being pursued. Each presents trade-offs among scalability, stability, and operational complexity, and hybrid architectures may ultimately combine multiple modalities.

C. Quantum Gates and Circuits

Quantum gates are the unitary operations that manipulate qubits. Single-qubit gates include the Pauli-X gate, analogous to the classical NOT, and the Hadamard gate, which creates equal superpositions. On the Bloch sphere, these gates correspond to specific rotations.

Multi-qubit gates such as the CNOT create entanglement, enabling universal quantum computation. A universal gate set, combining Hadamard, phase, and CNOT gates, can approximate any operation.

Quantum circuits arrange qubits and gates into sequences that transform an input state into a measurable output. Because measurements yield probabilistic results, algorithms must often be repeated to estimate correct outcomes reliably. Efficient circuit design, minimizing gate counts and noise, is a central software challenge as shown in figure 1.

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:35:03 UTC from IEEE Xplore. Restrictions apply.



Fig.1. A visual representation of a qubit's state on the Bloch Sphere.

D. *Prominent Quantum Algorithms*

Quantum algorithms exploit unique phenomena to outperform classical counterparts.

- Shor's Algorithm (1994): Uses quantum Fourier transforms to factor integers exponentially faster than classical methods. This threatens RSA and ECC cryptography [5].
- Grover's Algorithm: Provides a quadratic speedup for unstructured search, solving problems in √N steps instead of N [1].
- Variational Quantum Eigensolver (VQE): A hybrid algorithm for simulating molecular ground states. It uses quantum processors to prepare states and classical optimizers to minimize energy, making it suitable for noisy intermediate-scale quantum (NISQ) devices.

These algorithms demonstrate that quantum computing offers problem-specific advantages rather than universal superiority.

E. *The Concept of Quantum advantage*

Quantum advantage refers to achieving a computational task infeasible for classical supercomputers. Google's 2019 demonstration with the 53-qubit Sycamore processor claimed such a milestone by executing random circuit sampling in 200 seconds, a task estimated to require 10,000 years on a classical machine [2].

Though debated, this achievement validated the experimental feasibility of quantum advantage. Current efforts now aim to demonstrate useful quantum advantage for real-world problems, requiring advances in both hardware and algorithms.

IV. Applications and Future Prospects

Quantum computing's unique capabilities position it to disrupt numerous domains. Its main strengths lie in simulation, optimization, and cryptography.

A. *Potential Applications Across Industries*

Pharmaceuticals and healthcare could benefit from accurate molecular simulations to accelerate drug discovery. In materials science, quantum simulations may enable catalysts and superconductors with transformative properties. Optimization algorithms could improve aerospace logistics, automotive design, and supply chain efficiency. In artificial intelligence, quantum machine learning explores how quantum resources may accelerate training and enable new forms of pattern recognition.

B. *Drug Discovery and Materials Science*

Quantum computers directly simulate molecular behavior, a task classical supercomputers approximate only at prohibitive cost. VQE and similar algorithms may predict binding affinities and reaction pathways, reducing the time and cost of drug development [4].

In materials science, quantum simulations can guide the design of efficient catalysts, energy storage systems, and superconductors. These applications promise significant industrial and environmental benefits.

C. *Cryptography and Quantum Security*

Shor's algorithm threatens classical cryptography by efficiently factoring large numbers [5]. This creates urgency for post-quantum cryptography (PQC), which develops classical algorithms secure against both quantum and classical attacks. In addition to algorithm development, physics-based solutions are also being pursued.

Quantum key distribution (QKD) offers physics-based security. By encoding information in quantum states of photons, QKD protocols detect eavesdropping due to the no-cloning theorem and measurement disturbance. Despite challenges of implementation, QKD promises provably secure communications.

D. *Financial Modeling and Optimization Problems*

Finance depends on complex optimization and risk modeling. Quantum algorithms such as QAOA and quantum Monte Carlo may enhance portfolio optimization, derivative pricing, and risk simulations. These improvements could enable more accurate financial decisions in uncertain markets.

V. Challenges, Limitations, and the Road Ahead

Despite progress, several obstacles impede large-scale quantum computing.

A. *The Challenge of Decoherence and Error Correction*

Qubits are highly sensitive to environmental noise, leading to decoherence [7]. Error correction is essential but resource-intensive, often requiring thousands of physical qubits to encode a single logical qubit [9]. The feasibility of building a fault-tolerant universal quantum computer relies on the Quantum Error Correction Threshold Theorem. This theorem states that a universal, fault-tolerant quantum computer can be built if the error rate of the physical quantum gates is below a certain critical threshold (often estimated to be around 10^{-3} to 10^{-4}). Below this threshold, adding more physical qubits to encode a logical qubit results in a net decrease in the logical error rate, effectively overcoming decoherence and noise.

Quantum error correction codes, such as surface codes, can detect and correct errors through indirect measurements, but

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:35:03 UTC from IEEE Xplore. Restrictions apply.

achieving the fidelity necessary for large-scale error correction remains an engineering challenge [8].

B. *Scalability and Manufacturing Hurdles*

Scaling quantum processors requires integrating millions of qubits. Superconducting qubits face wiring and cryogenics challenges, while trapped ions encounter slower gate speeds and complexity at large ion counts [11][12].
Interconnects for linking processors are another critical need. Photonic interfaces and quantum transduction may enable modular architectures capable of scaling to practical fault-tolerant systems [8].

C. *Software and Algorithm Development*

Algorithmic progress lags behind hardware. Classical redundancy does not apply to quantum systems due to the no-cloning theorem. While landmark algorithms exist, most require fault-tolerant devices [13].
NISQ-era algorithms such as VQE and QAOA combine classical optimization with quantum state preparation, but challenges like barren plateaus remain [14]. Robust programming languages (Qiskit, Cirq, Q#) and compilers are essential for bridging high-level problems to low-level machine operations.

D. *The Future Trajectory of Quantum Computing*

The near future lies in NISQ devices, which may yield early applications in chemistry and optimization [15]. Medium-term goals include achieving stable logical qubits via quantum error correction. Long-term ambitions envision universal, fault-tolerant quantum computers capable of transformative impact.
Global collaboration among academia, industry, and governments will be vital for overcoming scientific and engineering barriers.

VI. Conclusion

Quantum computing departs from classical paradigms by leveraging superposition, entanglement, and measurement. These phenomena enable exponential parallelism and unique computational correlations that power algorithms such as Shor's and Grover's.
Applications span medicine, materials science, cybersecurity, and finance. Yet realizing this promise requires overcoming decoherence, error correction, and scalability challenges. The current results, exemplified by the rapid growth in qubit count and the demonstration of quantum advantage, confirm the fundamental feasibility of the technology, but the heterogeneous hardware landscape (Superconducting vs. Trapped Ion systems) illustrates that no single platform has yet achieved the optimal balance of scale and fidelity for universal fault-tolerant computation. The necessity of the QEC threshold theorem means current efforts must intensely focus on increasing gate fidelity alongside qubit count.The NISQ era represents an exploratory phase where noisy hardware is tested for practical value as represent in figure 2.



Fig. 2. A generalized quantum roadmap schematic depicting the future trajectory of quantum computing. The top graph shows the projected exponential growth in the number of qubits, with key milestones such as the "Quantum advantage Demo" and the eventual advent of "Commercial Quantum Computers" noted along the timeline. The bottom graph illustrates the critical trend of decreasing error rates (decoherence) necessary for achieving large-scale, fault-tolerant quantum systems.

The long-term vision is a fault-tolerant universal quantum computer. Achieving it demands interdisciplinary collaboration across physics, engineering, and computer science. While the path forward is uncertain, the transformative potential of quantum computing ensures it will remain a central focus of twenty-first-century technological progress.

REFERENCES

[1] M. A. Nielsen and I. L. Chuang, *Quantum Computation and Quantum Information*. Cambridge University Press, 2010.

[2] R. P. Feynman, "Simulating physics with computers," *Int. J. Theor. Phys.*, vol. 21, pp. 467–488, 1982.

[3] P. W. Shor, "Algorithms for quantum computation: Discrete logarithms and factoring," in *Proc. 35th Annu. Symp. Foundations of Computer Science*, 1994, pp. 124–134.

[4] A. Aspuru-Guzik, A. D. Dutoi, P. J. Love, and M. Head-Gordon, "Simulated quantum computation of molecular energies," *Science*, vol. 309, no. 5741, pp. 1704–1707, 2005.

[5] L. K. Grover, "A fast quantum mechanical algorithm for database search," in *Proc. 28th Annu. ACM Symp. Theory of Computing (STOC)*, 1996, pp. 212–219.

[6] H. Häffner, C. F. Roos, and R. Blatt, "Quantum computing with trapped ions," *Phys. Rep.*, vol. 469, no. 4, pp. 155–203, 2008.

[7] W. H. Zurek, "Decoherence and the transition from quantum to classical—Revisited," *Los Alamos Science*, vol. 27, pp. 2–25, 2002.

[8] A. G. Fowler, M. Mariantoni, J. M. Martinis, and A. N. Cleland, "Surface codes: Towards practical large-scale quantum computation," *Phys. Rev. A*, vol. 86, no. 3, p. 032324, 2012.

[9] P. W. Shor, "Scheme for reducing decoherence in quantum computer memory," *Phys. Rev. A*, vol. 52, no. 4, R2493, 1995.

[10] A. Steane, "Error correcting codes in quantum theory," *Phys. Rev. Lett.*, vol. 77, no. 5, p. 793, 1996.

[11] J. M. Martinis, "Qubit metrology for building a fault-tolerant quantum computer," *npj Quantum Inf.*, vol. 1, p. 15005, 2015.

[12] D. Kielpinski, C. Monroe, and D. J. Wineland, "Architecture for a large-scale ion-trap quantum computer," *Nature*, vol. 417, pp. 709–711, 2002.

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:35:03 UTC from IEEE Xplore. Restrictions apply.

[13] S. Aaronson, “The limits of quantum computers,” *Sci. Am.*, vol. 298, no. 3, pp. 62–69, 2008.

[14] J. R. McClean, J. Romero, R. Babbush, and A. Aspuru-Guzik, “The theory of variational hybrid quantum-classical algorithms,” *New J. Phys.*, vol. 18, no. 2, p. 023023, 2016.

[15] J. Preskill, “Quantum Computing in the NISQ era and beyond,” *Quantum*, vol. 2, p. 79, 2018.

[16] IBM Quantum. (2024/2025 Update). IBM Quantum Roadmap: A path to quantum-centric supercomputing and fault-tolerance. Accessed:october 2025.

[17] IonQ. (2024/2025 Update). IonQ Forte Enterprise Specifications and Algorithmic Qubit Benchmarks. Accessed: october 2025.

[18] Rigetti Computing. (2024/2025 Update). Ankaa-2 Processor and Fidelity Improvements: Investor Presentation/Technical Report. Accessed: october 2025.

[19] E. Chae, J. Choi, and J. Kim, “An elementary review on basic principles and developments of qubits for quantum computing,” Journal of Nano Convergence 11, 11 (2024).

[20] M. A. Shafique, A. Munir and I. Latif, "Quantum Computing: Circuits, Algorithms, and Applications," in *IEEE Access*, vol. 12, pp. 22296-22314, 2024, doi: 10.1109/ACCESS.2024.3362955.

[21] R. Horodecki, P. Horodecki, M. Horodecki, and K. Horodecki, “Quantum entanglement,” *Reviews of Modern Physics*, vol. 81, no. 2, pp. 865–942, 2009.

[22] M. Schlosshauer, “Decoherence, the measurement problem, and interpretations of quantum mechanics,” *Reviews of Modern Physics*, vol. 76, no. 4, pp. 1267–1305, 2004.

[23] L. Hardy, “Quantum theory from five reasonable axioms,” *Physical Review A*, vol. 63, no. 1, p. 012108, 2001.

[24] S. Abbas and A. M. Mahmoud, "Deep learning-aided brain tumor detection: An initial experience based cloud framework," Indonesian Journal of Electrical Engineering and Informatics, vol. 8, no. 4, pp. 770-780, 2020.

[25] A. M. Mahmoud, F. Alrowais, and H. Karamti, "A hybrid deep contractive autoencoder and restricted Boltzmann machine approach to differentiate representation of female brain disorder," Procedia Computer Science, vol. 176, pp. 1-10, 2020.

[26] S. M. A. Helmy, A. M. Amar, and E. M. El-Horabty, Internet of Things (IoT) based smart device for cardiac patients monitoring using Blynk App,International Journal of Informatics and Computer Science, 22, 2022. DOI: 10.21608/ijicis.2022.139226.1182.

[27] S. M. A. Helmy, M. Alfonse, A. M. Amar and E. -S. M. El-Horbaty, "Internet of Things (IoT) for cardiac patients: A comparative study," *2021 Tenth International Conference on Intelligent Computing and Information Systems (ICICIS)*, Cairo, Egypt, 2021, pp. 297-302, doi: 10.1109/ICICIS52592.2021.9694181.

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:35:03 UTC from IEEE Xplore. Restrictions apply.