Quantum Optimization for Network Capacity Expansion of Microgrid Models via Grover-Enhanced QAOA

Giulio Pisaneschi
Department of Information Engineering
University of Pisa
Pisa, Italy
giulio.pisaneschi@phd.unipi.it

Davide Poli
DESTEC
University of Pisa
Pisa, Italy
davide.poli@unipi.it

Davide Fioriti
DESTEC
University of Pisa
Pisa, Italy
davide.fioriti@unipi.it

2026 IEEE 23rd Mediterranean Electrotechnical Conference (MELECON) | 979-8-3315-2684-9/26/$31.00 ©2026 IEEE | DOI: 10.1109/MELECON64486.2026.11418844

***Abstract*—We propose a compact, application-driven instantiation of the Quantum Approximate Optimization Algorithm (QAOA) for constrained combinatorial network expansion problem for a typical microgrid. The approach pairs a Grover-style feasibility-aware mixer with an observable diagonal cost and a pragmatic grid + refine parameter search that respects the discrete nature of amplitude-amplification steps while optimising continuous phase angles. Benchmarked against a classical global solver on an instance derived from a PyPSA model and evaluated via noiseless statevector simulation and sampling, the method demonstrably elevates the quantum probability mass on the true classical optimum and improves the signal-to-noise ratio inside the feasible subspace. We discuss algorithmic trade-offs and outline promising directions for parameterisation and hardware validation.**

***Index Terms*—Quantum computing, microgrid, network planning, Mixed-Integer Linear Programming**



Fig. 1. The proposed procedure

I. Introduction

Design, operation and resilience of microgrids demand solving combinatorial configuration problems that jointly decide equipment sizing and topology under physical and economic constraints [1]–[3]. These problems are typically cast as mixed-integer programs and solved with mature classical solvers. However, as microgrids grow in complexity and as near-real-time reconfiguration becomes desirable, there is rising interest in alternative paradigms that can rapidly produce high-quality feasible design options [4], [5].

Quantum variational algorithms, and in particular the Quantum Approximate Optimization Algorithm (QAOA), appear as promising frameworks, yet still underexplored [6]. By preparing parameterised quantum states whose measurement statistics are biased toward low-cost solutions, QAOA can in principle explore combinatorial spaces, such as those of microgrid network expansion problems, with different trade-offs than classical local search [7], [8].

In this work we propose and empirically validate a compact, practically-oriented QAOA instantiation tailored to constrained design problems typical of microgrids. Our key design choices are (i) an explicit feasibility-aware mixer based on Grover amplitude amplification that concentrates amplitude on the small feasible subspace [9], [10], (ii) a diagonal cost observable that keeps the objective embedding transparent and interpretable, and (iii) a pragmatic grid + refine optimisation workflow that respects the discrete nature of Grover iterations while continuously tuning phase angles. We benchmark the method on an 11-variable instance derived from a PyPSA microgrid model and compare it directly to a Gurobi global optimum: despite the modest problem size, the experiments demonstrate that the Grover-mixer QAOA elevates the true classical optimum from a vanishing uniform background to substantial empirical probability at attainable circuit depth. The contribution of this paper is therefore twofold: we introduce a principled algorithmic recipe for combining feasibility amplification with phase-based cost discrimination, and we provide a reproducible numerical case study that quantifies the potential and limitations of this approach as a practical tool for microgrid configuration.

II. Methods

The procedure adopted in this study is summarized in Figure 1 and described in detail in the following.

Starting from a PyPSA model of a small distribution network we (i) solve the corresponding mixed-integer formulation with a classical MILP solver to obtain a reference optimum

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:36:48 UTC from IEEE Xplore. Restrictions apply.



Fig. 2. Scheme of the system.

and to enumerate feasible binary assignments, (ii) encode the objective as a diagonal cost observable on n qubits, which is solved through QAOA, and (iii) construct a Grover-style oracle that marks exactly the classically feasible states.

QAOA is a hybrid optimisation routine that produces samples from a tunable probability distribution over candidate (binary) solutions. One implements a short, parameterised procedure that alternates two simple operations: a *cost step* that biases the procedure toward lower-objective candidates, and a *mixing step* that redistributes probability mass so the search can explore alternatives. A classical optimiser adjusts the few parameters that control these steps to increase the likelihood of good solutions; after optimisation, the procedure is sampled repeatedly and the best observed candidates are reported. This compact cycle (prepare $\rightarrow$ evaluate $\rightarrow$ update) is the high-level template we instantiate with a Grover-style mixer in our methods.

A. Description of the PyPSA network and MILP formulation.

We model in PyPSA a minimal but representative distribution network, composed of a number ($N = 3$) of buses $B_0, ...B_n$, connected by a set of branches $L_{i,j}$ with candidate generators located in a subset of buses (e.g. B_0) and a fixed (optional) load at each bus (Figure 2).

The decision problem is formulated as a mixed-integer linear program with eleven binary variables that encode modular capacity choices, conductor types and whether local loads are connected. Importantly, the pairs of binary variables that describe generation and line capacity are *additive levels* rather than mutually exclusive alternatives: for the generator at B_0 the variables $G_{0,B0}$ and $G_{1,B0}$ represent two incremental capacity units whose sum $G_{0,B0} + 2G_{1,B0}$ determines the total dispatchable capacity available at that node (i.e. selecting $G_{0,B0} = 1, G_{1,B0} = 1$ corresponds to a capacity of $1 + 2 = 3$ units). The same modular logic applies to each line L_{ij}: the binaries $b_0^{L_{ij}}$ and $b_1^{L_{ij}}$ represent small and large discrete capacity increments whose linear combination $b_0^{L_{ij}} + 2b_1^{L_{ij}}$ sets the branch capacity chosen by the optimiser. Variables $z_{L_{ij}}$ are conductor-type selectors (for example standard vs. upgraded conductor), and $s_{B_k} \in \{0, 1\}$ indicate whether the fixed load at bus B_k is connected (served) or intentionally shed.

The objective function trades installation/upgrade costs against the benefit of serving loads and is written as

$$\min\ G_{0,B0} + 2G_{1,B0} - 5\sum_{k=0}^{2} s_{B_k} + 6\, z_{L_{0-1}} + 1 \cdot z_{L_{1-2}}, \tag{1}$$

where the negative coefficient on s-variables encodes a reward (or avoided penalty) for serving demand, while positive coefficients on the G and z terms model installation or upgrade costs. Network feasibility and local balance are enforced by linear constraints that couple generation levels, outgoing branch capacities and served load; for instance at bus B_0 the power balance reads

$$G_{0,B0} + 2G_{1,B0} - b_0^{L_{0-1}} - 2b_1^{L_{0-1}} - s_{B_0} = 0, \tag{2}$$

and analogous equalities propagate downstream to B_1 and B_2. Conductor selectors are linked to the chosen branch capacity through inequalities of the form

$$b_0^{L_{ij}} + 2b_1^{L_{ij}} - 3\, z_{L_{ij}} \leq 0, \tag{3}$$

which force $z_{L_{ij}} = 1$ whenever any non-zero capacity increment is selected (i.e. if the model activates either b-level the corresponding upgraded conductor must also be chosen). All decision variables are binary, producing a compact combinatorial design problem that jointly captures sizing (modular increments), topology (which loads are served) and equipment type choices. The MILP is solved to global optimality with Gurobi; the optimal configuration for the instance studied is the binary vector `11110111011` (interpreted according to the variable order $[G_{0,B0}, G_{1,B0}, b_0^{L_{0-1}}, b_1^{L_{0-1}}, z_{L_{0-1}}, b_0^{L_{1-2}}, b_1^{L_{1-2}}, z_{L_{1-2}}, s_{B_0}, s_{B_1}, s_{B_2}]$) with objective value -5. This Gurobi solution is used as the ground truth benchmark when assessing the QAOA-based heuristics.

B. Construction of the cost Hamiltonian.

To encode a classical linear cost function in a variational quantum algorithm, one uses a diagonal Hamiltonian whose expectation values on computational-basis states reproduce the classical cost [11]. Preparing the Hamiltonian's exact ground state thus yields the solution to the original optimization problem [6]. Let the classical cost be written in the standard linear form

$$C(\mathbf{b}) \;=\; \sum_{i=0}^{n-1} c_i\, b_i \;+\; C_0, \qquad b_i \in \{0, 1\}, \tag{4}$$

where c_i are real coefficients (positive or negative), C_0 is an optional constant offset and $\mathbf{b}$ is the binary decision vector. The Pauli-Z operator provides a convenient map between a qubit observable and a classical bit via the relation

$$b_i \;=\; \frac{1 - Z_i}{2}, \tag{5}$$

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:36:48 UTC from IEEE Xplore. Restrictions apply.

because the eigenvalues of Z_i are $+1$ (for $|0\rangle$) and -1 (for $|1\rangle$). Substituting this mapping yields the operator form of the cost:

$$\hat{H}_C = \sum_i c_i \frac{1 - Z_i}{2} + C_0 I = \Big(C_0 + \tfrac{1}{2}\sum_i c_i\Big) I + \sum_i \Big(-\tfrac{c_i}{2}\Big) Z_i. \tag{6}$$

Hence, up to an overall additive constant, the Hamiltonian is a linear combination of single-qubit Z-terms: each classical coefficient c_i contributes a Pauli-Z term with weight $-c_i/2$. The expectation value $\langle\psi|\hat{H}_C|\psi\rangle$ on a state $|\psi\rangle$ is therefore an affine re-scaling of the expected classical cost computed from the bit probabilities $p_i = \Pr(b_i = 1) = (1 - \langle Z_i\rangle)/2$.

In the implementation used for the experiments, the cost structure is specified by the coefficient vector (corresponding to the eleven binary decision variables in the order described in II-A):

$$\mathbf{c} = [\,1,\ 2,\ 0,\ 0,\ 6,\ 0,\ 0,\ 1,\ -5,\ -5,\ -5\,]. \tag{7}$$

Applying the canonical mapping above would produce Pauli-Z weights $-\frac{1}{2}\mathbf{c}$:

$$-\tfrac{1}{2}\mathbf{c} = [\,-0.5,\ -1.0,\ 0,\ 0,\ -3.0,\ 0,\ 0,\ -0.5,\ 2.5,\ 2.5,\ 2.5\,]. \tag{8}$$

The code then constructs a diagonal SparsePauliOp by placing a single-qubit Z on each qubit with the chosen weight and adding an explicit identity offset (in the code the identity term is set to $+15$). Concretely the operator assembled in the experiments takes the form

$$\hat{H}_{\text{impl}} = 15I + \sum_{i=0}^{10} a_i Z_i\ ,\ a = [1, 2, 0, 0, 6, 0, 0, 1, -5, -5, -5], \tag{9}$$

i.e. the implementation inserts the raw coefficient vector $\mathbf{a} = \mathbf{c}$ as weights on the Z-terms and compensates with a positive identity shift. We use an identity offset of $+15$, equal to $|\min \mathbf{c}| = 15$ (the only negative entries in $\mathbf{c}$ are three occurrences of -5); this guarantees the classical cost spectrum is shifted to nonnegative values with minimum 0. Shifting the Hamiltonian to be nonnegative (≥ 0) is numerically convenient, since it prevents large relative negative energies that induce extraneous global phases during phase-separator evolutions. Given the linear relation between $\langle Z_i\rangle$ and the outcome probabilities p_i, the expected classical cost and $\langle\hat{H}_{\text{impl}}\rangle$ are affinely related and can be converted when comparing quantum expectations with classical objective values. As $\hat{H}_{\text{impl}}$ is diagonal in the computational basis, its eigenvalues correspond directly to classical costs

C. The Grover-based mixer.

The use of a Grover-style mixer is motivated by a small, highly constrained feasible subset within a much larger discrete design space: with n binary variables the search space has size 2^n (here $n = 11$, so $2^n = 2048$). Let $\mathcal{F}$ denote the bit-strings satisfying the linear network constraints; typically $|\mathcal{F}| \ll 2^n$ for these combinatorial design problems, since many assignments violate capacity, balance, or equipment-linking constraints. When the feasible fraction

$$f = \frac{|\mathcal{F}|}{2^n} \tag{10}$$

is small, a transverse-field mixer (which spreads amplitude uniformly to Hamming neighbours) wastes amplitude on infeasible states unless the variational parameters concentrate on $\mathcal{F}$. By contrast, a Grover-style mixer employs an oracle that marks feasible states with a phase flip followed by a diffusion (reflection) step to amplify their amplitudes, directly targeting the feasible subspace and mitigating the principal combinatorial bottleneck.

Formally, we define the diagonal oracle O by $O\,|x\rangle = (-1)^{\mathbf{1}_{x\in\mathcal{F}}}\,|x\rangle$, which flips the phase of feasible states, and the diffusion operator

$$D = 2\,|s\rangle\,\langle s| - I, \qquad |s\rangle = \frac{1}{\sqrt{2^n}} \sum_{x\in\{0,1\}^n} |x\rangle\,. \tag{11}$$

The Grover iterate is $G = D\,O$. When initialized in the uniform superposition $|\psi_0\rangle$, repeated applications of G generate dynamics confined to the two-dimensional subspace spanned by the normalized uniform superpositions of feasible and infeasible states.

To make the mechanism completely explicit, consider a tiny toy instance with $n_{qubits} = 3$ qubits (so $2^{n_{qubits}} = 8$ basis states). Start from the uniform superposition

$$|\psi_0\rangle = \frac{1}{\sqrt{8}} \sum_{x\in\{0,1\}^3} |x\rangle\,, \qquad \alpha_0 \equiv \frac{1}{\sqrt{8}} \approx 0.35355339 \tag{12}$$

so every basis state has the same amplitude α_0. Pick a single marked (feasible) bitstring, e.g. $|m\rangle = |101\rangle$. We now apply (i) the oracle O that flips the sign of the marked state and (ii) the diffusion (inversion-about-the-mean) operator D. The sequence and arithmetic are:

1) **Initial amplitudes.** For all basis states x, $\alpha_x^{(0)} = \alpha_0$. In particular, for the marked state $\alpha_m^{(0)} = \alpha_0$.
2) **Oracle action O.** The oracle multiplies the amplitude of the marked state by -1:
$$\alpha_m^{(1)} = -\alpha_0 \quad \text{and} \quad \alpha_{x\neq m}^{(1)} = \alpha_0.$$
3) **Compute the mean amplitude after the oracle.** With seven unmarked amplitudes equal to α_0 and one marked amplitude $-\alpha_0$,
$$\mu = \frac{1}{8}\Big(7\alpha_0 + (-\alpha_0)\Big) = \frac{6}{8}\alpha_0 = 0.75\,\alpha_0 \approx 0.26516504.$$
4) **Diffusion action D.** The diffusion operator reflects each amplitude about the mean:
$$\alpha_x^{(2)} = 2\mu - \alpha_x^{(1)}.$$
For the marked state:
$$\alpha_m^{(2)} = 2\mu - (-\alpha_0) = 2(0.75\alpha_0) + \alpha_0 = 2.5\alpha_0 \approx 0.8839,$$
while for any unmarked state u:
$$\alpha_u^{(2)} = 2\mu - \alpha_0 = 1.5\alpha_0 - \alpha_0 = 0.5\alpha_0 \approx 0.17677670.$$

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:36:48 UTC from IEEE Xplore. Restrictions apply.

Converting amplitudes to probabilities yields the numerical effect of one full Grover iterate $G = D\,O$:

$$P_{\text{marked}} = |\alpha_m^{(2)}|^2 \approx (2.5\alpha_0)^2 = 2.5^2 \cdot \frac{1}{8} = 0.78125,$$

$$P_{\text{each unmarked}} = |\alpha_u^{(2)}|^2 \approx (0.5\alpha_0)^2 = 0.5^2 \cdot \frac{1}{8} = 0.03125.$$

Thus a single Grover iteration raises the probability of the target bitstring $|101\rangle$ from the uniform $1/8 \approx 12.5\%$ to $\approx 78.1\%$, while the probability mass on each non-marked string falls from $\approx 12.5\%$ to $\approx 3.1\%$.

This numeric sketch shows the elementary mechanism: the oracle imprints a π phase on marked amplitudes (sign flip), and the diffusion reflects all amplitudes about their mean, which, due to the sign flip, results in constructive interference on marked states and destructive interference on unmarked ones.

In the QAOA hybridisation used here the Grover operator plays the role of the mixer: each QAOA layer alternates a phase separator $U_C(\gamma) = \exp(-i\gamma\hat{H}_C)$, which imprints cost-dependent phases across all computational basis states, with a controlled number β of Grover iterations that enhance the mass on feasible states before the next phase step. This design has two important practical consequences for our setting. Since the oracle marks feasibility rather than objective quality, the Grover mixer preserves the feasible subspace $\mathcal{F}$: amplitude entering $\mathcal{F}$ is unlikely to leak back under subsequent mixing. The phase separator then differentiates feasible candidates by rotating their phases according to cost, directing amplitude toward low-cost feasible solutions. Thus, Grover amplification enhances the signal-to-noise ratio (feasible versus infeasible mass) enabling effective phase-separation.

In our implementation β is interpreted as a discrete number of Grover iterations, which makes the optimization landscape non-smooth with respect to β and complicates gradient-based continuous optimisation; this explains the grid-plus-refine strategy adopted in the experiments.

D. QAOA implementation.

The Quantum Approximate Optimization Algorithm (QAOA) is a hybrid variational algorithm designed to produce high-quality candidate solutions to combinatorial optimization problems by alternating two kinds of quantum operations. Starting from a simple reference state (typically the uniform superposition), QAOA applies —in each of p layers— a *phase separator* that imprints problem-dependent phases, followed by a *mixer* that redistributes amplitude across the computational basis. The two families of parameters, commonly denoted $\boldsymbol{\gamma} = (\gamma_1, \ldots, \gamma_p)$ for the phase separators and $\boldsymbol{\beta} = (\beta_1, \ldots, \beta_p)$ for the mixers, are chosen by a classical optimiser to minimise the expected value of the cost function measured on the final quantum state.

Formally, with an n-qubit cost Hamiltonian $\hat{H}_C$ diagonal in the computational basis, the idealised QAOA state after p layers is

$$|\psi(\boldsymbol{\beta}, \boldsymbol{\gamma})\rangle = \Big(\prod_{\ell=1}^{p} U_M(\beta_\ell)\, U_C(\gamma_\ell) \Big)\, H^{\otimes n}\, |0\rangle^{\otimes n}, \qquad (13)$$

where $U_C(\gamma) = e^{-i\gamma\hat{H}_C}$ and $U_M(\beta)$ denotes the chosen mixer. In standard QAOA, $U_M(\beta) = \exp(-i\beta \sum_i X_i)$ (a transverse-field mixer), whereas in our approach $U_M(\beta)$ is implemented by a *Grover-based block*: the mixer is the Grover operator G raised to an integer power, $U_M(\beta) = G^{r(\beta)}$, where $r(\beta)$ is interpreted as the number of Grover iterations to perform in that layer.

In plain language, the phase separator $U_C(\gamma)$ makes low-cost candidate solutions distinguishable by imprinting different relative phases on them; the Grover-based mixer then selectively amplifies (increases the amplitude of) those basis states that are declared *feasible* by the oracle.

Our concrete implementation choices and optimisation strategy are tuned to this design and to practicalities observed in simulation:

- **Initial state.** We initialize the uniform superposition $H^{\otimes n}\,|0\rangle^{\otimes n}$, assigning equal amplitude to every bitstring. This provides the natural starting point for amplitude amplification by placing non-zero amplitude on all feasible solutions.
- **Parametrisation of β.** Rather than treating β as a continuous rotation angle, we interpret each β_ℓ as an *integer* number of Grover iterations r_ℓ in layer ℓ. Since the Grover iterate represents one unit of amplitude amplification, discrete counting is natural. This creates a *non-smooth* optimization landscape: small changes in β_ℓ crossing an integer threshold alter circuit depth and the unitary qualitatively.
- **Parametrisation of γ.** The phase-separator angles γ_ℓ are continuous parameters (in the interval $(0, \pi]$) and are optimised with standard continuous optimisers. These angles tune how strongly the cost Hamiltonian differentiates among feasible candidates.
- **Grid + refine optimisation.** To address the mixed discrete–continuous search space, we adopt a two-stage strategy. First, we perform a coarse *grid search* over discrete β-vectors, sweeping plausible Grover iteration counts per layer and evaluating QAOA expected cost with default γ. Second, we *refine* the best grid points by optimizing only the γ-parameters via L-BFGS-B with fixed β. This separates discrete search from continuous tuning, respecting the integer nature of Grover iterations while remaining computationally efficient.
- **Penalty term enforcing feasible mass.** Since feasibility is central to solution quality, we incorporate a soft constraint rewarding high probability on feasible states. Let $m_{\mathcal{F}}(\boldsymbol{\beta}, \boldsymbol{\gamma})$ denote the *feasible mass*, i.e., total probability assigned to $\mathcal{F}$. Our optimization objective is

  $$\mathcal{L}(\boldsymbol{\beta}, \boldsymbol{\gamma}) = \mathbb{E}_{|\psi(\boldsymbol{\beta},\boldsymbol{\gamma})\rangle}\big[C(\mathbf{b})\big] + \lambda \cdot \max\big(0, \tau - m_{\mathcal{F}}(\boldsymbol{\beta}, \boldsymbol{\gamma})\big),$$

  where $\mathbb{E}[C]$ is the expected cost, τ is a target threshold (we use $\tau = 0.95$), and λ is a penalty coefficient (we use $\lambda = 100$). This steers optimization toward low expected cost with substantial feasible probability: the penalty vanishes when $m_{\mathcal{F}} \geq \tau$ and grows linearly otherwise. The threshold ensures near-complete concentration on feasible

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:36:48 UTC from IEEE Xplore. Restrictions apply.

states, while λ prioritizes feasibility without precluding cost improvements within $\mathcal{F}$.

- **Evaluation and measurement.** Each parameter set is evaluated by simulating the QAOA circuit statevector to obtain exact amplitudes, converting them to probabilities, and computing expected cost as $\sum_x p(x)C(x)$. For this analysis, we draw $N_{\text{shots}} = 5000$ samples from the simulated distribution to estimate empirical frequencies, feasible mass, and probability of the classical optimum.

This strategy exploits Grover amplification for feasibility focusing while preserving continuous phase-separator tunability for cost discrimination. The grid stage addresses the non-smooth, combinatorial β-search; the refinement stage exploits gradient-friendly γ-structure. The feasible-mass penalty ensures practical usability by guiding the search toward parameter regions where the quantum state predominantly occupies $\mathcal{F}$.

E. Simulation details and rationale.

All circuits are executed in a noiseless statevector simulator (Qiskit Aer `AerSimulator` with `method="statevector"`) to obtain exact amplitudes [12]. This provides two advantages: (i) access to the full statevector enables exact computation of $\mathbb{E}[C] = \sum_x p(x)C(x)$ from $p(x) = |\langle x|\psi\rangle|^2$, and (ii) it isolates algorithmic performance from hardware noise, appropriate for initial comparison against classical optima.

Circuits are transpiled at Qiskit `optimization_level=1` to reduce gate redundancies while preserving Grover block structure, balancing efficiency and algorithmic fidelity. Each parameter set is simulated by saving the statevector and deriving exact probabilities; we then draw $N_{\text{shots}} = 5000$ samples to estimate empirical frequencies, feasible mass $m_{\mathcal{F}}$, and probability of the classical optimum. This shot count provides stable frequency estimates for percent-level events while remaining computationally efficient for repeated evaluations during optimization.

Two clarifications aid interpretation. First, noiseless simulation means empirical frequencies reflect only sampling error, so reported feasible/exact masses represent algorithmic upper bounds that hardware noise may degrade. Second, expectation values are computed from the statevector for exact reference, while sampling mimics realistic readout statistics and produces counts-based metrics comparable to experiments.

III. Experimental studies

We focus on the classical optimum `11110111011` (cost -5) under Grover-mixer QAOA with varying depths and parameter strategies. At depth 1, the optimum already appears among the most probable outcomes ($p_{\text{exact}} \approx 0.0166$), showing that even shallow circuits place non-negligible weight on the global optimizer. At 2 layers the algorithm redistributes amplitude and the mode of the distribution becomes a different feasible candidate (`01101000110` with $p \approx 0.0678$); the exact optimum is not the strongest peak in that run, indicating that adding a layer can refocus amplitude onto other low-cost feasibles. Crucially, at 3 layers the exact classical optimum re-emerges with substantially larger support ($p_{\text{exact}} \approx 0.1730$) and sits essentially tied with the top empirical outcome (`00000000000` with $p \approx 0.1750$). At 4 layers the exact-solution probability falls again to $p_{\text{exact}} \approx 0.1172$ while other feasible strings retain or gain mass (top-1 probability rises to $p \approx 0.2090$).

This sequence is informative for two reasons. First, the persistent presence of the classical optimum across multiple layer settings (nonzero weight already at 1 layer and dominant weight at 3 layers) demonstrates that the Grover-mixer QAOA is not merely discovering arbitrary feasible states but repeatedly keeps the true optimal configuration within the support of the prepared state. That behaviour is a positive indicator of algorithmic fidelity: the combined action of feasibility-marking (oracle) and cost-dependent phase rotations is capable of steering amplitude toward the known global minimum. Second, the non-monotonic evolution of p_{exact} with depth highlights characteristic trade-offs of variational quantum heuristics on constrained problems: increasing depth expands expressiveness and can enable much stronger concentration on desired solutions (as for the 3-layer case), but it also makes the optimisation landscape more intricate (especially because our β parameters correspond to integer counts of Grover iterations). Thus depth can both help and hinder depending on whether the discrete choices of Grover iterations and the continuous phase angles align to produce constructive interference on the optimal bitstring.

Taken together, these observations support a constructive interpretation of the numerical campaign. The fact that the exact optimum attains its largest observed empirical probability at a modest circuit depth (3 layers) is encouraging: it shows that the Grover-mixer architecture can, with an attainable circuit size and with the grid+refine parameter search employed, amplify the correct solution from among a large set of feasibles. The cases where a different feasible candidate becomes dominant (e.g. 2 and 4 layers) do not negate the value of the approach; rather they expose inherent sensitivity to parameter choices and the discrete nature of Grover steps. Our results demonstrate (i) that feasibility-focused mixing preserves and enhances the feasible subspace so phase-separators can discriminate among viable candidates, and (ii) that a practical mixed search strategy (coarse grid for integer β, followed by continuous refinement of γ) is effective at locating configurations where the optimal solution receives substantial probability mass.

IV. Discussion

The empirical campaign provides a compact but compelling demonstration that a feasibility-focused QAOA construction — combining a Grover-style mixer, a diagonal cost Hamiltonian and a pragmatic grid+refine search for parameters — can meaningfully elevate the standing of a true classical optimum in the quantum output distribution. Concretely, the Gurobi reference solution `11110111011` (cost $= -5$) is present with non-zero weight already at minimal depth and reaches its largest observed empirical probability (approximately 0.173)

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:36:48 UTC from IEEE Xplore. Restrictions apply.

TABLE I
EMPIRICAL PROBABILITIES OF THE CLASSICAL OPTIMAL CONFIGURATION 11110111011 ACROSS QAOA RUNS WITH VARYING LAYER COUNTS (VALUES TAKEN FROM LOGS; SAMPLING $N_{\text{shots}} = 5000$).

# QAOA layers	Empirical p_{exact}	Short comment
1	0.0166	The global optimum is present already at minimal depth (small but non-zero weight).
2	not among top-5	The exact optimum is not among the reported top outcomes for this run (amplitude redistributed to a different feasible candidate).
3	0.1730	The optimum re-emerges with large support (peak observed close to the top empirical outcome). This is the strongest amplification recorded.
4	0.1172	Probability of the optimum decreases relative to 3 layers, while other feasible strings gain mass (non-monotonic behaviour).

for a modest depth of three QAOA layers, showing that the ansatz and the optimisation strategy are capable of concentrating amplitude on the global minimiser from an initially vanishing uniform background. It is important to acknowledge the reasons why performance is not purely monotonic: circuit depth increases expressivity but also introduces a more intricate mixed discrete–continuous optimisation landscape (in our case β is treated as an integer count of Grover iterations), and the experiments are run in a noiseless statevector simulator on a compact 11-qubit instance — conditions which highlight the algorithmic behaviour but do not directly capture noise-limited hardware effects or scaling challenges. These characteristics, however, should be read as diagnostic insights rather than failures: the sensitivity to depth and discrete Grover counts clarifies precisely where improvements in parameterization, smoother mixers or more targeted search heuristics will play a crucial role. Importantly, across runs the Grover mixer consistently preserves and amplifies the feasible subspace so that the phase-separator can discriminate among viable candidates; this pattern (low initial support $\rightarrow$ targeted amplification $\rightarrow$ high support at attainable depth) is the operational phenomenon we set out to achieve and it is observed in the data. In short, despite the necessarily limited scope of the present experiments, our results validate the central thesis of the work: a mixer that explicitly targets feasibility materially improves the signal-to-noise ratio for constrained combinatorial optimization inside QAOA and provides a practical, testable pathway for future work aimed at scaling and hardware validation.

V. CONCLUSION

We presented a compact but novel instantiation of QAOA that combines a Grover-style feasibility-aware mixer with a diagonal cost Hamiltonian and a pragmatic grid + refine parameter search, and demonstrated its effectiveness on an 11-qubit design instance derived from a PyPSA model. The main contributions are (i) the principled use of amplitude amplification to elevate a small feasible subspace, (ii) an optimisation workflow that respects the discrete nature of Grover iterations while tuning continuous phase angles, and (iii) a direct benchmarking against a Gurobi global optimum, showing substantial amplification of the true optimum at modest circuit depth. The strengths of our work lie in its clear demonstration that feasibility-focused mixing materially improves the signal-to-noise ratio for constrained combinatorial problems, in the transparency and reproducibility of the methodology, and in the diagnostic value of the observed non-monotonic behaviour which points to concrete refinements. Overall, the results provide a persuasive proof of concept and a practical recipe for follow-up investigations into parametrisations, smoother mixers and eventual hardware execution.

REFERENCES

[1] G. S. Thirunavukkarasu, M. Seyedmahmoudian, E. Jamei, B. Horan, S. Mekhilef, and A. Stojcevski, "Role of optimization techniques in microgrid energy management systems—a review," *Energy Strategy Reviews*, vol. 43, p. 100899, 2022.

[2] S. M. Dawoud, X. Lin, and M. I. Okba, "Hybrid renewable microgrid optimization techniques: A review," *Renewable and Sustainable Energy Reviews*, vol. 82, pp. 2039–2052, 2018.

[3] K. Gao, T. Wang, C. Han, J. Xie, Y. Ma, and R. Peng, "A review of optimization of microgrid operation," *Energies*, vol. 14, no. 10, p. 2842, 2021.

[4] F. A. Kassab, B. Celik, F. Locment, M. Sechilariu, S. Liaquat, and T. M. Hansen, "Optimal sizing and energy management of a microgrid: A joint milp approach for minimization of energy cost and carbon emission," *Renewable Energy*, vol. 224, p. 120186, 2024.

[5] F. F. Nicolosi, J. C. Alberizzi, C. Caligiuri, and M. Renzi, "Unit commitment optimization of a micro-grid with a milp algorithm: Role of the emissions, bio-fuels and power generation technology," *Energy Reports*, vol. 7, pp. 8639–8651, 2021.

[6] E. Farhi, J. Goldstone, and S. Gutmann, "A quantum approximate optimization algorithm," *arXiv preprint arXiv:1411.4028*, 2014.

[7] K. Blekos, D. Brand, A. Ceschini, C.-H. Chou, R.-H. Li, K. Pandya, and A. Summer, "A review on quantum approximate optimization algorithm and its variants," *Physics Reports*, vol. 1068, pp. 1–66, 2024.

[8] J. Choi and J. Kim, "A tutorial on quantum approximate optimization algorithm (qaoa): Fundamentals and applications," in *2019 international conference on information and communication technology convergence (ICTC)*. IEEE, 2019, pp. 138–142.

[9] A. Bärtschi and S. Eidenbenz, "Grover mixers for qaoa: Shifting complexity from mixer design to state preparation," in *2020 IEEE International Conference on Quantum Computing and Engineering (QCE)*. IEEE, 2020, pp. 72–82.

[10] G. Brassard, P. Hoyer, M. Mosca, and A. Tapp, "Quantum amplitude amplification and estimation," *arXiv preprint quant-ph/0005055*, 2000.

[11] A. Lucas, "Ising formulations of many np problems," *Frontiers in physics*, vol. 2, p. 5, 2014.

[12] A. Javadi-Abhari, M. Treinish, K. Krsulich, C. J. Wood, J. Lishman, J. Gacon, S. Martiel, P. D. Nation, L. S. Bishop, A. W. Cross, B. R. Johnson, and J. M. Gambetta, "Quantum computing with Qiskit," 2024.

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 20:36:48 UTC from IEEE Xplore. Restrictions apply.