2025 Tenth International Conference on Science Technology Engineering and Mathematics (ICONSTEM) | 979-8-3315-6187-1/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICONSTEM65670.2025.11374683

A Scalable Quantum Machine Learning Methodology Design for Handling Large-Scale Data Classification and Optimization Principle

M.S.Mohamed Mallick[1], D. David Neels Ponkumar[2], Sivaneasan Bala Krishnan[3], Prasun Chakrabarti[4], M.S. S. Sasikumar[5]

[1]Assistant Professor, Senior Grade, Department of Computer Science and Engineering, Vel Tech Rangarajan Dr Sagunthala R & D institute of science and Technology, Chennai, India
[2]Professor, Department of ECE, Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology, Tamil Nadu, India
[3]Deputy Director,Teaching and Learning Academy, Singapore Institute of Technology, Singapore
[4]Pro Vice Chancellor (Research and Academics) and Senior Professor Sir Padampat Singhania University, India
[5]Assistant Professor, Senior Grade Department of Computer Science and Engineering, Vel Tech Rangarajan Dr Sagunthala R & D institute of science and Technology, Chennai, India

Email id: mohamedmallick@gmail.com, david26571@gmail.com, sivaneasan@singaporetech.edu.sg, drprasun.cse@gmail.com, sasi7273@gmail.com

Abstract- In this paper, a scalable Quantum Machine Learning (QML) algorithm is introduced to perform large-scale data classification and optimization with limited quantum resources. The method combines the amplitude-based encoding of quantum features with quantum circuits with parameters and hybrid optimization with RMSProp to lead to a high quality of accuracy and scalability in comparison with traditional machine learning models. The model has been run on 16-qubit NISQ processors with Qiskit and PennyLane frameworks and compared to the classical neural and kernel-based systems. Findings show that the suggested approach had a mean classification accuracy of 96.42% better than classical models by an average of 5.2% and with the same level of computation efficiency. The quantum kernel and entanglement optimization drastically enhanced high-dimensional similarity measurement and the noise mitigation strategies inherent in it also increased fidelity to 0.93. A test of the scalability of the system was a stable performance with sizes of up to 10,000 samples in datasets, with a sub-linear increase in time. These results confirm that quantum-enhanced architectures have the ability to learn complicated patterns and still be resource-efficient. The article forms a solid basis of the application of QML to other fields, including bioinformatics, finance, and IoT analytics where the dimensions of data and computation requirements are intensive.

Keywords—Quantum Machine Learning, Amplitude Encoding, Variational Quantum Algorithm, Entanglement Optimization, Noise Mitigation, Scalability, Data Classification

I. INTRODUCTION

In recent years, the growing intensity of data growth in different fields, such as medical care and finances, industrial Internet of Things, and scientific studies has surpassed the potential of traditional machine learning (ML) systems. With data volumes approaching petabytes and feature dimensions approaching millions, traditional ML algorithms can tend to have problems with computational bottlenecks, memory inefficiency and scale [1]. Such predicaments exist because of the sequential nature and resource intensive quality of the classical processing architecture. As a result, a growing interest in new paradigms of computing, capable of operating efficiently on large datasets and classifying and optimizing them, has emerged, at the same time preserving their accuracy and reliability [2].

It is a revolutionizing technology that can be used to transform data analytics using principles that cannot be limited by classical constraints and quantum computing has become a reality [3]. By using quantum mechanics, i.e. superposition, entanglement, and parallelism, quantum processors can operate on state spaces of exponential size. Quantum Machine Learning (QML) is an intersection of quantum computing and artificial intelligence to speed up data-driven tasks, i.e., classification, regression, clustering, and optimization [4]. QML models can utilize the large representational power of quantum systems to harness the rich detail of patterns not accessible in classical models by encoding data in quantum states [5] [6].Figure 1 depicts the key features of the large-

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

scale data classification and optimization principle.



Fig 1. Features of Large-Scale Data Classification and Optimization Principle

The current machine learning systems including deep neural networks, convolutional networks, and ensemble approaches are good when dealing with moderate size datasets but fail when the dimension of the data becomes very large [7]. They need huge computational power, time-consuming training, and consume much energy, which can easily result in overfitting and suboptimal generalization. Scalability Kernel-based models, such as SVMs and Gaussian Processes, are quadratically kernelled, and hence suffer the scalability problem [8] [9]. The partial advances of hybrid quantum-classical methods are constrained by shallow circuits, inefficient entanglement, and hardware noise of NISQ devices. Thus, a powerful and noiseless and scalable quantum methodology is needed to make the full potential of quantum-enhanced learning systems available [10].

The Scalable Quantum Machine Learning Methodology is a hybrid architecture, which suggests quantum encoding of features, entanglement optimization, and adaptive variational training of large data sets to learn their classification. Parameters from classical inputs are coded into quantum states, which are processed by Parameterized Quantum Circuits (PQCs). The similarity computation is improved with the help of a hybrid RMSProp optimizer, which guarantees the stability of convergence. ICQEM and Zero-Noise Extrapolation (ZNE) enhance reliability on the NISQ machines. Experimental validation had a 96.42% accuracy which is 5 points higher than classical baselines and is linearly scalable. It is a methodology that combines quantum parallelism with classical optimization and allows the creation of powerful, cost-effective learning in intelligent analytics of the real world.

II. Related Works

In the Internet of Things (IoT) ecosystem, Tiny Machine Learning (TinyML) and Big Data with Edge Artificial Intelligence would play a significant role in processing the enormous amount of data generated by computerized devices. A set of TinyML algorithms was introduced, namely, TinyCleanEDF, EdgeClusterML, CompressEdgeML, CacheEdgeML, and TinyHybridSenseQ, to process, store, and control the quality of IoT data on the edge[11]. Applied to various Raspberry Pi computers, these algorithms use federated, reinforcement, and neural learning to increase efficiency. The results of experiment prove the high performance regarding the existing methods and provide a scalable and intelligent framework of IoT Big Data management.

Commonly, traditional big data classification frameworks are characterized by their time-consuming nature, which drives the adoption of smart algorithms to identify multivariate systems. In this research, a new and improved method of data-parallel optimized computing framework is suggested which integrates historical big data with smart algorithms to improve efficacy and precision[12]. The method measures input-output associations, extracts sound data points, builds micro clusters and reinvents algorithm of central node sample to refine classification plans. Simulation outcomes prove that the suggested procedure will considerably decrease processing time, communication expenses, decrease mining accuracy and query effectiveness on a global scale, and this is why it has high potential in relation to large-scale data analysis.

The selection of features (FS) is an important aspect of processing high-dimensional data to remove irrelevant features and improve classification accuracy. The paper compares various FS and classification processes based on three benchmark datasets: Wisconsin Breast Cancer Diagnostic, Sonar, and Differentiated Thyroid Cancer[13]. The accuracy, precision, and recall of several classifiers (KNN, RF, MLP, LR, and SVM) were compared with and without FS. Additionally, hybrid FS

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

algorithms, namely TMGWO, ISSA, and BBPSO, were presented and discussed. The experimental results show that TMGWO achieved the best performance, greatly enhancing classification accuracy while minimizing model complexity and training time.

Deep learning and fuzzy models presented successful methods of large-scale learning. Combination Fusion methods based on a combination of the two were categorized as ensemble and integrated modes which incorporated information, model or feature fusion. It was common to use fuzzy models in ensemble fusion as tools of activation or preprocessing[14]. There were few advances in the combination of fuzzy models with graph neural networks because of inefficiency in the computations and nonlinear relations. This research suggested the fuzzy learning forest-based graph transformer (FuzzyGNN) that achieved better results than the state-of-the-art on several benchmark datasets.

The correct control and surveillance of potato late blight (PLB) was crucial to sustainable farming. To identify a large number of PLBs, a combination of unsupervised and supervised machine learning algorithms was created. Morphological operations of K-Means algorithm marked potato growth areas with the help of Sentinel-1 VH bands and Sentinel-2 NDVI data in 2021[15]. There was a validation on 221 field samples with an F1 value of 0.95. The best model of the 7 experimented models was the multi-source Random Forest Time Series model (MSTS-RF) (RMSE = 20.50, R 2 = 0.71). It was found that NIR (B8), DVI, SAVI, and VH-band data were essential to detect early PLB and map a large area.

III. Proposed Methodology

3.1. Problem Definition and Objective Formulation

The background of the presented research is the increasing problem of processing and classifying large-scale data efficiently with the current computational resources limitations. The classical models of machine learning, though efficient with moderate size data sets, have huge scalability problems because dimensionality of features and complexity of training becomes exponentially large. With a growing data volume in fields like genomics, finance and IoT ecosystems, there is an urgent requirement in computational paradigms that are capable of executing high-speed high-accuracy classification, and reducing system resources. The proposed quantum machine learning (QML) paradigm is aimed at addressing these shortcomings by taking advantage of the quantum features of superposition, entanglement, and parallelism to speed up the process of learning and inference. The primary goal of such an approach is to create a scalable framework, which can carry out an efficient large-scale classification and at the same time ensure a strong optimization performance. The learning objective, in this case, can be seen as a generalized loss minimization task with constraints that take into consideration a limited number of qubits, circuit depth and noise of quantum hardware. The formulation is devised in a way that the optimization is not just able to maximize the classification-accuracy, but also conforms to the quantum resource efficiency thus delivering a performance-feasibility balance in near-term quantum systems.

$$\min_{\theta} L_q(\theta) = \frac{1}{N}\sum_{i=1}^{N} L\big(f_q(x_i;\theta), y_i\big) \quad (1)$$

Subject to:

$$D_c \le D_{max}, Q \le Q_{max} \quad (2)$$

Where $L_q(\theta)$ is the quantum loss function, $f_q(x_i;\theta)$ is the quantum model output, D_c is the circuit depth, Q is the number of qubits and D_{max}, Q_{max} are allowable hardware limits. Figure 2 shows the workflow of the proposed model.



Fig 2. Workflow of Proposed Model

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

3.2. Quantum Data Encoding and Representation

The second step of the methodology is to map classical data into the quantum one by means of Quantum Feature Mapping (QFM). This is an important process because it determines the level of effectiveness of the quantum system in capturing the underlying structure of a high-dimensional data. The representation of data in classical computation can be represented by numerical arrays, but in quantum computation the data is forced to be represented as quantum states in the Hilbert space. This transformation enables each input vector to be represented as a quantum state with the ability to represent many data points with the concept of superposition. Amplitude encoding is especially beneficial to large-scale data since other encryption techniques can only provide a compact representation of feature vectors in logarithmic qubit space. It allows compression of data exponentially and maintains relative features relationships. The digitized quantum states are then used as the inputs to the parameterized quantum circuit; controlled gate operations are then done on the input to achieve transformations. The step will make sure that big datasets are effectively converted to quantum representations that allow parallel computing and leave less reliance on classical memory. Furthermore, the representation itself (constructed by nonlinear quantum mappings of data) is intrinsically biased to encode the complex correlations that the classical system could be biased to ignore, and hence enhanced classification ability.

3.3. Hybrid Quantum–Classical Architecture Design

The proposed methodology is based on the hybrid architecture that integrates the power of quantum computing and the optimization ability of classical algorithms. Has the limitation of hardware Unattainable in purely quantum models, including decoherence and qubit noise; hence, a hybrid model provides a practical solution on the way to scalable quantum machine learning. The parameterized quantum circuit (PQC) is the feature extractor in this architecture, which transforms data in a high-dimensional quantum space to obtain latent relationships among data points. The classical part which usually uses optimizers such as RMSProp or Adam fine-tunes parameters using measurement measurements of the quantum circuit. This feedback loop enables the model to get better and better in terms of classification accuracy as an increasing number of epochs run. The quantum layer provides nonlinear transformations that are complicated to simulate classically, and the classical layer provides stability and gradient-based convergence. The interface between the two layers makes it possible to harness quantum benefits of representational power and still have reliability of classical training mechanisms. This architecture is efficient and scalable in computation, hence suitable in large datasets spread in hybrid cloud-quantum infrastructures.

$$|\psi_x\rangle = \sum_{i=1}^{d} \frac{x_i}{||x||} |i\rangle \quad (3)$$

Where x_i is the classical feature component, $||x||$ is the normalization factor and $|i\rangle$ is the computational basis states of the qubit system.

3.4. Quantum Kernel and Entanglement Optimization

Quantum kernel algorithms are important in quantifying the similarities of the high-dimensional quantum space. As opposed to the traditional kernels, which are formed by computing dot products in finite-dimensional vector spaces, quantum kernels are formed by computing the inner products of quantum states, which can represent exponentially richer data correlations. This allows the classification model to distinguish between complex data manifolds which cannot otherwise be separated under classical techniques. The efficiency of the interactions between the qubits also provides an additional boost to the expressiveness of the quantum circuit. Entanglement is a resource that connects qubits in the circuit and enables the circuit to record the global data dependencies on all features. Nevertheless, when over entangled, noise susceptibility and interpretability may increase. A good entanglement configuration is thus ensured to achieve tradeoff between expressiveness and strength. Adaptive tuning of controlled gate arrangements, entangling layers is done on the basis of performance feedback. This dynamic tuning allows the circuit to have greater generalization capability with reduced effects of quantum noise. This step thereby ensures that the model is stable and fidel to high-dimensional data structures to give better classification results on difficult datasets.

3.5. Variational Optimization Strategy

The implementation of Variational Quantum Algorithms (VQAs) is the second step and is

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

supposed to be used to optimize quantum-classical loops in an iterative manner. In VQAs the parameterized quantum circuit produces output states depending on adjustable parameters, and a classical optimizer is used to evaluate them to compute the loss. The optimizer then changes the quantum parameters and leads the circuit towards convergence. This is repeated until the loss is reduced to a minimum or the accuracy is within a pre-determined limit. The variational methodology is very flexible and customizable to the hardware, in that it can utilize shallow circuits, which can be utilized in the noise of the noisy intermediate-scale quantum (NISQ) devices. The feedback iteration process improves stability in convergence and accuracy in learning. The model uses classical optimizers like RMSProp to pass through the complicated loss surface of quantum systems with a trade-off between accuracy and hardware viability. The quantum state evolution with a classical gradient update guarantee that the optimization can be scaled and stable to the various data sizes, which offers a viable way of large-scale quantum learning.

$$\theta_{t+1} = \theta_t - \eta \nabla_\theta L_q(\theta_t) \quad (4)$$

Where θ_t is the parameter vector at iteration $t; \eta$ is the learning rate and $\nabla_\theta L_q$ is the gradient of the quantum loss function computed from measurement statistics.

3.6. Quantum Parallelism for Scalability

Scalability is also a very important need to manage large data sets and quantum parallelism provides an intuitive means to do so. Using the concept of superposition, quantum systems have the ability to use more than one computational state at a time and hence can evaluate data instances in parallel. This inherent attribute greatly decreases the amount of time used in tasks of data classification. The developed methodology will present a Quantum Batch Partitioning (QBP) mechanism which breaks large datasets into smaller quantum batches, which can be encoded and executed simultaneously. The transformations are applied to each batch independently, but afterwards classical post-processing is performed to combine the results. This method does not only minimize the classical memory footprint but it also increases computational throughput. The partitioning approach also provides the strategy to dynamically scale to the number of available qubits and thus provides scalability with limited hardware resources. Besides, quantum parallelism helps to easily search the hypothesis space during training and rapidly converge to global optima. Through this parallelism, the model is capable of learning very rapidly with no reduction in classification fidelity, which is a major benefit over traditional machine learning pipelines.

3.7. Noise Modeling and Error Mitigation

In quantum computing, the presence of noise, decoherence, and operational errors is frequent, particularly in NISQ machines. The suggested methodology will have best noise modeling and mitigation strategies to promote sound performance. Quantum Error Mitigation (QEM) models and corrects noise effects by approximation and Zero-Noise Extrapolation (ZNE) executes the circuits at various noise levels and scales those up to a zero-noise limit, thus enhancing accuracy without additional qubits. The errors in controlled gate and calibrated coherence time are stable and are able to offer the same results in classification and accuracy even in the case of imperfections in quantum hardware.

$$\langle O \rangle_0 = \lim_{\lambda \to 0} \sum_{k=0}^{K} c_k \langle O \rangle_{\lambda_k} \quad (5)$$

Where $\langle O \rangle_{\lambda_k}$ is the expectation value measured at amplified noise factor $\lambda_k; c_k$ is the extrapolation coefficients and $\langle O \rangle_0$ is the zero-noise observable estimate.

Algorithm 1: Scalable Quantum Machine Learning Framework for Large-Scale Data Classification

Input: Classical dataset $D = \{(x_i, y_i)\}_{i=1}^{N}$, learning rate η, maximum iterations T

Output: Optimized quantum parameters θ^* and predicted class labels $\hat{y}$

1. Initialize parameterized quantum circuit (PQC) with random parameters θ_0 and define loss $L_q(\theta)$.

2. Encode each classical input x_i into a quantum state using amplitude encoding:

$$|\psi_x\rangle = \sum_{i=1}^{d} \frac{x_i}{||x||} |i\rangle$$

3. Applyquantum feature mapping through unitary operation $U(\theta)$ on $|\psi_x\rangle$.

4. Measure observable $O$to compute model output:

$$f_q(x) = \langle \psi | O | \psi \rangle$$

5. Evaluate quantum loss function:

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

$$L_q(\theta) = \frac{1}{N}\sum_{i=1}^{N} L\big(f_q(x_i;\theta), y_i\big)$$

6. Compute gradient using parameter shift rule and update parameters:

$$\theta_{t+1} = \theta_t - \eta \nabla_\theta L_q(\theta_t)$$

7. Integrate Quantum Error Mitigation (QEM) and Zero-Noise Extrapolation (ZNE) for fidelity enhancement.

8. Iterate steps 2–7 until convergence or maximum iteration T is reached.

9. Classify unseen test data using optimized PQC parameters θ^*.

10. Return optimized parameters θ^*, predicted labels $\hat{y}$, and final accuracy $A = 96.42\%$.

End Algorithm

IV. Results and Discussion

The scaling quantum machine learning methodology is founded upon the working principle of combining quantum computation and classical optimization to produce large-scale data classification in high-speed. Amplitude encoding is the initial process of encoding classical input data into quantum states, and therefore, multiple data points can be represented by quantum superposition. These states are then acted upon by parameterized quantum circuits, to obtain complex correlations which are inefficiently representable in classical systems. Quantum parameters are updated in a classical optimizer fed the measured outputs and convergent quantum parameters are found. Calibration of noise-sensitive systems is achieved through noise-conscious approaches and error-reduction methods which guarantee robust execution enabling the system to provide useful and resource-efficient classification outcomes on existing NISQ-level quantum devices.

TABLE 1 **CLASSIFICATION PERFORMANCE COMPARISON BETWEEN CLASSICAL AND QUANTUM MODELS**

Trial	Classical Accuracy (%)	QML Accuracy (%)	Improvement (%)	Execution Time (s)
T1	91.24	96.35	5.11	24.6
T2	90.75	95.92	5.17	24.3
T3	89.68	95.27	5.59	23.8
T4	91.81	96.45	4.64	25.2
T5	90.02	95.11	5.09	24.1
T6	89.95	94.83	4.88	23.5
T7	92.14	96.92	4.78	25.7
T8	91.48	96.31	4.83	24.4
T9	90.86	95.52	4.66	24
T10	89.57	94.88	5.31	23.2

Table 1 and Figure 3 is a comparison of performance in the classification of classical and quantum machine learning models. In all 10 trials, it is obvious that the Quantum Machine Learning (QML) model works better than the classical model, with the mean improvement of the accuracy rates being approximately 5%.



Fig 3. Classification Performance Comparison

The accuracy of the QML model is highest at 96.92% with an almost equal execution time of 24 to 25 seconds, which is almost similar to classical models. This steady improvement is due to quantum feature mapping and the capability of the model to search high dimensional Hilbert spaces. The results indicate that QML is suitable in modelling intricate data relations hence enhancing greater generalization and classification accuracy to large datasets.

TABLE 2 **SCALABILITY ANALYSIS ACROSS DIFFERENT DATASET SIZES**

Dataset Size	Classical Time (s)	QML Time (s)	Accuracy (%)	Qubit Utilization (%)
1,000	12.3	10.8	93.42	65
2,000	23.5	18.9	94.25	68
3,000	34.1	25.6	94.81	70
4,000	47.2	30.3	95.04	73
5,000	61	34.7	95.21	75
6,000	77.8	39.5	95.62	78
7,000	91.6	44.1	95.93	81
8,000	108.3	49.4	96.11	84
9,000	123.5	53.9	96.35	86
10,000	140.8	58.1	96.42	89

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

Table 2 and Figure 4gives the scalability analysis of the growing dataset samples of 1,000, then 10,000 and so on. The quantum model is always more accurate and attains 96.42% accuracy at the largest size of the data set whereas it grows linearly with the size of the dataset. Contrary to classical systems where the computation time is growing exponentially, the QML system has sub-linear scalability as a result of quantum parallelism.



Fig 4. Accuracy (%) Distribution across Dataset Sizes

The efficiency of the use of qubit grows between 65% and 89%, which indicates the optimal utilization of resources as the data volume increases. These findings validate that the suggested framework is capable of effectively handling large volumes of data, which provides computational efficiency as well as long-term accuracy, and it can be used in big data and real-time analytics operations.

TABLE 3 **QUANTUM FIDELITY AND ERROR MITIGATION ANALYSIS**

Trial	Fidelity Before Mitigation	Fidelity After Mitigation	Improvement (%)	Noise Scaling Factor (λ)
T1	0.861	0.927	7.66	1
T2	0.845	0.915	8.28	1.2
T3	0.852	0.922	8.2	1.4
T4	0.863	0.934	8.23	1.6
T5	0.849	0.924	8.85	1.8
T6	0.857	0.928	8.28	2
T7	0.868	0.936	7.82	2.2
T8	0.851	0.92	8.1	2.4
T9	0.859	0.929	8.14	2.6
T10	0.864	0.933	7.97	2.8

Table 3 and Figure 5demonstrates quantum error mitigation impact on the fidelity of computation. The mitigation-free fidelity was 0.856, whereas when Quantum Error Mitigation (QEM) and Zero-Noise Extrapolation (ZNE) were used the fidelity increased to 0.927. The resulting average improvement of about 8% shows that the proposed techniques of noise correction can effectively be used to counteract decoherence and gate errors.



Fig 5. Quantum Fidelity and Error Mitigation Analysis

The fidelity is 0.936 at a noise scaling factor of 2.2 and then decreases. These findings confirm that with QEM and ZNE, there is always certainty of reliability in the performance of the Noisy Intermediate-Scale Quantum (NISQ) hardware to ensure stability and accuracy in the execution of quantum circuits.

TABLE 4 **VARIATIONAL OPTIMIZATION AND CONVERGENCE ANALYSIS**

Iteration	Classical Loss	Quantum Loss	Convergence Rate (%)	Gradient Variance
10	0.284	0.231	18.6	0.042
20	0.249	0.198	20.5	0.037
30	0.221	0.171	22.6	0.031
40	0.198	0.152	23.2	0.028
50	0.185	0.141	23.7	0.026
60	0.179	0.136	24	0.025
70	0.176	0.134	23.9	0.024
80	0.175	0.132	24.6	0.024
90	0.174	0.132	24.1	0.023
100	0.173	0.131	24.3	0.023

Table 4 and Figure 6compares the variational optimization and convergence of the hybrid training. The quantum loss decreases gradually with time starting with 0.231 and reaching 0.131, which means that the quantum loss converges faster than the classical model. The convergence rate is better at

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

24.6 and the gradient variance is lower at 0.023 which is a sign of smooth and steady optimization. This is achieved through hybrid RMSProp optimization and quantum parameter updates which allow an optimization to train quickly and reliably.



Fig 6. Convergence Rate (%)

The stable decrease in the number of losses as a result of 100 iterations demonstrates the stability of the suggested variational quantum algorithm. In general, the QML model attains effectiveness in terms of optimizing with minimized oscillations, and also exhibits better convergence properties than classical methods.

TABLE 5 **SYSTEM ROBUSTNESS UNDER VARIABLE NOISE AND RESOURCE SETTINGS**

Noise Level (p)	Qubits Used	Accuracy (%)	Execution Time (s)
0.005	8	96.42	23.1
0.01	8	96.11	23.4
0.015	10	95.78	24
0.02	10	95.32	24.3
0.025	12	94.88	25.1
0.03	12	94.41	25.6
0.035	14	93.97	26.3
0.04	14	93.56	27
0.045	16	92.89	27.5
0.05	16	92.38	28

Table 5 and Figure 7 measures the robustness of the system in the presence of different levels of noise as well as resource allocation. The proposed QML model is very resilient to noisy environment with high accuracy of above 94% and noise level of 0.03. Accuracy is 92.38 even at the highest noise level (0.05) which proves the effectiveness of error reduction measures.



Fig 7. Accuracy vs Noise Level

The noise and qubit consumption are slightly scaled with execution time, which suggests the efficient scaling to hardware conditions. The use of qubits between 8 and 16 also promises to take care of resources adaptively. These findings indicate that the system maintains consistent accuracy and reliability over a wide range of quantum noise conditions, which proves the applicability of the system to NISQ devices.

V. CONCLUSION AND FUTURE SCOPE

The proposed scaled quantum machine learning framework has a high potential of overcoming the problem of computational and scaling of classical data-driven models. The system had a stable performance with a classification accuracy of 96.42 and it outperformed the current models by a steady margin through hybrid implementation of quantum feature mapping and classical optimization. Improved convergence, robustness and generalization were achieved using the variational optimization loop and quantum kernel estimation, and high fidelity achieved using integrated Zero-Noise Extrapolation even in conditions of NISQ. These findings confirm that small scale quantum circuits with small numbers of qubits can be used to learn and classify large scale data sets with efficiency and lower computational costs. Future extensions of the architecture include multi-qubit entanglement-aware learning and federated quantum training, where distributed datasets can be safely trained in a quantum node. Generalization can also be improved with the addition of quantum attention and resistant to errors qubit encoder. In addition, a combination of quantum reinforcement learning might allow optimization in a dynamic data environment. The long term vision entails supercomputer implementation on superconducting systems with large quantum capabilities and

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.

investigation of its cooperation with classical backbones of the deep learning disciplines in hybrid intelligence. This research therefore provides the platform to the coming generation of scalable, noise-insensitive, and energy efficient quantum intelligence systems that can transform large scale computation analytics.

REFERENCES

[1]. Chen, X., Sun, Y., Qin, X., Cai, J., Cai, M., Hou, X., Yang, K., & Zhang, H. (2024). Assessing the Potential of UAV for Large-Scale Fractional Vegetation Cover Mapping with Satellite Data and Machine Learning. Remote Sensing, 16(19), 3587. https://doi.org/10.3390/rs16193587

[2]. Zhang, H., Feng, S., Wu, D., Zhao, C., Liu, X., Zhou, Y., Wang, S., Deng, H., & Zheng, S. (2024). Hyperspectral Image Classification on Large-Scale Agricultural Crops: The Heilongjiang Benchmark Dataset, Validation Procedure, and Baseline Results. Remote Sensing, 16(3), 478. https://doi.org/10.3390/rs16030478

[3]. Dou, S., Song, T., Wu, H., Sun, Y., & Xian, J. (2024). Spatial-Temporal Ship Pollution Distribution Exploitation and Harbor Environmental Impact Analysis via Large-Scale AIS Data. Journal of Marine Science and Engineering, 12(6), 960. https://doi.org/10.3390/jmse12060960

[4]. Wang, S., Zou, X., Li, K., Xing, J., Cao, T., & Tao, P. (2024). Towards Robust Pansharpening: A Large-Scale High-Resolution Multi-Scene Dataset and Novel Approach. Remote Sensing, 16(16), 2899. https://doi.org/10.3390/rs16162899

[5]. Ghanem, F. A., Padma, M. C., Abdulwahab, H. M., & Alkhatib, R. (2024). Novel Genetic Optimization Techniques for Accurate Social Media Data Summarization and Classification Using Deep Learning Models. Technologies, 12(10), 199. https://doi.org/10.3390/technologies12100199

[6]. Yin, S., Zou, X., Cheng, Y., & Liu, Y. (2024). Temperature Compensation of Laser Methane Sensor Based on a Large-Scale Dataset and the ISSA-BP Neural Network. Sensors, 24(2), 493. https://doi.org/10.3390/s24020493

[7]. Abbaszadeh Shahri, A., Shan, C., Larsson, S., & Johansson, F. (2024). Normalizing Large Scale Sensor-Based MWD Data: An Automated Method toward A Unified Database. Sensors, 24(4), 1209. https://doi.org/10.3390/s24041209

[8]. Tynchenko, Y., Kukartsev, V., Tynchenko, V., Kukartseva, O., Panfilova, T., Gladkov, A., Nguyen, V., & Malashin, I. (2024). Landslide Assessment Classification Using Deep Neural Networks Based on Climate and Geospatial Data. Sustainability, 16(16), 7063. https://doi.org/10.3390/su16167063

[9]. Xu, H., Seng, K. P., Smith, J., & Ang, L. M. (2024). Multi-Level Split Federated Learning for Large-Scale AIoT System Based on Smart Cities. Future Internet, 16(3), 82. https://doi.org/10.3390/fi16030082

[10]. Wu, C., Liu, Y., Yang, J., Dai, A., Zhou, H., Tang, K., Zhang, Y., Wang, R., Wei, B., & Wang, Y. (2025). Large-Scale Apple Orchard Identification from Multi-Temporal Sentinel-2 Imagery. Agronomy, 15(6), 1487. https://doi.org/10.3390/agronomy15061487

[11]. Karras, A., Giannaros, A., Karras, C., Theodorakopoulos, L., Mammassis, C. S., Krimpas, G. A., & Sioutas, S. (2024). TinyML Algorithms for Big Data Management in Large-Scale IoT Systems. Future Internet, 16(2), 42. https://doi.org/10.3390/fi16020042

[12]. D. Jingbo, "Big Data Classification Model and Algorithm Based on Double Quantum Particle Swarm Optimization. 2023 IEEE International Conference on Control, Electronics and Computer Technology (ICCECT), Jilin, pp. 1309-1313. https://doi.org/10.1109/ICCECT57938.2023.10140247

[13]. Salhi, A., Alshamrani, R., Althbiti, A. (2025). Optimizing high dimensional data classification with a hybrid AI driven feature selection framework and machine learning schema. Sci Rep 15, 35038. https://doi.org/10.1038/s41598-025-08699-4

[14]. Václav Snášel, Martin Štěpnička, Varun Ojha, Ponnuthurai Nagaratnam Suganthan, Ruobin Gao, Lingping Kong. (2024). Large-scale data classification based on the integrated fusion of fuzzy learning and graph neural network. Information Fusion, Volume 102, 102067, ISSN 1566-2535. https://doi.org/10.1016/j.inffus.2023.102067

[15]. Chi, Z., Chen, H., Chang, S., Li, Z.-L., Ma, L., Hu, T., Xu, K., & Zhao, Z. (2025). Large-Scale Monitoring of Potatoes Late Blight Using Multi-Source Time-Series Data and Google Earth Engine. Remote Sensing, 17(6), 978. https://doi.org/10.3390/rs17060978

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:08:45 UTC from IEEE Xplore. Restrictions apply.