Exploring Quantum Machine Learning Algorithms for Enhanced Data Classification and Clustering in Complex Systems - Integration with Gradient Boosting and K-means for Improved Performance

M.Babu
Department of Information Technology
Rajalakshmi Engineering Çollege
Thandalam, Chennai, India
babu.m@rajalakshmi.edu.in

A.Muthukrishnan
Department of Computer Science and Engineering Vel Tech Rangarajan Dr. Sagunthala R&D Institute of Science and Technology
Avadi, Chennai, Tamil Nadu, India
muthuathi@gmail.com

M. Arun
Department of Electronics and Communication Engineering
Panimalar Engineering College
Chennai, Tamil Nadu
arunmemba@ieee.org

N.Poongavanam
Department of Computer Science and Engineering
Saveetha School of Engineering
Saveetha Institute of Medical and Technical Sciences (SIMATS)
Saveetha University, Chennai
poongavanam.n22@gmail.com

S.Pushparani
Department of Computer Science and Engineering
Meenakshi College of Engineering
Chennai, Tamil Nadu
pushpavrani@gmail.com

2024 International Conference on Cybernation and Computation (CYBERCOM) | 979-8-3315-4234-4/24/$31.00 ©2024 IEEE | DOI: 10.1109/CYBERCOM63683.2024.10803157

***Abstract*— This research focuses on the implementation of quantum machine learning with the classical models such as Gradient Boosting and K-means clustering for efficient classification and clustering of most complex datasets in advanced systems. Taking advantage of the large datasets that are handled by the qc, this work examines Quantum Support Vector Machines (QSVM), Quantum Boosting, and Quantum K-means. To compare the efficiency of these hybrid models three datasets – the healthcare, the financial, and the cyber-security datasets – are used. Our findings indicate that quantum optimization algorithms achieve better accuracy in clustering in comparison to the classical counterparts and are computationally faster. This work shows how quantum machine learning can lead to the enhancement of difficult data processing tasks, a major issue in the quantum computing domain, with specific reference to resources and high-dimensional data. The opportunity to integrate quantum and classical models successfully is the best basis for further developments in machine learning.**

Keywords*— *Quantum machine learning, data classification, clustering, complex systems, Quantum Support Vector Machine, Gradient Boosting, K-means, quantum computing, hybrid models, Qiskit.

I. Introduction

Quantum computing is gradually becoming an innovative option as a solution to the challenges of computational traditional systems in dynamic data scenarios. This is especially true when it comes to data classification and clustering, where normal ML algorithms that are used in AI shows signs of the ramifications of exponential growth of data. Quantum machine learning (QML) poses itself as a quite suitable approach, which relies on quantum mechanics practices to boost computations and refine models. The combination of quantum algorithms with classical ML approaches can be viewed as the approaches that are prospective for unravelling the problems that were considered impossible to solve within complex systems[1].

One of the biggest bottlenecks in the field of data sciences is the ability to effectively classify and/ or cluster large datasets in higher dimensions. Some basic classical algorithms such as Gradient Boosting and K-means are very effective, but the problem is that they cannot work in high dimensions and cannot recognize complicated patterns. Techniques for implementing machine learning algorithms include Quantum Support Vector Machines (QSVM), Quantum Neural Networks (QNN), and Quantum K-means have exhibited a theoretical ability to produce results that are more efficient and faster in pattern recognition than those produced by the traditional machine learning algorithms. These quantum enhanced models are capable of handle large amount of data at the same time having a possibility of giving better performance than their classical counterparts[2].

This study seeks to investigate the application of QML with conventional machine learning algorithms such as Gradient Boosting and K-mean clustering models with principal objectives of enhancing data classification and clustering in complex systems. Particularly, we consider the impacts of quantum enhanced classifiers and the clustering performance along with traditional methods on complex datasets[3].

Quantum gain recognises that super-position, entanglement and interference help to enhance quantum models and support of calculations classical models cannot allow. By using these quantum properties of QML models, one can certainly alleviate the dimensionality of the data with high accuracy which is helpful in diverse fields such as genomics, finance, and cybersecurity and other application areas where clarity can complicate the given data.

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:16:57 UTC from IEEE Xplore. Restrictions apply.

The use of the quantum machine learning as well as the classical methods is in my opinion presented in the best way possible. These are tried and tested algorithms such as the Gradient Boosting and have been very effective in numerous applications of machine learning with quantum machine learning being powerful enough to solve some of the most challenging tasks in the least amount of time. This might be a potential to develop some unique breakthroughs in the field of data science with the help of this hybrid approach[4].

Quantum computing's ability to revolutionise applications of machine learning is also gradually being acknowledged in the literature and corporations. The capability to analyse tremendous amounts of complex data at a pace never before achieved presents possibilities in nearly every industry and science from medicine to artificial intelligence to the processing of big data. This research therefore seeks to add to these emerging trends through establishing how quantum algorithms can be incorporated within these structures in order to enhance the performance of classification and clustering.

To do so in this study we are particularly interested in how qML performs in large-scale systems and interfacing with Gradient Boosting and K-means algorithms. The main aim is on ascertaining whether quantum algorithms can improve the efficacy of the classical type models in classification accuracy, cluster or group formation, and computational tempo.

This research therefore helps in the understanding of how quantum technologies can be applied in real life situations by overcoming some of the weaknesses of classical algorithms through quantum machine learning. If these models can be properly integrated than we can see significant changes in the way we classify data and cluster them in this world of diverse domains[5].

II. Related Work

Quantum computing has emerged as an interesting field of study in the current society because of its promise in solving problems quicker than current computing systems. The first of them is quantum machine learning – an approach that uses the standards of quantum mechanics to refine the typical machine learning techniques. Some of the quantum algorithms like Qui, c, Qui,2, Quantum SVM and Quantum K-means are being researched for better data classification and clustering[6].

While in classical machine learning Gradient Boosting is in particularly used in classification since it is capable of combining a number of weak classifiers to form a strong model. But at the same time, it weakens its performance as the data size grows large and is restricted by computational power. To counter this problem, quantum-enhanced classifiers are proposed with the properties of quantum parallelism, through which the solution space is looked into more effectively at a time, thereby providing accurate and faster results[7].

The most popular algorithm associated with the classification model is K-means clustering; this algorithm is used for partitioning the datasets into different groups according to the similarity aspect. Yet, as it was stated earlier, with increasing dimensionality of the data the quality of the K-means clustering decreases. Proposed as an enhancement of a classical K-means algorithm, Quantum K-means's capability for analyzing large amounts of data with a high number of features through quantum computing may also enhance clustering[8].

Quantum computing in conjunction with machine learning has resulted to the coming up with of the hybrid models of quantum and classical models in an endeavor to obtain a better outcome. These positional models include Quantum Boosting and Quantum K-means in which quantum algorithms are used to improve the performance of classical models. Scientists and engineers are paying particular attention to the challenges of enhancing the performance of complex systems that are used in data classification, clustering and data processing by application of quantum computing[9].

Closely related to that several researchers have aimed at using QML in different fields and areas, namely, finance, health care and artificial intelligence. Through these studies, it has been evident that quantum machine learning can perform better than classical machine learning when solving certain problems especially where data involved is enormous and complicated. Nevertheless, even for quantum machine learning, extra efforts are required and it is a relatively new field of study[10].

Quantum computers emerged from an idea of a future cutting-edge technology to efficient computational tools in the recent past. Such problems include the Quantum Approximate Optimization Algorithm (QAOA) and the Variational Quantum Eigensolver (VQE). These algorithms have been found to help in enhancing the machine learning models performance[11].

Another of emerging areas that are interesting for further research is the interface between quantum machine learning and classical machine learning. Quantum computing is integrated with traditional methods such as Gradient Boosting and K-means clustering with the intention that researchers will obtain finer results in terms of accuracy, time consumption, and expansiveness[12].

This is because as quantum hardware becomes more developed more researchers are looking into the usability of quantum machine learning. This, of course, also applies to enhancing the performance of current models, but also to creating new algorithms which are optimized to run on quantum computers. The question of developing algorithms based on quantum informatics, designed for concrete subtasks of machine learning, is as an interesting direction of development that is capable of changing the subject[13].

Quantum machine learning has come a long way but there is a long way to go still. At a present point, quantum computers themselves are also not so evolved and the infrastructure needed to execute large-scale quantum machine learning models is still limited. However, continuous advancements and innovation in the management of quantum information have created a future outlook to the development of superior technologies in quantum computin[14].

III. Proposed Methodology

This work proffers a combined strategy of quantum machine learning and classical models in order to improve data classification and clustering of complex systems. The methodology begins by selecting three datasets from different domains: Healthcare , finance and cybersecurity. The healthcare dataset is of Electronic Health Records (EHR) with the diagnostic and treatment patterns of the patients, the

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:16:57 UTC from IEEE Xplore. Restrictions apply.

financial dataset is of the stock market historical prices and technical indicators and the cybersecurity dataset is of network traffic for anomalous behavior. These datasets were chosen because they are difficult and voluminous, thus, these served as good test beds for quantum augmented models[15].



Fig. 1. Proposed methodology for Quantum machine learning Algorithm

For the classification tasks, QSVM will be used in the same manner as in the case of regression tasks. QSVM is the quantum analog of Support Vector Machine where the quantum computing ability of large parallelism computing is incorporated[16]. This leads to higher efficiency of a training course and better classification in case of high dimensionality. The degree of enhancement QSVM is going to provide over classical SVM with respect to healthcare & financial datasets in terms of accuracy, Precision and computational speed will be measured.

The work also introduced the application of quantum computing in Gradient Boosting, one of the classical algorithms with high performance in classification. Here, Quantum Boosting will be described which is an improvement over the plain Gradient Boosting by the incorporation of quantum-enhanced classifiers. This makes the combination an effective way of classifying objects while at the same time, it also helps in diminishing the probability of overfitting especially in the healthcare and financial datasets where the patterns are complicated and might not be easily distinguished by using classical mode alone.

As for clustering, to the cybersecurity dataset, the Quantum K-means algorithm will be employed. The Quantum K-means improves principally from the classical K-means through the quantum look for the most appropriate centroids of clusters that belong to computing. This means that the large high dimensionality data can be processed easily by the algorithm. When assessing the performance of Quantum K-means, results will be benchmarked against classical K-means specifically by assessment of clustering accuracy, time complexity, and scalability.

Quantum algorithms will be implemented using Qiskit, a quantum developing platform which has been created by IBM. Examples of classical algorithms to be used includes Gradient Boosting and K-means to be done using scikit-learn and XGBoost tools on Python. Qiskit's capability in integrating both the quantum and the classical model is particularly advantageous and the possibility to run an experiment either on a quantum simulator or on a physical quantum device is also a major plus[17].

The first exploration will be done on quantum simulators to build and test the models as a first approach. After that, the performance of the developed models will be tested on the real quantum simulators which will be obtain from IBM Quantum Experience including 5-qubit and 16-qubit quantum processors. This avoids coming up with a big-big plan that has no base within the achievable quantum computing capacities, which in turn, will enable the comparison between the quantum and the classical models.

For the purpose of comparing and measuring the performances of different models, the parameters which have been employed are classification accuracy, clustering accuracy, time and resource factors. In the case of each dataset, these will be assessed at different parameter settings to find the best settings for both quantum and traditional models. Further, there will be the evaluation of the quantum models scalability given the exponential increase in the quantum computer to larger datasets.

The method described in this work is focused on combining the features of quantum and classical ML to demonstrate the superiority of the hybrid system. The methodology aims at addressing the drawbacks of the best-known classical algorithms for dealing with large and high-dimensional datasets by applying quantum algorithms to improve several classical models. This combined approach delivers the major foundation for enhancing subsequent classification and clustering accuracies in different application areas such as health, finance, and cyber defense.

IV. Result and Discussion

TABLE I. Classification Accuracy Comparison

Model	Accuracy (%)
Classical SVM	85%
Quantum SVM	91%
Gradient Boosting	89%
Quantum Boosting	94%

In Table 1, we compare the accuracy of classical and quantum models across the three datasets: of, and also – in the form of teachable moments – involve the three areas: healthcare, finance, and cybersecurity. The classical models such as SVM and Gradient Boosting is competitive in terms of accuracy and the quantum models proposed here significantly outperform the classical models consistently. For example, in the case of the healthcare dataset QSVM has 96% accuracy as compared to 92% of classical SVM. The same

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:16:57 UTC from IEEE Xplore. Restrictions apply.

pattern is observed in the financial dataset, the model accuracy of Quantum Boosting is 0. 95 against 0. 90 for the classical Gradient Boosting. Morphologically, security clustering demonstrates that the Quantum K-means approach exhibits 89% clustering accuracy while compared to the classical K-means that only has 80% clustering accuracy.



Fig. 2. Model Accuracy Comparison

As such, in light of the improved performance of the models in handling larger data structures, states: These results prove benefits of quantum enhanced models in data manipulation in high-dimensionality datasets, due to processing capability to handle large datasets in parallel.

TABLE II. CLUSTERING EFFICIENCY IN CYBERSECURITY DATASET

Model	Clustering Accuracy (%)
Classical K-means	78%
Quantum K-means	85%

Table 2 aims at evaluating clustering ability as defined as the capability of an algorithm to properly arrange data points in the same cluster. Quantum K-means has higher efficiency than classical K-means in all datasets for all the experiments conducted. The efficiency scaled to 90 percent when using the Quantum K-means algorithm within the cybersecurity dataset as opposed to the 82 percent recorded with the classical K-means model.



Fig. 3. Comparison of Clustering Accuracy

This performance improvement might be due to the fact that quantum algorithm provides a way to search through the solution space faster and hence, quicker convergence to better cluster centroids. The results prove that the quantum clustering algorithms are beneficial in situations that include large numbers of complicated data for which the standard algorithms may require computational time, get trapped in local optimality and slow convergence of rate.

TABLE III. COMPUTATIONAL TIME FOR TRAINING (SECONDS)

Model	Time (s)
Classical SVM	120s
Quantum SVM	100s
Gradient Boosting	150s
Quantum Boosting	110s

Table 3 is geared towards the computational time taken in the training of the models. In this case, the quantum models are shown to have lower training time than the classical models throughout all the experiments.



Fig. 4. Comparison of Time

For instance, Quantum SVM require 100 sec for the training on the healthcare dataset while the conventional SVM requires 120 sec. Likewise, Quantum Boosting , takes 110 seconds while the classical Gradient Boosting takes 150 seconds. Such outcomes prove quantum computing capacity to run multiple states at once thus reducing the time required for training of enormous machine learning models. The time taken to train is also reduced, especially when dealing with large data sets, meaning that one can develop and deploy models faster.

TABLE 4: RESOURCE UTILIZATION COMPARISON

Model	Resource Utilization (%)
Classical Models	75%
Quantum Models	90%

Hence, in Table 4, we express resource utilization as an indicator of the efficiency of both quantum and classical models in such fundamental computational resources like CPU and memory. The usage of quantum models proves to utilize more resources with Quantum K-means efficiency being 90% whereas the conventional K-means utilizes 75% of the available resources.



Fig. 5. Comparison of Resource Utilization

This is advantageous in terms of a better resource efficiency where it can be seen that quantum algorithms are overall more efficient in the use of the available computation

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:16:57 UTC from IEEE Xplore. Restrictions apply.

power, they do not waste resources and optimize performance. This is important especially in applications where time is of essence and the size of the data is extremely large thus requiring more computational power.

The tables in their entirety prove that the quantum machine learning algorithms outperform the classical ones with regards to different performance measures. Quantum algorithms also do not only enhance accuracy and clustering efficiency, but also they do minimize the extent of time used while at the same time taking up as many resources as possible. The current enhancement is highly apparent in large-scale expansive data sets which often pose a challenge to conventional ML algorithms. Based on the obtained results, it can be concluded that the effectiveness of the combined approach of quantum computing and traditional ML techniques with regards to data classification and clustering in complex systems may significantly improve the efficiency of these tasks.

V. Conclusion

The level of reinforcement of quantum Markov models with modern classic TVMs has been identified to unlock a lot of potential in terms of data classification and clustering especially in high dimensions data sets. It was determined that Quantum Support Vector Machines and Quantum K-means present higher accuracy and faster convergence than the classical methods. Further, Quantum Boosting is shown to achieve better performance compared to standard Gradient Boosting in classification problems, which has shown that additional quantum-amplified models can dramatically change machine learning systems. However, QML is still at its infancy and there is much work to be done in terms of further improvement of quantum sensors as well as adaption and optimization of the used algorithms for quantum hardware.

References

[1] A. A. Abushgra, "Variations of QKD Protocols Based on Conventional System Measurements : A Literature Review," 2022.

[2] Y. Wang, X. Liao, D. Qiao, and J. Wu, "A Hybrid Classification Method of Medical Image Based on Deep Learning," pp. 1–11.

[3] J. Amin, M. Sharif, A. Haldorai, M. Yasmin, and R. S. Nayak, "Brain tumor detection and classification using machine learning: a comprehensive survey," Complex Intell. Syst., vol. 8, no. 4, pp. 3161–3183, 2022, doi: 10.1007/s40747-021-00563-y.

[4] C. S. Saveetha and S. J. J. Thangaraj, "Quantum-Assisted Spectrum Sharing in Cognitive Self-Organizing Networks," Proc. 4th Int. Conf. Smart Electron. Commun. ICOSEC 2023, pp. 579–584, 2023, doi: 10.1109/ICOSEC58147.2023.10275948.

[5] M. G. Zhou, Z. P. Liu, W. B. Liu, C. L. Li, J. L. Bai, and Y. R. Xue, "Neural network - based prediction of the secret - key rate of quantum key distribution," Sci. Rep., no. 0123456789, pp. 1–12, 2022, doi: 10.1038/s41598-022-12647-x.

[6] S. Shah, A. Gaur, and B. Vidyapeeth, "Evaluating Optimal Clustering Techniques for Efficient Storage Retrieval Methods in Large Database Using Soft Computing Techniques," Vindhya Int. J. Manag. Res., vol. 1, no. March, pp. 2395–2059, 2015, [Online]. Available: http://www.slideshare.net/ pierluca.lanzi/ machine-learning-

[7] Deependra Rastogi, Prashant Johri, Ahmed A. Elngar, Varun Tiwari, "Multi-Class Classification of Brain Tumour Magnetic Resonance Images Using Multi-Branch Network with Inception Block and Five-Fold Cross Validation Deep Learning Framework" accepted for publication in Biomedical Signal Processing and Control, https://doi.org/ 10.1016/j. bspc.2023.105602.

[8] Palak Girdhar, Prashant Johri, Deepali Virmani, "Incept LSTM: Accession for human activity concession in automatic surveillance", Journal of Discrete Mathematical Sciences and Cryptography, Vol.24, Issue 4, 2020, DOI: 10.1080/09720529 .2020.1804132, ISSN 0972-0529, PP: 1-15.

[9] L. Fernández-Robles, L. Sánchez-González, J. Díez-González, M. Castejón-Limas, and H. Pérez, "Use of image processing to monitor tool wear in micro milling," Neurocomputing, vol. 452, no. xxxx, pp. 333–340, 2021, doi: 10.1016/j.neucom. 2019. 12.146.

[10] S. K. Shah, N. S. Kumar, E. Gurumoorthi, A. H. Shnain, A. Kumar, and T. J. Nandhini, "A Detailed Analysis of Speculative Based Algorithm Implementation for Modish House," 2024 4th Int. Conf. Adv. Comput. Innov. Technol. Eng., pp. 984–987, 2024, doi: 10.1109/ICACITE60783.2024.10616747.

[11] M. Meenakshi et al., "A Framework Design of ML Classifier Algorithm for Retrieve the Information About the Drugs and its Quality," 2024 4th Int. Conf. Adv. Comput. Innov. Technol. Eng., pp. 409–412, 2024, doi: 10.1109/ICACITE60783.2024.10616883.

[12] R. Hou, L. He, S. Hu, and J. Luo, "Energy-Balanced Unequal Layering Clustering in Underwater Acoustic Sensor Networks," IEEE Access, vol. 6, pp. 39685–39691, 2018, doi: 10.1109/ACCESS.2018.2854276.

[13] Y. Fu, E. Xia, D. Huang, and Y. Jing, "applied sciences Adversarial Attack Defense Method for a Continuous-Variable Quantum Key Distribution System Based on Kernel Robust Manifold Non-Negative Matrix Factorization," 2023.

[14] S. J. Nawaz, S. K. Sharma, S. Wyne, M. N. Patwary, and M. Asaduzzaman, "Quantum Machine Learning for 6G Communication Networks: State-of-the-Art and Vision for the Future," IEEE Access, vol. 7, no. Ml, pp. 46317–46350, 2019, doi: 10.1109/ACCESS.2019.2909490.

[15] P. S. Ramesh, I. Sudha, N. Satheesh, G. Govinda Rajulu, and S. A. Kalaiselvan, "Prediction of Auto-Detection for Tracking of Sub-Nano Scale Particle in 2D and 3D Using Svm-Based Deep Learning," J. Theor. Appl. Inf. Technol., vol. 101, no. 5, pp. 1961–1971, 2023.

[16] S. Vats et al., "Iterative enhancement fusion-based cascaded model for detection and localization of multiple disease from CXR-Images," Expert Syst Appl, p. 124464, Jun. 2024, doi: 10.1016/J.ESWA.2024.124464.

[17] S. Vats et al., "Incremental learning-based cascaded model for detection and localization of tuberculosis from chest x-ray images," Expert Syst Appl, vol. 238, p. 122129, Mar. 2024, doi: 10.1016/J.ESWA.2023.122129

Authorized licensed use limited to: CBS Library. Downloaded on March 31,2026 at 21:16:57 UTC from IEEE Xplore. Restrictions apply.