

This figure presents a comprehensive PCB layout for a multi-functional embedded system, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C connector interface circuit.
- DC-DC:** A DC-DC converter circuit for power regulation.
- FLASH:** A flash memory interface circuit.
- BAT&ADC:** A battery and ADC interface circuit.
- OUTPUT:** An output interface circuit.
- LCD_BL:** An LCD backlight driver circuit.
- SD_Card:** An SD card interface circuit.
- RGB_Prot:** An RGB protection circuit.
- MCU:** The main microcontroller unit (ESP32-S3R8) with its pin connections.
- RTC:** A real-time clock circuit.
- KEY&SWITCH:** A key and switch interface circuit.

The layout also includes a detailed pin list for the MCU, showing connections for various pins (e.g., GPIO0, GPIO1, GPIO2, etc.) to the system components. The components are labeled with their respective part numbers and values, and the layout is color-coded for clarity.

This figure presents a comprehensive PCB layout for a multi-functional electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C connector interface circuit.
- DC-DC:** A DC-DC converter circuit for power regulation.
- FLASH:** A flash memory interface circuit.
- BAT&ADC:** A battery and ADC interface circuit.
- OUTPUT:** An output interface circuit.
- LCD_BL:** An LCD backlight driver circuit.
- SD_Card:** An SD card interface circuit.
- RGB_Prot:** An RGB protection circuit.
- MCU:** The main microcontroller unit (ESP32-S3R8) with its pin connections.
- RTC:** A real-time clock circuit.
- KEY&SWITCH:** A key and switch interface circuit.

The layout also includes a detailed pin list for the MCU, showing connections for various pins (e.g., GPIO0, GPIO1, GPIO2, etc.) to the corresponding components. The overall design is a professional and detailed PCB layout for a complex electronic system.

This figure presents a comprehensive PCB layout for a custom electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C port connected to the MCU via a USB-to-UART bridge.
- DC-DC:** A buck converter stepping down 5V to 3.3V for the MCU and other components.
- FLASH:** An external flash memory chip connected to the MCU's SPI interface.
- BAT&ADC:** A battery management and ADC section for monitoring the 3V3 battery level.
- OUTPUT:** A section for the final output signals, including SCL, SDA, 3V3, and GND.
- LCD_BL:** A backlight driver for the LCD display.
- SD_Card:** An SD card interface for data storage.
- RGB_Prot:** A color calibration and protection circuit for the RGB display.
- MCU:** The central microcontroller unit, an ESP32-S3R8, with various peripheral connections.
- RTC:** A real-time clock module for timekeeping.
- KEY&SWITCH:** A section for user input via a key and a switch.

The layout is detailed with component values, pin connections, and a clear labeling system for each block. A table at the bottom right provides a summary of the pin connections for the MCU, LCD, SD Card, IMU, RTC, URAT, KEY_IO, and Other components.

GPIO	LCD	SD_Card	IMU	RTC	URAT	KEY_IO	Other
IO0						BOOT0	IO0
IO1	LCD SDA	SD MOSI					
IO2	LCD CLK	SD CLK					
IO3	R2						
IO4							BAT_ADC
IO5	B1						
IO6	BL_PWM						
IO7			IMU_SCL	RTC_SCL			SCL
IO8	R3						
IO9	G5						
IO10	G4						
IO11	G3						
IO12	G2						
IO13	G1						
IO14	G0						
IO15			IMU_SDA	RTC_SDA			SDA
IO16	LCD_RST						
IO17	R0						
IO18	R4						
IO19							USB_N
IO20							USB_P
IO21	B0						
IO38	HSYNC						
IO39	VSYNC						
IO40	DE						
IO41	PCLK						
IO42		SD_MISO					
IO43							
IO44							U0_TXD
IO45	B2						U0_RXD
IO46	R1						
IO47	B4						
IO48	B3						
RESET							CHP_UP

This figure presents a comprehensive PCB layout for a multi-functional electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** Schematic for the USB Type-C port, featuring a USB connector, a USB-to-UART bridge (M2301SFT1G), and a USB-to-USB bridge (M2301SFT1G).
- DC-DC:** Schematic for the DC-DC converter, showing a boost converter (MP1605GT-F) converting 2.3V-5.5V input to 3.3V output.
- FLASH:** Schematic for the flash memory (XM25QH128DHIQT), showing the connection to the microcontroller's SPI interface.
- BAT&ADC:** Schematic for the battery and ADC interface, showing the connection to the microcontroller's I2C interface.
- OUTPUT:** Schematic for the output interface, showing the connection to the microcontroller's I2C interface.
- LCD_BL:** Schematic for the LCD backlight, showing a boost converter (AP3032KTR-G1) driving the backlight.
- SD_Card:** Schematic for the SD card interface, showing the connection to the microcontroller's SPI interface.
- RGB_Prot:** Schematic for the RGB protection, showing the connection to the microcontroller's I2C interface.
- MCU:** Schematic for the microcontroller (ESP32-S3R8), showing the connection to various peripherals.
- QMI:** Schematic for the QMI interface (QMI8658A), showing the connection to the microcontroller's I2C interface.
- RTC:** Schematic for the real-time clock (PCF85063AT), showing the connection to the microcontroller's I2C interface.
- KEY&SWITCH:** Schematic for the key and switch interface, showing the connection to the microcontroller's I2C interface.

The layout is divided into sections labeled A, B, C, and D, corresponding to the grid columns. The rightmost section contains a table of pin connections for the microcontroller.

GPIO	LCD	SD_Card	IMU	RTC	URAT	KEY_IO	Other
IO0						BOOT0	IO0
IO1	LCD SDA	SD MOSI					
IO2	LCD CLK	SD CLK					
IO3	R2						
IO4							BAT_ADC
IO5	B1						
IO6	BL_PWM						
IO7			IMU_SCL	RTC_SCL			SCL
IO8	R3						
IO9	G5						
IO10	G4						
IO11	G3						
IO12	G2						
IO13	G1						
IO14	G0						
IO15			IMU_SDA	RTC_SDA			SDA
IO16	LCD_RST						
IO17	R0						
IO18	R4						
IO19							USB_N
IO20							USB_P
IO21	B0						
IO38	HSYNC						
IO39	VSYNC						
IO40	DE						
IO41	PCLK						
IO42		SD_MISO					
IO43							
IO44							
IO45	B2						
IO46	R1						
IO47	B4						
IO48	B3						
RESET							CHP_UP

This figure presents a comprehensive PCB layout for a multi-functional electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C connector (M2301SFT1G) with associated signal and power pins.
- DC-DC:** A buck converter (MP1605GT-F) converting 2.3V-5.5V input to a 3.3V output.
- FLASH:** An external flash memory (XM25QH128DHIQT) interfaced via SPI.
- BAT&ADC:** A battery management and ADC section (ETA6098) for monitoring and converting battery voltage.
- OUTPUT:** A section for output signals, including SCL, SDA, 3V3, and GND.
- LCD_BL:** A backlight driver (AP3032KTR-G1) for the LCD display.
- SD_Card:** An SD card interface (TF1) for data storage.
- RGB_Prot:** A color calibration module (U9) for the display.
- MCU:** The central microcontroller unit (ESP32-S3R8) with various peripheral connections.
- QMI:** A QMI module (QM18658A) for cellular communication.
- RTC:** A real-time clock (PCF85063AT) for timekeeping.
- KEY&SWITCH:** A section for user input, including a key and a switch.

The layout also includes a detailed pin list for the MCU, showing connections for various pins (e.g., GPIO0, GPIO1, GPIO2, etc.) to the appropriate components. The overall design is a professional-grade PCB layout for a complex embedded system.

This figure presents a comprehensive PCB layout for a multi-functional electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C connector (M2301SFT1G) with associated signal and power pins.
- DC-DC:** A buck converter (MP1605GT-F) converting 2.3V-5.5V input to a 3.3V output.
- FLASH:** An external flash memory (XM25QH128DHIQT) interfaced via SPI.
- BAT&ADC:** A battery management and ADC section (ETA6098) for monitoring and converting battery voltage.
- OUTPUT:** A section for output signals, including SCL, SDA, 3V3, and GND.
- LCD_BL:** A backlight driver (AP3032KTR-G1) for the LCD display.
- SD_Card:** An SD card interface (TF1) for data storage.
- RGB_Prot:** A color calibration module (U9) for the display.
- MCU:** The central microcontroller unit (ESP32-S3R8) with various peripheral connections.
- QMI:** A QMI module (QM18658A) for cellular communication.
- RTC:** A real-time clock (PCF85063AT) for timekeeping.
- KEY&SWITCH:** A section for user input, including a key and a switch.

The layout also includes a detailed pin list for the MCU, showing connections for various pins (e.g., GPIO0, GPIO1, GPIO2, etc.) to the appropriate components. The overall design is a professional-grade PCB layout for a complex embedded system.

This figure presents a comprehensive PCB layout for a multi-functional electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C connector (M2301SFT1G) with associated signal and power pins.
- DC-DC:** A buck converter (MP1605GT-F) converting 2.3V-5.5V input to a 3.3V output.
- FLASH:** An external flash memory (XM25QH128DHIQT) interfaced via SPI.
- BAT&ADC:** A battery management and ADC section (ETA6098) for monitoring and converting battery voltage.
- OUTPUT:** A section for output signals, including SCL, SDA, 3V3, and GND.
- LCD_BL:** A backlight driver (AP3032KTR-G1) for the LCD display.
- SD_Card:** An SD card interface (TF1) for data storage.
- RGB_Prot:** A color calibration module (U9) for the display.
- MCU:** The central microcontroller unit (ESP32-S3R8) with various peripheral connections.
- QMI:** A Qualcomm Mobile Interface module (QMI8658A) for sensor data.
- RTC:** A Real-Time Clock module (PCF85063AT) for timekeeping.
- KEY&SWITCH:** A section for user input, including a key and a switch.

The layout also includes a detailed pin list for the MCU, showing connections for various pins (e.g., GPIO0, GPIO1, GPIO2, etc.) to the MCU pins. The overall design is a professional-grade PCB layout for a complex embedded system.

This figure presents a comprehensive PCB layout for a multi-functional electronic device, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C connector (M2301SFT1G) with associated signal and power pins.
- DC-DC:** A buck converter (MP1605GT-F) converting 2.3V-5.5V input to a 3.3V output.
- FLASH:** An external flash memory (XM25QH128DHIQT) interfaced via SPI.
- BAT&ADC:** A battery management and ADC section (ETA6098) for monitoring and converting battery voltage.
- OUTPUT:** A section for output signals, including SCL, SDA, 3V3, and GND.
- LCD_BL:** A backlight driver (AP3032KTR-G1) for the LCD display.
- SD_Card:** An SD card interface (TF1) for data storage.
- RGB_Prot:** A color calibration module (U9) for the display.
- MCU:** The central microcontroller unit (ESP32-S3R8) with various peripheral connections.
- QMI:** A QMI module (QM18658A) for cellular communication.
- RTC:** A real-time clock (PCF85063AT) for timekeeping.
- KEY&SWITCH:** A section for user input, including a key and a switch.

The layout also includes a detailed pin list for the MCU, showing connections for various pins (e.g., GPIO0, GPIO1, GPIO2, etc.) to the board's components. The overall design is a professional-grade PCB layout for a complex embedded system.

This figure presents a comprehensive PCB layout for a multi-functional embedded system, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C port connected to the MCU via a USB-C to UART module.
- DC-DC:** A 5V to 3.3V step-down converter using the MP1605GT-FZ.
- FLASH:** An external flash memory (U5) connected to the MCU via SPI.
- BAT&ADC:** A battery monitoring and ADC module (U1) for voltage and current sensing.
- OUTPUT:** A module for driving LEDs and other outputs.
- LCD_BL:** A module for driving an LCD display.
- SD_Card:** An SD card interface module (U1) for data storage.
- RGB_Prot:** A module for controlling RGB LEDs.
- MCU:** The central microcontroller unit (U1) with various peripheral connections.
- RTC:** A real-time clock module (U6) for timekeeping.
- KEY&SWITCH:** A module for handling user input via buttons and switches.

The layout is detailed with component values, pin connections, and a clear labeling system for each block.

This figure presents a comprehensive PCB layout for a multi-functional embedded system, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C port connected to the MCU via a USB-C to UART module.
- DC-DC:** A 5V to 3.3V step-down converter using the MP1605GT-FZ.
- FLASH:** An external flash memory (U5) connected to the MCU via SPI.
- BAT&ADC:** A battery monitoring and ADC module (U1) for voltage and current sensing.
- OUTPUT:** A module for driving LEDs and other outputs.
- LCD_BL:** A module for driving an LCD display.
- SD_Card:** An SD card interface module (U1) for data storage.
- RGB_Prot:** A module for controlling RGB LEDs.
- MCU:** The central microcontroller unit (U1) with various peripheral connections.
- RTC:** A real-time clock module (U6) for timekeeping.
- KEY&SWITCH:** A module for handling user input via buttons and switches.

The layout is detailed with component values, pin connections, and a clear labeling system for each block.

This figure presents a comprehensive PCB layout for a multi-functional embedded system, organized into a grid of functional blocks. The layout includes:

- Type-C Interface:** A USB Type-C port connected to the MCU via a USB-C to UART module.
- DC-DC:** A 5V to 3.3V step-down converter using the MP1605GT-FZ.
- FLASH:** An external flash memory (U5) connected to the MCU via SPI.
- BAT&ADC:** A battery monitoring and ADC module (U1) for voltage and current sensing.
- OUTPUT:** A module for driving an LED (U1) and a buzzer (U2).
- LCD_BL:** A module for driving an LCD display (U1) and an LED (U2).
- SD_Card:** An SD card interface module (U1) for data storage.
- RGB_Prot:** A module for driving an RGB LED (U1) and a buzzer (U2).
- MCU:** The central microcontroller unit (U1) with various peripheral connections.
- RTC:** A real-time clock module (U1) for timekeeping.
- KEY&SWITCH:** A module for user input via a key and a switch.

The layout is detailed with component values, pin connections, and a clear labeling system for each block.