

Keywords of Plotfunction

Miguel Valbuena

September 20, 2026

Contents

1	Colors	8
1.0.1	beige	8
1.0.2	black	8
1.0.3	blue	8
1.0.4	brown	8
1.0.5	cyan	8
1.0.6	dblue	8
1.0.7	dgreen	8
1.0.8	gold	8
1.0.9	green	8
1.0.10	grey	8
1.0.11	lblue	8
1.0.12	lgreen	8
1.0.13	lgrey	9
1.0.14	magenta	9
1.0.15	olive	9
1.0.16	orange	9
1.0.17	pink	9
1.0.18	purple	9
1.0.19	red	9
1.0.20	skyblue	9
1.0.21	violet	9
1.0.22	white	9
1.0.23	yellow	9

2	Commands	9
2.1	analyze:	9
2.2	arclength:	9
2.3	binomtest:	10
2.4	calculate:	10
2.5	derive:	10
2.6	evaluate:	10
2.7	integral:	10
2.8	interpolation:	10
2.9	intersection:	11
2.10	latex-string:	11
2.11	lower-sum:	11
2.12	move:	11
2.13	normal:	11
2.14	osc-circle:	11
2.15	points-in-graph:	11
2.16	reflection:	12
2.17	regression:	12
2.18	reset-colors:	12
2.19	rotate:	12
2.20	show-function:	12
2.21	show-grid:	12
2.22	show-x-axis:	12
2.23	show-x-scale:	13
2.24	show-y-axis:	13
2.25	show-y-scale:	13
2.26	stammfunction:	13
2.27	stretch:	13
2.28	table:	13
2.29	tangent:	13
2.30	taylor-polynomial:	13
2.31	upper-sum:	14
2.32	zero-iteration:	14
3	Constants	14
3.0.1	inf:	14
3.0.2	PI:	14

4	Geometric Objects	14
4.1	bindensity:	14
4.2	bindistribution:	14
4.3	bitmap:	15
4.4	circle:	15
4.5	fill:	15
4.6	geodensity:	15
4.7	histogram:	16
4.8	line	16
4.9	normaldensity:	16
4.10	normaldistribution:	16
4.11	points:	16
4.12	poissondensity:	16
4.13	polygon:	17
4.14	rectangle:	17
4.15	text:	17
4.16	triangle:	17
5	Functions	17
5.1	abs:	17
5.2	arccos:	17
5.3	arcosh:	17
5.4	arcsin:	17
5.5	arctan:	18
5.6	arsinh:	18
5.7	artanh:	18
5.8	cos:	18
5.9	cosh:	18
5.10	exp:	18
5.11	log:	18
5.12	sin:	18
5.13	sinh:	18
5.14	sqrt:	18
5.15	tan:	18
5.16	tanh:	19
6	Settings	19
6.1	axis-color:	19
6.2	axis-fontsize:	19
6.3	axis-names:	19

6.4	axis-range:	19
6.5	axis-scale:	19
6.6	axis-width:	19
6.7	background-color:	19
6.8	default-color:	20
6.9	font-size:	20
6.10	function-color:	20
6.11	function-settings:	20
6.12	function-size:	20
6.13	grid-color:	20
6.14	grid-scale:	20
6.15	grid-width:	20
6.16	margin:	21
6.17	move-increment:	21
6.18	multicolored:	21
6.19	panel-size:	21
6.20	parameter-values:	21
6.21	point-decimals:	21
6.22	point-size:	21
6.23	regression-degree:	21
6.24	select:	22
6.25	values-number:	22
7	Operators in calculate	22
7.1	binomial:	22
7.2	gcd:	22
7.3	lcm:	22
7.4	prod:	22
7.5	sum:	22
8	Alphabetically	24
8.1	A	24
8.1.1	abs	24
8.1.2	analyze:	24
8.1.3	arccos	24
8.1.4	arclength	24
8.1.5	arcosh	24
8.1.6	arcsin	24
8.1.7	arctan	24
8.1.8	arsinh	24

	8.1.9	artanh	24
	8.1.10	axis-color	24
	8.1.11	axis-fontsize	24
	8.1.12	axis-names	24
	8.1.13	axis-range	24
	8.1.14	axis-scale	24
	8.1.15	axis-width	24
8.2	B		24
	8.2.1	background-color	24
	8.2.2	beige	24
	8.2.3	bindensity	24
	8.2.4	bindistribution	24
	8.2.5	binomial	24
	8.2.6	binomtest	24
	8.2.7	bitmap	24
	8.2.8	black	24
	8.2.9	blue	24
	8.2.10	brown	24
8.3	C		24
	8.3.1	calculate	24
	8.3.2	cos	24
	8.3.3	cosh	24
	8.3.4	cyan	24
8.4	D		24
	8.4.1	dblue	24
	8.4.2	derive	24
	8.4.3	default-color	24
	8.4.4	dgreen	24
8.5	E		24
	8.5.1	evaluate	24
	8.5.2	exp	24
8.6	F		24
	8.6.1	fill	24
	8.6.2	font-size	24
	8.6.3	function-color	24
	8.6.4	function-settings	24
	8.6.5	function-size	24
8.7	G		24
	8.7.1	gcd	24
	8.7.2	geodensity	24

	8.7.3	gold	24
	8.7.4	green	24
	8.7.5	grey	24
	8.7.6	grid-color	24
	8.7.7	grid-scale	24
	8.7.8	grid-width	24
8.8	H		24
	8.8.1	histogram	24
8.9	I		24
	8.9.1	inf	24
	8.9.2	integral	24
	8.9.3	interpolation	24
	8.9.4	intersection	24
8.10	L		24
	8.10.1	latex-string	24
	8.10.2	lblue	24
	8.10.3	lcm	24
	8.10.4	lgreen	24
	8.10.5	lgrey	24
	8.10.6	line	24
	8.10.7	log	24
	8.10.8	lower-sum	24
8.11	M		24
	8.11.1	magenta	24
	8.11.2	margin	24
	8.11.3	move	24
	8.11.4	move-increment	24
	8.11.5	multicolored	24
8.12	N		24
	8.12.1	normal	24
	8.12.2	normaldensity	24
	8.12.3	normaldistribution	24
8.13	O		24
	8.13.1	olive	24
	8.13.2	orange	24
	8.13.3	osc-circle	24
8.14	P		24
	8.14.1	panel-size	24
	8.14.2	parameter-values	24
	8.14.3	pink	24

8.14.4	PI	24
8.14.5	point-decimals	24
8.14.6	point-size	24
8.14.7	points	24
8.14.8	points-in-graph	24
8.14.9	poissondensity	24
8.14.10	polygon	24
8.14.11	prod	24
8.14.12	purple	24
8.15	R	24
8.15.1	rectangle	24
8.15.2	red	24
8.15.3	reflection	24
8.15.4	regression	24
8.15.5	regression-degree	24
8.15.6	reset-colors	24
8.15.7	rotate	24
8.16	S	24
8.16.1	select	24
8.16.2	show-function	24
8.16.3	show-grid	24
8.16.4	show-x-axis	24
8.16.5	show-x-scale	24
8.16.6	show-y-axis	24
8.16.7	show-y-scale	24
8.16.8	sin	24
8.16.9	sinh	24
8.16.10	skyblue	24
8.16.11	stammfunction	24
8.16.12	stretch	24
8.16.13	sqrt	24
8.16.14	sum	24
8.17	T	24
8.17.1	table	24
8.17.2	tan	24
8.17.3	tangent	24
8.17.4	tanh	24
8.17.5	taylor-polynomial	24
8.17.6	text	24
8.17.7	triangle	24

8.18	U	24
8.18.1	upper-sum	24
8.19	V	24
8.19.1	values-number	24
8.19.2	violet	24
8.20	W	24
8.20.1	white	24
8.21	Y	24
8.21.1	yellow	24
8.22	Z	24
8.22.1	zero-iteration	24

1 Colors

1.0.1 beige

1.0.2 black

1.0.3 blue

1.0.4 brown

1.0.5 cyan

1.0.6 dblue

Dark blue.

1.0.7 dgreen

Dark green

1.0.8 gold

1.0.9 green

1.0.10 grey

1.0.11 lblue

light blue

1.0.12 lgreen

light green

1.0.13 **lgrey**

light grey

1.0.14 **magenta**

1.0.15 **olive**

1.0.16 **orange**

1.0.17 **pink**

1.0.18 **purple**

1.0.19 **red**

1.0.20 **skyblue**

1.0.21 **violet**

1.0.22 **white**

1.0.23 **yellow**

2 **Commands**

2.1 **analyze:**

Usage: **analyze** [#nr = 1] [x₁ x₂] [prec = 1e-9] [iterations = number of pixels of width][decimals = 4]

Analyses the function number nr in the [x₁ , x₂] interval. prec is the precision used in the algorithms. Iteration is the number of evaluations of that function to count the changes of sign in the given interval. decimals are the number of decimals for rounding all results.

2.2 **arclength:**

Usage: **arclength** [#nr = 1 / “function”] [decimals=4 iterations=50 precision=1e-8] [x₁ x₂]

Calculates the arc length of the function #nr or “function” in the interval [x₁ x₂] if given, or the x axis interval (default). The approximate result is rounded by the given decimals. Iterations and precision are needed in the used algorithms to approximate the integral value (Kepler Simpson).

2.3 binomtest:

Usage: **binomtest** **n**; **<= / = / >=**; **p**; [**$\alpha = 0.05$**]; [**color reject = red**]; [**color accept = green**]

Computes and draws the binomial hypothesis test.

2.4 calculate:

Usage: **calculate arithmetic expression**

2.5 derive:

Usage **derive** [**#nr = 1**]

Derives function to x (x_1).

2.6 evaluate:

Usage **evaluate** [**#nr = 1**] **expressions** [**decimals = 4**]

Evaluates the $\#nr$ -th. function value of the expressions and rounds the result to the given decimals.

2.7 integral:

Usage: **integral** [**#nr = 1 / "term"**] [**decimals iterations precision**] [**x_1 x_2**] [**v <color = lblue**]

Numerical approximation (if possible also exact computation via a stamm-function) of the integral of the $\#nr$ -th function (or the function by the given term) in the interval $[x_1 \ x_2]$. The result is rounded to the given decimals and the algorithms use the given number or iterations and precision (Kepler-Simpson-Algorithm).

With the option v enabled, the areas between the graph of the function and the x -axis in the given interval will be coloured in the given colour.

2.8 interpolation:

Usage: **interpolation** **#nr / points for f** [**points for f'**] [**points for f''**]

Polynomial interpolation of the $\#nr$ -th geometric object (points or polygon) or the given points for f and eventually f' and f'' .

2.9 intersection:

Usage: **intersection** [#nr1 = 1] #nr2 [x₁ x₂] [precision] [iterations] [decimals]

Computes the approximation (if possible also the exact) points of intersection and intersection angle between the #nr1-th and #nr2-th object in the [x₁ x₂] interval. The coordinates are rounded to the given decimals. The Algorithm (Newton) uses the given precision and number of iterations.

2.10 latex-string:

Usage: **latex-string** [#nr = 1]

Translates the #nr-th function term to a latex string. Example: *latex-string* $x/exp(x)$ would compute the string: $\frac{x}{e^x}$

2.11 lower-sum:

Usage: **lower-sum** [#nr = 1]; n; a; b

Computes the lower sum of the function nr over [a,b] with n rectangles.

2.12 move:

Usage: **move** [#nr = 1] dx dy

Moves the #nr-th geometric object dx units to the right (left if dx < 0) and dy units to the top (bottom if dy < 0).

2.13 normal:

Usage: **normal** [#nr = 1] x / x y

Computes the normal to the #nr-th function at x or from the point (x,y).

2.14 osc-circle:

Usage: **osc-circle** [#nr = 1] x

Computes the osculating circle to the #nr-th function (or parametric curve) at x.

2.15 points-in-graph:

Usage: *points-in-graph [#nr = 1] expression1 (x= / y=); expression2... [ddecimal [= 4]] [T (with table)] *

Draws the points in the graph of the nr-th function wrt the given x-, y- or

parameter-expressions.

Example: *points-in-graph* $x=4; y=\text{sqrt}(2); d=2$ draws the points to the graph of the first function wrt to $x = 4$ and $y = \text{sqrt}(2)$. The number of decimals for these points is 2.

2.16 reflection:

Usage: **reflection** [#nr1 = 1] #nr2 / object

Reflects the object nr1 to the axis/point defined by the object nr2.

2.17 regression:

Usage: **regression** #nr [= 1]/points [degree = regression-degree]

Computes the regression polynomial of the given degree wrt the given points or the #nr-th geometric object.

2.18 reset-colors:

Resets all the colors to the default colors.

2.19 rotate:

Usage: **rotate** [#nr = 1] angle (in degrees) x y (center)

Rotates the #nr-th geometric object / function by an angle of the given degrees wrt the given center (x,y).

2.20 show-function:

Usage: **show-function** [#nr = 1] 0/1

Shows (if value is 1) or hides (if value is 0) the #nr-th object.

2.21 show-grid:

Usage: **show-grid** 0/1

Shows (if value is 1) or hides (if value is 0) the grid.

2.22 show-x-axis:

Usage: **show-x-axis** 0/1

Shows (if value is 1) or hides (if value is 0) the x-axis.

2.23 show-x-scale:

Usage: **show-x-scale** 0/1

Shows (if value is 1) or hides (if value is 0) the x-scale.

2.24 show-y-axis:

Usage: **show-x-axis** 0/1

Shows (if value is 1) or hides (if value is 0) the y-axis.

2.25 show-y-scale:

Usage: **show-x-scale** 0/1

Shows (if value is 1) or hides (if value is 0) the y-scale.

2.26 stammfunction:

Usage **stammfunction** [#nr = 1]

Tries to compute the stammfunction wrt (x_1).

2.27 stretch:

Usage: **stretch** [#nr = 1] sx [x]/y ; [sy y]

stretches function nr by stretching factor sx among the x- and sy among the y-axis.

2.28 table:

Usage: **table** [#nr = 1 / "function"] [x₁ x₂] [dx = 0.5] [;]

Evaluates the function in the values from x₁ to x₂ with an increment of dx.

If there is a ; at the end, the values are printed in fractions.

2.29 tangent:

Usage: **tangent** [#nr = 1] x / x y

Computes the tangent to the #nr-th function at x or from the point (x,y).

2.30 taylor-polynomial:

Usage: **taylor-polynomial** [#nr = 1] deg [x0 = 0]

Computes the taylor polynomial or deg-th degree of the nr-th function at x0.

2.31 upper-sum:

Usage: **upper-sum** [#nr = 1]; n; a; b

Computes the upper sum of the function nr over [a,b] with n rectangles.

2.32 zero-iteration:

Usage: *zero-iteration [#nr = 1 / “function”] [decimals iterations precision]
[x₁ x₂] *

Computes the approximation of a root in the [x₁, x₂] interval of the given object.

The result is rounded to the given decimals. The Algorithm (Newton) uses the given precision and number of iterations.

3 Constants

3.0.1 inf:

stands for infinity.

3.0.2 PI:

stands for the irrational number π .

4 Geometric Objects

4.1 bindensity:

Usage: **bindensity** n p [style [transparency [width]]]

Draws the binomial density wrt the variable $X \sim \text{Bin}(n,p)$ ($n > 0$ integer, $0 < p < 1$) in different styles:

style = 0: points are drawn

style = 1: vertical lines are drawn

style = 2: filled rectangles are drawn with the given transparency ($0 \leq \text{transparency} \leq 1$)

where transparency = 0 is transparent and transparency = 1 is solid.

width is the width of the columns (≤ 1).

4.2 bindistribution:

Usage: **bindistribution** n p [style [transparency [width]]]

Draws the binomial distribution wrt the variable $X \sim \text{Bin}(n,p)$ ($n > 0$ integer,

$0 < p < 1$) in different styles:

style = 0: points are drawn

style = 1: vertical lines are drawn

style = 2: filled rectangles are drawn with the given transparency ($0 \leq$
transparency ≤ 0)

where transparency = 0 is transparent and transparency = 1 is solid.

width is the width of the columns (≤ 1).

4.3 bitmap:

Usage: **bitmap_**[nr] x y width height

Draws the stored bitmap nr on to the position x y (axis-coordinates) with the given width and height in pixels.

4.4 circle:

Usage: **circle** x y r [α_1 α_2 [slice]] [<color>]

Draws a circle with middle-point x y, radius r. If α_1 , α_2 is given an arc of circle is drawn, beginning at the angle α_1 and ending at α_2 . If slice = 1 a transparent slice is drawn, if slice = 2 a filled slice is drawn.

4.5 fill:

Usage: **fill** x y [<color>]

Floodfill at the point (x,y) with the given color.

4.6 geodensity:

Usage: **geodensity** p [style [transparency [width]]]

Draws the geometric density wrt the variable $X \sim \text{Geo}(p)$ ($n > 0$ integer,

$0 < p < 1$) in different styles:

style = 0: points are drawn

style = 1: vertical lines are drawn

style = 2: filled rectangles are drawn with the given transparency ($0 \leq$
transparency ≤ 0)

where transparency = 0 is transparent and transparency = 1 is solid.

width is the width of the columns (≤ 1).

4.7 histogram:

Usage: **histogram** **points** [**t** = 0 , **w** = 1] [<color>]

Draws a histogram wrt the given points. t is the value for the transparency of the background color, where 0 is transparent and 1 is opaque. w is the width of the columns wrt the x-axis range.

4.8 line

Usage: **line** **point₁** **point₂** [**h** = 0] [<color,>] l>

Draws a line (or arrow if $h \neq 0$) from point₁ to point₂. h is a float number for the size of the arrowhead (h = 0 for no arrowhead). If l >= 1 the line will be dotted.

4.9 normaldensity:

Usage: **normaldensity** μ σ^2 [**[x1 ,x2]**] [<color,style>]

Draws the normal density function wrt the variable $X \sim \text{Norm}(\mu, \sigma^2)$,
The rest of parameters are used as in usual functions.

4.10 normaldistribution:

Usage: **normaldistribution** μ σ^2 [**[x1 ,x2]**] [<color,style>]

Draws the normal distribution function wrt the variable $X \sim \text{Norm}(\mu, \sigma^2)$,
The rest of parameters are used as in usual functions.

4.11 points:

Usage: **points** **x₁** **y₁** **x₂** **y₂** ... **x_n** **y_n** [<color>]

Draws n points with the given coordinates.

4.12 poissondensity:

Usage: **poissondensity** **lambda** [**style** [**transparency** [**width**]]]

Draws the Poisson density wrt the variable $X \sim \text{Poi}(\text{lambda})$,
where $\text{lambda} > 0$, in different styles:

style = 0: points are drawn

style = 1: vertical lines are drawn

style = 2: filled rectangles are drawn with the given transparency ($0 \leq \text{transparency} \leq 1$)

where transparency = 0 is transparent and transparency = 1 is solid.

width is the width of the columns (≤ 1).

4.13 polygon:

Usage: **polygon** x_1 y_1 x_2 y_2 $\dots$ x_n y_n [**<color>**]

Draws polygon with the n vertices $(x_{1,y1}), \dots, (x_{n,y_n})$.

4.14 rectangle:

Usage: **rectangle** x_1 y_1 x_2 y_2

Draws a rectangle with the left bottom corner $(x_{1,y1})$ and the top right corner $(x_{2,y2})$.

4.15 text:

Usage: **text** {[**l**] **string**} x y [**<color>**]

Displays a string at the coordinates (x,y) .

If latex is installed you can use `lto` to generate a latex string.

4.16 triangle:

Usage: **triangle** x_1 y_1 x_2 y_2 x_3 y_3 [**<color,>**] **l**

Draws a triangle with vertices $(x_{1,y1}), (x_{2,y2}), (x_{3,y3})$.

If $l \geq 1$ the line will be dotted.

5 Functions

5.1 abs:

Absolute value of a real or a complex number.

5.2 arccos:

Arcus cosine function.

5.3 arcosh:

Area hyperbolic cosine function.

5.4 arcsin:

Arcus sine function.

5.5 arctan:

Arcus tangent function.

5.6 arsinh:

Area hyperbolic sine function.

5.7 artanh:

Area hyperbolic tangent function.

5.8 cos:**5.9 cosh:**

Hyperbolic cosine.

5.10 exp:

The exponential function.

5.11 log:

Logarithmus Naturalis.

5.12 sin:

Sine function.

5.13 sinh:

Hyperbolic cosine.

5.14 sqrt:

The square root function.

5.15 tan:

The trigonometric tangent function.

5.16 tanh:

Hyperbolic tangent function.

6 Settings

6.1 axis-color:

Usage: **axis-color** / **Red Green Blue**

Use with the defined colors or input three values from 0 to 255 for the red, green and blue part.

6.2 axis-fontsize:

Usage **axis-fontsize** **unsigned int**

6.3 axis-names:

Usage: **axis-names** **string string**

Example: *axis-names x y*

6.4 axis-range:

Usage: **axis-range** **x₁ x₂ [: y₁ y₂]**

Example: *axis-range -3 5 : -2 7* : x values range from -3 to 5, y values from -2 to 7 *axis-range 5 : 10* : x values from -5 to 5, y values from -10 to 10.

6.5 axis-scale:

Usage : **axis-scale** **sx [sy = sx]**

Example: *axis-scale PI/2 1*

6.6 axis-width:

Usage: **axis-width** **unsigned int**

thickness of axis lines in pixels

6.7 background-color:

Usage: **background-color** **def. color / Red Green Blue**

Use with the defined colors or input three values from 0 to 255 for the red, green and blue part.

6.8 default-color:

Usage: **default-color** **def. color** / **Red Green Blue**

Sets the default color for objects when multicolored is off.

6.9 font-size:

Usage: **font-size** **unsigned int**

Sets the font size in pixels for input/output text.

6.10 function-color:

Usage: **function-color** [**#nr = 1**] **defined color** / **Red Green Blue**

Draws the #nr-th function/geometric object with the given defined color or the color defined by the three values from 0 to 255 for the red, green and blue part.

6.11 function-settings:

Usage: **function-settings** [**#nr = 1**]

Opens a settings dialog for the #nr-th. function or geometric object.

6.12 function-size:

Usage: **function-size** [**#nr = 1**] **unsigned number**

Sets the line thickness of the #nr-th. function/geometric object to the given number.

6.13 grid-color:

Usage: **grid.-color** **def. color** / **Red Green Blue**

Draws the grid lines in the given defined or the color obtained by the three values for the red, green and blue part (from 0 to 255 each).

6.14 grid-scale:

Usage: **grid-scale** **sx** [**sy = sx**]

Example: *grid-scale* $\pi/2$ 1

6.15 grid-width:

Usage: **grid-width** **unsigned int**

thickness of grid lines in pixels

6.16 margin:

Usage: **margin unsigned int**

Sets the margin (offset) of the coordinates system in pixels.

6.17 move-increment:

Usage: **move-increment dx [dy=dx] (p for pixels)**

Move increment values for moving objects or the coordinate system with the arrow-keys.

6.18 multicolored:

Usage: **multicolored 1/0**

Toggle multicolored objects.

6.19 panel-size:

Usage: **panel-size sx [sy = sx]**

6.20 parameter-values:

Usage: **parameter-values double ...**

Sets the values for the parameter t of the functions.

6.21 point-decimals:

Usage: **point-decimals int**

6.22 point-size:

Usage: **point-size int**

Sets the size in pixel for points (wrt to style 1 and 2)

6.23 regression-degree:

Usage: **regression-degree unsigned int**

Sets the regression degree for the regression computations.

6.24 **select:**

Usage: **select** [#nr=1]

Selects (highlights) the nr-th function.

6.25 **values-number:**

Usage: **values-number unsigned int**

The number of points that are evaluated for rendering the functions.

7 Operators in calculate

When applying calculate, these operators are available:

7.1 **binomial:**

Usage: **binomial(n,k)**

Computes the binomial coefficient on n over k.

7.2 **gcd:**

Usage: **gcd(a₁, a₂, ..., a_n)**

Computes the greatest common divisor of the integers a_i's.

7.3 **lcm:**

Usage: **lcm(a₁, a₂, ..., a_n)**

Computes the least common multiple of the integers a_i's.

7.4 **prod:**

Usage: **prod([var = k] = beg, end, expression)**

Computes the product over the variable var from integer beg to end of the expression.

7.5 **sum:**

Usage: **sum([var = k] = beg, end, expression)**

Computes the sum over the variable var from integer beg to end of the expression.

8 Alphabetically

8.1 A

8.1.1 abs

8.1.2 analyze:

8.1.3 arccos

8.1.4 arclength

8.1.5 arcosh

8.1.6 arcsin

8.1.7 arctan

8.1.8 arsinh

8.1.9 artanh

8.1.10 axis-color

8.1.11 axis-fontsize

8.1.12 axis-names

8.1.13 axis-range

8.1.14 axis-scale

8.1.15 axis-width

8.2 B

8.2.1 background-color

8.2.2 beige

8.2.3 bindensity

8.2.4 bindistribution

8.2.5 binomial

8.2.6 binomtest

8.2.7 bitmap

8.2.8 black

8.2.9 blue

8.2.10 brown

8.3 C

8.3.1 calculate

8.3.2 cos

8.3.3 cosh