

Keywords of Plotfunction

Miguel Valbuena

May 17, 2026

Contents

1	Colors	7
1.0.1	beige	7
1.0.2	black	7
1.0.3	blue	7
1.0.4	brown	7
1.0.5	cyan	7
1.0.6	dblue	7
1.0.7	dgreen	7
1.0.8	gold	8
1.0.9	green	8
1.0.10	grey	8
1.0.11	lblue	8
1.0.12	lgreen	8
1.0.13	lgrey	8
1.0.14	magenta	8
1.0.15	olive	8
1.0.16	orange	8
1.0.17	pink	8
1.0.18	purple	8
1.0.19	red	8
1.0.20	skyblue	8
1.0.21	violet	8
1.0.22	white	8
1.0.23	yellow	8

2	Commands	8
2.1	analyze:	8
2.2	arclength:	9
2.3	calculate:	9
2.4	derive:	9
2.5	evaluate:	9
2.6	integral:	9
2.7	interpolation:	9
2.8	intersection:	10
2.9	latex-string:	10
2.10	move:	10
2.11	normal:	10
2.12	osc-circle:	10
2.13	points-in-graph:	10
2.14	reflection:	11
2.15	regression:	11
2.16	reset-colors:	11
2.17	rotate:	11
2.18	show-function:	11
2.19	show-grid:	11
2.20	show-x-axis:	11
2.21	show-x-scale:	11
2.22	show-y-axis:	12
2.23	show-y-scale:	12
2.24	table:	12
2.25	tangent:	12
2.26	taylor-polynomial:	12
2.27	zero-iteration:	12
3	Constants	12
3.0.1	inf:	12
3.0.2	PI:	13
4	Geometric Objects	13
4.1	bindensity:	13
4.2	bitmap:	13
4.3	circle:	13
4.4	fill:	13
4.5	geodensity:	13
4.6	histogram:	14

4.7	line	14
4.8	normaldensity:	14
4.9	normaldistribution:	14
4.10	points:	14
4.11	poissondensity:	14
4.12	polygon:	15
4.13	rectangle:	15
4.14	text:	15
4.15	triangle:	15
5	Functions	15
5.1	abs:	15
5.2	arccos:	15
5.3	arcosh:	16
5.4	arcsin:	16
5.5	arctan:	16
5.6	arsinh:	16
5.7	artanh:	16
5.8	cos:	16
5.9	cosh:	16
5.10	exp:	16
5.11	log:	16
5.12	sin:	16
5.13	sinh:	16
5.14	sqrt:	17
5.15	tan:	17
5.16	tanh:	17
6	Settings	17
6.1	axis-color:	17
6.2	axis-fontsize:	17
6.3	axis-names:	17
6.4	axis-range:	17
6.5	axis-scale:	17
6.6	background-color:	18
6.7	font-size:	18
6.8	function-color:	18
6.9	function-settings:	18
6.10	function-size:	18
6.11	grid-color:	18

6.12	grid-scale:	18
6.13	margin:	19
6.14	move-increment:	19
6.15	panel-size:	19
6.16	parameter-values:	19
6.17	point-decimals:	19
6.18	point-size:	19
6.19	regression-degree:	19
6.20	select:	19
6.21	values-number:	20
7	Alphabetically	22
7.1	A	22
7.1.1	abs	22
7.1.2	analyze:	22
7.1.3	arccos	22
7.1.4	arclength	22
7.1.5	arcosh	22
7.1.6	arcsin	22
7.1.7	arctan	22
7.1.8	arsinh	22
7.1.9	artanh	22
7.1.10	axis-color	22
7.1.11	axis-fontsize	22
7.1.12	axis-names	22
7.1.13	axis-range	22
7.1.14	axis-scale	22
7.2	B	22
7.2.1	background-color	22
7.2.2	beige	22
7.2.3	bindensity	22
7.2.4	bitmap	22
7.2.5	black	22
7.2.6	blue	22
7.2.7	brown	22
7.3	C	22
7.3.1	calculate	22
7.3.2	cos	22
7.3.3	cosh	22
7.3.4	cyan	22

7.4	D	22
	7.4.1 dblue	22
	7.4.2 derive	22
	7.4.3 dgreen	22
7.5	E	22
	7.5.1 evaluate	22
	7.5.2 exp	22
7.6	F	22
	7.6.1 fill	22
	7.6.2 font-size	22
	7.6.3 function-color	22
	7.6.4 function-settings	22
	7.6.5 function-size	22
7.7	G	22
	7.7.1 geodensity	22
	7.7.2 gold	22
	7.7.3 green	22
	7.7.4 grey	22
	7.7.5 grid-color	22
	7.7.6 grid-scale	22
7.8	H	22
	7.8.1 histogram	22
7.9	I	22
	7.9.1 inf	22
	7.9.2 integral	22
	7.9.3 interpolation	22
	7.9.4 intersection	22
7.10	L	22
	7.10.1 latex-string	22
	7.10.2 lblue	22
	7.10.3 lgreen	22
	7.10.4 lgrey	22
	7.10.5 line	22
	7.10.6 log	22
7.11	M	22
	7.11.1 magenta	22
	7.11.2 margin	22
	7.11.3 move	22
	7.11.4 move-increment	22
7.12	N	22

7.12.1	normal	22
7.12.2	normaldensity	22
7.12.3	normaldistribution	22
7.13	O	22
7.13.1	olive	22
7.13.2	orange	22
7.13.3	osc-circle	22
7.14	P	22
7.14.1	panel-size	22
7.14.2	parameter-values	22
7.14.3	pink	22
7.14.4	PI	22
7.14.5	point-decimals	22
7.14.6	point-size	22
7.14.7	points	22
7.14.8	points-in-graph	22
7.14.9	poissondensity	22
7.14.10	polygon	22
7.14.11	purple	22
7.15	R	22
7.15.1	rectangle	22
7.15.2	red	22
7.15.3	reflection	22
7.15.4	regression	22
7.15.5	regression-degree	22
7.15.6	reset-colors	22
7.15.7	rotate	22
7.16	S	22
7.16.1	select	22
7.16.2	show-function	22
7.16.3	show-grid	22
7.16.4	show-x-axis	22
7.16.5	show-x-scale	22
7.16.6	show-y-axis	22
7.16.7	show-y-scale	22
7.16.8	sin	22
7.16.9	sinh	22
7.16.10	skyblue	22
7.16.11	sqrt	22
7.17	T	22

7.17.1	table	22
7.17.2	tan	22
7.17.3	tangent	22
7.17.4	tanh	22
7.17.5	taylor-polynomial	22
7.17.6	text	22
7.17.7	triangle	22
7.18	V	22
7.18.1	values-number	22
7.18.2	violet	22
7.19	W	22
7.19.1	white	22
7.20	Y	22
7.20.1	yellow	22
7.21	Z	22
7.21.1	zero-iteration	22

1 Colors

1.0.1 beige

1.0.2 black

1.0.3 blue

1.0.4 brown

1.0.5 cyan

1.0.6 dblue

Dark blue.

1.0.7 dgreen

Dark green

1.0.8 gold

1.0.9 green

1.0.10 grey

1.0.11 lblue

light blue

1.0.12 lgreen

light green

1.0.13 lgrey

light grey

1.0.14 magenta

1.0.15 olive

1.0.16 orange

1.0.17 pink

1.0.18 purple

1.0.19 red

1.0.20 skyblue

1.0.21 violet

1.0.22 white

1.0.23 yellow

2 Commands

2.1 analyze:

Usage: **analyze** [#nr = 1] [x₁ x₂] [prec = 1e-9] [iterations = number of pixels of width][decimals = 4]

Analyses the function number nr in the [x₁ , x₂] interval. prec is the precision used in the algorithms. Iteration is the number of evaluations of that function

to count the changes of sign in the given interval. decimals are the number of decimals for rounding all results.

2.2 arclength:

Usage: **arclength** [#nr = 1 / “function”] [decimals=4 iterations=50 precision=1e-8] [x₁ x₂]

Calculates the arc length of the function #nr or “function” in the interval [x₁ x₂] if given, or the x axis interval (default). The approximate result is rounded by the given decimals. Iterations and precision are needed in the used algorithms to approximate the integral value (Kepler Simpson).

2.3 calculate:

Usage: **calculate arithmetic expression**

2.4 derive:

Usage **derive** [#nr = 1]

Derives function to x (x₁).

2.5 evaluate:

Usage **evaluate** [#nr = 1] expressions [decimals = 4]

Evaluates the #nr-th. function value of the expressions and rounds the result to the given decimals.

2.6 integral:

Usage: **integral** [#nr = 1 / “term”] [decimals iterations precision] [x₁ x₂]

Numerical approximation (if possible also exact computation via a stamm-function) of the integral of the #nr-th function (or the function by the given term) in the interval [x₁ x₂]. The result is rounded to the given decimals and the algorithms use the given number or iterations and precision (Kepler-Simpson-Algorithm).

2.7 interpolation:

Usage: **interpolation** #nr / points for f [; points for f'] [;points for f'']

Polynomial interpolation of the $\#nr$ -th geometric object (points or polygon) or the given points for f and eventually f' and f'' .

2.8 intersection:

Usage: **intersection** [$\#nr1 = 1$] $\#nr2$ [x_1 x_2] [**precision**] [**iterations**] [**decimals**]

Computes the approximation (if possible also the exact) points of intersection and intersection angle between the $\#nr1$ -th and $\#nr2$ -th object in the $[x_1$ $x_2]$ interval. The coordinates are rounded to the given decimals. The Algorithm (Newton) uses the given precision and number of iterations.

2.9 latex-string:

Usage: **latex-string** [$\#nr = 1$]

Translates the $\#nr$ -th function term to a latex string. Example: *latex-string* $x/exp(x)$ would compute the string: $\frac{x}{e^x}$

2.10 move:

Usage: **move** [$\#nr = 1$] dx dy

Moves the $\#nr$ -th geometric object dx units to the right (left if $dx < 0$) and dy units to the top (bottom if $dy < 0$).

2.11 normal:

Usage: **normal** [$\#nr = 1$] x / x y

Computes the normal to the $\#nr$ -th function at x or from the point (x,y) .

2.12 osc-circle:

Usage: **osc-circle** [$\#nr = 1$] x

Computes the osculating circle to the $\#nr$ -th function (or parametric curve) at x .

2.13 points-in-graph:

Usage: **points-in-graph** [$\#nr = 1$] **expression1** ($x=$ / $y=$); **expression2**... [**ddecimals** [$= 4$]]

Draws the points in the graph of the nr -th function wrt the given x -, y - or parameter-expressions.

Example: *points-in-graph* $x=4; y=sqrt(2); d=2$ draws the points to the graph

of the first function wrt to $x = 4$ and $y = \sqrt{2}$. The number of decimals for these points is 2.

2.14 reflection:

Usage: **reflection** [#nr1 = 1] #nr2 / object

Reflects the object nr1 to the axis/point defined by the object nr2.

2.15 regression:

Usage: **regression** #nr [= 1]/points [degree = regression-degree]

Computes the regression polynomial of the given degree wrt the given points or the #nr-th geometric object.

2.16 reset-colors:

Resets all the colors to the default colors.

2.17 rotate:

Usage: **rotate** [#nr = 1] angle (in degrees) x y (center)

Rotates the #nr-th geometric object / function by an angle of the given degrees wrt the given center (x,y).

2.18 show-function:

Usage: **show-function** [#nr = 1] 0/1

Shows (if value is 1) or hides (if value is 0) the #nr-th object.

2.19 show-grid:

Usage: **show-grid** 0/1

Shows (if value is 1) or hides (if value is 0) the grid.

2.20 show-x-axis:

Usage: **show-x-axis** 0/1

Shows (if value is 1) or hides (if value is 0) the x-axis.

2.21 show-x-scale:

Usage: **show-x-scale** 0/1

Shows (if value is 1) or hides (if value is 0) the x-scale.

2.22 show-y-axis:

Usage: **show-x-axis** 0/1

Shows (if value is 1) or hides (if value is 0) the y-axis.

2.23 show-y-scale:

Usage: **show-x-scale** 0/1

Shows (if value is 1) or hides (if value is 0) the y-scale.

2.24 table:

Usage: **table** [#nr = 1 / “function”] [x₁ x₂] [dx = 0.5] [;]

Evaluates the function in the values from x₁ to x₂ with an increment of dx.

If there is a ; at the end, the values are printed in fractions.

2.25 tangent:

Usage: **tangent** [#nr = 1] x / x y

Computes the tangent to the #nr-th function at x or from the point (x,y).

2.26 taylor-polynomial:

Usage: **taylor-polynomial** [#nr = 1] deg [x0 = 0]

Computes the taylor polynomial of deg-th degree of the nr-th function at x0.

2.27 zero-iteration:

Usage: *zero-iteration [#nr = 1 / “function”] [decimals iterations precision]
[x₁ x₂] *

Computes the approximation of a root in the [x₁, x₂] interval of the given object.

The result is rounded to the given decimals. The Algorithm (Newton) uses the given precision and number of iterations.

3 Constants

3.0.1 inf:

stands for infinity.

3.0.2 PI:

stands for the irrational number π .

4 Geometric Objects

4.1 bindensity:

Usage: **bindensity n p [style [transparency [width]]]**

Draws the binomial density wrt the variable $X \sim \text{Bin}(n, p)$ ($n > 0$ integer, $0 < p < 1$) in different styles:

style = 0: points are drawn

style = 1: vertical lines are drawn

style = 2: filled rectangles are drawn with the given transparency ($0 \leq \text{transparency} \leq 1$)

where transparency = 0 is transparent and transparency = 1 is solid.

width is the width of the columns (≤ 1).

4.2 bitmap:

Usage: **bitmap _[nr] x y width height**

Draws the stored bitmap nr on to the position x y (axis-coordinates) with the given width and height in pixels.

4.3 circle:

Usage: **circle x y r [α_1 α_2 [slice]] [<color>]**

Draws a circle with middle-point x y, radius r. If α_1, α_2 is given an arc of circle is drawn, beginning at the angle α_1 and ending at α_2 . If slice = 1 a transparent slice is drawn, if slice = 2 a filled slice is drawn.

4.4 fill:

Usage: **fill x y [<color>]**

Floodfill at the point (x,y) with the given color.

4.5 geodensity:

Usage: **geodensity p [style [transparency [width]]]**

Draws the geometric density wrt the variable $X \sim \text{Geo}(p)$ ($n > 0$ integer, $0 < p < 1$) in different styles:

style = 0: points are drawn
 style = 1: vertical lines are drawn
 style = 2: filled rectangles are drawn with the given transparency ($0 \leq \text{transparency} \leq 1$)
 where transparency = 0 is transparent and transparency = 1 is solid.
 width is the width of the columns (≤ 1).

4.6 histogram:

Usage: **histogram** **points** [**t** = 0 , **w** = 1] [<color>]

Draws a histogram wrt the given points. t is the value for the transparency of the background color, where 0 is transparent and 1 is opaque. w is the width of the columns wrt the x-axis range.

4.7 line

Usage: **line** **point₁** **point₂** [**h** = 0] [<color,>] l>

Draws a line (or arrow if $h \neq 0$) from point₁ to point₂. h is a float number for the size of the arrowhead ($h = 0$ for no arrowhead). If $l \geq 1$ the line will be dotted.

4.8 normaldensity:

Usage: **normaldensity** μ σ^2 [[**x1** ,**x2**]] [<color,style>]

Draws the normal density function wrt the variable $X \sim \text{Norm}(\mu, \sigma^2)$,
 The rest of parameters are used as in usual functions.

4.9 normaldistribution:

Usage: **normaldistribution** μ σ^2 [[**x1** ,**x2**]] [<color,style>]

Draws the normal distribution function wrt the variable $X \sim \text{Norm}(\mu, \sigma^2)$,
 The rest of parameters are used as in usual functions.

4.10 points:

Usage: **points** **x₁** **y₁** **x₂** **y₂** ... **x_n** **y_n** [<color>]

Draws n points with the given coordinates.

4.11 poissondensity:

Usage: **poissondensity** **lambda** [**style** [**transparency** [**width**]]]

Draws the Poisson density wrt the variable $X \sim \text{Poi}(\text{lambda})$,

where $\lambda > 0$, in different styles:
 style = 0: points are drawn
 style = 1: vertical lines are drawn
 style = 2: filled rectangles are drawn with the given transparency ($0 \leq \text{transparency} \leq 1$)
 where transparency = 0 is transparent and transparency = 1 is solid.
 width is the width of the columns (≤ 1).

4.12 polygon:

Usage: **polygon** $x_1 y_1 x_2 y_2 \dots x_n y_n$ [**<color>**]
 Draws polygon with the n vertices $(x_{1,y1}), \dots, (x_{n,y_n})$.

4.13 rectangle:

Usage: **rectangle** $x_1 y_1 x_2 y_2$
 Draws a rectangle with the left bottom corner $(x_{1,y1})$ and the top right corner $(x_{2,y2})$.

4.14 text:

Usage: **text** {[**l**] **string**} $x y$ [**<color>**]
 Displays a string at the coordinates (x,y) .
 If latex is installed you can use `\to` generate a latex string.

4.15 triangle:

Usage: **triangle** $x_1 y_1 x_2 y_2 x_3 y_3$ [**<[color,] l>**]
 Draws a triangle with vertices $(x_{1,y1}), (x_{2,y2}), (x_{3,y3})$.
 If $l \geq 1$ the line will be dotted.

5 Functions

5.1 abs:

Absolute value of a real or a complex number.

5.2 arccos:

Arcus cosine function.

5.3 arcosh:

Area hyperbolic cosine function.

5.4 arcsin:

Arcus sine function.

5.5 arctan:

Arcus tangent function.

5.6 arsinh:

Area hyperbolic sine function.

5.7 artanh:

Area hyperbolic tangent function.

5.8 cos:**5.9 cosh:**

Hyperbolic cosine.

5.10 exp:

The exponential function.

5.11 log:

Logarithmus Naturalis.

5.12 sin:

Sine function.

5.13 sinh:

Hyperbolic cosine.

5.14 **sqrt:**

The square root function.

5.15 **tan:**

The trigonometric tangent function.

5.16 **tanh:**

Hyperbolic tangent function.

6 Settings

6.1 **axis-color:**

Usage: **def. color / Red Green Blue**

Use with the defined colors or input three values from 0 to 255 for the red, green and blue part.

6.2 **axis-fontsize:**

Usage **axis-fontsize unsigned int**

6.3 **axis-names:**

Usage: **axis-names string string**

Example: *axis-names x y*

6.4 **axis-range:**

Usage: **axis-range x₁ x₂ [: y₁ y₂]**

Example: *axis-range -3 5 : -2 7* : x values range from -3 to 5, y values from -2 to 7 *axis-range 5 : 10* : x values from -5 to 5, y values from -10 to 10.

6.5 **axis-scale:**

Usage : **axis-scale sx [sy = sx]**

Example: *axis-scale PI/2 1*

6.6 background-color:

Usage: **background-color** **def. color** / **Red Green Blue**

Use with the defined colors or input three values from 0 to 255 for the red, green and blue part.

6.7 font-size:

Usage: **font-size** **unsigned int**

Sets the font size in pixels for input/output text.

6.8 function-color:

Usage: **function-color** [**#nr = 1**] **defined color** / **Red Green Blue**

Draws the #nr-th function/geometric object with the given defined color or the color defined by the three values from 0 to 255 for the red, green and blue part.

6.9 function-settings:

Usage: **function-settings** [**#nr = 1**]

Opens a settings dialog for the #nr-th. function or geometric object.

6.10 function-size:

Usage: **function-size** [**#nr = 1**] **unsigned number**

Sets the line thickness of the #nr-th. function/geometric object to the given number.

6.11 grid-color:

Usage: **grid.-color** **def. color** / **Red Green Blue**

Draws the grid lines in the given defined or the color obtained by the three values for the red, green and blue part (from 0 to 255 each).

6.12 grid-scale:

Usage: **grid-scale** **sx** [**sy = sx**]

Example: *grid-scale* $\pi/2$ 1

6.13 margin:

Usage: **margin unsigned int**

Sets the margin (offset) of the coordinates system in pixels.

6.14 move-increment:

Usage: **move-increment dx [dy=dx] (p for pixels)**

Move increment values for moving objects or the coordinate system with the arrow-keys.

6.15 panel-size:

Usage: **panel-size sx [sy = sx]**

6.16 parameter-values:

Usage: **parameter-values double ...**

Sets the values for the parameter t of the functions.

6.17 point-decimals:

Usage: **point-decimals int**

6.18 point-size:

Usage: **point-size int**

Sets the size in pixel for points (wrt to style 1 and 2)

6.19 regression-degree:

Usage: **regression-degree unsigned int**

Sets the regression degree for the regression computations.

6.20 select:

Usage: **select [#nr=1]**

Selects (highlights) the nr-th function.

6.21 values-number:

Usage **values-number unsigned int**

The number of points that are evaluated for rendering the functions.

7 Alphabetically

7.1 A

7.1.1 abs

7.1.2 analyze:

7.1.3 arccos

7.1.4 arclength

7.1.5 arcosh

7.1.6 arcsin

7.1.7 arctan

7.1.8 arsinh

7.1.9 artanh

7.1.10 axis-color

7.1.11 axis-fontsize

7.1.12 axis-names

7.1.13 axis-range

7.1.14 axis-scale

7.2 B

7.2.1 background-color

7.2.2 beige

7.2.3 bindensity

7.2.4 bitmap

7.2.5 black

7.2.6 blue

7.2.7 brown

7.3 C

7.3.1 calculate

7.3.2 cos

7.3.3 cosh

7.3.4 cyan

7.4 D

7.4.1 dblue

7.4.2 derive