

TP QPE and Shor

Valeran MAYTIE

1 Small Practice




Figure 1: Circuit that calculate $\frac{1}{\sqrt{2}}(|000\rangle + |111\rangle)$

To compute $\frac{1}{\sqrt{2}}(|000\rangle + |111\rangle)$, we created the circuit shown in Figure 1. Firstly we apply an Hadamard Gate on the first qubit to have a 50/50 chance of having it at 1 or 0. If it's equal to one then with a *CNot* gate controlled by the first qubit we inverse q_1 and q_2 , so they are all equal to 1. Else nothing change and it remains at 0.

When you run it, you'll find the right measurements the result is roughly 50/50, 000 or 111.

The code for this exercise is shown in Listing 1

```
1 q = QuantumRegister(3)
2 c = ClassicalRegister(3)
3 qc = QuantumCircuit(q,c)
4
5 qc.h(q[0])
6
7 qc.cnot(q[0],q[1])
8 qc.cnot(q[0],q[2])
9
10 qc.measure(q, c)
```

Listing 1: Code that generates the circuit in Figure 1

2 QPE

We construct the operator \mathbf{U} with this matrix :

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & e^{2i\pi\frac{6}{8}} \end{pmatrix}$$

2.1 Math Questions

1. What is doing this operator ? ('2j' is in Python the complex number $2 \cdot i$)

The operator \mathbf{U} compute this :

- $\mathbf{U}|00\rangle = |00\rangle$
- $\mathbf{U}|01\rangle = |01\rangle$
- $\mathbf{U}|10\rangle = |10\rangle$
- $\mathbf{U}|11\rangle = e^{2i\pi\frac{6}{8}}|11\rangle$

2. On how many qubits does it act ?

This operator act on 2 qubits.

3. What are its eigenvalues/eigenvectors ?

eigenvectors	eigenvalues
$ 00\rangle$	1
$ 01\rangle$	1
$ 10\rangle$	1
$ 11\rangle$	$e^{2i\pi\frac{6}{8}}$

4. For each eigenvector, what should QPE return with 3 bits of precisions, as seen in the course ?

eigenvectors	QPE return
$ 00\rangle$	000
$ 01\rangle$	000
$ 10\rangle$	000
$ 11\rangle$	110

2.2 Implementing QPE




Figure 2: QPE circuit

```

1 eig = QuantumRegister(size_eig, name="eig")
2 phi = QuantumRegister(size_phi, name="phi")
3 ceig = ClassicalRegister(size_eig, name="ceig")
4 qc = QuantumCircuit(eig, phi, ceig)
5
6 qc.x(phi[0])
7 qc.x(phi[1])
8 for i in range(0, size_eig):
9     qc.h(eig[i])
10    qc.append(U.power(2**i).control(), [eig[i], phi[0], phi[1]])
11
12 qc.append(QFT(size_eig).inverse(), eig)
13 qc.measure(eig, ceig)

```

Listing 2: Code that generate the QPE circuit

2.3 Exact result

1. Is it the expected result ?

Yes, we calculated $110 \equiv \frac{1}{2} + \frac{1}{4} = \frac{6}{8}$ so $\mathbf{U}|11\rangle = e^{2i\pi\theta}|11\rangle$.

With 3 bits precision θ is equal to $\frac{6}{8}$ seen in Exercise 2.1.1.

2. Change the $\frac{6}{8}$ of the phase of U : use $\frac{1}{8}$, then $\frac{2}{8}$... Is QPE returning the correct answer ?

Yes, we have 001, 010, ... and 111, when we tested up to $\frac{7}{8}$, because there is enough precision. But then we get the right result modulo 8.

3. Change the precision : use 4 qubits for "eig", and change the fraction in the phase of \mathbf{U} to $\frac{10}{16}$: is QPE indeed returning 10 in binary ?

We have 10 written in binary. It works because we have enough precision to get the real eigenvalues.

4. Move to 5 bits of precision is it still working ?

It works, we have $\frac{1}{2} + \frac{1}{8} = \frac{10}{16}$

2.4 Approximate result

The QPE approach calculations with 3-bits precision are given in the table below

value	number of times obtained
000	21
001	34
010	178
011	708
100	39
101	20
110	10
111	14
average / 2^3	0.365

We can see that the average divided by two power of precision is close to the eigenvalue ($\frac{1}{3}$). And the more you increase the accuracy, the closer you get to $\frac{1}{3}$.

2.5 Superposition

By changing the phi initialization to $\frac{1}{\sqrt{2}}(|\phi_1\rangle + |\phi_2\rangle)$ Two calculations are performed in parallel, one to calculate the eigenvalue of eigenvectors $|11\rangle$ and $|00\rangle$.

For the phase it works very well we have :

<i>phi</i>	<i>eig</i>	
00	000	498
11	011	526

3 Implementing Shor's algorithm

3.1 Oracle synthesis

3.2 Plugging everything together : Shor