TÖL304G Einstaklingsverkefni 2

Valtýr Örn Kjartansson (vok4)

12. september 2019

1. Dæmi

```
Permalink á lausn: https://rise4fun.com/Dafny/tRrK
Lausn:
// Exercise in TÖL304G
// Write your name and university email address here:
// Valtýr Örn Kjartansson vok4@hi.is
// Finish the following so that Dafny accepts
// it by adding some program text where indicated.
// Make no other changes.
function SumInts( k: int ): int
  requires k \ge 0;
{
  if k==0 then
    0
  else
    SumInts(k-1)+k
}
method ComputeSumIntsLoop( k: int ) returns ( r: int )
  requires k \ge 0;
  ensures r == (k+1)*k/2;
  ensures r == SumInts(k);
{
  r := 0;
  var i := 0;
  while i != k
```

```
decreases k - i;
    invariant 0 <= i <= k;</pre>
    invariant r == (i+1)*i/2;
    invariant r == SumInts(i);
    i := i + 1;
    r := r + i;
  }
}
method ComputeSumIntsRecursive( k: int ) returns ( r: int )
  requires k \ge 0;
  ensures r == (k+1)*k/2;
  ensures r == SumInts(k);
  decreases k;
{
  if k==0
  {
   r := 0;
    return;
 r := ComputeSumIntsRecursive(k-1);
  r := r + k;
}
method ComputeSumIntsTailRecursive( k: int, i: int, q: int ) returns ( r: int )
  requires 0 <= i <= k;
  requires q == (i+1)*i/2;
  requires q == SumInts(i);
  ensures r == (k+1)*k/2;
  ensures r == SumInts(k);
  decreases k-i;
{
  if i==k
   r := q;
    return;
 r := ComputeSumIntsTailRecursive(k, i+1, q + i + 1);
```