

# P8160 Group Project Presentation

## Optimization and Bootstrap

Xinlei Chen, Guojing Wu, Yujing Yao

Department of Biostatistics, Columbia University

April 19, 2019

- 1 Introduction
- 2 Project: Optimization
- 3 Project: Bootstrap



# Introduction

# Introduction

- **Group project 2:** Optimization algorithms on a breast cancer diagnosis dataset
- **Group project 3:** Bootstrapping on developing classification model

# Project: Optimization

# Background


# Breast Cancer Data

- **Amin:** Build a predictive model based on logistic regression to facilitate cancer diagnosis, and we compared methods including Newton Raphson, Gradient Decent with general logistic regression and Pathwise Coordinate Descent with regularized logistic regression



# Multicollinearity plot of the dataset

- **Variable Selection:** Reduce multicollinearity based on both correlation coefficient and eigenvalue of correlation matrix



# Method

# Logistic Model

## Logistic Regression:

$y$ : the vector of  $n$  response random variable

$X$ : the  $n \times p$  design matrix ( $X_i$  denote the  $i$ th row)

$\beta$ : the  $p \times 1$  coefficient

- The logistic regression model:

$$\log\left(\frac{\eta}{1-\eta}\right) = X\beta$$

- The likelihood function:

$$L(\beta; X, y) = \prod_{i=1}^n \left\{ \left( \frac{\exp(X_i\beta)}{1 + \exp(X_i\beta)} \right)^{y_i} \left( \frac{1}{1 + \exp(X_i\beta)} \right)^{1-y_i} \right\}$$

# Newton Raphson

- The log likelihood:

$$l(\beta) = \sum_{i=1}^n \{y_i(X_i\beta) - \log(1 + \exp(X_i\beta))\}$$

- The gradient:

$$\nabla l(\beta) = X^T(y - p)$$

where  $p = \frac{\exp(X\beta)}{1 + \exp(X\beta)}$

- The Hessian:

$$\nabla^2 l(\beta) = -X^T W X$$

where  $W = \text{diag}(p_i(1 - p_i)), i = 1, \dots, n$ . The Hessian is negative definite.

# Newton Raphson

*Update coefficients*

$$\beta_{i+1} = \beta_i - [\nabla^2 l(\beta_i)]^{-1} \nabla l(\beta_i)$$

*Step-halving*

$$\beta_{i+1}(\gamma) = \beta_i - \gamma [\nabla^2 l(\beta_i)]^{-1} \nabla l(\beta_i)$$

- Set  $\gamma = 1$
- If  $f(\theta_{i+1}(1)) \geq f(\theta_i)$ , then set  $\theta_{i+1} = \theta_{i+1}(1)$
- If  $f(\theta_{i+1}(1)) \leq f(\theta_i)$ , search for a value  $\gamma \in (0, 1)$  for which  $f(\theta_{i+1}(\gamma)) \geq f(\theta_i)$ , set  $\theta_{i+1} = \theta_{i+1}(\gamma)$

# Newton Raphson

## Newton-Raphson: gradient decent

For Newton's method with a large  $p$ , the computational burden in calculating the inverse of the Hessian Matrix  $[\nabla^2 f(\beta_i)]^{-1}$  increases quickly with  $p$ . One can update

$$\beta_{i+1} = \beta_i + H_i \nabla f(\beta_i)$$

where  $H_i = (X^T X)^{-1}$  for every  $i$ . This is easy to compute, but could be slow in convergence.

The steps are:

- get the objective (loglik, grad, Hess) function
- use the principle of newton raphson to update the estimate, if the step size too large, step-halving step
- stop searching until the convergences of the estimates.

# Logistic-LASSO Model with Pathwise Coordinate Descent

- Applied coordinate-wise descent with weighted update:

$$\tilde{\beta}_j^{lasso}(\lambda) \leftarrow \frac{S(\sum_{i=1}^n \omega_i x_{i,j} (y_i - \tilde{y}_i^{(-j)}), \lambda)}{\sum_{i=1}^n \omega_i x_{i,j}^2}$$

where  $\tilde{y}_i^{(-j)} = \sum_{k \neq j} x_{i,k} \tilde{\beta}_k$  and  $S(\hat{\beta}, \lambda) = \text{sign}(\hat{\beta})(|\hat{\beta}| - \lambda)_+$

- In the context of logistic regression, we are aiming to maximize the penalized log likelihood:

$$\max_{\beta \in \mathbb{R}^{p+1}} \frac{1}{n} \sum_{i=1}^n \{y_i (X_i \beta) - \log(1 + \exp(X_i \beta))\} - \lambda \sum_{j=0}^p |\beta_j|$$

for some  $\lambda \geq 0$

# Result



# Estimation Path and Cross validation for LASSO

Figure 2: A path of solutions with a sequence of descendi





Figure 3: Lasso regression by 5 fold cross validation



# Model Comparison-prediction performance

**Table 1:** The comparison of performance for estimation algorithms and models

|                 | GLM package | Newton Raphson | Gradient Decent | Logistic Lasso | Lasso package |
|-----------------|-------------|----------------|-----------------|----------------|---------------|
| iteration times | NA          | 12             | 1001            | 100            | NA            |
| MSE             | 0.02        | 0.02           | 0.02            | 0.02           | 0.02          |

<sup>a</sup> Dataset: Breast Cancer Diagnosis

# Model Comparison-coefficient

**Table 2:** The comparison of performance for estimation algorithms and models

|                        | GLM package | Newton Raphson | Gradient Decent | Logistic Lasso | Lasso package |
|------------------------|-------------|----------------|-----------------|----------------|---------------|
| radius_mean            | 4.43        | 4.43           | 3.18            | 2.63           | 2.71          |
| texture_mean           | 1.89        | 1.89           | 1.34            | 1.29           | 1.37          |
| smoothness_mean        | 0.78        | 0.78           | 0.47            | 0.00           | 0.00          |
| compactness_mean       | -1.14       | -1.14          | -0.59           | 0.00           | 0.00          |
| symmetry_mean          | -0.63       | -0.63          | -0.44           | -0.10          | -0.14         |
| fractal_dimension_mean | -0.66       | -0.66          | -0.72           | -0.14          | -0.21         |
| radius_se              | 5.13        | 5.13           | 3.28            | 2.50           | 2.58          |
| texture_se             | 0.59        | 0.59           | 0.46            | 0.00           | 0.00          |
| smoothness_se          | 1.10        | 1.10           | 0.77            | 0.00           | 0.00          |
| compactness_se         | -0.80       | -0.80          | -0.68           | -0.33          | -0.38         |
| concavity_se           | 1.24        | 1.24           | 0.88            | 0.08           | 0.19          |
| concave.points_se      | -1.11       | -1.11          | -0.80           | 0.00           | 0.00          |
| symmetry_se            | -0.53       | -0.53          | -0.39           | -0.36          | -0.42         |
| fractal_dimension_se   | -2.73       | -2.73          | -1.55           | -0.25          | -0.31         |
| smoothness worst       | 0.31        | 0.31           | 0.31            | 0.86           | 0.92          |

## Conclusion

## Conclusion and Discussion

- The results of our methods are compared to the the same parameter estimation as R's built-in packages
- Newton-Raphson has the convincing estimation and it converged quickly
- Gradient decent method showed similar estimation as Newton-Raphson method but it was less efficient
- For Pathwise Coordinate descent with LASSO logistic, according to the result of 5 fold cross validation and estimation result, the  $\lambda$  with the lowest MSE and it shrunk six parameters to zero, which is comparable to the result by R's built-in packages.

# Project: Bootstrap

# Background

## Down Syndrome Data

- **Aim:** Build a predictive model based on logistic regression to facilitate down syndrome diagnosis, and compared methods including and Pathwise Coordinate Descent with regularized logistic regression and smoothed bootstrap estimation.
- **Variable Selection:** Delete variables with high missing rate ( $\geq 20\%$ )

Also due to the intrinsic correlation between individual proteins (Fig. 2), it's impossible to apply normal regression methods to this dataset because of singularity problem. Instead, we choose regularized methods, LASSO, to be more specific.



Figure 1: proteins' missing percentage



# Methods

# Methods

- First we need to prepare a couple of candidate models
- for each bootstrap in bootstrap with B times, select the best model and get estimates for the coefficient denoted as  $t(y^*)$
- smooth  $\hat{\mu} = t(y)$  by averaging over the bootstrap replications, defining

$$\tilde{\mu} = s(y) = \frac{1}{B} \sum_{i=1}^B t(y^*)$$

# Smoothed Bootstrap Estimation (SBE) and Inference

And in addition to the percentile confidence interval, the nonparametric delta-method estimate of standard deviation for  $s(y)$  in the nonideal case is:

$$\tilde{sd}_B = \left[ \sum_{i=1}^n \hat{c} \hat{v}_j^2 \right]^{1/2}$$

where


$$\hat{c} \hat{v}_j = \sum_{i=1}^B (Y_{ij}^* - Y_{\cdot j}^*)(t_i^* - t_{\cdot}^*)/B$$

with  $Y_{\cdot j}^* = \sum_{i=1}^B Y_{ij}^*/B$  and  $t_{\cdot}^* = \sum_{i=1}^B t_i^*/B = s(y)$ .

# Result

# Pathwise coordinate descent logistic-LASSO

Fig. 3A shows us that as the  $\lambda$  increases, all the variable estimates of parameters shrink accordingly since we penalize all the parameters. When  $\lambda = 0$ , the result is the same as least square method and when  $\lambda$  is too large, all the estimates of parameters shrink to 0. Fig. 3B shows us the cross validation result for choosing the best  $\lambda$ .



# Model selection based on SBE for Logistic Lasso


algorithm:

- bootstrap data from the original dataset
- do cross validation and select the best  $\lambda_i^*$  for each repetition
- calculate average  $\lambda^* = \frac{1}{B} \sum_{i=1}^B \lambda_i^*$


We can see the discrepancy between results of PCD-LASSO and SBE for Logistic LASSO both in prediction (Fig 4A) and finding the best  $\lambda$  (Fig 4B), the results of PCD-LASSO is deviated from the center of empirical distribution.

# Lambda selection based on SBE for Logistic LASSO

A) Expected value of subject 1 from smoothed bootstrap



B) penalty term from smoothed bootstrap





## Cross validation for model prediction comparison

We used 10 fold cross-validation to compare two different models, one is with  $\lambda$  selected from data, the other is selected from the SBE. Table 1 shows us that while the Cross Validation MSE are similar between these two methods, SBE provides a more accurate classification result.

**Table 3:** The comparison of performance for two models

|  | Misclassification rate | Mean squared error |
|--|------------------------|--------------------|
| Penalty chosen by data                   | 0.0353                 | 0.0229             |
| Penalty selected from smoothed bootstrap | 0.0335                 | 0.0216             |

<sup>a</sup> Dataset: Proteins expression levels of Down syndrome

# Significant random variable selection from SBE

Table 2 & 3 provide the full results of SBE for logistic LASSO. Our identification criteria here are:

- 1 the chosen probability greater than 96%
- 2 SBE confidence interval excludes zero.

Based on that, we got 27 proteins that meets these two criteria (Table 1).

# Significant Proteins

## Conclusion