Status	Finished
Started	Thursday, 15 October 2026, 4:25 PM
Completed	Thursday, 15 October 2026, 4:28 PM
Duration	3 mins 36 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The file's read/write position
b. The access mode of the file
c. The encoding of the file
d. The buffer size for the file operations ✓

The correct answer is: The buffer size for the file operations

Question **2**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. Move file pointer five characters ahead from the beginning
b.
- Move file pointer five characters ahead from the current position. ✓

c.
- Move file pointer five characters behind from the current position.

d.
- Move file pointer five characters behind ahead from the end of a file.

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. a
b. r
c. w
d. r+ ✓

The correct answer is: r+

Question **4**

Correct

Mark 1.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Creates a new file for writing ✓
b. Appends to an existing file
c. Opens a file in binary mode
d. Opens an existing file in read mode

The correct answer is: Creates a new file for writing

Question **5**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Deletes the file
b. Moves the file cursor to the specified position ✓
c. Reads the file line by line
d. Writes data to the file

The correct answer is: Moves the file cursor to the specified position

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write()
b. writelines() ✓
c. write_all()
d. write_list()

The correct answer is: writelines()

Question **7**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. A new file is created
b. An error is raised ✓
c. An empty file object is returned
d. The operation is ignored

The correct answer is: An error is raised

Question **8**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Append
b. Binary
c. Write
d. Read ✓

The correct answer is: Read

Question **9**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)

b. infile = open(“a.txt”, “r”) ✓

c. infile = open(file, “a.txt”, “r”)

d. infile = open(file = “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **10**

Incorrect

Mark 0.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. read()

b. readline(size) ✗

c. readlines()

d. readline()

The correct answer is: readline()

Question **11**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

a. writelines(list) ✓

b. writelist(list)

c. write(list)

d. None of the mentioned

The correct answer is: writelines(list)

Question **12**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

a. The name of the file
b. The size of the file
c. The current position of the file cursor
d. The access mode in which the file was opened ✓

The correct answer is: The access mode in which the file was opened

Question **13**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The encoding format of the file ✓
b. The buffer size
c. The mode of the file
d. The size of the file

The correct answer is: The encoding format of the file

Question **14**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. None
b. 0
c. EOFError
d. An empty string ✓

The correct answer is: An empty string

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. Hello, world! ✓

b. world

c. An error is raised

d. Hello

The correct answer is: Hello, world!