Status	Finished
Started	Thursday, 15 October 2026, 3:34 PM
Completed	Thursday, 15 October 2026, 3:39 PM
Duration	5 mins 5 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. ii

b. i,ii ✓

c. All of the above

d. iii

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. (1,2,3)(4,5,6)

b. (1,2,3,4,5,6) ✓

c. (1,2,3,3,2,1)

d. Error

Question **3**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain either string or integer but not both at a time.

b. In Python, a tuple can contain only strings as its elements.

c. In Python, a tuple can contain both integers and strings as its elements. ✓

d. In Python, a tuple can contain only integers as its elements.

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. TypeError: update() doesn't allow list as a argument.

b. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

d. Name Error

Question **5**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

a. 2

b. 117 ✓

c. 100

d. Error

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. True
False

c. False
False

d. True ✓
True

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. SynatxError: Different types cannot be used with sets

b. {40, 10, 50, 20, 60, 30}

c. {40, '10', 50, 20, 60, 30}

d. {40, 10, '10', 50, 20, 60, 30} ✓

Question **8**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [2, 3, 9]

b. (1, 4, 8)

c. [1, 2, 4, 3, 8, 9]

d. [1, 4, 8] ✓

Question **9**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. Error

b. (16,17,18)

c. (25,19,18,17)

d. (16,17,18,19) ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

a. i,ii

b. ii,iv

c. iii,iv

d. i,iii ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

a. [11,11,11,3,3,3]

b. (11,3)(11,3)(11,3)

c. (11,3,11,11,3,11,11,11,3)

d. (11, 3, 11, 3, 11, 3) ✓

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl.append(2)

b. tupl1=tupl+tupl ✓

c. tupl[1]=2

d. tupl.sort()

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. False
True

c. True ✓
True

d. True
False

Question **14**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. "==" is not supported for set in Python

b. Yes, Yes

c. No, No

d. Yes, No ✓

Question **15**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove “ECE” from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. del.sampleSet("ECE")

b. sampleSet.delete("ECE")

c. remove.sampleSet("ECE")

d. sampleSet.discard("ECE") ✓