Introduction to Hydrodynamic Analysis with Ansys Aqwa

Workshop 06.1: Aqwa Articulations – FPSO and Turret

Release 2021 R2

FPSO & Turret

•The goal of this workshop is to:

- Create the Hydrodynamic Diffraction (HD) system
- Import multi-part CAD geometry
- Create anchor points and mooring lines
- Create a turret articulation
- Set up the Hydrodynamic Response (HR) system



Create HD System

- Set Units
- Add HD system by drag & drop onto WB Project Schematic page.
- RMB on Geometry cell, Import Geometry > Browse, and browse to FPSOTurret.scdoc



Review Geometry

- Double-click on Geometry in the Project Schematic to view the model for this exercise. The geometry consists of an FPSO which will be joined to a moored Turret.
- The Turret includes a line body ('Rod'), which will be represented by Morison elements in Aqwa. Note how the line body is assigned a Cross Section (CircularTube1).
- Close SpaceClaim.



Adding Aqwa Specific Parameters

- Double-click on the Model cell in the Project Schematic.
- Note that the line body in the Turret structure is now graphically represented with the diameter corresponding to its Cross Section in SpaceClaim.



Details

Details of Circular Tube 1	
Name	Circular Tube 1
Solver Line Type	Cylindrical (TUBE)
Geometric Properties	
Cross Section Name	CircularTube1
Cross Section Type	Circular Tube
Inner Radius	1.48 m
Outer Radius	1.5 m
Cross Section Area	0.18724 m²
Second Moment of Area	0.20785 m⁴
Mass Properties	
Material Density	7850 kg/m³
Inertia/Unit Length	1631.65333 (kg.m²)/m
Hydrodynamic Properties	
Displaced Area	7.06858 m²
Transverse Drag Coefficient	0.75
Axial Drag Coeffcient	0.016
Added Mass Coefficient	1
Inertia Coefficient	2

Global Parameters

- Set the Water Depth to 500m in the Details of Geometry panel.



Details

Details of Geometry	
Name	Geometry
Attached Assembly Path	C:\Rohit\Mech_AQWA_19.2-20190826...
Environment Constants	
Water Depth	500 m
Water Density	1025 kg/m³
Gravity	9.80665 m/s²
Water Size X	1060 m
Water Size Y	280 m
Stability/Time Response-Specific Options	
Tube Drag Coefficients	Defined in Line Body Details
Seabed Inline Friction Coeffici...	0.0
Seabed Lateral Friction Coeff...	0.0
Composite Cable Seabed Definition	
Seabed Type	No Composite Cable Seabed
Import Preferences	
Import Solid Bodies	Yes
Import Surface Bodies	Yes
Import Line Bodies	Yes

Provide Additional Aqwa Elements

- For each vessel/structure (FPSO & Turret) provide a Point Mass element



FPSO Point Mass Input

- As before, if Mass Definition is Program Controlled the mass will equal the displacement.
- Set k_{XX}, k_{YY} and k_{ZZ} and VCG for FPSO using the same formulation as in the ship model in Workshop 1

Details	
Details of Point Mass	
Name	Point Mass
Visibility	Visible
Activity	Not Suppressed
Point Mass Properties	
Mass Definition	Program Controlled
Z	8.5 m
Mass	Solve Hydrostatics to Update
Inertia Properties	
Define Inertia Values By	Radius of Gyration
Kxx	13.6 m
Kyy	50 m
Kzz	52 m
Ixy	0.0 kg.m²
Ixz	0.0 kg.m²
Iyz	0.0 kg.m²

Turret Point Mass Input

- Set the Mass definition to Manual and specify a Mass of 265.670 tonnes
- Set Define Inertia Values by to Direct Input of Inertia, and set I_{XX}, I_{YY} and I_{ZZ} to:
  - I_{XX} = 67270000 kg.m² (you can just type '6.727e7')
  - I_{YY} = 67270000 kg.m²
  - I_{ZZ} = 7432200 kg.m²
- Set the VCG (Z coordinate) to -25.38 m and the LCG (X coordinate) to 220 m





Turret Submerged Structure Setting

- Since the Turret does not have diffracting elements at the water line we need to set up the structure as a Fully Submerged Body.



- **Select Turret In the Geometry tree**
- **Set Submerged Structure Detection to Fully Submerged**

Anchor Connection Points

- Select the Fixed Points object in the tree and add three fixed points for the mooring system representing the anchor locations
- Set the x, y, z coordinates as follows:
  - Anchor 1 -700m, 700m, -500m
  - Anchor 2 -700m, -700m, -500m
  - Anchor 3 1300m, 0m, -500m



Connection Points

- Select the part FPSO and add a connection point
- Set the X, Y, Z, coordinates as follows and rename Turret Connection;
  - Turret Connection 220m, 0m, 13m
- Select the part Turret and add four connection points
- Define names and set the X, Y, Z, coordinates as follows:
  - FPSO Connection 220m, 0m, 12m
  - Mooring 1 215.0m, 8.66m, -32.0m
  - Mooring 2 215.0m, -8.66m, -32.0m
  - Mooring 3 230.0m, 0.0m, -32.0m
- Check the locations of the connection points. Note that all coordinates defined are in the global system (FRA)



Set Up Mooring Line Properties

- As in Workshop 2 we are going to use composite catenary lines for the mooring system. These are lines made up of one or more segments with varying properties e.g. chain/wire/chain.
- Select Connections > Connection Data > Insert Connection Data > Catenary Section



Mooring Line Properties

- Provide data for Mass/Unit Length, Equivalent Cross Sectional Area, Stiffness, Maximum Tension and Equivalent Diameter as below for three catenary sections. Use the Duplicate function to avoid entering the same data many times.

Details

Details of Catenary Section 1	
Name	Catenary Section 1
Section Properties	
Mass/Unit Length	150 kg/m
Equivalent Cross-Sectional A...	0.01 m²
Stiffness, EA	600000000 N
Maximum Tension	7500000 N
Bending Stiffness, EI	0.0 N.m²
Axial Stiffness Coefficient k1	0.0 N
Axial Stiffness Coefficient k2	0.0 N
Axial Stiffness Coefficient k3	0.0 N
Section Hydrodynamic Properties	
Added Mass Coefficient	1
Transverse Drag Coefficient	1
Equivalent Diameter	0.2 m
Longitudinal Drag Coefficient	0.025

Details

Details of Catenary Section 2	
Name	Catenary Section 2
Section Properties	
Mass/Unit Length	120 kg/m
Equivalent Cross-Sectional A...	0.01 m²
Stiffness, EA	900000000 N
Maximum Tension	7500000 N
Bending Stiffness, EI	0.0 N.m²
Axial Stiffness Coefficient k1	0.0 N
Axial Stiffness Coefficient k2	0.0 N
Axial Stiffness Coefficient k3	0.0 N
Section Hydrodynamic Properties	
Added Mass Coefficient	1
Transverse Drag Coefficient	1
Equivalent Diameter	0.25 m
Longitudinal Drag Coefficient	0.025

Details

Details of Catenary Section 3	
Name	Catenary Section 3
Section Properties	
Mass/Unit Length	170 kg/m
Equivalent Cross-Sectional A...	0.01 m²
Stiffness, EA	900000000 N
Maximum Tension	7500000 N
Bending Stiffness, EI	0.0 N.m²
Axial Stiffness Coefficient k1	0.0 N
Axial Stiffness Coefficient k2	0.0 N
Axial Stiffness Coefficient k3	0.0 N
Section Hydrodynamic Properties	
Added Mass Coefficient	1
Transverse Drag Coefficient	1
Equivalent Diameter	0.2 m
Longitudinal Drag Coefficient	0.025

Mooring Line Connections

- To add a line select Connections > Insert Connection > Cable



Mooring Line Connections

- Create cable 1 using the information highlighted opposite
- The composition of the line is now defined
  - Segment allocation
  - Line length
- Segments are defined from the anchor location up to the connection point on the turret
- Section 1 type should be set to Catenary Section 1
- Length 400 m
- Repeat for sections 2 and 3 as shown
- Finally set the dZ Range parameters under Cable Properties to 10m

Details	
Details of Cable 1	
Name	Cable 1
Visibility	Visible
Activity	Not Suppressed
General Attributes	
Type	Nonlinear Catenary
Connectivity	Fixed Point to Structure
Start Fixed Point	Anchor 1 (Fixed)
End Connection Point	Mooring 1 (Turret)
Initial Attachment Point Separation	1238.62827175872 m (Point to Point)
Cable Dynamics Properties	
Use Dynamics	Defer to Analysis Settings "Use Cable ...
Number of Elements	100
Catenary Section Selection	
Section 1: Type	Catenary Section 1
Section 1: Length	400 m
Joint 1/2: Mass/Buoyancy	None
Section 2: Type	Catenary Section 2
Section 2: Length	500 m
Joint 2/3: Mass/Buoyancy	None
Section 3: Type	Catenary Section 3
Section 3: Length	500 m
Section 4: Type	None
Cable Properties	
Negative dZ Range of Expect...	10 m
Positive dZ Range of Expecte...	10 m
Number of Vertical Partitions	15
Number of X Coordinates	40
Initial Cable Data	
Initial Cable Tension at Start	312786.969 N
Initial Cable Tension at End	1021422.625 N

Mooring Line Connections

- Use the same information to populate cables 2 and 3 (using Duplicate to save data entry).
- Change the fixed point and end point connections as follows:
  - Cable 2 Anchor 2 (Fixed), Mooring 2 (Turret)
  - Cable 3 Anchor 3 (Fixed), Mooring 3 (Turret)
- Select Connections in the Outline to see the final mooring configuration



Articulation

- Select Connections in the outline and Insert Connection > Joint
- Set the Joint type to Hinged
- Set the connection points as shown
- Set the stiffness about the X axis to 1000N/°
- Set the damping about the X axis to 20000N.m/(°/s)
- Note that the orientation of the hinge is incorrect
- The axis system local to the hinge can be rotated







Articulation

- To change the joint axis, under Joint 1, select Joint Axes On Structure A
- Change the Alignment Method to Direction Entry as shown
- Then change the Rotation About Local Y to 90
- Do likewise for Joint Axes On Structure B
- Finally confirm the hinge is orientated correctly

Details	
Details of Joint Axes On Structure A	
Name	Joint Axes On Structure A
Visibility	Visible
Axes Alignment	
Alignment Method	Direction Entry
Rotation About Global Z	0.0°
Rotation About Local Y	90°
Rotation About Local X	0.0°
Unit Vector X	[0.0, 0.0, -1]
Unit Vector Y	[0.0, 1, 0.0]
Unit Vector Z	[1, 0.0, 0.0]



Meshing

- Set Max Element Size to 4m
- Apply a Mesh Sizing Control to the Turret with Local Element Size of 1m
- Generate Mesh

•Hint: When scoping the geometry for the Mesh Sizing select the bodies in the turret from top to bottom

•



Analysis Settings

- Set Ignore Modelling Rule Violations to “Yes”
- Set Include Multi-Directional Wave Interaction to “No”
- Set Calculate Full QTF Matrix to “No”

Details	
Details of Analysis Settings	
Name	Analysis Settings
External Operation before Solving	None
External Operation after Solving	None
Parallel Processing	Program Controlled
Generate Wave Grid Pressures	Yes
Wave Grid Size Factor	2
Common Analysis Options	
Ignore Modelling Rule Violations	Yes
Calculate Extreme Low/High Fre...	Yes
Include Multi-Directional Wave Int...	No
Near Field Solution	Program Controlled
Linearized Morison Drag	No
QTF Options	
Calculate Full QTF Matrix	No
Output File Options	
Source Strengths	No
Potentials	No
Centroid Pressures	No
Element Properties	No
ASCII Hydrodynamic Database	No
Example of Hydrodynamic Datab...	No
Generate AHD Pressure Output	No

Structure Selection

- Structure Selection enables the definition of interacting structure groups (for multi-body problems). By default all vessels are assumed interacting.

Details	
Details of Structure Selection	
Name	Structure Selection
Structures to Exclude	None
Group of Structures	
Interacting Structure Group 1	All
Interacting Structure Group 2	None
Motion Locks	
Apply Motion Lock to Group 1	No
Structure Ordering	
Structure 1	FPSO
Structure 2	Turret

- To reduce the computation time select the first Interacting Structure Group and set this to None by clicking in empty space in the Graphics window and selecting Apply

Details	
Details of Structure Selection	
Name	Structure Selection
Structures to Exclude	None
Group of Structures	
Interacting Structure Group 1	None
Structure Ordering	
Structure 1	FPSO
Structure 2	Turret

Wave Directions and Frequencies

- Computing additional wave directions is computationally cheap. In Wave Directions, increase the Number of Intermediate Directions to 11.

Details	
Details of Wave Directions	
Name	Wave Directions
Visibility	Visible
Type	Range of Directions, No Forward Speed
Required Wave Input	
Wave Range	-180° to 180°
Interval	30°
Number of Intermediate Directions	11

- The computational cost scales linearly with the number of frequencies, however, so we will reduce this to 15. In Wave Frequencies:

Details	
Details of Wave Frequencies	
Name	Wave Frequencies
Intervals Based Upon	Frequency
Incident Wave Frequency/Period Definition	
Range	Program Controlled
Total Number of Frequencies	15

Review Results

- Solve full analysis
- Insert some results
  - Hydrostatic Table for FPSO
  - Hydrodynamic Graphs
    - ❑ RAOs in X and Z for FPSO with a wave direction of -180 degrees
  - Pressures and Motions
    - ❑ Since we have two non-interacting structures it is possible to plot information for each of these individually



Hydrostatics

- When selected these results appear on the Properties tab.
- Since we now have two structures, ensure the required one is selected



Hydrodynamic Graphs



Geometry | Properties | **Graph** | Report Preview

Tabulated Results Data

Wave Frequency (Hz)	Line A (m/m)	Line B (m/m)
0.01592	1.52039	0.99727
0.03449	0.96873	0.97344
0.05307	0.82319	0.85679
0.07164	0.54906	0.55408
0.09022	0.17193	0.19718
0.10879	0.05171	0.26396
0.12737	0.03314	0.16249
0.14594	0.03502	0.07336
0.16452	0.02518	0.02589
0.18309	0.01581	0.0128
0.20167	0.01048	4.22311e-3
0.22024	6.80733e-3	2.83984e-3
0.23882	3.97374e-3	1.32575e-3
0.25739	2.56115e-3	8.3235e-4
0.27597	1.64725e-3	3.45101e-4

Hydrodynamic Pressures and Motions



A Note on Connections

- In this example the mooring lines and articulation have been defined before the Hydrodynamic Diffraction system has been Solved. However, it must be noted that the effects of these connections will not be seen in the Hydrodynamic Diffraction results.
- It is possible to enter a 6x6 Connection Stiffness matrix (under Connections), applied between one structure and the ground or between two structures, which is accounted for in the HD system. However, in many cases the stiffness matrix can only be approximated.
- To fully assess the effects of the mooring lines and articulation on the system the user must view the results of a Hydrodynamic Response analysis. This is covered next.



Stability Analysis and Time Domain Simulation

- Add two HR systems by dragging and dropping on to the Workbench Project Schematic page



Define the Environment

- Right-click on **Hydrodynamic Response (B4)**, Insert > Irregular Wave > Pierson-Moskowitz
- Set Direction of Spectrum to 170°
- Set Significant Wave Height to 4m
- Set Zero Crossing Period to 8s
- Right-click on **Hydrodynamic Response (B4)**, Insert > Current > Constant Velocity
- Set a 1 m/s current at 175°. Note that since we have not defined any hull drag coefficients for the FPSO there will be no current loading on that vessel. The Turret, however, will be loaded since it is modelled in part by a tubular Morison element.
- Right-click and Propagate each of Irregular Wave 1 and Current 1 into the time domain analysis, Hydrodynamic Response (C4)



Time Domain Analysis Settings

- In the time domain Analysis Settings of **Hydrodynamic Response (C4)**:
- Check that Analysis Type is set to Irregular Wave Response with Slow Drift
- Check that Time Step is set to 0.1 seconds
- Set Duration to 1000 seconds
- Check that Use Cable Dynamics is set to Yes



Check Solution

- Right-click on the time domain Hydrodynamic Response Solution (C5) to Insert Result > Structure Position > Actual Response
- Select FPSO for the Structure and Global RZ as the Component of motion
- Obtain forces on the turret joint connection - Insert Result > Joint Forces

Details

Details of Structure Position, Actual Response	
Name	Structure Position, Actual Response
Presentation Method	Line
Axes Selection	Distance/Rotation vs Time
Line A	
Structure	FPSO
Type	Structure Position
SubType	Actual Response
Component	Global RZ

Details

Details of Joint Forces	
Name	Joint Forces
Presentation Method	Line
Axes Selection	Force/Moment vs Time
Line A	
Structure	Turret
Type	Joint Forces
Component	Global X
Connection	Joint 1

- Hit **Solve** on time domain Hydrodynamic Response (C4). Notice that the Stability Analysis (system B) is automatically updated first.

Typical Results





Setting Up Parameters

- For design studies, several input parameters can be set as variable (such as environmental parameters)
- Click the check box on the left hand side of the Significant Wave Height in the Irregular Wave Details
- The letter P will indicate that this value is a variable parameter and the value input box will be locked.
- Repeat for the Zero Crossing Period



Setting Up Output Parameters

- In the Solution, set as output parameter the Joint Forces Minimum and Maximum Value.

Details	
Details of Joint Forces	
Name	Joint Forces
Presentation Method	Line
Axes Selection	Force/Moment vs Time
Export CSV File	Select CSV File...
Line A	
Structure	Turret
Type	Joint Forces
Connection	Joint 1
Component	Global X
Abscissa Position of Minimum	904.9 s
Abscissa Position of Maximum	856.1 s
P Minimum Value	-717925.75 N
P Maximum Value	475902.438 N
Line B	
Structure	Undefined...

Setting Up Parameters

- Go back to Project Schematic
- You will see that the Parameter Set box has appeared. Double-click on the Parameter Set box



Design Points View

- Design Points view in Workbench consists of several sub-views:
  - Outline of all parameters
  - Table of design points
  - Properties
  - Chart
  - Parameters Chart Toolbox



Setting Up Design Points

- Go to Table of Design Points and vary both the wave height and zero crossing period, as shown to define three additional design points. Save the Project
- Click ⚡⚡Update All Design Points
- The solution will take several minutes, so be patient.
- Note the Retained Data column. If one or more of these boxes are checked then the complete solution for that particular design point(s) will be saved. Otherwise only the initial design point (marked as Current) is preserved.

Table of Design Points

	A	B	C	D	E	F	G	H
1	Name	P1 - Irregular Wave 1 Significant Wave Height	P2 - Irregular Wave 1 Zero Crossing Period	P3 - Joint Forces Minimum Value (Joint 1)	P4 - Joint Forces Maximum Value (Joint 1)	Reta	Retained Data	Note
2	Units	m	s	N	N			
3	DP 0 (Current)	4	8	-7.1793E+05	4.759E+05	☑	✓	
4	DP 1	4	10	⚡	⚡	☐		
5	DP 2	3	9	⚡	⚡	☐		
6	DP 3	3	11	⚡	⚡	☐		
*						☐		

Design Points Results

- Review the results table for each design point

Table of Design Points

	A	B	C	D	E	F	G	H
1	Name	P1 - Irregular Wave 1 Significant Wave Height	P2 - Irregular Wave 1 Zero Crossing Period	P3 - Joint Forces Minimum Value (Joint 1)	P4 - Joint Forces Maximum Value (Joint 1)	Reta	Retained Data	Note
2	Units	m	s	N	N			
3	DP 0 (Current)	4	8	-7.1793E+05	4.759E+05	☑	✓	
4	DP 1	4	10	-5.8844E+05	4.9245E+05	☐		
5	DP 2	3	9	-4.6713E+05	3.4514E+05	☐		
6	DP 3	3	11	-4.2083E+05	4.2942E+05	☐		
*						☐		

Results of Parameter Studies

- You can also plot them from the Parameter Charts Toolbox:
  - Select Outline Of All Parameters to see the Toolbox
  - Double-click on Parameters Chart
  - Select X axis and Y axis parameters from Properties of Outline
- The resulting plot appears in Parameter Chart window (Note that line properties may be modified by RMB on the line and select Edit Properties)