
DNV-ST-F101 · API RP 1111 · ASME B31.4 · ASME B31.8 · PD 8010-2 · ISO 13623 · DNV-ST-F201 · API STD 2RD

Wall thickness — sizing & code checks

Pipeline and riser wall-thickness sizing and pressure-integrity code checks — one geometry / material / loads spec dispatched across ten registered design codes (edition-aware: DNV-OS-F101 2007 vs DNV-ST-F101 2021, API RP 1111 3rd vs 4th edition), with burst, collapse (solved from the cubic, not tabulated), propagation-buckling and combined-loading utilizations, minimum-thickness solvers and cross-code comparison reports. Every result carries a code_reference kept in sync with the codes register.

10

registered design codes

369

live engine evaluations

~19.5 mm

min wall, pipeline codes

WHAT YOU GET

- Strategy-registry engine: submarine pipeline, riser LRFD and onshore / transmission codes behind one PipeGeometry / PipeMaterial / DesignLoads spec
- Edition-aware safety factors with a machine-readable clause / equation manifest per code
- Cross-code comparison live: the same 12.75" X65 deepwater line under all registered codes, min wall to pass per code
- API RP 1111 installation screens — propagating-buckle pressure, transition water depth, buckle-arrestor verdicts
- Screening-level quick check from a minimal input deck, plus 30 CFR Part 250 regulatory burst / minimum-thickness cards