

TUNGSTEN EXPLORER

6th GEN ULTRA DEEPWATER DRILLSHIP

For more information contact marketing@vantagedrilling.com



TECHNICAL SPECIFICATIONS

General Information

Rig Design	DSME 12,000
Year Entered Service	2013
Builder	Daewoo Shipbuilding & Marine Engineering
Class	DNV 1A Ship-Shaped Drilling Unit BIS DPS (3)
Flag	Bahamas

General Specification

Hull Length	781 ft
Hull Breadth	138 ft
Hull Depth	62 ft
Moon Pool	82 ft x 41 ft
Accommodation	200 POB
Helideck	CAP437, 75ft Octagon, Sikorsky S-61N, S-92 Compatible. 11.8MT Load capacity

Operational Capabilities

Maximum Water Depth	12,000 ft designed / 11,000 ft outfitted
Minimum Water Depth	1,150 ft
Transit Draft	27.8 ft
Maximum Drilling Depth	40,000 ft
Variable Deck Load	20,000 MT
Maximum Setback	1,000 MT

Tubular Handling Capabilities

Pipe Feeding Machine	1 x AKMH Tubular Feeding Machine, SWL 15 MT, 2-7/8" to 30", suitable for handling 45 ft tubular
Pipe Rackers	2 x AKMH Bridge Racking cranes, Lower Guiding Arms, each 15 MT, 3 1/2" to 13 5/8"
Riser Feeding Machine	1 X AKMH Riser Feeding Machine, SWL 40 MT, 2-7/8" to 54"
Manipulator Arm	1 x AKMH Drill Floor Manipulator arm, 3 1/2" to 60"
Pipe Deck Handling Crane	1 x AKMH PDPH, SWL 4.5 MT to 9 MT, 2 7/8" to 20"
Pipe Handling Automation	AKMH

Power Generation

Main Engines	6 x STX MAN 14V32/40 diesel engines, 7,000 kW @ 720 rpm c/w HHI 8,437 kVA AC alternators
Emergency Engines	1 x STX MAN B&W diesel engine c/w HHI 2,625 kVA AC alternator

Storage Capacities

Diesel	59,628 bbls
Drill Water	20,033 bbls
Potable Water	8,628 bbls
Bulk Material	28,250 ft3 (mud + cement)
Base Oil	5,118 bbls
Brine	5,118 bbls
Active Mud	8,883 bbls / 10,561 reserve
Trip Tank	137 bbls
Sack Store	10,000 Sacks

Mud System

Working Pressure	7,500 psi 4 x AKMH Wirth model TPK-7½ x 14 / 2200 CL, Gear driven, 2,200 hp 7,500 psi, GE AC Motor drive
Mud Pumps	
Shakers	8 x DP 626 dual deck shakers (2 configured as Mud cleaners with 4 x 20" cones each)

Handling Systems

Deck Cranes	- 3 x Liebherr model BOS 4200-85, 85 mt max load at 9 m radius & 32.7 mt at 46 m radius (static), Auxiliary hook 15 mt max load at 51 m radius - 1 x Liebherr model BOS 4200-50, 50 mt max load at 9 m radius & 34.2 mt at 46 m radius (static), Auxiliary hook 15 mt max load at 51 m radius
Riser Gantry Crane	1 x AKMH Riser Gantry Crane, SWL 40 MT 1 x AKMH BOP Trolley, SWL 500 MT c/w 1000 MT hang off adapter plate for riser hang-off
BOP Handling	2 x AKMH LMRP Overhead Gantry Crane, each SWL 75 MT
Xmas Tree Handling	1 x AKMH Xmas Tree Trolley, SWL 150 MT 2 x AKMH Xmas Tree Overhead Gantry Crane, each SWL 75 MT

Well Control Equipment

Blowout Preventer	1 x Cameron BOP, 18¾" 15,000 psi, 6 x ram cavities (3 x Type TL doubles) 2 x Cameron Type DL, 18 ¾", 10,000 psi annular preventer 1 x Cameron x 75½" 500 psi with 16" diverter lines, 16" flow line, 16" Mud Gas separator line, 8" trip tank line, 4" fill up line. 21" nominal bore.
Diverter	

TUNGSTEN EXPLORER

6th GEN ULTRA DEEPWATER DRILLSHIP

For more information contact marketing@vantagedrilling.com



TECHNICAL SPECIFICATIONS

Drilling Package		Riser Equipment	
Derrick	Aker Kvaerner Maritime Hydraulics Riser (AKMH) Single Pyramid Dynamic Derrick, 46 ft. x 52 ft. base x 210 ft. clear working height, API-4F 3rd Edition	Riser	21", Cameron Load King riser 3.5 w/ 15k psi - 4.5" ID Choke & Kill Line, 5k psi - 4" ID booster line, 2 x 5K psi - 3.5" ID hydraulic lines.
Hookload Capacity	2.8 million lbs Static Hookload Capacity	Riser Tensioning	8 x AKMH Dual wire line tensioner, 3,600,000 lbs. combined capacity with a maximum net effective stroke of 12.5 ft.
Racking Capacity	6 3/4" Drill pipe—368 stands x 135 ft (49,680ft) 9 1/2" Drill collars— 8 stands x 135 ft (992 ft) 13 3/4" casing - 35 stands x 135 ft (4,725 ft) or, 9 3/4" casing - 54 stands x 135 ft (7,290 ft) or, 7" liner — 91 stands x 135 ft (12,285 ft)	Motion Compensators	- 1 x AKMH 680-1270-25 Crown Mounted Compensator, rated at 1,270 MT / 1,400 tons (static) and 680 MT / 750 tons (Compensation) with a 25 ft. stroke - 1 x AKMH Active Heave Compensator, rated at 20 MT x 2 with a 25 ft. stroke, Upgraded to AHC WD (while drilling)
Drawworks	1 x AKMH Wirth GH 9000-EG-01-AC electric motor driven 9,000 hp	Station Keeping & Propulsion System	
Rotary Table	1 x AKMH Wirth RTSS 75 1/2", hydraulically driven, 20 rpm, 1,500 ton capacity	DP Control System	DPS33, GE Converteam, Triplex DP + IJS 3 x independent GNSS + 2x independent acoustic systems
Iron Roughneck	1 x AKMH 1899 MKII Iron Roughneck for Well Center Operations, 2 3/8" to 9 3/4"	Thrusters	6 x 5.5 MW Rolls Royce Ulstein Aquamaster UUC 455 Azimuth (100 mt thrust nominal), variable speed, fixed pitch, fully azimuthing
Topdrive	1 x AKMH model MDDM-1250-AC-2M, 1,250 tons hoisting capacity, 945 tons drilling load path capacity, 101,200 ft lbs max continuous torque, 151,300 ft lbs intermittent, 0 -282 max rpm, 2 x 1150 hp AC motors		
Offline Capabilities			
Offline Stand Building	1 x AKMH Stand building arm for offline tubular handling lifting capacity of 6.4 MT, 15 ft. to 45 ft. tubular, 3 1/4" to 13 5/8"		
Offline Roughneck	1 x AKMH 'Torque Master' for tubular range 2 7/8" to 20" for offline operations		
Offline Mouseholes	2 x AKMH Hydraulic Mouseholes for up to 13 5/8"		
Bucking Unit	McCoy Clincher 3-1/2" to 17-1/2" pipe range Make-up torque - 160,000lb-ft Break-up torque - 190,000lb-ft		

This is the end of the Technical Specifications Sheet
For more information, please, contact: marketing@vantagedrilling.com

Revision Date: March 2025

These specifications are intended for general reference purpose only and shall not be contractually binding. Contractor reserves the right to change these specifications at any time without prior notice. All equipment shall be operated and maintained in line with Vantage guidelines and within the limits of OEM specifications.

TUNGSTEN EXPLORER

6th GEN ULTRA DEEPWATER DRILLSHIP

For more information contact marketing@vantagedrilling.com



GENERAL ARRANGEMENT

