

VANTAGE

SOEHANAH

BAKER MARINE PACIFIC CLASS 375 JACK-UP

For more information contact marketing@vantagedrilling.com



TECHNICAL SPECIFICATIONS

General Information

Rig Design	BMC 375
Year Entered Service	2007
Builder	PPL Shipyard Pte Ltd
Class	ABS
Flag	Panama

General Specification

Hull Length	236.5 ft
Hull Breadth	224.4 ft
Hull Depth	28 ft
Legs	3 / Triangular
Accommodation	120 POB
Helideck	CAP437, 75 ft Octagon, Sikorsky S-61N, suitable for Sikorsky S-92.

Operational Capabilities

Maximum Water Depth	375 ft designed/ 375 ft outfitted
Minimum Water Depth	30 ft (25 ft under site specific conditions)
Transit Draft	19.5 ft
Leg Length below hull	434 ft max.
Maximum Drilling Depth	25,000 ft
Cantilever	75 ft x 30 ft
Max Cantilever Load	883 MT
Variable Deck Load	2,268 MT (Transit), 3,356 MT (Drilling)
Maximum Setback	294 MT

Power Generation

Main Engines	5 x CAT 3516B Diesel engines, 1383 kW, 1200 rpm
Main Generators	5 x Kato AC alternator, 2150 kVA, 1720 kW, 1200 rpm, 690V, 60 Hz, 3 Ph
Emergency Generators	1 x Leroy Somer AC alternator, 900kVA (720kW), 1800 rpm, 480V, 60 Hz, 3 Ph

Special Features & Other Information

Jacking System	Baker Marine model BMPL J800, c/w 54 active drive pinions powered by N°36 46 kW AC drive motors (18 per jackcase, 6 per chord), normal jacking capacity 19,738 MT
Mooring System	4 x 40 KW / 60 KW (Forward / Reverse) Mentrade Anchor Winches, 6 MT delta flippers
Work Offline	Ability to make-up drill pipe stands offline.

Offline Capabilities

Offline Tubular	1 x Crane Safe OAC offline activities crane, 5,000 lbs SWL
-----------------	--

Storage Capacities

Diesel	3,720 bbls
Drill Water	17,004.4 bbls
Potable Water	3,652 bbls
Bulk Material	11,652 ft3 (mud + cement)
Base Oil	1,397 bbls
Brine	1,437 bbls
Liquid Mud	3,703 bbls
Sack Store	5,000 sack

Mud System

Working Pressure	7,500 psi
Mud Pumps	3 x AKMH Wirth TPK 7½" x 14" 2200 CL, 2200 hp, 7,500 psi, c/w 2 x GE AC motors
Shakers	5 x NOV Brandt VSM 300 BEM dual deck shakers (1 configured as Desander/Desilter)

Handling Systems

Deck Cranes	- 1 x Baker Marine 2250 (Port) w/ 120 ft boom, main hoist ratings – 68 MT @ 25 ft radius and 14.28 MT @ 127.5 ft radius (static), 45.35 MT @ 25 ft radius and 9.52 MT @ 127.5 ft radius (dynamic) - 1 x Baker Marine 1600 (Stbd) w/ 120 ft boom, main hoist ratings – 39.04 MT @ 25 ft radius and 5.89 MT @ 126.54 ft radius (static), 26.02 MT @ 25 ft radius and 3.93 MT @ 126.54 ft radius (dynamic) - 1 x Baker Marine 900 (Port Aft) w/ 100 ft boom, main hoist ratings - 22.67 MT @ 20 ft radius and 6.84 MT @ 102.57 ft radius (static), 15.07 MT @ 20 ft radius and 4.55 MT @ 102.57 ft radius (dynamic)
BOP Handling	2 x pneumatically operated BOP, SWL 45MT each 2 x OHS BOP / Xmas Tree skidding trolleys each rated at 100 MT
Xmas Tree Handling	2 x Xmas Tree trolley beams each rated at 15 MT c/w hoist
Conductor Tensioner	1 x Patriot 200 mt capacity CTU with 305 mm stroke

Well Control Equipment

Blowout Ram Preventers	2 x Cameron, Type U, 13 5/8"-10M psi Double Ram Preventer
BOP Annular Preventer	1 x Cameron DL type, 13 5/8"-5M psi Annular
Diverter	1 x Vetco Gray 49 ½" KFDJ-500 STD 500 psi (27½" ID) diverter with 16" flow line and 2 x 12" overboard lines



TECHNICAL SPECIFICATIONS

Drilling Package	
Derrick	AKMH offset derrick, 35 x 35 ft @ base; 19 ft @ top x 160 ft clear
Hookload Capacity	1.4 million lbs Static Hookload Capacity 336 Stands of 5 7/8" drill pipe range II triples x 93 ft (31,248')
Racking Capacity	12 Stands of 9 1/2" drill collar range II triples x 93 ft (1,116 ft)
Drawworks	Maritime Hydraulics Wirth GH 3000 EG-SC-SV (3,000 hp)
Rotary Table	Maritime Hydraulics RTSS - 49 1/2" H hydraulically operated, 800 tons static load rated, maximum continuous torque of 29,502 ft-lbs @ 20 rpm
Iron Roughneck	1 x AKMH model MH 1898 Mk-I Hydraulic roughneck for tubular range 3 1/2" to 9 1/4". Make - up torque: 100,000 ft-lbs Break-out torque: 125,000 ft-lb Maritime Hydraulics GH 3000 EG-SC-SV 3,000, lifting capacity 650 tons, drilling capacity 650 tons, 63,000 ft lbs max continuous torque @ 93 rpm, 89,000 ft lbs intermittent torque, 0-268 Max rpm, 1 x 1150 hp AC motor.
Topdrive	

This is the end of the Technical Specifications Sheet
For more information, please, contact: marketing@vantagedrilling.com

Revision Date: March 2025

These specifications are intended for general reference purpose only and shall not be contractually binding. Contractor reserves the right to change these specifications at any time without prior notice. All equipment shall be operated and maintained in line with Vantage guidelines and within the limits of OEM specifications.

VANTAGE

SOEHANAH

BAKER MARINE PACIFIC CLASS 375 JACK-UP

For more information contact marketing@vantagedrilling.com



GENERAL ARRANGEMENT

