

DEALFLOW BACKEND

Postman API Guide

A practical request catalog for authentication, deal workflow, approvals, exceptions, audit history, and the current CPQ integration boundary.

Base URL

`http://localhost:8081`

API version

Current project endpoints under `/api`

Generated

September 2026

1. Postman Setup

Create a Postman environment named **DealFlow Local**.

Variable	Value	Purpose
baseUrl	http://localhost:8081	Local backend URL
token	Empty initially	JWT returned by login
dealId	Empty initially	Current deal under test
approvalId	Empty initially	Approval request under test
exceptionId	Empty initially	Exception request under test
quoteNumber	Q-10482	Mock CPQ quote number

Collection authorization: Set the collection-level authorization to Bearer Token with token `{{token}}`. Set Login and Health requests to **No Auth**.

Start the backend first: from `backend`, run `./mvnw.cmd spring-boot:run` if your environment allows it, or use the project's verified test command for validation. The default port is 8081.

2. Suggested Collection Structure

```
DealFlow API
├─ 01 - Health
├─ 02 - Authentication
├─ 03 - Deals
├─ 04 - Approvals
├─ 05 - Exceptions
├─ 06 - Audit Trail
├─ 07 - CPQ
└─ 08 - Authorization Tests
```

Use request names in the form `[Action] - [Resource]`, for example `Create - Deal` and `Approve - Approval Request`.

3. Health

GET `{{baseUrl}}/api/health`

No Auth

Suggested name: **Get - Application Health**

```
{
  "status": "UP",
  "application": "DealFlow"
}
```

The security configuration also permits `/actuator/health`, but the project has an explicit custom health endpoint at `/api/health`.

4. Authentication

POST `{{baseUrl}}/api/auth/login`

No Auth

Suggested name: **Login - User**

```
{
  "email": "alice@example.com",
  "password": "your-password"
}
```

Save the response token as the Postman `token` variable:

```
const response = pm.response.json();
if (response.token) pm.environment.set("token", response.token);
```

GET `{{baseUrl}}/api/auth/me`

Authenticated

Suggested name: **Get - Current User**

```
{
  "id": 3,
  "firstName": "Alice",
  "lastName": "Smith",
  "email": "alice@example.com",
  "roles": ["SALES_REP"]
}
```

5. Deals

Suggested request name	Method and path	Access
List - All Deals	GET /api/deals	Any authenticated user
Get - Deal By ID	GET /api/deals/{{dealId}}	Any authenticated user
Create - Deal	POST /api/deals	SALES_REP , CPQ_ADMIN
Update - Deal	PUT /api/deals/{{dealId}}	SALES_REP , CPQ_ADMIN
Submit - Deal	POST /api/deals/{{dealId}}/submit	SALES_REP , CPQ_ADMIN
Resubmit - Deal	POST /api/deals/{{dealId}}/resubmit	SALES_REP , CPQ_ADMIN

Create - Deal

POST {{baseUrl}}/api/deals

```
{
  "quoteNumber": "Q-10482",
  "customerName": "Acme Corporation",
  "dealValue": 520000.00,
  "discountPercentage": 25.00,
  "marginPercentage": 13.00
}
```

Expected result: **201 Created**, with initial status **DRAFT**. Save the returned ID as **dealId**. This creates **DEAL_CREATED** in the audit trail.

Update - Deal

PUT {{baseUrl}}/api/deals/{{dealId}}

```
{
  "customerName": "Acme Corporation Updated",
  "dealValue": 400000.00,
  "discountPercentage": 18.00,
  "marginPercentage": 20.00
}
```

Valid while the deal is **DRAFT** or **CHANGES_REQUESTED**. Records **DEAL_UPDATED** with changed values.

Submit - Deal

POST {{baseUrl}}/api/deals/{{dealId}}/submit

No body. Valid transition: **DRAFT** -> **SUBMITTED**. Required exceptions must be approved first. Records **DEAL_SUBMITTED** and generates approval requests.

Resubmit - Deal

POST `{{baseUrl}}/api/deals/{{dealId}}/resubmit`

No body. Valid transition: `CHANGES_REQUESTED` -> `SUBMITTED` . Supersedes the prior pending approval cycle, records `DEAL_RESUBMITTED` , and creates a new cycle.

6. Approvals

Suggested request name	Method and path	Access
List - Deal Approvals	<code>GET /api/deals/{{dealId}}/approvals</code>	Authenticated
List - Pending Approval Queue	<code>GET /api/approvals/pending</code>	Approver roles
Approve - Approval Request	<code>POST /api/approvals/{{approvalId}}/approve</code>	Manager, Finance, VP, Admin
Reject - Approval Request	<code>POST /api/approvals/{{approvalId}}/reject</code>	Manager, Finance, VP, Admin
Request Changes - Approval Request	<code>POST /api/approvals/{{approvalId}}/request-changes</code>	Manager, Finance, VP, Admin

List - Pending Approval Queue

GET `{{baseUrl}}/api/approvals/pending?role=SALES_MANAGER`

Valid filters: `SALES_MANAGER` , `FINANCE` , `VP_SALES` . Results are limited to active, current, next-in-sequence approvals.

Approve - Approval Request

POST `{{baseUrl}}/api/approvals/{{approvalId}}/approve`

```
{ "comments": "Pricing approved for the strategic account." }
```

The authenticated role must match the approval's assigned role, unless the user is `CPQ_ADMIN` .
Records `APPROVAL_APPROVED` .

Reject - Approval Request

POST `{{baseUrl}}/api/approvals/{{approvalId}}/reject`

```
{ "comments": "Margin is below the acceptable threshold." }
```

Moves the deal to `REJECTED` and records `APPROVAL_REJECTED` .

Request Changes - Approval Request

POST `{{baseUrl}}/api/approvals/{{approvalId}}/request-changes`

```
{ "comments": "Please revise the discount and improve the margin." }
```

Moves the deal to `CHANGES_REQUESTED` and records `APPROVAL_CHANGES_REQUESTED`.

7. Exceptions

Suggested request name	Method and path	Access
List - Deal Exceptions	GET <code>/api/deals/{{dealId}}/exceptions</code>	Authenticated
Get - Exception Requirements	GET <code>/api/deals/{{dealId}}/exceptions/requirements</code>	Authenticated
Create - Deal Exception	POST <code>/api/deals/{{dealId}}/exceptions</code>	SALES_REP , CPQ_ADMIN
List - Pending Exception Queue	GET <code>/api/exceptions/pending</code>	Authenticated
Approve - Exception	POST <code>/api/exceptions/{{exceptionId}}/approve</code>	Manager, Finance, VP, Admin
Reject - Exception	POST <code>/api/exceptions/{{exceptionId}}/reject</code>	Manager, Finance, VP, Admin

Create - Deal Exception

POST `{{baseUrl}}/api/deals/{{dealId}}/exceptions`

```
{
  "exceptionType": "DISCOUNT",
  "requestedValue": 25.00,
  "standardValue": 20.00,
  "justification": "Three-year strategic agreement requires additional discount."
}
```

Valid types: `DISCOUNT` , `MARGIN` . The backend obtains `createdBy` from the JWT. Do not send a user ID in the body.

List - Pending Exception Queue

GET `{{baseUrl}}/api/exceptions/pending?type=DISCOUNT`

Optional filter values: `DISCOUNT` , `MARGIN` .

Approve - Exception

POST `{{baseUrl}}/api/exceptions/{{exceptionId}}/approve`

No body. Records `EXCEPTION_APPROVED` and stores the authenticated reviewer as `resolvedBy`.

Reject - Exception

POST `{{baseUrl}}/api/exceptions/{{exceptionId}}/reject`

No body. Records `EXCEPTION_REJECTED` and stores the authenticated reviewer as `resolvedBy`.

8. Audit Trail

GET `{{baseUrl}}/api/deals/{{dealId}}/audit`

Authenticated

Suggested name: **Get - Deal Audit Trail**

Returns chronological events including:

`DEAL_CREATED`, `DEAL_UPDATED`, `DEAL_SUBMITTED`, `DEAL_RESUBMITTED`, `APPROVAL_CREATED`, `APPROVAL_APPROVED`, `APPROVAL_REJECTED`, `APPROVAL_CHANGES_REQUESTED`, `APPROVAL_SUPERSEDED`, `EXCEPTION_CREATED`, `EXCEPTION_APPROVED`, `EXCEPTION_REJECTED`, `EXCEPTION_SUPERSEDED`, and `DEAL_WORKFLOW_TRANSITION`.

```
{
  "eventType": "DEAL_CREATED",
  "actorType": "USER",
  "actorUserId": 3,
  "oldStatus": null,
  "newStatus": "DRAFT",
  "description": "Deal created."
}
```

9. CPQ

GET `{{baseUrl}}/api/cpq/quotes/{{quoteNumber}}`

SALES_REP

CPQ_ADMIN

Suggested name: **Get - CPQ Quote**

With the current default `cpq.enabled=false`, this uses `MockCpqClient`.

```
{
  "quoteNumber": "Q-10482",
  "customerName": "Acme Corporation",
  "totalPrice": 520000.00,
  "discount": 25.00,
  "margin": 13.00,
  "status": "OPEN"
}
```

10. Authorization Tests

Suggested name	Request	Expected result
Security Test - Unauthenticated Request	GET /api/deals with No Auth	401 Unauthorized
Security Test - Sales Rep Creates Deal	POST /api/deals with SALES_REP token	201 Created
Security Test - Manager Attempts Deal Creation	POST /api/deals with SALES_MANAGER token	403 Forbidden
Security Test - Wrong Approval Role	Finance token approves SALES_MANAGER approval	403 Forbidden
Security Test - Correct Approval Role	Sales Manager token approves SALES_MANAGER approval	200 OK

11. Recommended End-to-End Run

1. Get - Application Health
2. Login - User
3. Get - Current User
4. Create - Deal
5. Get - Deal By ID
6. Get - Exception Requirements
7. Create - Deal Exception, if required
8. List - Pending Exception Queue
9. Approve - Exception
10. Submit - Deal

11. List - Deal Approvals
12. List - Pending Approval Queue
13. Approve - Approval Request
14. Request Changes - Approval Request, if needed
15. Update - Deal
16. Resubmit - Deal
17. Get - Deal Audit Trail
18. Get - CPQ Quote

DealFlow API Guide · Generated from the current backend controller mappings and security configuration. Keep credentials, tokens, and production customer data out of Postman exports and source control.