

Machine Learning Programming Assignment – 1

1. Numpy:

a. Using NumPy create random vector of size 15 having only Integers in the range 1-20.

1. Reshape the array to 3 by 5

2. Print array shape.

3. Replace the max in each row by 0

Create a 2-dimensional array of size 4 x 3 (composed of 4-byte integer elements), also print the shape, type and data type of the array.

b. Write a program to compute the eigenvalues and right eigenvectors of a given square array given below: $\begin{bmatrix} 3 & -2 \\ 1 & 0 \end{bmatrix}$

c. Compute the sum of the diagonal element of a given array. $\begin{bmatrix} 0 & 1 & 2 \\ 3 & 4 & 5 \end{bmatrix}$

d. Write a NumPy program to create a new shape to an array without changing its data.

Reshape 3x2: $\begin{bmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{bmatrix}$ Reshape 2x3: $\begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \end{bmatrix}$

```
import numpy as np

# create random vector of size 15 with integers in range 1-20
vec = np.random.randint(1, 21, size=15)

# reshape to 3 by 5
arr = vec.reshape(3, 5)

# print array shape
print("Array shape:", arr.shape)

# replace max in each row by 0
arr[np.arange(len(arr)), arr.argmax(axis=1)] = 0
print(arr)
```

Output:

```
Array shape: (3, 5)
[[ 7  0 10  5  8]
 [ 4 14 10 15  0]
 [ 1 14  0  7 18]]

Process finished with exit code 0
```

```
import numpy as np

# create square array
arr = np.array([[3, -2], [1, 0]])

# compute eigenvalues and right eigenvectors
eig_vals, eig_vecs = np.linalg.eig(arr)

print("Eigenvalues:", eig_vals)
print("Right eigenvectors:\n", eig_vecs)
```

OUTPUT:

```
Eigenvalues: [2. 1.]
Right eigenvectors:
[[0.89442719 0.70710678]
 [0.4472136  0.70710678]]

Process finished with exit code 0
```

```
import numpy as np

# create array
arr = np.array([[0, 1, 2], [3, 4, 5]])

# compute sum of diagonal elements
diag_sum = np.trace(arr)

print("Sum of diagonal elements:", diag_sum)
```

OUTPUT:

```
Sum of diagonal elements: 4

Process finished with exit code 0
```

```
import numpy as np

# create original array
arr = np.array([[1, 2], [3, 4], [5, 6]])

# reshape to 3 by 2
arr_3by2 = arr.reshape(3, 2)

# reshape to 2 by 3
arr_2by3 = arr.reshape(2, 3)

print("Original array:\n", arr)
print("Reshaped to 3 by 2:\n", arr_3by2)
print("Reshaped to 2 by 3:\n", arr_2by3)
```

OUTPUT:

```
Original array:
[[1 2]
 [3 4]
 [5 6]]
Reshaped to 3 by 2:
[[1 2]
 [3 4]
 [5 6]]
Reshaped to 2 by 3:
[[1 2 3]
 [4 5 6]]

Process finished with exit code 0
```

2. Matplotlib

1. Write a Python programming to create a below chart of the popularity of programming Languages.
2. Sample data: Programming languages: Java, Python, PHP, JavaScript, C#, C++ Popularity: 22.2, 17.6, 8.8, 8, 7.7, 6.7

```
# Import the matplotlib.pyplot module, which allows us to create plots
import matplotlib.pyplot as plt


# Define the data we want to plot
languages = 'Java', 'Python', 'PHP', 'JavaScript', 'C#', 'C++'
popularity = [22.2, 17.6, 8.8, 8, 7.7, 6.7]
colors = ["#1f77b4", "#ff7f0e", "#2ca02c", "#d62728", "#9467bd", "#8c564b"]

# Define how much we want to "explode" each slice of the pie chart
explode = (0.1, 0, 0, 0, 0, 0)

# Use the pie function to create the pie chart
plt.pie(popularity,      # The data to plot (popularity percentages)
        explode=explode, # How much to "explode" each slice
        labels=languages, # Labels for each slice (the language names)
        colors=colors,    # Colors for each slice
        autopct='%1.1f%%', # Format for the percentage labels
        shadow=True,      # Whether to include a shadow effect
        startangle=140    # The angle at which the chart starts
        )

# Set the aspect ratio of the chart to be equal, so it appears circular
plt.axis('equal')

# Display the chart
plt.show()
```



GitHub URL: <https://github.com/vamshijuluri1808/ProgAssignment1.git>

Video URL:

<https://drive.google.com/file/d/1LMxr2hBWdAig4OS1EezuR5mCkU5d1qM7/view?usp=sharing>