

2.1 Function Implementation of Image :: Translation

Explanation: Shift the image to 'ty' pixels horizontally and Shift the image to "tx' pixels vertically

Implementing the Translation: myTranslation.m

Equation for Translation:

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} x \\ y \end{pmatrix} + \begin{pmatrix} t_x \\ t_y \end{pmatrix}$$

Reading input images: Lena.jpeg

Output:



Function working:

1. Read input image lena.jpeg. Enter inputs tx=45 and ty=30
2. Shift tx units by rows and ty units by columns
3. Store it as the output. Display now.

NOTE: We will lose tx and ty units on opposite sides of image by translation, if we want to display the image in same pixels of that of an input image size.

2.2 Function Implementation of Image :: Rotation

Explanation: Take the center of the image and rotate the image to 'theta' angle.



Implementing the Translation: myRotation.m

Equation for Rotation:

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix} \begin{pmatrix} x - x_c \\ y - y_c \end{pmatrix} + \begin{pmatrix} x_c \\ y_c \end{pmatrix}$$

Reading input images: cameraman.tif

Output:




Function working:

1. Read input image cameraman.tif. Enter inputs theta= -30 degrees.
2. Take the center of the image . Rotate it.
3. Store it as the output. Display now.

2.2.1 Interpolation


Interpolation: Rotation doesnot lead to perfect mapping of pixels instead leaves gaps in between the pixels after rotation. So we accumulate the surrounding pixels inorder to fill the gaps.


Nearest Neighbor: Take the average of all the corner pixel intensities to interpolate.(top, bottom, left,right)



Bilinear Transformation:

1. Set the reference pixel to rotate. Suppose take a pixel intensities I_1, I_2, I_3, I_4 respectively around four corners of the reference pixel.
2. Calculate the reference pixel's distances along x and y reference axes (Let, say a, b).
3. Then we find linear relation between Intensities and pixels in one row of successive pixels.
4. We do this step twice for top and bottom corner pixel intensities. (w.r.t. opposite pixel intensities)
5. Then we take linear combination for resulting hollow dotted pixels.





NOTE: We will definitely find bilinear transformation accumulative than the nearest neighbor technique.


3. Function Implementation of Image :: Projective Transformation

Explanation: Camera captures 3D object and uses perspective mapping on the object to corresponding points of the image and orientation. We align images more flat that obtained from various view points.

Implementing the Translation: `projectiveTransform.m`

Function working:

1. Read input image `plate_side.jpg`.
2. Using pointer select the pixels points for the extraction of the input.
3. Select the pixels points for the reference image `plate_reference.jpg`.
4. We then display the projective transformation of the input.
5. Crop it and display the output image.



4. Function Implementation of Image :: Procrustes Analysis

Explanation: We perform fitting of one image over the dimension of the other image.

Implementing the Translation: myProcrustes.m

Function working:

1. Load star pattern.mat file
2. Find the procrustes matrix of the given input.
3. Take centroid of input to base pixels by Translation.
4. Scale the input pixels to the base image size.
5. Then rotate it to align the set of points in both the images.
6. Repeat it same for handpoints also.

Equation for Translation:





$$X_i \rightarrow X_i - \bar{X},$$

Equation for Scaling: we calculate the equation for :: norm of $x = \{x_i/\sqrt{x_i}\}$





$$X \rightarrow SI \text{ with } S = sI \text{ and } s = \frac{\sum_{i=1}^N x_i^T x_i}{\sum_{i=1}^N x_i^T x_i}$$

Equation for Rotation:

- form the product of the coordinate matrices XY^T
- calculate its SVD as $XY^T = USV^T$
- calculate the rotation matrix as $R = VU^T$



Observation for starpoints



Observation for handpoints

Contents

- [Function Implementation of Image :: Translation, Rotation and Interpolation](#)
- [Function Implementation of Image :: Procrustes Analysis](#)

```
clear all; close all; clc;
```

Function Implementation of Image :: Translation, Rotation and Interpolation

```
% I = imread('lena.jpeg');  
% myTranslation(I, 45, 30);  
  
% J = imread('cameraman.tif');  
% myRotation(J, -30, 'bilinear');  
  
% Function Implementation of Image :: Projective Transformation  
  
% Input = imread('plate_side.jpg');  
% Ref = imread('plate_reference.jpg');  
% projectiveTransform(Input, Ref);
```

Function Implementation of Image :: Procrustes Analysis

```
M = load('star_points.mat');  
myProcrustes(M.input_points,M.base_points);
```

□

Contents

- [Function starts here](#)

```
function [O] = myTranslation(I, tx, ty)
```

```
%MYTRANSLATION Function shifts the image vertically by tx pixels and horizontally by ty pixels.  
% Input:: I - Input Image      tx - Vertical Shift      ty - Horizontal Shift  
%  
% Output:: O - Translated Image
```

Function starts here

```
O = uint8( zeros(size(I,1), size(I,2), size(I,3)));  
[r,c,~] = size(O);  
for i=1:r  
    for j=1:c  
  
        % Shifted vertically by tx and horizontally by ty  
        O(i+tx:end, j+ty:end, :) = I(i:end-tx,j:end-ty,:);  
  
    end  
end  
  
% Display the Resultant of Translated Image  
figure,  
subplot(1,2,1), imshow(I), title('Original Image');  
subplot(1,2,2), imshow(O), title('Translated Image');
```

```
Not enough input arguments.
```

```
Error in myTranslation (line 8)  
O = uint8( zeros(size(I,1), size(I,2), size(I,3)));
```

```
end
```

Contents

- [Function starts here](#)

```
function [O] = myRotation(I, ang, method)
```

```
%MYROTATION rotates the image from its centre with an angle 'theta'.  
% Input :: Input Image      ang - Angle of Rotation      method - Interpolation method {'nearest', 'bilinear'}  
  
% Output:: O - Rotated Image
```

Function starts here

```
I = im2double(I);  
  
theta=(ang)*pi/360; % Angle of Rotation  
  
[r, c] = size(I); % Size of the Image  
  
O = zeros(size(r,c));  
  
midx = r./2; % Midpoint of x-axis  
midy = c./2; % Midpoint of y-axis  
  
for i=1:r  
    for j=1:c  
  
        % Rotation steps (based on the Given Formula)  
        x=(i-midx)*cos(theta)-(j-midy)*sin(theta);  
        y=(i-midx)*sin(theta)+(j-midy)*cos(theta);  
        x1=round(x)+midx;  
        y1=round(y)+midy;  
  
        % Interpolation steps  
        if (1 <= x1 && x1 <= r && 1 <= y1 && y1 <= c)  
            top = floor(x1);          bottom = top+1;  
            left = floor(y1);         right = left+1;  
            switch method % Select any one method to interpolate  
                case 'nearest' % Nearest Neighbour Interpolation  
                    if (bottom <= r && right <= c)  
                        inten_1 = I(top, left);  inten_2 = I(bottom, left);  
                        inten_3 = I(top, right);  inten_4 = I(bottom, right);  
                        inten = (inten_1 + inten_2 + inten_3 + inten_4)/4;  
                    end  
                case 'bilinear' % Bilinear Interpolation  
                    if (bottom <= r && right <= c)  
                        inten_1 = I(top, left);  inten_2 = I(bottom, left);  
                        leftInten = (x1-top) * (inten_2 - inten_1) + inten_1;  
  
                        inten_3 = I(top, right); inten_4 = I(bottom, right);  
                        rightInten = (x1-top) * (inten_4 - inten_3) + inten_3;  
  
                        inten = (y1 - left) * (rightInten - leftInten) + leftInten;  
                    end  
                else  
                    inten = 0; % Parts other than input image appears black  
                end  
            end  
            O(i,j)=inten; % Store the output image  
        end  
    end  
end  
  
% Display the Result  
figure,  
subplot(1,2,1),imshow(I), title('Original Image of cameraman');  
subplot(1,2,2),imshow(O), title('Rotated Image of cameraman');
```

Not enough input arguments.

Error in myRotation (line 9)

I = im2double(I);


```
end
```

Contents

- [Function starts here](#)

```
function [Projected_image] = projectiveTransform(I, ref)
```

```
%MYPROCRUSTES Function that stretches or contracts the input points set to fit the reference points set.  
%   Input    I - Input image      Y - Reference image  
%  
%   Output    O - Output Image (after projective transformation)
```

Function starts here

```
% Get coordinates of input and reference image  
figure, imshow(I), title('Input Image of plate');  
[x,y] = ginput(4);  
  
figure, imshow(ref), title('Reference Image of the plate');  
[x1, y1] = ginput(4);  
  
X = [x,y];  
Y = [x1,y1];  
  
% Performing Projective Transformation [fitgeotrans is same as cp2tform]  
T = cp2tform(X, Y, 'projective');  
  
% Applying Transformation on the input image  
Projected_image = imtransform(I, T);  
figure, imshow(Projected_image), title('Projective Transformation');  
  
% Cropping the Transformed image  
[~, rect] = imcrop(Projected_image);  
Img_crop = imcrop(Projected_image, rect);  
figure, imshow(Img_crop), title('Cropped Image (After Transformation)');
```

Not enough input arguments.

Error in projectiveTransform (line 10)
figure, imshow(I), title('Input Image of plate');

```
end
```

Contents

- [Function starts here](#)
- [Translation \(to fix the centre of both points set at the origin\)](#)
- [Scaling \(to stretch the points set to the same scale\)](#)
- [Rotate \(to impose input points set on reference\)](#)

```
function [Z] = myProcrustes(X,Y)
```

```
%MYPROCRUSTES Function that stretches or contracts the input points set to fit the reference points set.  
%   Input  
%       X - Input points set  
%       Y - Reference points set  
%  
%   Output  
%       Z - Fitted points set
```

Function starts here

```
figure,  
subplot(2,2,1), plot(X(:,1),X(:,2), 'ks',Y(:,1),Y(:,2), 'r*'), title('Original Points Set');
```

Not enough input arguments.

```
Error in myProcrustes (line 13)  
subplot(2,2,1), plot(X(:,1),X(:,2), 'ks',Y(:,1),Y(:,2), 'r*'), title('Original Points Set');
```

Translation (to fix the centre of both points set at the origin)

```
x = X - mean(X,1);  
y = Y - mean(Y,1);  
  
subplot(2,2,2), plot(x(:,1),x(:,2), 'ks',y(:,1),y(:,2), 'r*'), title('Translated Points Set');
```

Scaling (to stretch the points set to the same scale)

```
sx = sum(x.^2,1);  
sy = sum(y.^2,1);  
sx=sum(sx);  
sy=sum(sy);  
  
normX = sqrt(sx);  
normY = sqrt(sy);  
  
% Scale to equal (unit) norm  
x = x / normX;  
y = y / normY;  
  
subplot(2,2,3), plot(x(:,1),x(:,2), 'ks',y(:,1),y(:,2), 'r*'), title('Scaled Points Set');
```

Rotate (to impose input points set on reference)

```
Scaled = x * transpose(y);  
[U, ~, V] = svd(Scaled);  
R = V * transpose(U);  
  
Z = R * x;  
  
subplot(2,2,4), plot(y(:,1),y(:,2), 'ks',Z(:,1),Z(:,2), 'r*'), title('Rotated Points Set');
```

```
end
```