

Confusion Matrix



0:12 / 50:06



Analytics Vidhya

Learn everything about Data Science



Confusion Matrix : Intuition

PassengerId	Survived	Pclass
1	0	3
2	1	1
3	1	3
4	1	1
5	0	3

survived and not survived respectively
therefore



0:54 / 50:06



Analytics Vidhya

Learn everything about Data Science



Survived only 2 classes yes or no so 2*2 matrix

Confusion Matrix : Intuition


Survived
0
1
1
1
0

2x2

in the dependent variable but for this video we are

Evaluation Metrics for Machine Learning Models | Full Course

Confusion Matrix : Intuition

		Prediction outcome	
		positive	negative
Actual value	positive		
	negative		

represents a class under the actual value and each

Rows-> actual value

Col-> predicted values

as negative wire model
once

Are the values we predicted as positive actually positive in the dataset?
value is negative in this case the prediction is incorrect or

Confusion Matrix : Intuition

		Prediction outcome	
		positive	negative
Actual value	positive	TP	FN
	negative	FP	TN

positive I can say the prediction is incorrect or false so the total number

3:41 / 50:06

Confusion Matrix : Intuition

		Prediction outcome		
		positive	negative	
Actual value	positive	TP	FN	$TP + FN$ Total Actual positive
	negative	FP	TN	$FP + TN$ Total Actual negative

negative now that we have understood the notation what they mean and

Confusion Matrix : Intuition

ID	Actual Survived?	Predicted Survived?	Notation
ID1	1	0	
ID2	1	1	
ID3	1	0	
ID4	0	0	
ID5	1	1	
ID6	1	1	
ID7	0	1	
ID8	0	0	

		Prediction outcome	
		positive	negative
Actual value	positive	<i>TP</i>	<i>FN</i>
	negative	<i>FP</i>	<i>TN</i>

4:33 / 50:06

Confusion Matrix : Intuition

ID	Actual Survived?	Predicted Survived?	Notation
ID1	1	0	<i>FN</i>
ID2	1	1	
ID3	1	0	
ID4	0	0	
ID5	1	1	
ID6	1	1	
ID7	0	1	
ID8	0	0	

		Prediction outcome	
		positive	negative
Actual value	positive	<i>TP</i>	<i>FN</i>
	negative	<i>FP</i>	<i>TN</i>

from predicted survived N

Confusion Matrix : Intuition

ID	Actual Survived?	Predicted Survived?	Notation
ID1	1	0	<i>FN</i>
ID2	1	<u>1</u>	
ID3	1	0	
ID4	0	0	
ID5	1	1	
ID6	1	1	
ID7	0	1	
ID8	0	0	

		Prediction outcome	
		positive	negative
Actual value	positive	<i>TP</i>	<i>FN</i>
	negative	<i>FP</i>	<i>TN</i>



4:46 / 50:06



Analytics Vidhya

Learn everything about analytics



Confusion Matrix : Intuition

ID	Actual Survived?	Predicted Survived?	Notation
ID1	1	0	FN
ID2	1	1	TP
ID3	1	0	FN
ID4	0	0	TN
ID5	1	1	TP
ID6	1	1	TP
ID7	0	1	FP
ID8	0	0	TN

		Prediction outcome	
		positive	negative
Actual value	positive	<i>TP</i>	<i>FN</i>
	negative	<i>FP</i>	<i>TN</i>



Analytics Vidhya

Learn everything about analytics



Confusion Matrix : Intuition

ID	Actual Survived?	Predicted Survived?	Notation
ID1	1	0	FN
ID2	1	1	TP
ID3	1	0	FN
ID4	0	0	TN
ID5	1	1	TP
ID6	1	1	TP
ID7	0	1	FP
ID8	0	0	TN

		Prediction outcome	
		positive	negative
Actual value	positive	TP 3	FN 2
	negative	FP 1	TN 2

Accuracy

Accuracy

It is the ratio of correct predicted values over the total predicted values.

Evaluation Metrics for Machine Learning Models | Full Course

Accuracy

Accuracy: It is the ratio of correct predicted values over the total predicted values.

$$\text{Accuracy} = \frac{\text{Correct Predictions}}{\text{Total Predictions}}$$

$$\text{Accuracy} = \frac{TP + TN}{TP + FN + FP + TN}$$

		Prediction outcome	
		positive	negative
Actual value	positive	TP	FN
	negative	FP	TN

Accuracy

We train a model to detect cancer

		Prediction outcome	
		positive	negative
Actual value	positive	4	2
	negative	8	486

500 Patients with Cancer symptoms



494 Negative Results

6 Positive Results



8:58 / 50:06



Analytics Vidhya

Learn everything about Analytics



Accuracy

We train a model to detect cancer

		Prediction outcome	
		positive	negative
Actual value	positive	4	2
	negative	8	486

$$\text{Accuracy} = \frac{TP + TN}{TP + FN + FP + TN}$$

$$\frac{4 + 486}{4 + 8 + 2 + 486} = 98\%$$



9:43 / 50:06



Analytics Vidhya

Learn everything about Analytics



Accuracy : dumb model

We train a "dumb" model to detect cancer

Negative report for every patient

Or

No patient has cancer

$$\text{Accuracy} = \frac{TP + TN}{TP + FN + FP + TN}$$

$$\frac{0 + 494}{0 + 6 + 0 + 494} = 98.8\%$$

		Prediction outcome	
		positive	negative
Actual value	positive	0	6
	negative	0	494



11:11 / 50:06



Analytics Vidhya

Learn everything about Data Science



Accuracy not great on unbalanced data..

Alternatives of Accuracy

11:14 / 50:06

Evaluation Metrics for Machine Learning Models | Full Course

True Positive Rate

$$TPR = \frac{TP}{TP + FN}$$

		Prediction outcome			
		positive	negative		
Actual value	positive	TP	FN	TP + FN	Total Actual positive
	negative	FP	TN	FP + TN	Total Actual negative

Ratio of actual positive predictions over total actual positives

11:59 / 50:06

False Negative Rate

$$TPR = \frac{TP}{TP + FN}$$

$$FNR = \frac{FN}{TP + FN}$$

		Prediction outcome			
		positive	negative		
Actual value	positive	TP	FN	TP + FN	Total Actual positive
	negative	FP	TN	FP + TN	Total Actual negative

Ratio of actual positive, predicted as negative; over total actual positive



12:48 / 50:06



Analytics Vidhya

Learn everything about Data Science



False Positive Rate

$$TPR = \frac{TP}{TP + FN}$$

$$FNR = \frac{FN}{TP + FN}$$

< -33

$$TNR = \frac{TN}{FP + TN}$$

$$FPR = \frac{FP}{FP + TN}$$

		Prediction outcome			
		positive	negative		
Actual value	positive	TP	FN	TP + FN	Total Actual positive
	negative	FP	TN	FP + TN	Total Actual negative

Ratio of actual negative, predicted as positive; over total actual negative



14:21 / 50:06



Analytics Vidhya

Learn everything about Data Science



Precision and Recall

17:23 / 50:06

Evaluation Metrics : Precision

Out of all the positive predictions, how many are actually positive.

$$\text{precision} = \frac{\text{Predictions Actually Positive}}{\text{Total Predicted positive}}$$

$$\text{precision} = \frac{TP}{TP + FP}$$

		Prediction outcome	
		positive	negative
Actual value	positive	TP	FN
	negative	FP	TN

18:07 / 50:06

Evaluation Metrics : Precision

- Aim: Arrest "only" the criminals
- Avoid VIP > Catch Criminal
- Minimise false positives
(arresting innocents)

$$\text{precision} = \frac{TP}{TP + FP}$$

- False negative rate is high
(all criminals may not be arrested)

FP ↓

FN ↑



Analytics Vidhya
Learn everything about Analytics

to catch criminals in party full of innocent businessman

Evaluation Metrics : Recall

Out of all actual positive, how many are predicted positive.

$$\text{recall} = \frac{\text{Predictions Actually Positive}}{\text{Total Actual Positive}}$$

$$\text{recall} = \frac{TP}{TP + FN}$$

		Prediction outcome	
		positive	negative
Actual value	positive	TP	FN
	negative	FP	TN



Analytics Vidhya
Learn everything about Analytics

Evaluation Metrics : Recall


- Aim: "ALL" weapon carriers "MUST" be caught
- Catching weapon > checking innocent
- Minimize False Negative
(undetected weapon carrier)
- False positive rate is high
(detects innocent as weapon carrier)

$$\text{recall} = \frac{TP}{TP + FN}$$

Evaluation Metrics for Machine Learning Models | Full Course


Evaluation Metrics : Precision/Recall tradeoff

- High Precision, Low Recall
- High Recall, Low Precision
- Choice depends upon the use case



Evaluation Metrics : Precision/Recall tradeoff

- High Precision, Low Recall
- High Recall, Low Precision
- Choice depends upon the use case
- Combined using F1 Score




$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}}$$

Evaluation Metrics for Machine Learning Models | Full Course

Evaluation Metrics : Precision/Recall tradeoff

- High Precision, Low Recall
- High Recall, Low Precision
- Choice depends upon the use case
- Combined using F1 Score
- F1 is maximum when precision = recall



$$F_1 = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}}$$



Question:

For a given classifier, suppose the first 10 predictions of our classifier and 10 true observations are as follows:

True Label	0	1	1	1	0	0	0	1	1	1
Prediction	1	1	1	1	1	0	1	1	1	1

- i. [1 Pt] What is the accuracy of our classifier on these 10 predictions?

$$\frac{7}{10} = 0.7$$

- ii. [1 1/2 Pts] What is the precision on these 10 predictions?

$$\frac{6}{9} = \frac{2}{3}$$

- iii. [1 1/2 Pts] What is the recall on these 10 predictions?

$$\frac{6}{6} = 1$$

<https://ds100.org/fa21/resources/assets/exams/fa19/fa19midterm2sol.pdf>

www.goclasses.in



- i. [1 Pt] What is the accuracy of our classifier on these 10 predictions?

Solution: 7 of our predictions were correct, out of 10 total. Thus, our accuracy

is $\frac{7}{10}$.

- ii. [1 1/2 Pts] What is the precision on these 10 predictions?

Solution: The number of true positives, TP , is 6. The number of false positives, FP , is 3. Then, the precision is $\frac{TP}{TP+FP} = \frac{6}{9} = \frac{2}{3}$.

- iii. [1 1/2 Pts] What is the recall on these 10 predictions?

Solution: From the solution to the previous part, we know that $TP = 6$. The number of false negatives, FN , here is 0 (we only predicted 0 once, and in that case the true value was actually 0). Thus, the recall is $\frac{TP}{TP+FN} = \frac{6}{6+0} = 1$.

www.goclasses.in



$[T, T, F, T, F, T, F, T]$ ← correct
 $[T, F, T, T, F, F, F, T]$ ← Predicted

Acc. = $\frac{5}{8}$

Precision = $\frac{3}{4}$

Recall = $\frac{3}{5}$



$[T, F, F, F, F, F, F, T]$ ← correct
 $[F, T, F, F, F, F, F, F]$ ← Predicted

Acc. = $\frac{5}{8}$

Precision = $\frac{0}{1} = 0$

Recall = $\frac{0}{2} = 0$

GO CLASSES

Machine Learning

GO Classe

Question:

9. Suppose we train a binary classifier on some dataset. Suppose y is the set of true labels, and \hat{y} is the set of predicted labels.

y	0	0	0	0	0	1	1	1	1	1
\hat{y}	0	1	1	1	1	1	1	0	0	0

Determine each of the following quantities.

(a) [1 Pt] The number of true positives

Solution:

(b) [1 Pt] The number of false negatives

Solution:

(c) [1 Pt] The precision of our classifier. Write your answer as a simplified fraction.

Solution:

← Actual

← Pred.

<https://ds100.org/fa20/resources/assets/exams/fa18/fa18finalsol.pdf>

1:24:11
~42:33

GO CLASSES

Machine Learning

GO Classe

9. Suppose we train a binary classifier on some dataset. Suppose y is the set of true labels, and \hat{y} is the set of predicted labels.

y	0	0	0	0	0	1	1	1	1	1
\hat{y}	0	1	1	1	1	1	1	0	0	0

Determine each of the following quantities.

(a) [1 Pt] The number of true positives

Solution: 2

(b) [1 Pt] The number of false negatives


Solution: 3

(c) [1 Pt] The precision of our classifier. Write your answer as a simplified fraction.

Solution: $\frac{2}{2+4} = \frac{1}{3}$

www.goclasses.in

1:25:02
~41:42



Machine Learning

GO Classe

Confusion Matrix


	what does the model think?			
	dog	cat	mouse	
what is it actually?	dog	4	0	0
cat	2	2	0	
mouse	0	0	2	


Cat Recall: when we **actually** have a cat (row!), what percentage of the time is the model right? $\frac{2}{4}$

Dog Recall: when we **actually** have a dog (row!), what percentage of the time is the model right? $\frac{4}{4}$

Dog Precision: when the model **predicts** a dog (column!), what percentage is it right? $\frac{4}{6}$

Cat Precision: when the model **predicts** a cat (column!), what percentage is it right? $\frac{2}{2}$





Machine Learning

GO Classe

Question:

Given the following confusion matrix for a classification task with three classes (A, B, and C), which of the following statements is correct?


	Ground Truth			
	A	B	C	
Predicted	A	0	0	2
B	1	3	1	
C	0	0	3	

A. Precision(B) = 1.0

B. Precision(C) = 0.5

C. Recall(B) = 1.0

D. Recall(C) = 0.5




https://archive.nptel.ac.in/content/storage2/courses/downloads_new/106106213/nnc20_cs44_assignment_2.pdf

GO CLASSES
Machine Learning
GO Classe


3. (1 point) Again, consider a binary classification data set with 9000 positively labelled examples and 1000 negatively labelled examples. What is the precision and the recall of a classifier that always classifies any example as positive?

- A. The precision is 0.1, and the recall is 0.9.
- B. The precision is 0.9, and the recall is 0.1.
- C. The precision is 1.0, and the recall is 0.9.
- D. The precision is 0.9, and the recall is 1.0.
- E. The precision is 0.1, and the recall is 1.0.

Solution: D. The precision is $9000/10000 = 0.9$ since all examples are classified as positive. The recall is $9000/9000 = 1.0$ (perfect recall) since all positive examples are classified as positive.



Host


www.goclasses.in

1:35:07
||
-31:37

GO CLASSES
Machine Learning
GO Classe

Combining precision and recall


- ▶ **Key insight:** Two moderate values are better than two extremes. Use the product, which shrinks when either term in the product is small.
- ▶ New way of combining precision and recall: **F-score**

$$\frac{2PR}{P+R}$$


2. $\frac{1}{\frac{1}{P} + \frac{1}{R}}$

(harmonic mean of P, R)

- ▶ Compare:
 - ▶ Classifier A ($P = 0, R = 1$) $\rightarrow \frac{2 \cdot 0 \cdot 1}{0 + 1} = 0$ bad
 - ▶ Classifier B ($P = 0.5, R = 0.6$) $\rightarrow \frac{2 \cdot 0.5 \cdot 0.6}{0.5 + 0.6} = \frac{6}{11}$



Host



1:50:03
||
-16:41

Thresholding



24:03 / 50:06



AUC-ROC



29:49 / 50:06



Area Under Curve

AUC - ROC



30:14 / 50:06




Analytics Vidhya

Learn everything about Data Science



Area Under Curve



30:24 / 50:06




Analytics Vidhya

Learn everything about Data Science




Area Under Curve




The ROC Curve

- ROC: Receiver Operating Characteristic
- Originally used for distinguishing 'noise' from 'not noise'
- Evaluation Metric for Binary Classification
- Gives trade-off between True Positives and False Positives

The ROC Curve



The ROC Curve



The more the area under curve better the prediction

Problem with AUC-ROC

- Considers only the order of probability
- Cannot be used for comparing two models



35:03 / 50:06



Analytics Vidhya
Learn everything about Data Science

