

Function Reference

1. ``openfilenet.token : str``

Token/namespace identifier.

Only peers with matching token discover each other.

2. ``openfilenet.port.udp_discovery : int``

UDP port used for broadcast/discovery.

Default: 51230

3. ``openfilenet.port.tcp_server : int``

TCP port for file server.

Default: 0 (OS chooses a free port).

4. ``openfilenet.debug : bool``

Enable verbose logging.

True/False.

5. ``openfilenet.encrypt : bool``

Enable AES-256-GCM encryption for file transfer.

6. ``openfilenet.key : str``

Shared secret string if encrypt is set to True.

7. ``share_files(paths)``

Register files or directories to share.

Accepts: Path string, ``Path`` object, List of paths

Automatically walks directories.

8. `list_files() -> list[dict]`

Returns file metadata from all known peers:

```
{  
  "peer_id": "...",  
  "path": "folder/file.txt",  
  "size": 12345,  
  "mtime": 16900000.1  
}  
...  
---
```

9. `get_file(peer_id, path, dest=None)`

Fetch a file from a specific peer.

`dest=None` → returns bytes in memory

`dest="local/file.txt"` → saves file to disk

Handles encryption/decryption automatically.

10. `add_peer(host, port, peer_id=None)`

Manually add a peer.

Use only when:

UDP broadcast is blocked

Hidden networks or VLANs

Wi-Fi AP with isolated clients