



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

Understanding Higher-Order Functions (HOFs)

A Higher-Order Function (HOF) is a function that either takes another function as an argument or returns a function. These are widely used in JavaScript to enhance code reusability and maintainability.

1. Delayed Execution Using Callback (HOF + Callback)

Concept:

A function can accept another function as an argument (callback) and execute it after a delay using `setTimeout`.

Implementation

```
function delayedExecution(callback) {  
  setTimeout(callback, 3000);  
  // Calls the callback function after 3 seconds  
}  
  
// Example usage  
delayedExecution(() =>  
  console.log("Executed after 3 seconds"));
```

Explanation:

- `delayedExecution` accepts a function callback.
- `setTimeout` is used to delay the execution of the callback for 3 seconds.
- When called, it logs a message to the console after 3 seconds.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

2. Implementing Custom Function (HOF)

Concept:

The `.map()` method is used to transform an array by applying a callback function to each element. We can create our own version of `.map()`.

Implementation

```
function customMap(array, callback) {  
  let result = [];  
  for (let i = 0; i < array.length; i++) {  
    result.push(callback(array[i], i, array));  
    // Apply callback to each element  
  }  
  return result;  
}  
  
// Example usage  
console.log(customMap([1, 2, 3], num => num * 2));  
// Output: [2, 4, 6]
```

Explanation:

- `customMap` takes an array and a callback function.
- Iterates over the array, applies the callback function to each element, and stores the result.
- Works similarly to `Array.prototype.map` but is implemented manually.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

3. Closures: Creating a Counter Function

Concept:

A closure is a function that retains access to variables from its outer scope even after the outer function has finished execution.

Implementation

```
function createCounter() {  
  let count = 0;  
  return function() { // Closure retains access to `count`  
    return ++count;  
  };  
}  
  
// Example usage  
const counter = createCounter();  
console.log(counter()); // Output: 1  
console.log(counter()); // Output: 2  
console.log(counter()); // Output: 3
```

Explanation:

- createCounter defines a variable count and returns a function.
- The inner function forms a closure, keeping count in memory.
- Each time the inner function is called, count is incremented and returned.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

4. Limiting Function Calls (Closure + HOF)

Concept:

A function should only be executed a limited number of times. This can be achieved using closures.

Implementation

```
function createCounter() {  
  let count = 0;  
  return function() { // Closure retains access to `count`  
    return ++count;  
  };  
}  
  
// Example usage  
const counter = createCounter();  
console.log(counter()); // Output: 1  
console.log(counter()); // Output: 2  
console.log(counter()); // Output: 3
```

Explanation:

- limit takes a function fn and a limit value.
- It tracks the number of times the function has been called.
- Once the limit is reached, further calls do nothing



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

Conclusion

- Higher-Order Functions (HOFs) enable cleaner and reusable code by accepting functions as arguments.
- Callbacks allow asynchronous behavior and function execution control.
- Closures help retain variable states and create private data.
- These concepts are crucial in modern JavaScript development, especially in functional programming and asynchronous operations.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

1. Repeating a Function at Intervals (Using Callbacks)

Concept:

A callback function is a function passed as an argument to another function. Using `setInterval`, we can execute a callback function repeatedly at specified intervals.

Implementation

```
function repeatFunction(callback, interval) {  
  setInterval(callback, interval * 1000);  
}  
  
// Example usage  
repeatFunction(() => console.log("Repeating..."), 2);  
// Logs "Repeating..." every 2 seconds
```

Explanation:

- The function `repeatFunction` takes two parameters:
 - `callback`: The function to execute
 - `interval`: The time in seconds between executions
- `setInterval` is used to call `callback` repeatedly after every interval seconds.
- In the example, the function logs "Repeating..." every 2 seconds.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

2. Creating a Function with a Preset Greeting (Using Closures)

Concept:

A closure allows a function to "remember" variables from its outer scope even after the outer function has finished executing.

Implementation

```
function greetUser(greeting) {  
  return function (name) {  
    return `${greeting}, ${name}!`;  
  };  
}  
  
// Example usage  
const greetHello = greetUser("Hello");  
console.log(greetHello("Alice")); // "Hello, Alice!"  
console.log(greetHello("Bob"));   // "Hello, Bob!"
```

Explanation:

- greetUser is a higher-order function that returns another function.
- The returned function remembers the greeting value from greetUser (closure property).
- When greetHello("Alice") is called, it uses the stored greeting ("Hello") and returns "Hello, Alice!".
- This technique is useful for creating pre-configured functions.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

3. Executing a Function Only Once (Using HOFs + Closures)

Concept:

A function should only be executed once, no matter how many times it is called.

Implementation

```
function once(fn) {  
  let executed = false;  
  return function (...args) {  
    if (!executed) {  
      executed = true;  
      return fn(...args);  
    }  
  };  
}  
  
// Example usage  
const init = once(() => console.log("Initialized!"));  
init(); // "Initialized!"  
init(); // (No output)
```

Explanation:

- The once function wraps another function (fn) and ensures it only executes once.
- The variable executed keeps track of whether the function has already been called.
- The first call executes fn, but all subsequent calls do nothing.
- Useful for initialization functions.



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

4. Throttling a Function (Using HOFs + Closures)

Concept:

Throttling ensures that a function is not executed more than once within a specified time period. This is useful in event listeners to improve performance.

Implementation

```
function throttle(fn, delay) {  
  let lastCall = 0;  
  return function (...args) {  
    let now = Date.now();  
    if (now - lastCall >= delay) {  
      lastCall = now;  
      fn(...args);  
    }  
  };  
}  
  
// Example usage  
const throttledFn = throttle(() =>  
  console.log("Throttled Execution"), 2000);  
throttledFn();  
throttledFn();  
throttledFn();  
// Only executes the first call,  
others are ignored until 2 sec passes
```



JAVASCRIPT ADVANCED HOF'S , CALLBACKS, AND CLOSURES

Explanation:

- throttle ensures that fn runs only once in every delay milliseconds.
- The lastCall variable stores the last execution time.
- If delay hasn't passed, additional calls are ignored.
- Useful in scenarios like scrolling events or resizing windows.