

CS35L – Software Construction Lab

Spring 2016

TA – Sharath Gopal

CS35L – Course info

- Syllabus & detailed course information
 - Website (<http://www.cs.ucla.edu/classes/spring16/cs35L/>)
- Announcements – 'News' section of the website
- Piazza (piazza.com/ucla/spring2016/cs35l) for class discussions
 - No sharing code or answers.
- Prerequisites – CS 31
- Operating system/Shell options
 - **Install** a GNU/Linux distribution on laptop on a separate partition (Take a backup!)
 - You can use any other flavor of linux (Ubuntu, RedHat, etc)
 - **Virtual machine** – VirtualBox, etc
 - **Windows** users
 - Cygwin (ssh, gcc, gdb, emacs, coreutils, etc)
 - Putty (Just a lightweight 'ssh' client that lets you logon to SEASnet)
 - **Mac** users
 - Use Macports or homebrew to install required command line tools
 - Or, you can just use ssh on the mac terminal to logon to seasnet servers
- Get a SEASnet account asap
 - Add `/usr/local/cs/bin` to `$PATH`

CS35L – Course Info

- Assignments (10)
 - Lab exercises – Expected to be done in the lab
 - Homework
- All assignments to be done individually
- Submitted on CCLE
- Grading
 - Assignments – 50% (equally weighted)
 - Final exam – 50%
- Lateness penalty
 - 2^N % of the assignment's value for being 'N' days late
 - No assignments accepted after Friday of last week of instruction
- Assignment 1 and 10 are available
 - Assignment 1 – Due Friday (1st Mar)
 - Assignment 10 – Research and Development
 - Report and Class presentation
 - Resources at - <http://cs.ucla.edu/classes/spring16/cs35L/comm.html>


CS35L - Contact & Office Hours

- Sharath Gopal
 - sharath@cs.ucla.edu
- Office Hours
 - BH2432 – TBD

Introduction to Unix Shell

Operating Systems & Shells

- An OS is a **system software** that manages hardware/software resources.
- OS is responsible for managing:
 - Processes
 - Memory
 - I/O
 - Security
 - File system
 - ...
- An OS **shell** is a user-interface to access the operating system's services
 - Navigating the file system
 - Process monitoring
 - Remote login
 - Access to any installed app (editors, browsers, compilers, debuggers, etc)



```
[sharath@lnxsr07 A1]$ ls -l
total 20
-rwxr-xr-x 1 sharath csgrad 6 Jan 4 11:29 cha
-rw-r--r-- 1 sharath csgrad 8 Jan 5 2015 cha1
-rw-r--r-- 1 sharath csgrad 9 Apr 2 2013 chab
-rw-r--r-- 1 sharath csgrad 10 Apr 1 2015 chap
-rw-r--r-- 1 sharath csgrad 7 Jan 8 2013 chap01
-rw-r--r-- 1 sharath csgrad 7 Jan 8 2013 chap02
-rw-r--r-- 1 sharath csgrad 7 Jan 8 2013 chap03
-rw-r--r-- 1 sharath csgrad 11 Apr 3 2013 chap8
-rw-r--r-- 1 sharath csgrad 6 Jan 8 2013 chapx
-rw-r--r-- 1 sharath csgrad 6 Jan 8 2013 chapy
-rw-r--r-- 1 sharath csgrad 6 Jan 8 2013 chapz
-rw-r--r-- 1 sharath csgrad 43 Jan 5 2015 charenamed
-rw-r--r-- 1 sharath csgrad 9 Apr 2 2013 haz
-rw-r--r-- 1 sharath csgrad 11 Mar 30 2015 clap
-rw-r--r-- 1 sharath csgrad 38 Apr 1 2015 duphellofile.png
-rw-r--r-- 1 sharath csgrad 602 Jan 4 11:49 emacsCommands.txt
-rw-r--r-- 1 sharath csgrad 27 Oct 8 2014 foo001.txt
-rw-r--r-- 1 sharath csgrad 15 Oct 8 2014 foo01.txt
-rw-r--r-- 1 sharath csgrad 6 Jan 8 2013 foo02.txt
-rw-r--r-- 1 sharath csgrad 12 Apr 1 2013 foo03.txt
-rw-r--r-- 1 sharath csgrad 37 Apr 1 2015 hellofile.txt
-rw-r--r-- 1 sharath csgrad 43 Sep 28 13:17 key1.txt
-rw-r--r-- 1 sharath csgrad 60 Jan 6 12:05 myfile2.txt
-rw-r--r-- 1 sharath csgrad 26 Jan 7 2015 myfilereverse
-rw-r--r-- 1 sharath csgrad 72 Jan 4 13:22 myfile.txt
-rw-r--r-- 1 sharath csgrad 33 Sep 28 12:56 myfirstfile.txt
drwxr-xr-x 2 sharath csgrad 4096 Jan 6 12:49 prog
drwxr-xr-x 2 sharath csgrad 4096 Apr 1 2015 temp
-rw-r--r-- 1 sharath csgrad 1735 Jan 6 12:18 temp.txt
[sharath@lnxsr07 A1]$ whoami
sharath
[sharath@lnxsr07 A1]$
```

Why Ubuntu?

- Multics (1964) → Unix (1970) → Minix (1987) → GNU/Linux (1991) → Ubuntu (2004)
- Debian based Linux
- Free software package via GNU
- Linux kernel (Unix-like OS)
- LiveCD Linux distribution
- Allows us to understand the workings of Unix
- Practice software construction via **command line interface** (CLI)

CLI vs. GUI

CLI

- Steep learning curve
- Pure control (e.g., scripting)
- Cumbersome multitasking
- Speed: Hack away at keys
- Convenient remote access

GUI

- Intuitive
- Limited Control
- Easy multitasking
- Limited by pointing
- Bulky remote access

Unix File System Layout

- Everything is a file (including devices)
 - /dev/hda
 - /dev/sda
- Tree structured hierarchy
 - Top of the tree is /
 - /usr/include
 - /usr/bin
- Admin/Non-Admin
 - Admin/SuperUser/RootUser
 - Can do anything on the system!
 - NonAdmin/RestrictedUser
 - Restricted set of permissions
- Lost? Man Pages
 - man: get manual or man pages
 - man ls : shows the man page for 'ls' command
 - /keyword : forward slash followed by keyword to search within a man page (press 'n' to goto the next occurrence)
 - q : quit the man page

The Basics

- Environment variables
 - These are a set of global key(variable)/value pairs that affect a user's login env
 - \$PATH – List of directories to search for commands
 - \$HOME – Home directory
- Commonly used commands...
 - printenv: prints all env variables
 - echo \$PATH
 - echo \$HOME
 - mv: move a file (no undos!)
 - cp: copy a file
 - rm: remove a file
 - mkdir: make a directory
 - rmdir: remove a directory
 - ls: list contents of a directory
 - -l: show long listing including permission info
 - -a: list all files including hidden ones
 - -s: show size of each file, in blocks
 - -h: human readable form

The Basics Contd...

- Moving around
 - pwd: print working directory
 - cd: change working directory
 - ~: home directory
 - .: current directory
 - /: root directory, or directory separator
 - ..: parent directory
- Filename matching (wildcards)
 - ?: matches any single character in a filename
 - *: matches one or more characters in a filename
 - []: matches any one of the characters between the brackets. Use '-' to separate a range of consecutive characters.

The Basics Contd...

- File and directory permissions are important for security on linux
- User (u) / Group (g) / Others (o)
 - User is the owner of the file
 - Group – csugrad
 - Other – others with accounts on the system
- Permission bits
 - Read (r), Write (w), Execute(x)
- rwx-rwx-rwx – 111 110 110
 - `chmod 766 file.txt`
- Other ways of using chmod
 - `chmod u+x file.txt` → Sets the execute bit for User
 - `chmod g-r file.txt` → Clears the read bit for Group
 - `chmod o-w file.txt` → Clears the write bit for Others

The Basics Contd...

- Command History
 - <up arrow>: previous command
 - <tab>: auto-complete
 - !!: replace with previous command
 - `ls`
 - `man !!`
- Standard Streams
 - STDOUT – Standard output
 - STDERR – Standard error
 - STDIN - Standard input
- Redirection to/from files
 - `> file` : write stdout to a file (overwrites existing file!)
 - `>> file` : append stdout to a file
 - `< file` : use contents of a file as stdin
- Pipes : Redirecting the output of one command to another
 - `ls -l | wc -l`

The Basics Contd...

- Changing file attributes
 - ln: create a link
 - Hard links: points to physical data – (`ln file.txt hlink`)
 - Soft links aka symbolic links (-s): points to a file – (`ln -s file.txt slink`)
 - touch: update access & modification time to current time
 - chmod – Changing permissions
- find – Locate files on disk
 - Example Usage – `find /usr/include -name 'stdio.h'`
 - Useful options
 - -type: type of a file (e.g., directory, symbolic link)
 - -perm: permission of a file
 - -name: name of a file
 - -prune: don't descend into a directory
 - -ls: list current file

The Basics: Look These Up

Use man pages to see what these commands do.

- cat
- head
- tail
- du
- ps
- kill
- diff
- cmp
- wc
- sort

SSH (Secure Shell) & SCP (Secure Copy)

- Remote Login via CLI
 - `ssh username@lnxsrv.seas.ucla.edu`
- Copy to/from seasnet server
 - `scp`
 - Usage similar to `cp`
 - `scp [source] [destination]`
 - Transferring files to remote host
 - `scp /home/username/doc.txt username@lnxsrv.seas.ucla.edu:/home/user/docs/`
 - Transferring files from remote host
 - `scp username@lnxsrv.seas.ucla.edu:/home/user/docs/foo.txt /home/username`

Emacs

- Almost like a Windows text editor, but much more powerful
- Sometimes easier to use than vi
- Useful features for a programmer
 - Multiple windows/files
 - Integration with gdb
 - Execute commands or fire up a shell inside the editor
 - Very customizable!

The screenshot shows the Emacs editor interface with a terminal window. The terminal displays the following commands and output:

```
print go run until next step finish up down Gud Complete In/Out Signals Help
#include<stdio.h>

int main(int argc, char *argv[])
{
    printf("Hello world\n");
    return 0;
}

/usr/lib/skel/.cshrc: No such file or directory.
[sharath@lnxsr07 prog]$ ls
main.c  mainexec
[sharath@lnxsr07 prog]$ gcc -g main.c -o mainexec
[sharath@lnxsr07 prog]$ ./mainexec
Hello world
[sharath@lnxsr07 prog]$
```

The Emacs editor window shows the C program code. The status bar at the bottom indicates the current file is `*gud-mainexec*` and the debugger is `(Debugger: run [ready])`.

GNU Emacs Reference Card

(for version 20)

Starting Emacs

To enter GNU Emacs 20, just type its name: **emacs**

To read in a file to edit, see Files, below.

Leaving Emacs

suspend Emacs (or iconify it under X)	C-z
exit Emacs permanently	C-x C-c

Files

read a file into Emacs	C-x C-f
save a file back to disk	C-x C-s
save all files	C-x s
insert contents of another file into this buffer	C-x i
replace this file with the file you really want	C-x C-v
write buffer to a specified file	C-x C-w
version control checkin/checkout	C-x C-q

Getting Help

The help system is simple. Type **C-h** (or **F1**) and follow the directions. If you are a first-time user, type **C-h t** for a **tutorial**.

remove help window	C-x 1
scroll help window	C-M-v
apropos: show commands matching a string	C-h a
show the function a key runs	C-h c
describe a function	C-h f
get mode-specific information	C-h m

Error Recovery

abort partially typed or executing command	C-g
recover a file lost by a system crash	M-x recover-file
undo an unwanted change	C-x u or C-_
restore a buffer to its original contents	M-x revert-buffer
redraw garbaged screen	C-l

Incremental Search

search forward	C-s
search backward	C-r
regular expression search	C-M-s
reverse regular expression search	C-M-r
select previous search string	M-p
select next later search string	M-n
exit incremental search	RET
undo effect of last character	DEL
abort current search	C-g

Use **C-s** or **C-r** again to repeat the search in either direction. If Emacs is still searching, **C-g** cancels only the part not done.

Motion

entity to move over	backward	forward
character	C-b	C-f
word	M-b	M-f
line	C-p	C-n
go to line beginning (or end)	C-a	C-e
sentence	M-a	M-e
paragraph	M-{	M-}
page	C-x [C-x]
sexp	C-M-b	C-M-f
function	C-M-a	C-M-e
go to buffer beginning (or end)	M-<	M->
scroll to next screen		C-v
scroll to previous screen		M-v
scroll left		C-x <
scroll right		C-x >
scroll current line to center of screen		C-u C-l

Killing and Deleting

entity to kill	backward	forward
character (delete, not kill)	DEL	C-d
word	M-DEL	M-d
line (to end of)	M-0 C-k	C-k
sentence	C-x DEL	M-k
sexp	M-- C-M-k	C-M-k
kill region		C-w
copy region to kill ring		M-w
kill through next occurrence of <i>char</i>		M-z char
yank back last thing killed		C-y
replace last yank with previous kill		M-y

Marking

set mark here	C-0 or C-SPC
exchange point and mark	C-x C-x
set mark <i>arg</i> words away	M-0
mark paragraph	M-h
mark page	C-x C-p
mark sexp	C-M-0
mark function	C-M-h
mark entire buffer	C-x h

Query Replace

interactively replace a text string	M-%
using regular expressions	M-x query-replace-regexp

Valid responses in query-replace mode are

replace this one, go on to next	SPC
replace this one, don't move	,
skip to next without replacing	DEL
replace all remaining matches	!
back up to the previous match	^
exit query-replace	RET
enter recursive edit (C-M-c to exit)	C-r

Multiple Windows

When two commands are shown, the second is for “other frame.”

delete all other windows		C-x 1
split window, above and below	C-x 2	C-x 5 2
delete this window	C-x 0	C-x 5 0
split window, side by side		C-x 3
scroll other window		C-M-v
switch cursor to another window	C-x o	C-x 5 o
select buffer in other window	C-x 4 b	C-x 5 b
display buffer in other window	C-x 4 C-o	C-x 5 C-o
find file in other window	C-x 4 f	C-x 5 f
find file read-only in other window	C-x 4 r	C-x 5 r
run Dired in other window	C-x 4 d	C-x 5 d
find tag in other window	C-x 4 .	C-x 5 .
grow window taller		C-x ^
shrink window narrower		C-x {
grow window wider		C-x }

Formatting

indent current line (mode-dependent)	TAB
indent region (mode-dependent)	C-M-\
indent sexp (mode-dependent)	C-M-q
indent region rigidly <i>arg</i> columns	C-x TAB
insert newline after point	C-o
move rest of line vertically down	C-M-o
delete blank lines around point	C-x C-o
join line with previous (with <i>arg</i> , next)	M-^
delete all white space around point	M-\
put exactly one space at point	M-SPC
fill paragraph	M-q
set fill column	C-x f
set prefix each line starts with	C-x .
set face	M-g

Case Change

uppercase word	M-u
lowercase word	M-l
capitalize word	M-c
uppercase region	C-x C-u
lowercase region	C-x C-l

The Minibuffer

The following keys are defined in the minibuffer.

complete as much as possible	TAB
complete up to one word	SPC
complete and execute	RET
show possible completions	?
fetch previous minibuffer input	M-p
fetch later minibuffer input or default	M-n
regexp search backward through history	M-r
regexp search forward through history	M-s
abort command	C-g

Type **C-x ESC ESC** to edit and repeat the last command that used the minibuffer. Type **F10** to activate the menu bar using the minibuffer.

GNU Emacs Reference Card

Buffers

select another buffer	C-x b
list all buffers	C-x C-b
kill a buffer	C-x k

Transposing

transpose characters	C-t
transpose words	M-t
transpose lines	C-x C-t
transpose sexps	C-M-t

Spelling Check

check spelling of current word	M-\$
check spelling of all words in region	M-x ispell-region
check spelling of entire buffer	M-x ispell-buffer

Tags

find a tag (a definition)	M-.
find next occurrence of tag	C-u M-.
specify a new tags file	M-x visit-tags-table
regexp search on all files in tags table	M-x tags-search
run query-replace on all the files	M-x tags-query-replace
continue last tags search or query-replace	M-,

Shells

execute a shell command	M-!
run a shell command on the region	M-
filter region through a shell command	C-u M-
start a shell in window *shell*	M-x shell

Rectangles

copy rectangle to register	C-x r r
kill rectangle	C-x r k
yank rectangle	C-x r y
open rectangle, shifting text right	C-x r o
blank out rectangle	C-x r c
prefix each line with a string	C-x r t

Abbrevs

add global abbrev	C-x a g
add mode-local abbrev	C-x a l
add global expansion for this abbrev	C-x a i g
add mode-local expansion for this abbrev	C-x a i l
explicitly expand abbrev	C-x a e
expand previous word dynamically	M-/

Regular Expressions

any single character except a newline	.	(dot)
zero or more repeats	*	
one or more repeats	+	
zero or one repeat	?	
quote regular expression special character c	\c	
alternative ("or")		
grouping	((...)
same text as nth group	\n	
at word break	\b	
not at word break	\B	
entity		match start
line	^	match end
word	\<	\>
buffer	\'	\'
class of characters		match these
explicit set	[...]	[^ ...]
word-syntax character	\w	\W
character with syntax c	\sc	\Sc

International Character Sets

specify principal language	M-x set-language-environment
show all input methods	M-x list-input-methods
enable or disable input method	C-\
set coding system for next command	C-x RET c
show all coding systems	M-x list-coding-systems
choose preferred coding system	M-x prefer-coding-system

Info

enter the Info documentation reader	C-h i
find specified function or variable in Info	C-h C-i

Moving within a node:

scroll forward	SPC
scroll reverse	DEL
beginning of node	. (dot)

Moving between nodes:

next node	n
previous node	P
move up	u
select menu item by name	m
select nth menu item by number (1-9)	n
follow cross reference (return with 1)	f
return to last node you saw	l
return to directory node	d
go to any node by name	g

Other:

run Info tutorial	h
quit Info	q
search nodes for regexp	M-s

Registers

save region in register	C-x r s
insert register contents into buffer	C-x r i
save value of point in register	C-x r SPC
jump to point saved in register	C-x r j

Keyboard Macros

start defining a keyboard macro	C-x (
end keyboard macro definition	C-x)
execute last-defined keyboard macro	C-x e
append to last keyboard macro	C-u C-x (
name last keyboard macro	M-x name-last-kbd-macro
insert Lisp definition in buffer	M-x insert-kbd-macro

Commands Dealing with Emacs Lisp

eval sexp before point	C-x C-e
eval current defun	C-M-x
eval region	M-x eval-region
read and eval minibuffer	M-:
load from standard system directory	M-x load-library

Simple Customization

customize variables and faces	M-x customize
-------------------------------	---------------

Making global key bindings in Emacs Lisp (examples):

```
(global-set-key "\C-cg" 'goto-line)
(global-set-key "\M-#" 'query-replace-regexp)
```

Writing Commands

```
(defun command-name (args)
  "documentation" (interactive "template")
  body)
```

An example:

```
(defun this-line-to-top-of-window (line)
  "Reposition line point is on to top of window.
With ARG, put point on line ARG."
  (interactive "P")
  (recenter (if (null line)
    0
    (prefix-numeric-value line))))
```

The `interactive` spec says how to read arguments interactively. Type `C-h f` `interactive` for more details.

Copyright © 1997 Free Software Foundation, Inc.
v2.2 for GNU Emacs version 20, June 1997
designed by Stephen Gildea

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.

For copies of the GNU Emacs manual, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

vi

- Modes:
 - Normal: Enter commands
 - Insert: Insert text
 - Visual: Like normal, but you can highlight
 - Replace: Like insert, but you replace characters as you type
 - Recording: Record a sequence of key sequences

vi Editor "Cheat Sheet"

Invoking vi: `vi filename`
Format of vi commands: `[count][command]` (count repeats the effect of the command)

Command mode versus input mode

Vi starts in command mode. The positioning commands operate only while vi is in command mode. You switch vi to input mode by entering any one of several vi input commands. (See next section.) Once in input mode, any character you type is taken to be text and is added to the file. You cannot execute any commands until you exit input mode. To exit input mode, press the escape (**Esc**) key.

Input commands (end with Esc)

a	Append after cursor
i	Insert before cursor
o	Open line below
O	Open line above
<code>r file</code>	Insert <i>file</i> after current line

Any of these commands leaves vi in input mode until you press **Esc**. Pressing the **RETURN** key will not take you out of input mode.

Change commands (Input mode)

cw	Change word (Esc)
cc	Change line (Esc) - blanks line
c\$	Change to end of line
rc	Replace character with <i>c</i>
R	Replace (Esc) - typeover
s	Substitute (Esc) - 1 char with string
S	Substitute (Esc) - Rest of line with text
.	Repeat last change

Changes during insert mode

<code><ctrl>h</code>	Back one character
<code><ctrl>w</code>	Back one word
<code><ctrl>u</code>	Back to beginning of insert

File management commands

<code>:w name</code>	Write edit buffer to file <i>name</i>
<code>:wq</code>	Write to file and quit
<code>:q!</code>	Quit without saving changes
<code>ZZ</code>	Same as <code>:wq</code>
<code>:sh</code>	Execute shell commands (<code><ctrl>d</code>)

Window motions

<code><ctrl>d</code>	Scroll down (half a screen)
<code><ctrl>u</code>	Scroll up (half a screen)
<code><ctrl>f</code>	Page forward
<code><ctrl>b</code>	Page backward
<code>/string</code>	Search forward
<code>?string</code>	Search backward
<code><ctrl>l</code>	Redraw screen
<code><ctrl>g</code>	Display current line number and file information
<code>n</code>	Repeat search
<code>N</code>	Repeat search reverse
<code>G</code>	Go to last line
<code>nG</code>	Go to line <i>n</i>
<code>:n</code>	Go to line <i>n</i>
<code>z<CR></code>	Reposition window: cursor at top
<code>z</code>	Reposition window: cursor in middle
<code>z-</code>	Reposition window: cursor at bottom

Cursor motions

H	Upper left corner (home)
M	Middle line
L	Lower left corner
h	Back a character
j	Down a line
k	Up a line
^	Beginning of line
\$	End of line
l	Forward a character
w	One word forward
b	Back one word
fc	Find <i>c</i>
:	Repeat find (find next <i>c</i>)

Deletion commands

<code>dd</code> or <code>n dd</code>	Delete <i>n</i> lines to general buffer
<code>dw</code>	Delete word to general buffer
<code>dww</code>	Delete <i>n</i> words
<code>d)</code>	Delete to end of sentence
<code>db</code>	Delete previous word
<code>D</code>	Delete to end of line
<code>x</code>	Delete character

Recovering deletions

<code>p</code>	Put general buffer after cursor
<code>P</code>	Put general buffer before cursor

Undo commands

<code>u</code>	Undo last change
<code>U</code>	Undo all changes on line

Rearrangement commands

<code>yy</code> or <code>Y</code>	Yank (copy) line to general buffer
<code>"r6yy</code>	Yank 6 lines to buffer <i>r</i>
<code>yw</code>	Yank word to general buffer
<code>"a9dd</code>	Delete 9 lines to buffer <i>a</i>
<code>"49dd</code>	Delete 9 lines; Append to buffer <i>a</i>
<code>"ap</code>	Put text from buffer <i>a</i> after cursor
<code>p</code>	Put general buffer after cursor
<code>P</code>	Put general buffer before cursor
<code>J</code>	Join lines

Parameters

<code>:set list</code>	Show invisible characters
<code>:set nolist</code>	Don't show invisible characters
<code>:set number</code>	Show line numbers
<code>:set nonumber</code>	Don't show line numbers
<code>:set autoindent</code>	Indent after carriage return
<code>:set noautoindent</code>	Turn off autoindent
<code>:set showmatch</code>	Show matching sets of parentheses as they are typed
<code>:set noshowmatch</code>	Turn off showmatch
<code>:set showmode</code>	Display mode on last line of screen
<code>:set noshowmode</code>	Turn off showmode
<code>:set all</code>	Show values of all possible parameters

Move text from file *old* to file *new*

<code>vi old</code>	
<code>"a10yy</code>	yank 10 lines to buffer <i>a</i>
<code>:w</code>	write work buffer
<code>:e new</code>	edit new file
<code>"ap</code>	put text from <i>a</i> after cursor
<code>:30,60w new</code>	Write lines 30 to 60 in file <i>new</i>

Regular expressions (search strings)

<code>^</code>	Matches beginning of line
<code>\$</code>	Matches end of line
<code>.</code>	Matches any single character
<code>*</code>	Matches any previous character
<code>*</code>	Matches any character

Search and replace commands

Syntax:

`:(address) s/old_text/new_text/`

Address components:

<code>.</code>	Current line
<code>n</code>	Line number <i>n</i>
<code>.+m</code>	Current line plus <i>m</i> lines
<code>\$</code>	Last line
<code>/string/</code>	A line that contains "string"
<code>%</code>	Entire file
<code>[addr1],[addr2]</code>	Specifies a range

Examples:

The following example replaces only the first occurrence of *Banana* with *Kumquat* in each of 11 lines starting with the current line (`.`) and continuing for the 10 that follow (`.+10`).

```
.,.+10s/Banana/Kumquat
```

The following example replaces every occurrence (caused by the `g` at the end of the command) of *apple* with *pear*.

```
%s/apple/pear/g
```

The following example removes the last character from every line in the file. Use it if every line in the file ends with `^M` as the result of a file transfer. Execute it when the cursor is on the first line of the file.

```
%s/. $//
```