Cursor Okta SCIM Provisioning Setup

Steps to enable SCIM provisioning from Okta to Cursor, for an existing Cursor Okta SAML application.

Step 1: Enable SCIM on the Okta app

1. Open the **General** tab of your existing Cursor Okta SAML application.
2. Under **App Settings**, click **Edit**.
3. Select the **SCIM** option under Provisioning and save.

If you don't already have an Okta application for Cursor, create a new SCIM application first.

Step 2: Configure the SCIM connection

1. Select the **Provisioning** tab.
2. Under **SCIM Connection**, click **Edit**.
3. Enter these two values:

SCIM connector base URL	`https://authenticate.cursor.sh/scim/v2.0/iCw25CoEXpCqz2mB`
Unique identifier field for users	`userName`

Under **Supported provisioning actions**, select:

- Push new users
- Push profile updates
- Push groups

Next, choose how Okta authenticates SCIM requests. Cursor supports two methods:

- **Bearer token:** a static token your identity provider sends with each request.
- **OAuth client credentials:** a client ID and secret your identity provider exchanges for a short-lived access token.

If you use a bearer token:

1. Set **Authentication Mode** to **HTTP Header**.
2. Copy the bearer token into the **Authorization** field (token is shown in the Cursor admin portal).

Authorization bearer token	`<paste token from the Cursor admin portal>`

Click **Test Connector Configuration** to validate the credentials, then click **Save**. The test must pass before you continue.

Step 3: Configure provisioning actions

1 With the **Provisioning** tab still selected, open **To App** in the left navigation.

2 In the **Provisioning to App** section, click **Edit**.

3 Enable these actions, then save:

- Create Users
- Update User Attributes
- Deactivate Users

Step 4: Assign people

1 In the top navigation, select the **Assignments** tab.

2 Click **Assign**, then **Assign to People**.

3 Find each person who needs access and click **Assign** next to them.

4 Click **Save and Go Back**.

Step 5: Push groups

1 In the top navigation, select the **Push Groups** tab.

2 Click **Push Groups**, then **Find groups by name**.

3 Select the appropriate group and click **Save** to push it to Cursor.

> **Caution:** Okta advises using separate groups for push groups and group assignments. Otherwise, membership changes are not reflected without manual group pushes.

If SSO users were provisioned before SCIM was enabled, provision them again: open the **Assignments** tab and click **Provision User**. This starts a job that re-provisions all users.