

**SEMESTER 2
2024-2025**

**CS605
The Mathematics and Theory of Computer Science**

Asst. Prof. G. Di Liberto, Assoc. Prof. A. Mooney, Prof. T. Naughton

Time allowed: 3 hours

Answer all **seven** questions

All questions carry equal marks

Instructions

	Yes	No	N/A
Formulae and Tables book allowed (<i>i.e. available on request</i>)		X	
Formulae and Tables book required (<i>i.e. distributed prior to exam commencing</i>)		X	
Statistics Tables and Formulae allowed (<i>i.e. available on request</i>)		X	
Statistics Tables and Formulae required (<i>i.e. distributed prior to exam commencing</i>)		X	
Dictionary allowed (<i>supplied by the student</i>)		X	
Non-programmable calculator allowed		X	
Students required to write in and return the exam question paper	X		
One physical (paper) copy of textbook Michael Sipser, Introduction to the Theory of Computation, without annotations or extra pages (supplied by the student)	X		
Students required to sign the declaration page at the end of this document	X		

Only the answers on this exam question paper will be marked – rough work on extra pages will not be marked. If your answer requires more space than the exam question paper allows, at the bottom of your answer in the exam question paper, specify the page number(s) in your answer booklet where your answer continues.

Write your name, student number, and desk number below.

Name Student no..... Desk no.....

[10 marks]

- 1** (a) Prove that the following language is not regular.

$L1A = \{0^m + 0^n = 0^p : m, n \geq 0, p = m + n\}$ e.g. an example word in the language is $00+0=000$

[4 marks]

- (b) Prove that the following language is not context-free.

(b) $L1B = \{wx0^m1^n : w \in \{0, 1\}^*, m, n \geq 0, w \text{ contains } m \text{ zeros and } n \text{ ones}\}$ [6 marks]
e.g. an example word in the language is 1001011#0001111

You must use this exam question sheet for your proofs.

Proofs

This image shows a full page of dot grid paper. The background is white, and it is covered with a regular pattern of small, black dots. The dots are arranged in straight horizontal and vertical lines, creating a grid-like appearance. There are no margins, text, or other markings on the page.

Page in answer booklet where this answer continues: _____

[10 marks]

- 2 (a)** Prove that the following language is decidable.

L2A is the language of finite automata that accept word 011 as well as possibly accepting other words. It is defined formally as $\text{L2A} = \{ \langle M \rangle : M \text{ is a finite automaton with input alphabet } \{0, 1\} \text{ and } 011 \in \mathcal{L}(M) \}$. [5 marks]

- (b) Prove that the following language is Turing-recognisable.

L2B = { $\langle J, a, b \rangle$: J is a Java program, a and b are integer variables declared in J , and when J is run, both a and b have value zero at the same time at least once}

You must use this exam question sheet for your proofs.

Proof

This image shows a full page of dot grid paper. The background is white, and it is covered with a regular pattern of small, dark grey dots. The dots are arranged in straight horizontal and vertical lines, creating a grid-like appearance. There are no margins, text, or other markings on the page.

Page in answer booklet where this answer continues: _____

[10 marks]

- 3** Prove that the problem associated with language L3 defined below is undecidable. You are given that $\text{HALT} = \{ \langle M, w \rangle : M \text{ is a Turing machine and } M \text{ halts on } w \}$ is undecidable. Use the template provided to perform a mapping reduction. You must give your answer on this exam question sheet.

The language L_3 is defined as

L3 = { $\langle J, g \rangle$: J is a Java program and g is an integer and while running, J uses a maximum of g gigabytes (10^9 bytes) of memory}.

Note, in the template below, some blanks have a small subscript number. Blanks with the same subscript number must have the same value. Blank N = "... " is worth 10 marks, and each other blank scores -1 if incorrect.

Proof

Optional: The complement $\overline{L3} =$

We will use a mapping reduction to prove the reduction

.....M.....

Assume that₁ is decidable.

The transition function f that maps instances of to instances of

. is given by TM F given by the following pseudocode.

$F = \text{"On input } \langle \dots \rangle_2 \text{:"}$

1. Construct the following N given by the following pseudocode.

$N = "$

2. Output <.3>."

Now, $\langle \dots . _3 \rangle$ is an element of \dots iff $\langle \dots . _2 \rangle$
is an element of \dots .

So, using f and the assumption that₁ is decidable, we can decide

..... A contradiction.

Therefore, $\{ \langle M, w \rangle \mid M \text{ accepts } w \}$ is undecidable. (Also, the complement of $\{ \langle M, w \rangle \mid M \text{ accepts } w \}$ is undecidable; the complement of an undecidable language is undecidable.)

[10 marks]

- 4** In the case of L_3 defined earlier, and its complement $\overline{L_3}$, prove whether each language is Turing-recognisable or not Turing-recognisable.

You can refer to your previous proof that L3 is undecidable in your answer. Note, you are not told whether L3 is Turing-recognisable or not. You must give your answer on this exam question sheet.

Proof

[illegible]

Page in answer booklet where this answer continues: _____

[10 marks]

5 Prove that the problem associated with language L5 defined below is undecidable. You are given that $HALT = \{ \langle M, w \rangle : M \text{ is a Turing machine and } M \text{ halts on } w \}$ is undecidable. Use the template provided to perform a mapping reduction. You must give your answer on this exam question sheet.

The language L5 is defined as
 $L5 = \{ \langle J \rangle : J \text{ is a Java program that tries to write something to disk} \}$.

Note, in the template below, some blanks have a small subscript number. Blanks with the same subscript number must have the same value. Blank $N = \dots$ is worth 10 marks, and each other blank scores -1 if incorrect.

Proof

Optional: The complement $\overline{L5} = \dots$

We will use a mapping reduction to prove the reduction

. \leq

Assume that₁ is decidable.

The transition function f that maps instances of to instances of

. is given by TM F given by the following pseudocode.

$F =$ "On input $\langle \dots \rangle$:"

1. Construct the following N given by the following pseudocode.

$N = \dots$
.
.
.
.
.
.

2. Output $\langle \dots \rangle$."

Now, $\langle \dots \rangle$ is an element of iff $\langle \dots \rangle$ is an element of

So, using f and the assumption that₁ is decidable, we can decide A contradiction.

Therefore,₁ is undecidable. (Also, the complement of₁ is undecidable; the complement of an undecidable language is undecidable.)

[10 marks]

6 Prove that each of these problems is in \mathcal{NP} . You must use this exam question sheet for your proofs.

- (a) $L6A = \{ \langle G, k \rangle : G = (V, E) \text{ is an undirected graph of vertices } V \text{ and edges } E \text{ and there exists a subset of vertices } S \subseteq V \text{ of size } |S| = k \text{ such that every edge in } E \text{ touches one of the vertices in } S \}$ [5 marks]
- (b) $L6B = \{ \langle A \rangle : A = \{x_1, \dots, x_m\} \text{ is a set of natural numbers and there exists a subset } Q \subseteq A \text{ where the sum of the elements in } Q \text{ is exactly a quarter of the sum of the elements in } A \}$ [5 marks]

Proofs

[illegible]

Page in answer booklet where this answer continues:

[10 marks]

[7 marks]

- 7 (a) Use a reduction to prove that the language L6A defined previously is \mathcal{NP} -complete. You are given that 3-SAT is \mathcal{NP} -complete. Refer to your proof that L6A is in \mathcal{NP} in your answer. You must give your answer on this exam question sheet.

- (b) Give an example of the output of your reduction for the input $C = (a \vee \bar{b} \vee \bar{d}) \wedge (\bar{b} \vee c \vee d) \wedge (a \vee d \vee \bar{e}) \wedge (\bar{b} \vee c \vee \bar{e}) \in 3\text{-SAT}$. [3 marks]

Proof

This image shows a full page of dot grid paper. The background is white, and it is covered with a regular pattern of small, dark grey dots. The dots are arranged in straight horizontal and vertical lines, creating a grid-like appearance. There are no margins, text, or other markings on the page.

Page in answer booklet where this answer continues:



OLLSCOIL NA hÉIREANN MÁ NUAD

THE NATIONAL UNIVERSITY OF IRELAND MAYNOOTH

SUMMER 2025 EXAMINATION

CS605

The Mathematics and Theory of Computer Science

Asst. Prof. G. Di Liberto, Assoc. Prof. A. Mooney, Prof. T. Naughton

Declaration

To be signed by each student and returned with their exam paper at the end of the examination

- i. I have searched through my copy of M. Sipser, *Introduction to the Theory of Computation*, any edition, (the Sipser book) and it does not contain any extra pages or annotations (except for annotations that correct minor typographical errors).
- ii. I understand that by failing to notify an invigilator of any annotations or extra pages in my copies of the Sipser book, I will receive a mark of zero in this examination. This does not affect any further disciplinary actions that the University may wish to take.
- iii. I understand also that directly copying large amounts of material from the Sipser books without substantially tailoring it to the question asked will not gain any marks for that question.

Name (capital letters) _____

Student number _____ Desk number _____

Signature _____ Date _____