

Docker CIS Compliance Report

Generated on 2026-04-29 12:46:15

Compliance Score	67%
Checks Passed	10 / 15
Status	PASS: 10 FAIL: 5 WARN: 0 N/A: 5
Failures by Severity	HIGH: 2 MEDIUM: 3

Host Configuration (0/2 passed)

Control	Severity	Status	Description	Details
1.2.1	HIGH	ERROR	Ensure auditing is configured for the Do...	Command '['auditpol', '/get', '/category:Detailed ...
1.1.2	HIGH	MANUAL_REVIEW	Ensure only trusted users are allowed to...	Users in docker group: HP

Daemon Configuration (1/4 passed)

Control	Severity	Status	Description	Details
2.4	HIGH	FAIL	Ensure insecure registries are not used	Insecure registries configured: ::1/128
Daemon_Status	CRITICAL	PASS	Ensure Docker daemon is running	Docker daemon is active and reachable
2.11	MEDIUM	FAIL	Ensure centralized and remote logging is...	Current logging driver: json-file
2.6	CRITICAL	MANUAL_REVIEW	Ensure TLS authentication for Docker dae...	TLS flags not in process args. Check daemon.json m...

Remediation for 2.4:
Remove insecure registries from /etc/docker/daemon.json:
Remove the "insecure-registries" key or set it to an empty list:
{"insecure-registries": []}
Then restart Docker: sudo systemctl restart docker
Ref: CIS Docker Benchmark v1.6.0, Section 2.4

Remediation for 2.11:

Configure a remote logging driver in /etc/docker/daemon.json:
{"log-driver": "syslog", "log-opts": {"syslog-address": "tcp://your-log-server:514"}}
Other options: splunk, gelf, fluentd, awslogs
Then restart Docker: sudo systemctl restart docker
Ref: CIS Docker Benchmark v1.6.0, Section 2.11

Socket Configuration (0/4 passed)

Control	Severity	Status	Description	Details
3.15	HIGH	N/A	Ensure that the Docker socket file owner...	Socket not found
3.16	HIGH	N/A	Ensure that the Docker socket file permi...	Socket not found
3.3	MEDIUM	N/A	Ensure that docker.socket file ownership...	File not found
3.4	MEDIUM	N/A	Ensure that docker.socket file permissio...	File not found

Container Runtime (7/7 passed)

Control	Severity	Status	Description	Details
5.32	CRITICAL	PASS	Ensure that the Docker socket is not mou...	No running containers
5.10	CRITICAL	PASS	Ensure that the host's network namespace...	No running containers
5.11	HIGH	PASS	Ensure that the memory usage for contain...	No running containers
5.5	CRITICAL	PASS	Ensure that privileged containers are no...	No running containers
4.1	HIGH	PASS	Ensure that a user for the container has...	No running containers
5.13	MEDIUM	PASS	Ensure that the container's root filesys...	No running containers
5.6	CRITICAL	PASS	Ensure sensitive host system directories...	No running containers

Image Security (2/6 passed)

Control	Severity	Status	Description	Details
IMG-03	HIGH	FAIL	Ensure Content Trust for Docker is enabl...	DOCKER_CONTENT_TRUST is not set. Image pulls are
IMG-04	LOW	PASS	Ensure there are no dangling images	No dangling images found.
IMG-05	LOW	PASS	Ensure Docker images are not excessively...	All images are under 1.00 GB.
IMG-01	MEDIUM	FAIL	Ensure images are not tagged with 'lates...	Images using latest/untagged: project-3_team_34-se...
IMG-02	MEDIUM	FAIL	Ensure Docker images are not outdated	Stale images (>90d): alpine:latest (91d old)

Control	Severity	Status	Description	Details
IMG-06	CRITICAL	N/A	Ensure Docker images are scanned for vul...	Scanner execution failed for 'project-3_team_34-se...

Remediation for IMG-03:
Enable Docker Content Trust:
export DOCKER_CONTENT_TRUST=1
To make it permanent, add to your shell profile (~/.bashrc or ~/.profile):
echo 'export DOCKER_CONTENT_TRUST=1' >> ~/.bashrc
Windows PowerShell:
[System.Environment]::SetEnvironmentVariable('DOCKER_CONTENT_TRUST','1','User')
Ref: CIS Docker Benchmark v1.6.0, Section 4.5

Remediation for IMG-01:
Always use specific version tags instead of :latest:
docker pull nginx:1.25.3 (instead of docker pull nginx:latest)
In Dockerfile:
FROM python:3.12-slim (instead of FROM python:latest)
Re-tag existing images:
docker tag myapp:latest myapp:1.0.0
Ref: CIS Docker Benchmark v1.6.0, Section 4.7

Remediation for IMG-02:
Rebuild images from updated base images regularly:
docker pull :
docker build --no-cache -t myapp:latest .
Set up a CI/CD pipeline to rebuild images on a schedule (e.g., weekly).
Ref: Docker Security Best Practices – Image Freshness