

Docker CIS Compliance Report

Generated on 2026-05-12 11:00:30

Compliance Score	65%
Checks Passed	72 / 111
Status	PASS: 72 FAIL: 39 PARTIAL_COMPLIANCE: 2 N/A: 14
Failures by Severity	CRITICAL: 4 HIGH: 17 MEDIUM: 4 LOW: 14

How to Read This Report

This report checks your Docker setup against CIS security best practices. Higher compliance means lower security risk.

- **Compliance %:** Percentage of checks currently passing.
- **Failures by Severity:** Shows which failed checks are most urgent.
- **Section Tables:** Lists exact controls, findings, and remediation steps.

Status Legend	
PASS	Control meets expected security requirement.
FAIL	Control is not compliant and should be fixed.
PARTIAL_COMPLIANCE	Partly compliant; more hardening is needed.
N/A	Check does not apply in this environment.
MANUAL_REVIEW	Needs human verification.

Severity Legend	
CRITICAL	High probability of serious compromise impact.
HIGH	Serious exposure to prioritize quickly.
MEDIUM	Important hardening issue to schedule soon.
LOW	Lower risk improvement item.

INFO	Informational context, usually low risk.
------	--

References

1. CIS Docker Benchmark: <https://www.cisecurity.org/benchmark/docker>
2. Docker Engine Security Documentation: <https://docs.docker.com/engine/security/>
3. OWASP Docker Top 10: <https://owasp.org/www-project-docker-top-10/>

Host Configuration (0/2 passed)

Control	Severity	Status	Description	Details
1.2.1	HIGH	FAIL	Ensure auditing is configured for the Docker daemon	No audit rules found for /usr/bin/dockerd.
1.1.2	HIGH	MANUAL_REVIEW	Ensure only trusted users are allowed to control Docker daemon	Users in docker group: purva-dobariya

Remediation for 1.2.1:

Linux: Add audit rules for Docker daemon:

```
sudo auditctl -w /usr/bin/dockerd -k docker
```

```
sudo auditctl -w /etc/docker -k docker
```

Windows: Enable Detailed Tracking via:

```
auditpol /set /category:"Detailed Tracking" /success:enable /failure:enable
```

Ref: CIS Docker Benchmark v1.6.0, Section 1.2.1

Daemon Configuration (2/4 passed)

Control	Severity	Status	Description	Details
2.4	HIGH	FAIL	Ensure insecure registries are not used	Insecure registries configured: ::1/128
Daemon_Status	CRITICAL	PASS	Ensure Docker daemon is running	Docker service is active
2.11	MEDIUM	PASS	Ensure centralized and remote logging is configured	Current logging driver: syslog
2.6	CRITICAL	MANUAL_REVIEW	Ensure TLS authentication for Docker daemon is configured	TLS flags not in process args. Check daemon.json manually.

Remediation for 2.4:

Remove insecure registries from /etc/docker/daemon.json:

Remove the "insecure-registries" key or set it to an empty list:

```
{"insecure-registries": []}
```

Then restart Docker: `sudo systemctl restart docker`

Ref: CIS Docker Benchmark v1.6.0, Section 2.4

Socket Configuration (4/4 passed)

Control	Severity	Status	Description	Details
3.15	HIGH	PASS	Ensure that the Docker socket file ownership is set to root:docker	Owner: root, Group: docker
3.16	HIGH	PASS	Ensure that the Docker socket file permissions are set to 660 or more restrictively	Permissions: 660
3.3	MEDIUM	PASS	Ensure that docker.socket file ownership is set to root:root	Owner: root, Group: root
3.4	MEDIUM	PASS	Ensure that docker.socket file permissions are set to 644 or more restrictive	Permissions: 644

Container Runtime (0/7 passed)

Control	Severity	Status	Description	Details
5.32	CRITICAL	FAIL	Ensure that the Docker socket is not mounted inside any containers	Containers mounting docker.sock: cis_test_vulnerable
5.10	CRITICAL	FAIL	Ensure that the host's network namespace is not shared	Containers using host network: cis_test_vulnerable
5.11	HIGH	FAIL	Ensure that the memory usage for containers is limited	Containers without memory limits: cis_test_vulnerable
5.5	CRITICAL	FAIL	Ensure that privileged containers are not used	Privileged containers: cis_test_vulnerable
4.1	HIGH	FAIL	Ensure that a user for the container has been created (Non-root)	Running as root: cis_test_vulnerable
5.13	MEDIUM	FAIL	Ensure that the container's root filesystem is mounted as read only	Containers with writable rootfs: cis_test_vulnerable
5.6	CRITICAL	FAIL	Ensure sensitive host system directories are not mounted	Violations: {'cis_test_vulnerable': ['/']}

Remediation for 5.32:

Do NOT mount the Docker socket inside containers:

Remove `-v /var/run/docker.sock:/var/run/docker.sock` from your `docker run` command.

If you need Docker API access, use a restricted proxy like `docker-socket-proxy`:

```
docker run -v /var/run/docker.sock:/var/run/docker.sock tecnativa/docker-socket-proxy
```

Ref: CIS Docker Benchmark v1.6.0, Section 5.32

Remediation for 5.10:

Do NOT use `--network=host`. Use bridge (default) or custom networks:

```
docker run --network=bridge
```

Or create a custom network:

```
docker network create mynet
```

```
docker run --network=mynet
```

Ref: CIS Docker Benchmark v1.6.0, Section 5.10

Remediation for 5.11:

Set memory limits when running containers:
docker run --memory=512m --memory-swap=1g
In docker-compose.yml:
deploy:
resources:
limits:
memory: 512M
Ref: CIS Docker Benchmark v1.6.0, Section 5.11

Remediation for 5.5:

Do NOT use the --privileged flag. Instead, grant only specific capabilities:
docker run --cap-drop ALL --cap-add NET_BIND_SERVICE
If a container currently uses --privileged, re-create it without that flag:
docker stop && docker rm
docker run --cap-drop ALL --cap-add
Ref: CIS Docker Benchmark v1.6.0, Section 5.5

Remediation for 4.1:

Always specify a non-root user in your Dockerfile:
RUN useradd -r appuser
USER appuser
Or pass --user at runtime:
docker run --user 1000:1000
Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for 5.13:

Run containers with a read-only root filesystem:
docker run --read-only
Use tmpfs for writable directories:
docker run --read-only --tmpfs /tmp --tmpfs /run
Ref: CIS Docker Benchmark v1.6.0, Section 5.13

Remediation for 5.6:

Do NOT mount sensitive host directories. Remove volume mounts for:
/, /boot, /dev, /etc, /lib, /proc, /sys, /usr
Use named volumes instead of host bind mounts:
docker volume create app-data
docker run -v app-data:/app/data
Ref: CIS Docker Benchmark v1.6.0, Section 5.6

Image Security (1/6 passed)

Control	Severity	Status	Description	Details
IMG-03	HIGH	FAIL	Ensure Content Trust for Docker is enabled	DOCKER_CONTENT_TRUST is not set. Image pulls are not signature-verified.
IMG-04	LOW	PARTIAL COMPLIANCE	Ensure there are no dangling images	2 dangling image(s) found. Run 'docker image prune' to clean up.
IMG-05	LOW	PASS	Ensure Docker images are not excessively large	All images are under 1.00 GB.

Control	Severity	Status	Description	Details
IMG-01	MEDIUM	FAIL	Ensure images are not tagged with 'latest'	Images using latest/untagged: test_env_secure-app:latest, test_env_vulnerable-app:latest, personal-fi nance-management-system_service:latest, postgres:latest, secure-nginx:latest, nginx:latest, libretranslate/libretranslate:latest, hello-world:latest
IMG-02	MEDIUM	FAIL	Ensure Docker images are not outdated	Stale images (>90d): adoptopenjdk:15_36-jdk-hotspot (2029d old), alpine:3.15 (893d old), alpine:3.19.1 (836d old)
IMG-06	CRITICAL	N/A	Ensure Docker images are scanned for vulnerabilities	Scanner execution failed for 'test_env_secure-app:latest'. Ensure Docker Scout or Trivy is properly configured.

Remediation for IMG-03:

Enable Docker Content Trust:
`export DOCKER_CONTENT_TRUST=1`
 To make it permanent, add to your shell profile (~/.bashrc or ~/.profile):
`echo 'export DOCKER_CONTENT_TRUST=1' >> ~/.bashrc`
 Windows PowerShell:
`[System.Environment]::SetEnvironmentVariable('DOCKER_CONTENT_TRUST','1','User')`
Ref: CIS Docker Benchmark v1.6.0, Section 4.5

Remediation for IMG-04:

Remove dangling (untagged) images to reclaim disk space:
`docker image prune -f`
 To also remove unused images (not just dangling):
`docker image prune -a -f`
 Automate cleanup in CI/CD pipelines after builds.
Ref: Docker Security Best Practices – Image Hygiene

Remediation for IMG-01:

Always use specific version tags instead of :latest:
`docker pull nginx:1.25.3` (instead of `docker pull nginx:latest`)
 In Dockerfile:
`FROM python:3.12-slim` (instead of `FROM python:latest`)
 Re-tag existing images:
`docker tag myapp:latest myapp:1.0.0`
Ref: CIS Docker Benchmark v1.6.0, Section 4.7

Remediation for IMG-02:

Rebuild images from updated base images regularly:
`docker pull :`
`docker build --no-cache -t myapp:latest .`
 Set up a CI/CD pipeline to rebuild images on a schedule (e.g., weekly).
Ref: Docker Security Best Practices – Image Freshness

Dockerfile Security (65/104 passed)

Control	Severity	Status	Description	Details
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 05455a08881e] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 05455a08881e] No apt-get install commands found.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 05455a08881e] No EXPOSE instructions found.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 05455a08881e] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 05455a08881e] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 05455a08881e] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 05455a08881e] No ENV instructions found.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 05455a08881e] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 6748144caf4e] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 6748144caf4e] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 6748144caf4e] Port 22 is not exposed.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 6748144caf4e] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 6748144caf4e] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 6748144caf4e] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 6748144caf4e] No secrets found in ENV instructions.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 6748144caf4e] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 0e8c3f2c9417] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 0e8c3f2c9417] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 0e8c3f2c9417] Port 22 is not exposed.

Control	Severity	Status	Description	Details
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 0e8c3f2c9417] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 0e8c3f2c9417] No HEALTHCHECK instruction found.
DL-02	HIGH	PASS	Ensure a non-root USER is specified	[Image 0e8c3f2c9417] Non-root USER 'libretranslate' is set (line 15).
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 0e8c3f2c9417] No secrets found in ENV instructions.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 0e8c3f2c9417] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image ec3d8ae15632] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image ec3d8ae15632] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image ec3d8ae15632] No EXPOSE instructions found.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image ec3d8ae15632] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image ec3d8ae15632] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image ec3d8ae15632] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image ec3d8ae15632] No ENV instructions found.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image ec3d8ae15632] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 9d4191e5a8c7] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 9d4191e5a8c7] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 9d4191e5a8c7] Port 22 is not exposed.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 9d4191e5a8c7] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 9d4191e5a8c7] No HEALTHCHECK instruction found.

Control	Severity	Status	Description	Details
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 9d4191e5a8c7] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 9d4191e5a8c7] No secrets found in ENV instructions.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 9d4191e5a8c7] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 413d57cb67bb] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 413d57cb67bb] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 413d57cb67bb] Port 22 is not exposed.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 413d57cb67bb] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 413d57cb67bb] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 413d57cb67bb] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 413d57cb67bb] No secrets found in ENV instructions.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 413d57cb67bb] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image fd0774e0b6ea] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image fd0774e0b6ea] No apt-get install commands found.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image fd0774e0b6ea] No EXPOSE instructions found.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image fd0774e0b6ea] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image fd0774e0b6ea] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image fd0774e0b6ea] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image fd0774e0b6ea] No ENV instructions found.

Control	Severity	Status	Description	Details
DL-07	MEDIUM	PARTIAL_COMPLIANCE	Ensure update instructions are not used alone	[Image fd0774e0b6ea] Isolated update commands found: Line 5: apk update used without add/upgrade
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 99133eed2307] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 99133eed2307] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 99133eed2307] Port 22 is not exposed.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 99133eed2307] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 99133eed2307] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 99133eed2307] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 99133eed2307] No secrets found in ENV instructions.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 99133eed2307] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 237a3a6754ac] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 237a3a6754ac] No apt-get install commands found.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 237a3a6754ac] No EXPOSE instructions found.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 237a3a6754ac] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 237a3a6754ac] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 237a3a6754ac] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 237a3a6754ac] No ENV instructions found.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 237a3a6754ac] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 32b91e3161c8] No ADD instructions found. COPY is used correctly.

Control	Severity	Status	Description	Details
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 32b91e3161c8] No apt-get install commands found.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 32b91e3161c8] No EXPOSE instructions found.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 32b91e3161c8] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 32b91e3161c8] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 32b91e3161c8] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 32b91e3161c8] No ENV instructions found.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 32b91e3161c8] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image f8203f79caac] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image f8203f79caac] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image f8203f79caac] No EXPOSE instructions found.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image f8203f79caac] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image f8203f79caac] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image f8203f79caac] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image f8203f79caac] No ENV instructions found.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image f8203f79caac] No isolated update instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 1b44b5a3e06a] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 1b44b5a3e06a] No RUN instructions found.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 1b44b5a3e06a] No EXPOSE instructions found.

Control	Severity	Status	Description	Details
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 1b44b5a3e06a] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 1b44b5a3e06a] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 1b44b5a3e06a] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 1b44b5a3e06a] No ENV instructions found.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 1b44b5a3e06a] No RUN instructions found.
DL-03	LOW	PASS	Ensure ADD is not used for remote URLs	[Image 8e7905b2227d] No ADD instructions found. COPY is used correctly.
DL-05	LOW	PASS	Ensure apt-get uses --no-install-recommends	[Image 8e7905b2227d] All apt-get install commands use --no-install-recommends.
DL-04	HIGH	PASS	Ensure SSH port 22 is not exposed	[Image 8e7905b2227d] Port 22 is not exposed.
DL-01	MEDIUM	N/A	Ensure FROM does not use :latest tag	[Image 8e7905b2227d] FROM instructions are not preserved in image history. See Image Security checks (IMG-01) for tag validation.
DL-06	LOW	FAIL	Ensure HEALTHCHECK instructions have been added to container images	[Image 8e7905b2227d] No HEALTHCHECK instruction found.
DL-02	HIGH	FAIL	Ensure a non-root USER is specified	[Image 8e7905b2227d] No USER instruction found. Container will run as root by default.
DL-08	CRITICAL	PASS	Ensure secrets are not stored in Dockerfile ENV instructions	[Image 8e7905b2227d] No secrets found in ENV instructions.
DL-07	MEDIUM	PASS	Ensure update instructions are not used alone	[Image 8e7905b2227d] No isolated update instructions found.

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
  CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
  CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:
HEALTHCHECK --interval=5m --timeout=3s \\
CMD curl -f http://localhost/ || exit 1

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:
HEALTHCHECK --interval=5m --timeout=3s \\
CMD curl -f http://localhost/ || exit 1

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:
HEALTHCHECK --interval=5m --timeout=3s \\
CMD curl -f http://localhost/ || exit 1

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:
HEALTHCHECK --interval=5m --timeout=3s \\
CMD curl -f http://localhost/ || exit 1

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:
HEALTHCHECK --interval=5m --timeout=3s \\
CMD curl -f http://localhost/ || exit 1

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-07:

Combine apt-get update and apt-get install into a single RUN instruction:
RUN apt-get update && apt-get install -y

Ref: CIS Docker Benchmark v1.6.0, Section 4.7

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1

Remediation for DL-06:

Add a HEALTHCHECK instruction to your Dockerfile:

```
HEALTHCHECK --interval=5m --timeout=3s \
CMD curl -f http://localhost/ || exit 1
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.6

Remediation for DL-02:

Add a USER instruction to your Dockerfile to run as a non-root user:

```
RUN groupadd -r appuser && useradd -r -g appuser appuser
```

```
USER appuser
```

Ref: CIS Docker Benchmark v1.6.0, Section 4.1