

Abstract

cloud native, need for resiliency, service meshes as solution, demo, pros of istio – resiliency and fault injection

Evaluation and Discussion

- demo works, tests, screenshots/results
- comparison to k8s only

Kubernetes has only round robin load balancing. Istio with the help of destinations rules extends native kubernetes load balancing and presents the following types: random, round robin, weighted least request, ring hash (#istio). In such a case istio can give any microservice replica set it's own load balancer. To show how istio load balancing can be configured, we need first to learn about routing mechanism provided by istio.

Istio routing mechanism

This solution can be used to make canary deployments and also make user experience more resilient - “user resilience”. For example, new version of service can be made available only to one group of users (test group). It can be as much as only 1% of of the hole traffic. Users can be filtered by headers in http request. If something goes wrong with new version of service it is very easy to rollback and switch all the traffic back to production version.

This mechanism allows also to do blue/green deployments.

```
$ make deploy-app-default
```

```
$ make deploy-istio-default
```

```
$ make health
```

```
curl http://192.168.99.113:31221/status
CPanel v1 : Online
curl http://192.168.99.113:31221/cameras/1/state
{"streaming":false,"cycle":88,"fps":0,"section":"1","destination":"http://collector.default.svc.cluster.local:8080","event":"exit"}
curl http://192.168.99.113:31221/cameras/2/state
{"streaming":false,"cycle":92,"fps":0,"section":"1","destination":"http://collector.default.svc.cluster.local:8080","event":"entry"}
curl http://192.168.99.113:31221/collector/status
Collector v1 : Online
curl http://192.168.99.113:31221/alerts/status
Alerts v1 : Online
curl http://192.168.99.113:31221/sections/1/status
Section 1 v1 : Online
```

```
$ make start-cameras
```


```
$ make health
```

```
curl http://192.168.99.113:31221/status
CPanel v1 : Online
curl http://192.168.99.113:31221/cameras/1/state
{"streaming":true,"cycle":7,"fps":0,"section":"1","destination":"http://collector.default.svc.c
luster.local:8080","event":"exit"}
curl http://192.168.99.113:31221/cameras/2/state
{"streaming":true,"cycle":5,"fps":0,"section":"1","destination":"http://collector.default.svc.c
luster.local:8080","event":"entry"}
curl http://192.168.99.113:31221/collector/status
Collector v1 : Online
curl http://192.168.99.113:31221/alerts/status
Alerts v1 : Online
curl http://192.168.99.113:31221/sections/1/status
Section 1 v1 : Online
```

```
curl http://192.168.99.113:31221/status
```

```
CPanel v1 : Online
```

```
curl http://192.168.99.113:31221/cameras/1/state
{"streaming":true,"cycle":7,"fps":0,"section":"1","destination":"http://
collector.default.svc.cluster.local:8080","event":"exit"}
curl http://192.168.99.113:31221/cameras/2/state
{"streaming":true,"cycle":5,"fps":0,"section":"1","destination":"http://
collector.default.svc.cluster.local:8080","event":"entry"}
curl http://192.168.99.113:31221/collector/status
Collector v1 : Online
curl http://192.168.99.113:31221/alerts/status
Alerts v1 : Online
curl http://192.168.99.113:31221/sections/1/status
Section 1 v1 : Online
```



Dashboard V1

Section 1

timestamp: 2020-02-25T14:35:38.204522Z

gender: male | age: 38-43 | event: exit

Alert


timestamp: 2020-02-25T14:35:27.224857Z

section: 1

event: entry

name: **PersonX**

Default app with cpanel v1 without load:




\$ make load

for i in {1..100}; do sleep 0.2; curl http://192.168.99.113:31221/status; printf "\n"; done

CPanel v1 : Online

CPanel v1 : Online

CPanel v1 : Online



\$ make cpanel-50-50

./kubectl apply -f istio/virt_svc_50-50.yaml

virtualservice.networking.istio.io/cpanel configured

check configuration

\$ k get virtualservices cpanel -o yaml

route:

- destination:

host: cpanel.default.svc.cluster.local

port:

number: 8080

subset: v1


weight: 50

- destination:


host: cpanel.default.svc.cluster.local

port:
 number: 8080
 subset: v2
 weight: 50

\$ make start-cameras



\$ make load
 for i in {1..100}; do sleep 0.2; curl http://192.168.99.113:31221/status; printf "\n"; done
 CPanel v1 : Online
 CPanel v1 : Online
 CPanel v1 : Online
 CPanel v2 : Online
 CPanel v2 : Online
 CPanel v2 : Online



\$ make cpanel-v2
 ./kubectl apply -f istio/virt_svc_v2.yaml
 virtualservice.networking.istio.io/cpanel configured

check configuration

```
$ k get virtualservices cpanel -o yaml
```

route:

- destination:

host: cpanel.default.svc.cluster.local

port:

number: 8080

subset: v1

weight: 0

- destination:

host: cpanel.default.svc.cluster.local


port:

number: 8080

subset: v2

weight: 100

```
$ make start-cameras
```



Dashboard V2

Section 1



timestamp: 2020-02-25T15:27:21.900453Z

gender: male | age: 25-32 | event: entry

gender: male | age: 25-32 | event: entry

Alert



timestamp: 2020-02-25T15:26:55.022111Z

section: 1

event: exit

name: **George W**

```
$ make load
```


```
for i in {1..100}; do sleep 0.2; curl http://192.168.99.113:31221/status; printf "\n"; done
```

CPanel v2 : Online

CPanel v2 : Online

CPanel v2 : Online

CPanel v2 : Online



Load balancing

Default round robin between v1 and v2 cpanel (should be 1:3)

```
$ make scale_v2_x3
```

```
kubectl scale deployment cpanel-v2 --replicas=3
```

```
collector-deploy-558dd7dd45-8rlwq      2/2   Running   3      9h
cpanel-v1-8446d9dd45-wx6mz             2/2   Running   2      9h
cpanel-v2-8445ff5964-lgj84             1/2   Running   0      6s
cpanel-v2-8445ff5964-qdhk8             0/2   Running   0      6s
cpanel-v2-8445ff5964-r4r2d             2/2   Running   3      9h
face-recognition-deploy-7b954c454-fdphg 2/2   Running   3      9h
```

Here we can see how kubernetes scales our service.

```
$ make load_balancing
```

```
./kubectl apply -f istio/round_robin.yaml
```

route:

- destination:

host: cpanel.default.svc.cluster.local

port:

number: 8080

```
$ make load
```

```
for i in {1..100}; do sleep 0.2; curl http://192.168.99.113:31221/status; printf "\n"; done
```

CPanel v2 : Online

CPanel v2 : Online

CPanel v2 : Online

CPanel v2 : Online

CPanel v2 : Online

CPanel v1 : Online

CPanel v2 : Online

CPanel v1 : Online

```
$ make random
```

```
./kubectl apply -f istio/random_lb.yaml
destinationrule.networking.istio.io/cpanel configured
$ k get destinationrules cpanel -o yaml
```

```
$ make load
for i in {1..100}; do sleep 0.2; curl http://192.168.99.113:31221/status; printf "\n"; done
CPanel v2 : Online
CPanel v2 : Online
CPanel v1 : Online
CPanel v2 : Online
CPanel v1 : Online
CPanel v2 : Online
CPanel v1 : Online
CPanel v2 : Online
```

```
$ make all-reset
./kubectl delete service --all
```