

附录四、常见问题解答

Github无法访问的解决办法

1. 每日更新 [hosts · 若风/github-hosts - 码云 - 开源中国\(gitee.com\)](#).
2. 安装everything: [下载 - voidtools](#)
3. 在everything里面搜索 `etc\hosts`, 右键打开文件路径。
4. `ctrl+拖动` 复制该文件到桌面, 编辑并修改hosts文件 (记事本)

```
185.199.109.154 github.githubassets.com
140.82.112.22 central.github.com
185.199.111.133 desktop.githubusercontent.com
185.199.109.153 assets-cdn.github.com
185.199.108.133 camo.githubusercontent.com
185.199.108.133 github.map.fastly.net
146.75.37.194 github.global.ssl.fastly.net
140.82.114.3 gist.github.com
185.199.110.153 github.io
140.82.114.3 github.com
140.82.113.6 api.github.com
185.199.111.133 raw.githubusercontent.com
185.199.108.133 user-images.githubusercontent.com
185.199.108.133 favicons.githubusercontent.com
185.199.109.133 avatars5.githubusercontent.com
185.199.108.133 avatars4.githubusercontent.com
185.199.108.133 avatars3.githubusercontent.com
185.199.108.133 avatars2.githubusercontent.com
185.199.108.133 avatars1.githubusercontent.com
185.199.111.133 avatars0.githubusercontent.com
185.199.110.133 avatars.githubusercontent.com
140.82.114.10 codeload.github.com
52.217.118.49 github-cloud.s3.amazonaws.com
3.5.25.229 github-com.s3.amazonaws.com
3.5.22.177 github-production-release-asset-2e65be.s3.amazonaws.com
52.217.198.89 github-production-user-asset-6210df.s3.amazonaws.com
3.5.30.95 github-production-repository-file-5c1aeb.s3.amazonaws.com
185.199.110.153 githubstatus.com
140.82.114.18 github.community
185.199.108.133 media.githubusercontent.com
```

5. **win+R**，输入 **cmd**，右键+右键，管理员执行：**ipconfig /flushdns**，使用`ping github.com`

Obsidian安装后无法打开界面，但是后台在运行

1. 根据[win11打不开obsidian了 - 疑问解答 - Obsidian 中文论坛](#)
2. 下载 [Obsidian.1.6.3-allusers.exe](#)
3. 手动指定安装路径，路径中**不要有空格和中文**

如何存储和恢复文件的创建时间

Obsidian的**文件列表**可以按照文件的**创建时间**排序，但是Linux系统往往没有存储文件的创建时间（其实默认为修改时间）。此外，可能还需要重新按照创建时间来排列新的文件。那么我们可以使用这个脚本。

```

@echo off
setlocal

:: Prompt for the directory path
set /p "directory=Enter the directory path (e.g., C:\path\to\markdown\files): "

:: Validate if the directory exists
if not exist "%directory%" (
    echo The directory does not exist.
    exit /b
)

:: Define the file to store creation times
set "timestamps_file=%directory%\creation_times.txt"

:: Function to store creation times
if "%1"=="store" (
    echo Storing creation times...
    :: Clear the timestamps file
    rm "%timestamps_file%"

    for %%f in ("%directory%\*.md") do (
        :: Retrieve the creation time and append to the timestamps file
        powershell -Command "(Get-Item '%%f').CreationTime.ToString('yyyy-MM-dd HH:mm:ss') >> '%timestamps_file%'
        echo %%f >> '%timestamps_file%'
    )
    echo Creation times stored in %timestamps_file%
    exit /b
)

:: Function to restore creation times
if "%1"=="restore" (
    echo Restoring creation times...
    setlocal enabledelayedexpansion
    set restoring=false
    for /f "tokens=1* delims=" %%a in (%timestamps_file%) do (
        set line=%%a
        if not "!line!"=="" (
            if "!restoring!"=="true" (
                :: Restore the creation time using PowerShell
                powershell -Command "(Get-Item '!line!').CreationTime = '!date!'"
            )
        )
    )
)

```

```
        set restoring=false
    ) else (
        :: Store the creation time
        set date=!line!
        set restoring=true
    )
)
)
)
echo Creation times restored!
exit /b
)

:: Instructions
echo Usage:
echo.
echo To store creation times: script.bat store
echo To restore creation times: script.bat restore

endlocal
```

ManageMarkdownCreationTimes.bat

使用脚本

1. **存储:** **PowerShell** 运行 **ManageMarkdownCreationTimes.bat store**, 输入包含 markdown 文件的文件夹, 例如 **E:\MathNotes\MathSoftwear**
2. **恢复:** **PowerShell** 运行 **ManageMarkdownCreationTimes.bat restore**, 输入包含 markdown 文件的文件夹, 例如 **E:\MathNotes\MathSoftwear**