

SIMATS ENGINEERING

ASSESSMENT TOOL 1

COURSE NAME: Artificial Intelligence

COURSE CODE: CSA17

COURSE OUTCOME COVERED

CO1: Apply AI basics such as intelligent agents and uninformed search methods to solve problems effectively. (BL3)

Assessment Tool Weightage: 50%

QUESTIONS: 5

Duration : 1 Hour

Total Marks:50

Annexure A

Analytical Problem Solving

Code of Conduct:

I Vanaganti Shiva / (192311361) (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student:

V Shiva

RUBRICS FOR CALCULATION:

Criteria	Weightage	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Problem Understanding	20%	Clearly interprets problem, identifies all parameters and requirements accurately	Understands problem with minor gaps	Partial understanding; misses key elements	Misinterprets or unable to understand problem
Method Selection	20%	Selects most appropriate method/formula with strong justification	Selects correct method with minor errors	Inappropriate or partially correct method	Unable to select method
Solution Process	25%	Logical, systematic steps with correct approach throughout	Mostly correct steps with minor mistakes	Disorganized steps; multiple errors	No clear process
Accuracy of Calculation	20%	All calculations accurate; correct final answer	Minor calculation errors	Frequent errors; incorrect final answer	No valid calculations
Interpretation of Results	15%	Clearly interprets results with units and engineering relevance	Basic interpretation with minor omissions	Limited or unclear interpretation	No interpretation
Problem Understanding	20%	Clearly interprets problem, identifies all parameters and requirements accurately	Understands problem with minor gaps	Partial understanding; misses key elements	Misinterprets or unable to understand problem

1. Solve the Water Jug problem: you are given 2 jugs, a 4-gallon one and 3-gallon one. Neither has any measuring maker on it. There is a pump that can be used to fill the jugs with water. How can you get exactly 2 gallons of water into 4-gallon jug?
Explicit assumptions: A jug can be filled from the pump, water can be poured out of a jug onto the ground, water can be poured from one jug to another and that there are no other measuring devices available.

Algorithm

1. Start with both jugs empty (0,0).
2. Fill the 3-gallon jug.
3. Pour water from the 3-gallon jug into the 4-gallon jug.
4. Fill the 3-gallon jug again.
5. Pour water from the 3-gallon jug into the 4-gallon jug until the 4-gallon jug becomes full.
6. Empty the 4-gallon jug.
7. Pour the remaining 2 gallons from the 3-gallon jug into the 4-gallon jug.
8. Stop when the 4-gallon jug contains exactly 2 gallons.

State Space Representation :-

Step	4-Gallon Jug	3-Gallon Jug	Action
1	0	0	Initial State
2	0	3	Fill 3-gallon jug
3	3	0	Pour into 4-gallon jug
4	3	3	Fill 3-gallon jug again
5	4	2	Pour into 4-gallon jug until full
6	0	2	Empty 4-gallon jug
7	2	0	Pour remaining water into 4-gallon jug

Solution

Initially both jugs are empty. Fill the 3-gallon jug and pour it into the 4-gallon jug. Fill the 3-gallon jug again and pour water into the 4-gallon jug until it becomes full. This leaves exactly 2 gallons in the 3-gallon jug. Empty the 4-gallon jug and pour the remaining 2 gallons into it.

Final Answer: The 4-gallon jug contains exactly 2 gallons.

2. Find out how Mars Rover, analyse and explore the samples on Mars by answering the following questions. i. What are the percept's for this agent? ii. Characterize the operating environment. iii. What are the actions the agent can take? iv. How can one evaluate the performance of the agent? v. What sort of agent architecture do you think is most suitable for this agent? Why?

i) What are the percepts for this agent?

Percepts are the inputs received by the Mars Rover through its sensors.

- Camera images
- Rock and soil composition
- Temperature
- Atmospheric pressure
- Terrain information
- Obstacle detection
- Position and location
- Battery level

ii) Characterize the operating environment

Characteristic	Description
Observability	Partially Observable
Deterministic	Stochastic (Uncertain)
Episodic/Sequential	Sequential
Static/Dynamic	Dynamic
Discrete/Continuous	Continuous
Single/Multi Agent	Single Agent

iii) What are the actions the agent can take?

- Move forward

- Move backward
- Turn left/right
- Capture images
- Drill rocks
- Collect soil samples
- Analyze samples
- Send data to Earth
- Avoid obstacles

iv) How can one evaluate the performance of the agent?

The performance is evaluated based on:

- Accuracy of sample collection
- Safe navigation
- Obstacle avoidance
- Efficient battery usage
- Successful communication with Earth
- Completion of mission objectives

v) What type of agent architecture is suitable? Why?

Learning Agent is the most suitable architecture.

Reason:

- Learns from previous experiences.
- Adapts to unknown environments.
- Improves navigation over time.
- Makes better decisions in uncertain situations.
- Suitable for autonomous exploration.

3. Explore the search space using search strategies and formulate the problem components for the 8-Queens problem using the following information: Place 8 queens on a chessboard such that none of the queen's attack any of the others. A configuration of 8 queens on the board as shown in the figure below, but this does not represent a solution as the queen in the first column is on the same diagonal as the queen in the last column.

Problem Formulation

Place **8 queens** on an **8 × 8 chessboard** such that no two queens attack each other.

Problem Components

Initial State

An empty chessboard.

State Space

All possible arrangements of queens on the chessboard.

Operators

- Place a queen in a safe position.
- Move to the next row.

Goal State

Eight queens are placed without attacking each other.

Goal Test

No two queens share:

- Same row
- Same column
- Same diagonal

Path Cost

Each move has equal cost.

Search Strategy

The **Backtracking Search Algorithm** is used.

Algorithm

1. Start from the first row.
2. Place a queen in a safe column.
3. Check whether the position is safe.
4. If safe, place the queen.
5. Move to the next row.
6. If no safe position exists, backtrack.
7. Continue until all 8 queens are placed.

Advantages

- Efficient compared to brute force.
- Eliminates invalid states early.
- Finds a valid solution quickly.

4. A customer wants to travel from the one location to another location using OLA Cab booking mobile application. The customer can select the any of the cab type as mini, micro, sedan, shared, prime and so on based on his comfort to reach the destination. Identify what type of problem-solving agent can be used and write the pseudocode for the above problem.

Type of Problem-Solving Agent

Goal-Based Agent

Reason

A goal-based agent chooses actions based on the customer's goal of reaching the destination safely and efficiently.

The agent evaluates:

- Pickup location
- Destination
- Available cab types
- Fare
- Estimated arrival time
- Traffic conditions

Then it selects the most suitable cab.

PseudocodeStart

Input Pickup Location

Input Destination

Display Available Cab Types

Customer selects Cab

Calculate Fare

Search Nearby Drivers

If Driver Available

Assign Driver

Confirm Booking

Else


Display "No Cab Available"

End

Working

1. Customer enters pickup and destination.
2. System displays available cab types.
3. Customer selects one.
4. Fare is calculated.
5. Nearby drivers are searched.
6. Driver is assigned.
7. Booking confirmation is sent.

5. A logistics company operates a delivery network where packages must be transported between warehouses at minimum cost. Each route between warehouses has an associated travel cost (fuel + time). The company wants to determine the least-cost path from the starting warehouse S to the destination warehouse G using the Uniform Cost Search (UCS) algorithm. The delivery network is represented as a weighted graph:



Algorithm

1. Insert the start node into the priority queue.
2. Remove the node having the lowest path cost.
3. If it is the goal node, stop.
4. Expand the node.
5. Add all neighboring nodes with cumulative cost.
6. Repeat until the goal node is reached.

Graph

Edges:

$$S \rightarrow A = 1$$

$$S \rightarrow G = 12$$

$$A \rightarrow B = 3$$

$$A \rightarrow C = 1$$

$$B \rightarrow D = 3$$

$$C \rightarrow D = 1$$

$$C \rightarrow G = 2$$

$$D \rightarrow G = 3$$

Possible Paths

Path	Cost
$S \rightarrow G$	12
$S \rightarrow A \rightarrow B \rightarrow D \rightarrow G$	$1 + 3 + 3 + 3 = 10$
$S \rightarrow A \rightarrow C \rightarrow D \rightarrow G$	$1 + 1 + 1 + 3 = 6$
$S \rightarrow A \rightarrow C \rightarrow G$	$1 + 1 + 2 = 4$

Working of UCS

Initially, the search starts from node **S**.

From **S**, two paths are available:

- $S \rightarrow A$ (Cost = 1)
- $S \rightarrow G$ (Cost = 12)

Since UCS always chooses the path with the **lowest cumulative cost**, node **A** is selected.

From **A**, two new paths are generated:

- $S \rightarrow A \rightarrow B$ (Cost = 4)
- $S \rightarrow A \rightarrow C$ (Cost = 2)

Again, UCS selects the minimum-cost path, so node **C** is expanded.

From **C**, two paths are generated:

- $S \rightarrow A \rightarrow C \rightarrow D$ (Cost = 3)
- $S \rightarrow A \rightarrow C \rightarrow G$ (Cost = 4)

The goal node **G** is now reached with a total cost of **4**, which is smaller than all other possible paths.

Therefore, UCS stops because it has found the least-cost path.

Least-Cost Path

$S \rightarrow A \rightarrow C \rightarrow G$

Total Cost

$\text{Cost} = 1 + 1 + 2 = 4$

Conclusion

Uniform Cost Search expands nodes in increasing order of path cost. It guarantees the optimal solution when all edge costs are positive. In the given delivery network, the least-cost path from **S** to **G** is:

$S \rightarrow A \rightarrow C \rightarrow G$

Minimum Cost = 4