

IT4552 – Web programming

Chapter 3.1. Conditional Statements

1

Objectives

- ❖ To learn to use conditional test statements to compare numerical and string data values
- ❖ To learn to use looping statements to repeat statements
- ❖ To learn to use logical test operators to create compound conditional test statements

2

Content

1. Using Conditional Test Statements
2. Using Loops to Repeat Statements

3

Content

- ➡ 1. Using Conditional Test Statements
2. Using Loops to Repeat Statements

4

1. Conditional Test Statements

- ❖ Conditional statements provide a way for scripts to test for certain data values and then to react differently depending on the value found.
- ❖ Will examine
 - the if statement,
 - the elseif clause,
 - the else clause,
 - and the switch statement.

1.1. Using the if Statement

- ❖ Use an if statement to specify a test condition and a set of statements to run when a test condition is *true*.

```
if ($average > 69) {  
    $Grade="Pass";  
    print "Grade=$Grade ";  
}  
print "Your average was $average";
```

When \$average is greater than 69 execute these statements.

- ❖ if \$average was equal to 70 then the above would output:
Your average was 70

a. Test Expressions

- ❖ Test expressions use test operators within their expressions.
 - Test operators work much like the expression operators.
 - The if statement above uses the greater than (>) operator to test whether \$average is greater than 69.
 - Test operators evaluate to *true* or *false*

PHP Test Operators

Operator Test	Effect	Example	Result
==	Equal to	if (\$x == 6){ \$x = \$y + 1; \$y = \$x + 1; }	Run the second and third statements if the value of \$x is equal to 6.
!=	Not equal to	if (\$x != \$y) { \$x = 5 + 1; }	Run the second statement if the value of \$x is not equal to the value of \$y.
<	Less than	if (\$x < 100) { \$y = 5; }	Run the second statement if the value of \$x is less than 100.
>	Greater than	if (\$x > 51) { print "OK"; }	Run the second statement if the value of \$x is greater than 51.
>=	Greater than or equal to	if (16 >= \$x) { print "x=\$x"; }	Run the second statement if 16 is greater than or equal to the value of \$x.
<=	Less than or equal to	if (16 >= \$x) { print "x=\$x"; }	Run the second and third statements if the value of \$x is less than or equal to the value of \$y.

A Full Example ...

❖ Consider the following application:

- Receives two grades as input and determines whether their average is above 89.
- It uses an HTML form for input grades:

Enter First Score
 Enter Second Score

Sets
\$grade1

Sets
\$grade2

Receiving Code

```
1. <html>
2. <head><title>Decisions</title></head>
3. <body>
4. <?php
5.     $grade1= $_POST["grade1"];
6.     $grade2= $_POST["grade2"];
7.     $average = ($grade1 + $grade2)/ 2;
8.     if ( $average > 89 ) {
9.         print "Average score: $average You got an A! <br>";
10.    }
11.    $max=$grade1;
12.    if ($grade1 < $grade2) {
13.        $max = $grade2;
14.    }
15.    print ("Your max score was $max");
16. ?>
17. </body></html>
```

Get grade1 and grade2
from HTML form.


Calculate average

Output if \$average
is more than 89

Set when \$grade2 is
more than \$grade1

A Full Example ...

The previous code can be executed at



b. Comparing Strings

❖ PHP represents strings using the ASCII code values (American Standard Code for Information Interchange).

- ASCII provides a standard, numerical way to represent characters on a computer.
- Every letter, number, and symbol is translated into a code number.
 - "A" is ASCII code 65, "B" is 66, "C" is 67, and so on.
 - Lowercase "a" is ASCII code 97, "b" is 98, "c" is 99, and so on.
 - ASCII "A" is less than ASCII "a," "B" is less than "b," and "c" is less than "d".
 - ASCII characters have ASCII code values lower than letters. So ASCII character "1" is less than "a" or "A"

b. Comparing Strings (2)

- ❖ You can use == operator to check if one string is equal to another. For example,

```
$name1 = "George"; $name2 = "Martha";  
if ($name1 == $name2) {  
    print ("$name1 is equal to $name2" );  
} else {  
    print ("$name1 is not equal to $name2");  
}
```

- ❖ Would output: "George is not equal to Martha".

b. Comparing Strings (3)

- ❖ Also can use <, >, <=, and >= operators to compare string values using ASCII code values.

- ❖ For Example

```
$name1 = "George"; $name2 = "Martha";  
if ($name1 < $name2) {  
    print ("$name1 is less than $name2");  
} else {  
    print ("$name1 is not less than $name2");  
}
```

- ❖ It would output "George is less than Martha".

A Full Example ...

- ❖ Consider the following application:
 - Compares two input strings.
 - It uses the HTML form element that sets the variables \$first and \$second.

```
First Name: <input type="text" size="10"  
            maxlength="15" name="first">  
Second Name: <input type="text" size="10"  
             maxlength="15" name="second">
```

Sets
\$first

Sets
\$second

Receiving Code

```
1. <html>  
2. <head><title>String Comparison Results</title></head>  
3. <body>  
4. <?php  
5. $first = $_POST["first"];  
6. $second = $_POST["second"];  
7. print ("First=$first Second=$second<br>");  
8. if ($first == $second) {  
9.     print ("$first and $second are equal");  
10. }  
11. if ($first < $second) {  
12.     print ("$first is less than $second");  
13. }  
14. if ($first > $second) {  
15.     print ("$first is greater than $second");  
16. }  
17. >?></body></html>
```

Get the values of \$first
and \$second


Output if \$first is
equal to \$second

Set when \$second
is less than \$first

Set when \$first is
more than \$second

The Output ...

The previous code can be executed at



17

c. Using the elseif Clause

- ❖ Use an elseif clause with an if statement to specify an additional test condition

```
if (test expression) {
    one or more PHP statements
} elseif (test expression){
    one or more PHP statements
}
```

- ❖ The above script checks the elseif test expression when the test condition for the if statement is *false*.

18

c. Using the elseif Clause (2)

- ❖ One or more elseif clauses can be used with an if statement.

```
if ($hour < 9) {
    print "Sorry, it is too early.";
} elseif ($hour < 12) {
    print "Good morning. The hour is $hour. ";
    print "How can we help you?";
} elseif ($hour < 13) {
    print "Sorry, we are out to lunch. ";
} elseif ($hour < 17) {
    print "Good afternoon. The hour is $hour. ";
    print "How can we help you?";
} elseif ($hour <= 23) {
    print "Sorry, we have gone home already.";
}
```

Check this test expression when the first condition is *false*.

Check this test expression when the first two conditions are all *false*.

Check this test expression when the first three conditions are all *false*.

if \$hour == 15, output "Good afternoon. The hour is 15. How can we help you?" if \$hour == 24, then this code outputs nothing.

19

d. Using the else Clause

- ❖ Use an else clause with if and possibly one or more elseif clauses

- Specify set of statements to run when all the previous test conditions are *false*.

- Has the following general format shown in the

```
if (test expression) {
    one or more PHP statements
} else {
    one or more PHP statements
}
```

20

19

d. Using the else Clause (2)

- ❖ For example, if \$count had a value of -75, then this code would output "Illegal value for count = -75"

```
if ( $count == 0 ) {  
    print ("Time to reorder.");  
    $reorder=1;  
} elseif ( $count == 1 ) {  
    $reorder=1;  
    print ("Warning: we need to start reordering.");  
} elseif ( $count > 1 ) {  
    $reorder = 0;  
    print ("We are OK for now.");  
} else {  
    print ("Illegal value for count = $count");  
}
```

A Full Example ...

- ❖ Full example that extends the grade-averaging to determine a letter grade (A, B, C, D, or F) and to catch illegal input.
- ❖ Use the following HTML form for input

Enter First Score
Enter Second Score

Sets
\$grade1

Sets
\$grade2

Receiving Code

```
1. <html> <head><title>Grade Calculation</title></head>  
2. <body>  
3. <?php  
4. $grade1 = $_POST["grade1"]; $grade2 = $_POST["grade2"];  
5. $average = ($grade1 + $grade2) / 2;  
6. if ($average > 89) {  
7.     print ("Average=$average You got an A");  
8. } elseif ($average > 79) {  
9.     print ("Average=$average You got a B");  
10. } elseif ($average > 69) {  
11.     print ("Average=$average You got a C");  
12. } elseif ($average > 59) {  
13.     print ("Average=$average You got a D");  
14. } elseif ($average >= 0) {  
15.     print ("Grade=$grade You got an F");  
16. } else {  
17.     print ("Illegal average less than 0 average=$average");  
18. }  
19. $max=$grade1;  
20. if ($grade1 < $grade2) {  
21.     $max = $grade2;  
22. }  
23. print ("The maximum score was $max");  
24. ?> </body></html>
```


Get values of
\$grade1 and \$grade2

Compute average of
\$grade1 and \$grade2

Check if \$average
is an "A", "B", "C",
"D" or "F"

Would output the following...

The previous code can be executed at



1.2. Using the switch Statement

❖ Use switch statement as another conditional test

```
1. switch ($rating) {
2.   case 1:
3.     $rated = "Poor";
4.     print "The rating was $rated";
5.     break;
6.   case 2:
7.     $rated = "Fair";
8.     print "The rating was $rated";
9.     break;
10.  case 3:
11.    $rated = "Good";
12.    print "The rating was $rated";
13.    break;
14.  default:
15.    print "Error: that rating does not ex";
16. }
```

Enclose in curly brackets

Run these when \$rating has value 1.

Run these when \$rating has value 2.

Run these when \$rating has value 3.

When value not 1, 2, or 3.



25

Content

1. Using Conditional Test Statements

➡ 2. Using Loops to Repeat Statements



26

2. Using Loops to Repeat Statements

- ❖ Scripts can use loop statements to repeat sections of code
- ❖ Advantages of loops include
 - Scripts can be more concise
 - Can write more flexible scripts
- ❖ Will discuss while loops and for loops now
 - Will review foreach loops later



27

2.1. Using a for loop

❖ Use a **for** loop to repeat of set of statements a specific number of times.

The *initialization expression* sets the initial value of \$i. Enclose statements to repeat in curly brackets.

The *iteration expression* increments \$i at the end of each loop iteration.

The *loop-end condition* determines when the loop will end.

```
for ( $i = 0; $i < $max; $i++ ) {
  Set of statements to repeat
}
```

Note the use of ; after first 2 but not 3rd.



28

Full Script Example ...

```

1. <html><head><title>Loops</title></head>
2. <body><font size="5" color="blue">
3.   Generate Square and Cube Values </font>
4.   <br>
5.   <form action="http://webwizard.aw.com/~phpgpn/C3/whileloop.php" method="post">
6.     <?php
7.       print ("Select Start Number");
8.       print ("<select name='start'\>");
9.       for ($i=0; $i<10; $i++) {
10.        print ("<option>$i</option>");
11.      }
12.      print ("</select>");
13.      print ("<br>Select End Number");
14.      print ("<select name='end'\>");
15.      for ($i=10; $i<20; $i++) {
16.        print ("<option>$i</option>");
17.      }
18.      print ("</select>");
19.    >
20.    <br><input type="submit" value="Submit">
21.    <input type="reset" value="Clear and Restart"> </form></body></html>

```


Repeat print statement
10 times with values 0,
1, 2, ... 9 for \$i.

Repeat print statement
10 times with values 10,
11, 12, ... 19 for \$i.

29

Would output the following...


The previous code can be executed at



30

2.2. Using the while loop

- ❖ Use the while loop to repeat a set of statements as long as a conditional test is true.



31

2.2. Using the while loop (2)

- ❖ A while loop will repeat as long as the loop conditional test is *true*.
 - If initially *false*, then the statements within the loop body will never run.
- ❖ A bad idea to create an Infinite Loop
 - If the loop conditional test always *true*, then the loop will never end (infinite loop).
 - It will consume resources on the Web server and possibly slow down other server activity. (might have to exit the window that's running your script)

32

A Full Script Example

```


1. <html>
2. <head><title>While Loop</title></head>
3. <body>
4. <font size="4" color="blue"> Table of Square and Cube Values
   </font>
5. <table border=1>
6. <th> Numb </th> <th> Sqr </th> <th> Cubed </th>
7. <?php
8.     $start = $_POST["start"];  $end = $_POST["end"];
9.     $i = $start;
10.    while ($i <= $end) {
11.        $sqr=$i*$i;
12.        $cubed=$i*$i*$i;
13.        print ("<tr><td>$i</td><td>$sqr</td><td>$cubed</td></tr>");
14.        $i = $i + 1;
15.    }
16. ?></table></body></html>

```

33

The Output ...

The previous code can be executed at



34

TIP Using Either the while Loop or the for Loop for Some Problems

- ❖ For some loops you can use either the while loop or the for loop.

```

▪ for ( $i=0; $i<5; $i++ ) {
    print "i=$i ";
}
▪ $i = 0;
  while ($i < 5 ) {
    print "i=$i "; $i=$i + 1;
  }

```

The two above loops both output "i=0 i=1 i=2 i=3 i=4".

35

2.3. Using Logical Test Operators

- ❖ PHP supports a set of logical test operators you can use to create compound test expressions

- used within an if statement or a while statement to specify more than one test condition.

- For example, consider the following line

```

while ($x > $max && $found != 1) {
    ...
}

```

36

Logical Test Operators

- ❖ PHP supports three logical test operators.
 - `&&`: *the AND operator*
 - `||`: *the OR operator*
 - `!`: *the NOT operator*



37

And Operator

- ❖ Use in if statements and while loops.

❖ E.g.:

```
while ($ctr < $max && $flag == 0) {  
    ...  
}
```

Whenever either of these expressions is *false*, the loop will terminate.



38

Or operator

- ❖ Used much like the AND operator in if statements and while loops.

❖ E.g.

```
if ($ctr != $max || $flag == 0) {
```

Carries out the statements within the if statement if either \$ctr is not equal to \$max or \$flag is equal to 0.



39

Not operator

- ❖ Used to test whether an expression is *false* (used in while loops and in if statements).

❖ E.g.

```
if (!$flag == 0) {
```

This statement is *true* when \$flag is anything except 0.



40

Example

- ❖ Asks the user to guess a “secret” two-digit combination, uses logical test operators.
- ❖ The Input HTML form uses the following to set pick1. A similar group sets a variable pick2.
 - Pick a number from 1 to 9

 - <input type="radio" name="pick1" value="1">1
 - <input type="radio" name="pick1" value="2">2
 - <input type="radio" name="pick1" value="3">3
 - <input type="radio" name="pick1" value="4">4
 - <input type="radio" name="pick1" value="5">5
 - <input type="radio" name="pick1" value="6">6
 - <input type="radio" name="pick1" value="7">7
 - <input type="radio" name="pick1" value="8">8
 - <input type="radio" name="pick1" value="9">9



41

A Full Script Example ...


```
1. <html><head><title>Number Guess Results </title></head>
2. <body>
3. <?php
4. $pick1=$_POST["pick1"]; $pick2=$_POST["pick2"];
5. $combo1=5;
6. $combo2=6;
7. if (($pick1 == $combo1) && ($pick2 == $combo2)) {
8.     print ("Congratulations you got both secret numbers
   $combo1 $combo2!");
9. } elseif (($pick1 == $combo1) || ($pick2 == $combo2)){
10.     print ("You got one number right.");
11. } else {
12.     print ("Sorry, you are totally wrong!");
13. }
14. print ("You guessed $pick1 and $pick2.");
15. ?></body></html>
```



42

The Output ...

The previous code can be executed at



43

Summary

- ❖ Use conditional statements to test for certain conditions and, based on the results of the test, to run specific script statements.
- ❖ Loops expand the types of programming problems that you can solve and allow you to solve some programming problems much more concisely
- ❖ Use logical AND (&&), OR (||) and NOT (!) operators to carry out compound tests.



44

Summary

- ❖ Variables are used to store and access data in computer memory. You can associate a value with a variable, change that value, print it out, and perform many different operations on it.
- ❖ PHP supports both numeric and string variables. String variables use different methods for value manipulation (for example, concatenation) than numeric variables do.

Question?

