

Create the Amazon RDS MySQL Instance

Provision the managed database within your isolated database subnets.

1. Open the [AWS RDS Console](#).
2. Click **Create database** and select **Full Configuration** with **MySQL**.
3. Choose the version specified in your DB.md (or the latest stable **MySQL 8.0/8.4**).
4. Under **Deployment options**, pick your required availability strategy (Multi-AZ for production or Single DB instance for dev/testing and minimum 2 subnet).
5. In **Connectivity**:
 1. Select target **VPC**.
 2. Choose or create a **DB Subnet Group** that includes only your **Private Database Subnets**.
 3. Set **Public access** to **No**.
 4. Create or choose a **Database Security Group** that allows **Inbound TCP on Port 3306 only** from the Security Group attached to your Application Tier EC2 instances.

my_db_subnet

Subnet group details

VPC ID

vpc-081c241c4e4b95465 [🔗](#)

ARN

arn:aws:rds:us-east-1:041944951715:subgrp:my_db_subnet

Supported network types

IPv4

Description

allow ssh

Subnets (2)

Availability zone	Subnet name	Subnet ID	CIDR block
us-east-1a	MY_SUBNET_Privet_DB_1a	subnet-03be8c5ef29e866fe 🔗	192.168.5.0/24
us-east-1b	MY_SUBNET_Privet_DB_1b	subnet-07935d787c185e728 🔗	192.168.6.0/24

Tags (0)

[Manage tags](#)

🔍 Filter by Tag key

< 1 > ⚙️

Tags



Value



You don't have any tags associated with this resource.

[Manage tags](#)

Configure Database Credentials & Settings

During the RDS setup wizard, configure your master identity records:

- DB Instance Identifier: e.g., my-app-db
- Master Username: Choose an administrative username (e.g., admin).
- Master Password: Generate a secure string (avoid special characters that break terminal strings like @ or :).
- Initial Database Name: Expand *Additional Configuration* at the bottom and specify an initial database name (e.g., database-1) as called out in your repository setup notes

< Connectivity & security Monitoring Logs & events Configuration Zero-ETL integrations Maintenance >			
Instance			
Configuration	Instance class	Primary storage	Monitoring
DB instance ID database-1	Instance class db.t4g.micro	Encryption Enabled	Monitoring type Database Insights - Standard
Engine version 8.4.9	vCPU 2	AWS KMS key aws/rds	Database counter metrics Disabled
RDS Extended Support Disabled	RAM 1 GB	Storage type General Purpose SSD (gp2)	Enhanced Monitoring Disabled
DB name -	Availability	Storage 20 GiB	
DB name -	Availability	Storage 20 GiB	
License model General Public License	Master username admin	Provisioned IOPS -	
Option groups default:mysql-8-4 In sync	Master password *****	Storage throughput -	
Amazon Resource Name (ARN) arn:aws:rds:us-east-1:041944:951715:db:database-1	IAM DB authentication Not enabled	Storage autoscaling Enabled	
Resource ID db-KVS4MWOR5ZF4ZIUYS7Y6GBSA4Y	Multi-AZ No	Maximum storage threshold 1000 GiB	
Created time September 24, 2026, 14:00 (UTC+05:30)	Secondary Zone -	Storage file system configuration Current	

Connect to the DB from the App EC2 Terminal

Log back into private Application Tier EC2 instance via Jump server. must install a MySQL client.

From the private EC2 instance, connect to the MySQL database:

```
mysql -h <RDS-ENDPOINT> -u admin -p
```

Inside the MySQL shell, create the application database:

```
CREATE DATABASE feedbackdb;
```

Select the database:

```
USE feedbackdb;
```

Create the table to store customer feedback:

```
CREATE TABLE feedback (  
  id INT AUTO_INCREMENT PRIMARY KEY,  
  name VARCHAR(100),  
  email VARCHAR(100),  
  feedback TEXT,  
  created TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

Check that the table has been created successfully:

```
mysql> SHOW TABLES;  
+-----+  
| Tables_in_feedbackdb |  
+-----+  
| feedback              |  
+-----+  
1 row in set (0.00 sec)  
  
mysql> 
```

View the table structure:

```
DESCRIBE feedback;
```

```
mysql> DESCRIBE feedback;  
+-----+-----+-----+-----+-----+-----+  
| Field | Type      | Null | Key | Default      | Extra          |  
+-----+-----+-----+-----+-----+-----+  
| id    | int       | NO   | PRI | NULL         | auto_increment |  
| name  | varchar(100) | YES  |     | NULL         |                |  
| email | varchar(100) | YES  |     | NULL         |                |  
| feedback | text      | YES  |     | NULL         |                |  
| created | timestamp | YES  |     | CURRENT_TIMESTAMP | DEFAULT_GENERATED |  
+-----+-----+-----+-----+-----+-----+  
5 rows in set (0.03 sec)
```

Restart the Flask Application

*****Before restart flask application need to add db. endpoint name and login credential*****

Stop the currently running Flask application:

```
pkill -f "python3 app.py"
```

Start the application again:

```
python3 ~/app.py &
```

Test Database Connectivity

Send a test request to the Flask API:

```
curl -X POST http://localhost:5000/submit \
-H "Content-Type: application/json" \
-d '{
  "name": "Test",
  "email": "t@t.com",
  "feedback": "Hello RDS!"
}'
```

```
ubuntu@ip-192-168-3-95:~$ curl -X POST http://localhost:5000/submit \
-H "Content-Type: application/json" \
-d '{
  "name": "Test",
  "email": "t@t.com",
  "feedback": "Hello RDS!"
}'
{"message": "Feedback submitted successfully!"}
ubuntu@ip-192-168-3-95:~$
```

For verify output go to db terminal

USE feedbackdb;

View the stored feedback:

SELECT * FROM feedback;

```
mysql> USE feedbackdb;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> SELECT * FROM feedback;
+----+-----+-----+-----+-----+
| id | name  | email          | feedback      | created                |
+----+-----+-----+-----+-----+
| 1  | Test  | t@t.com        | Hello RDS!    | 2026-10-05 15:58:20    |
| 2  | Test1 | t@t1.com       | Hello1 RDS!   | 2026-10-05 15:59:14    |
| 3  | Test  | t@t.com        | Hello RDS!    | 2026-10-06 08:37:46    |
| 4  | pritam | pritam@gmail.com | good          | 2026-10-06 16:04:17    |
| 5  | demo  | demo@rediffmail.com | nice          | 2026-10-06 16:37:53    |
| 6  | demo1 | demo1@gmail.com | good          | 2026-10-06 16:47:40    |
| 7  | demo2 | demo2@gmail.com | finally completed | 2026-10-06 16:53:08    |
| 8  | Test  | t@t.com        | Hello RDS!    | 2026-10-08 08:41:15    |
+----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

****Need to remember DB Credential .**