


Schematic:

Inductance: (1-2): 3mH \pm 10% @ 20KHz, 0.1V

RDC: (1-2): 200 m Ω Max




Mechanical Specification:

Notes:



1. Marking shall include:
GCi Part Number,
GCi Name, Date Code,
RoHS Symbol

Marking

G154038LF
GCi XXXX e1




Top View




Front View

2x ØE




R-Side View

Ref	mm
A	52.0 Max
B	30.5 Max
C	55.0 Max
D	4.0±0.5
E	Ø1.15±0.1
F	30.0±0.5
G	20.0±0.5



Bottom View



Suggested PCB Layout



"ALL CURRENT CHANGES INDICATED BY ASTERISKS"

Electrical / Mechanical Requirements			Inductor			
DESIGN ENG: Ignatius C.	APPD. BY: Rich McCormick	RELEASED BY:	REV: 1	DRAFTER: Christina T.	DATE: 07/21/15	
S/O NUMBER: 154038	GCI PART NO: G154038LF	CUSTOMER PART NO:			SHEET 1 OF 1	



****Proprietary & Confidentiality Notice****

This document contains GCi Technologies, Inc. proprietary and confidential data and is not to be copied, reproduced, used, or divulged to unauthorized persons, in whole or in part without proper written authorization from GCi Technologies, Inc. GCi Technologies, Inc. reserves all rights herein.

1301 Precision Drive * Plano, Texas 75074 U.S.A. * Tel: (972) 423-8411 * Fax: (972) 423-4550 * email: gci@gcitechologies.com * website: www.gcitechologies.com