

Machine Learning: Rental Housing Data

...

By Valerie Andrade

Project Overview

Objective

Explore and predict the rental prices in the private property market using machine learning algorithms on web scraped Craigslist housing data

Presentation Sections

Data Acquisition

Data Exploration & Preliminary Analysis

Machine Learning

What I Used

Language



Libraries



Tools



Algorithms

- Linear Regression
- Random Forest

Data Acquisition



Web Scraped Datasets

- Web Scraping code includes a **splinter** that opens each listing (3000) and pulls out the specific details within the post
- Code took about 1.5 hours to webscrape 3000 listings
- I web scraped Miami and San Francisco and used the different data sets on my ML models

reply favorite hide flag Posted a day ago print

\$1,450 / 2br - 884ft² - Nice 2 Bed 1 Bath condo in a small Building (Miami)

image 1 of 5



2BR / 1Ba 884ft²

cats are OK - purrr
dogs are OK - woof
condo
w/d in unit
off-street parking

Nice 2 Bed 1 Bath condo in a small Building, near the Golf Course ,Normandy Park and the Beach. Security entrance to the Building!

Web Scrapped DataFrame

	datetimes	hoods	prices	bedrooms	bathrooms	sqft	housing_type	laundry	parking	cats	dogs	furnished
0	2021-05-30 14:02	(Dadeland 2/2)	\$1,900	2BR	2Ba	none	apartment	w/d in unit	carport	none	none	none
1	2021-05-30 14:02	(Doral)	\$2,557	2BR	2Ba	none	apartment	w/d in unit	attached garage	none	none	none
2	2021-05-30 14:02	(Miami)	\$2,241	2BR	2Ba	1106	apartment	w/d in unit	off-street parking	yes	yes	none
3	2021-05-30 14:02	(Doral)	\$3,399	3BR	2Ba	none	apartment	w/d in unit	attached garage	none	none	none
4	2021-05-30 14:01	(doral)	\$1,978	1BR	1Ba	none	apartment	w/d in unit	attached garage	none	none	none

Data Exploration

Data Exploration - ETL Process

Extract

Extract datasets using web scrape method ensuring it has all necessary information and limited null values.

Null values in sq. ft. presents a challenge

Transform

Transform data by removing duplicate listings, converting data types, replacing string values, creating separate data frames

Convert null values to 0 instead of dropping

Load

Load the data into PostgreSQL

Dataset 1: Miami Rental Listings

neighborhood	br	ba	sqft	housingType	laundry	parking	cats	dogs	furnished	rent
Dadeland	2	2.0	0.0	apartment	w/d in unit	carport	no	no	no	1900
Doral	2	2.0	0.0	apartment	w/d in unit	attached garage	no	no	no	2557
Miami	2	2.0	1106.0	apartment	w/d in unit	off-street parking	yes	yes	no	2241
Doral	3	2.0	0.0	apartment	w/d in unit	attached garage	no	no	no	3399
Doral	1	1.0	0.0	apartment	w/d in unit	attached garage	no	no	no	1978

```
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 1836 entries, 0 to 1835
```

```
Data columns (total 11 columns):
```

#	Column	Non-Null	Count	Dtype
0	neighborhood	1836	non-null	object
1	br	1836	non-null	int64
2	ba	1836	non-null	float64
3	sqft	1836	non-null	float64
4	housingType	1836	non-null	object
5	laundry	1836	non-null	object
6	parking	1836	non-null	object
7	cats	1836	non-null	object
8	dogs	1836	non-null	object
9	furnished	1836	non-null	object
10	rent	1836	non-null	int64

```
dtypes: float64(2), int64(2), object(7)
```

```
memory usage: 157.9+ KB
```

	br	ba	sqft	rent
count	1836.000000	1836.00000	1836.000000	1836.000000
mean	1.735294	1.69390	342.716231	2016.338235
std	0.774721	0.55118	538.560115	799.370174
min	0.000000	1.00000	0.000000	500.000000
25%	1.000000	1.00000	0.000000	1500.000000
50%	2.000000	2.00000	0.000000	1800.000000
75%	2.000000	2.00000	750.000000	2250.000000
max	5.000000	4.50000	2921.000000	4950.000000



Dataset 2: San Francisco Rental Listings

neighborhood	br	ba	sqft	housingType	laundry	parking	cats	dogs	furnished	rent
Sunset / Parkside	4	2.0	1600.0	apartment	laundry on site	street parking	no	no	no	4200
Lower Pac Hts	0	1.0	0.0	apartment	laundry in bldg	attached garage	no	no	no	2850
SOMA / South Beach	1	1.0	598.0	apartment	w/d in unit	detached garage	yes	yes	no	3431
Lower Pac Hts	1	1.0	915.0	apartment	w/d in unit	attached garage	no	no	no	3795
Ingleside / SFSU / CCSF	1	1.0	0.0	apartment	no laundry on site	street parking	no	no	no	2000

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 2596 entries, 0 to 2595
Data columns (total 11 columns):
#   Column              Non-Null Count  Dtype
---  -
0   neighborhood        2596 non-null   object
1   br                  2596 non-null   int64
2   ba                  2596 non-null   float64
3   sqft                2596 non-null   float64
4   housingType         2596 non-null   object
5   laundry             2596 non-null   object
6   parking             2596 non-null   object
7   cats                2596 non-null   object
8   dogs                2596 non-null   object
9   furnished           2596 non-null   object
10  rent                2596 non-null   int64
dtypes: float64(2), int64(2), object(7)
memory usage: 223.2+ KB
```

	br	ba	sqft	rent
count	2596.000000	2596.000000	2596.000000	2596.000000
mean	1.417951	1.211287	402.965331	3007.330123
std	1.095361	0.444560	508.831219	1187.119637
min	0.000000	1.000000	0.000000	650.000000
25%	1.000000	1.000000	0.000000	2190.000000
50%	1.000000	1.000000	0.000000	2795.000000
75%	2.000000	1.000000	750.000000	3688.500000
max	8.000000	4.000000	3700.000000	7995.000000

Preliminary Analysis




Heatmaps of Correlation Matrix and Scatter Plots to see if there's any obvious relationship between X variables and Rent Price

Machine Learning

Model Testing

Model Name	Data Processing	Model Parameters	Independent Variable(s) Used	RMSE	R2
LinearRegression()	80/20 train test split		sqft	\$3,286.06	0.22
LinearRegression() - Multiple	80/20 train test split		br, ba, sqft, housingType, laundry, parking, cats, dogs, furnished	\$3,285.83	0.72
RandomForestRegressor()	K-fold cross validation with cv = 10 (10 90/10 splits)	(n_estimators = 1000, random_state = 42, criterion = 'mse', bootstrap=True)	neighborhood, br, ba, sqft, housingType, laundry, parking, cats, dogs, furnished	\$579.54	0.7597
RandomForestRegressor()	RandomizedSearch CV param_distributions = {'bootstrap': [True, False], 'max_depth': [10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, None], 'max_features': ['auto', 'sqrt'], 'min_samples_leaf': [1, 2, 4], 'min_samples_split': [2, 5, 10], 'n_estimators': [200, 400, 600, 800, 1000, 1200, 1400, 1600, 1800, 2000]}	best_params = 'n_estimators': 600, 'min_samples_split': 5, 'min_samples_leaf': 1, 'max_features': 'sqrt', 'max_depth': 60, 'bootstrap': False	neighborhood, br, ba, sqft, housingType, laundry, parking, cats, dogs, furnished	\$567.28	0.7703

Findings



Questions?