
Introducción a ruby on rails

— Blackbox Texting —

Overview

- Concepto blackbox testing

Blackbox testing

- No nos interesa en qué está hecha la aplicación sino que tenga los resultados que esperamos.
- Combinando Rspec y Capybara se pueden hacer test muy intuitivos y expresivos.

Ejemplo

```
describe "Recipes App" do
  it "displays chocolate by default" do
    visit "/"
    expect(page).to have_content 'Chocolate Tea'
  end

  it "displays beef when keyword is beef" do
    visit "?keyword=beef"
    expect(page).to have_content 'Delicious Scalloped Potato'
  end
end
```



This repository

Search

Pull requests

Issues

Gist



jnicklas / capybara

Watch

244

Star

7,412

Fork

1,083

Code

Issues 11

Pull requests 5

Projects 0

Pulse

Graphs

Acceptance test framework for web applications <http://jnicklas.github.com/capybara/>

2,457 commits

61 branches

60 releases

213 contributors

MIT

Branch: master

New pull request

Create new file

Upload files

Find file

Clone or download



twalpole committed on GitHub Merge pull request #1784 from amatsuda/



...

Latest commit 374d113 5 days ago

.github

Add github issue template

2 months ago

.yard

Add custom yard extensions to the Gem

2 months ago

features

remove unneeded require

20 days ago

gemfiles

Update testing and travis matrix for selenium-webdriver 3.0 release

21 days ago

lib

! method redefined; discarding old reuse_server=

5 days ago

spec

optional clearing of local/session storage for selenium driver

11 days ago

.gitignore

Add .ruby-version and .ruby-gemset to .gitignore

3 years ago

.rspec

Added fuubar

6 years ago

<https://github.com/jnicklas/capybara>

rspec --init

FOLDERS

▼ ruby-on-rails-intro

▶ modulo-1

▶ modulo-2

▼ modulo-3

▶ practicas

▶ slides

▼ sources

▶ leccion-2

▶ leccion-7

▶ my_first_app

▼ spec

my_fist_app_spec.rb

spec_helper.rb

.rspec


.gitignore

LICENSE

README.md

```
1 --color
2 --require spec_helper
3 |
```

spec_helper



```
1 |require 'rspec'
2 |require 'capybara'
3 |require 'capybara/dsl'
4 |require 'capybara/poltergeist'
5
6 |Capybara.register_driver :selenium do |app|
7 |  Capybara::Selenium::Driver.new(app, browser: :chrome)
8 |end
9
10 |RSpec.configure do |config|
11 |  config.include Capybara::DSL
12 |end
13
```

Se incluye todo lo que necesitamos..

El RSpec debería incluir Capybara::DSL, un lenguaje que provee Capybara.


```
1 |Capybara.default_driver = :selenium
2 # Capybara.default_driver = :poltergeist
3
4 Capybara.app_host = "http://localhost:3000"
5
6 describe "Course App" do
7
8   describe "visit root" do
9     before { visit '/' }
10
11     it "displays 'Afrikaans' (default)" do
12       expect(page).to have_content 'Afrikaans'
13     end
14
15     it "displays table element that has a row with 2 columns" do
16       expect(page).to have_selector(:xpath, "//table//tr[count(td)=2]")
17     end
18   end
end
```

Tests

Pasos previos

```
gem install rspec
```

```
gem install selenium-webdriver
```

```
gem install capybara
```

```
gem install poltergeist
```

```
gem install chromedriver-helper
```

Ejecución

```
→ sources git:(master) ✕ rspec --format documentation
```

```
Course App
```

```
  visit root
```

```
    displays 'Afrikaans' (default)
```

```
    displays table element that has a row with 2 columns
```

```
  visit recipes
```

```
    displays 'Bacon Wrapped Jalapeno Popper Stuffed Chicken when text=chicken
```

```
    displays table element that has a row with 3 columns
```

```
    column 1 should have the thumbnail inside img tag
```

```
  visit recipes with search
```

```
    displays 'Cookie Monster cupcakes when text=chocolate
```

```
Finished in 18.22 seconds (files took 0.26456 seconds to load)
```

```
6 examples, 0 failures
```

Poltergeist

```
spec_helper.rb  x  my_fist_app_spec.rb  ●  
1  #Capybara.default_driver = :selenium  
2  | Capybara.default_driver = :poltergeist  
3  
4  Capybara.app_host = "http://localhost:3000"  
5  
6  describe "Course App" do  
7  
8    describe "visit root" do  
9      before { visit '/' }  
10  
11      it "displays 'Afrikaans' (default)" do  
12        expect(page).to have_content 'Afrikaans'  
13      end  
14
```

```
→ sources git:(master) ✕ rspec --format documentation
```

```
Course App
```

```
  visit root
```

```
You're running an old version of PhantomJS, update to >= 2.1.1 for a better experience.
```

```
    displays 'Afrikaans' (default)
```

```
    displays table element that has a row with 2 columns
```

```
  visit recipes
```

```
    displays 'Bacon Wrapped Jalapeno Popper Stuffed Chicken when text=chicken
```

```
    displays table element that has a row with 3 columns
```

```
    column 1 should have the thumbnail inside img tag
```

```
  visit recipes with search
```

```
    displays 'Cookie Monster cupcakes when text=chocolate
```

```
Finished in 15.75 seconds (files took 0.32054 seconds to load)
```

```
6 examples, 0 failures
```