

Chapter 5 Propeller shaft, drive shaft and universal joint - Posttest

Time:

04:15

Points:

9/10

Correct

1/1 Points

1

Talking about propeller shaft, which of the following sentence is incorrect?

The propeller shaft is constructed to produce relative rotation and relative translation (sliding).

The instantaneous angular velocities of two shafts on the same joint are different, but the instantaneous angular velocities at the two ends of the propeller shaft are the same.

On the shafts, there are dynamic balancing pads welded.

The type of propeller shaft with two halves connected by a slip joint does not need alignment marks because it is balanced.

Correct

1/1 Points

2

Talking about propeller shaft, which of the following sentence is incorrect?

The propeller shaft is constructed to produce relative rotation and relative translation (sliding).

Cardan universal joint use spider (cross shaft) and needle bearings.

On the shafts, there are dynamic balancing pads welded.

The type of propeller shaft with two halves connected by a slip joint does not need alignment marks because it is balanced.

Incorrect

0/1 Points

3

Regarding constant velocity joint, which of the following statements is incorrect?

To obtain constant velocity joint, the plane of force transfer between the two shaft ends of the joint must be the bisector of the angle formed by the centerlines of the two shafts.

Constant velocity joint should be specially lubricated with heat-resistant grease.

Constant velocity joints are wrapped in special rubber, heat resistant, good grease resistance.

Joints named Tripot are constant velocity joints.

Correct

1/1 Points

4

Regarding constant velocity joint, which of the following statements is incorrect?

To obtain constant velocity joint, the plane of force transfer between the two shaft ends of the joint must be the bisector of the angle formed by the centerlines of the two shafts.

Constant velocity joint should be specially lubricated with heat-resistant grease.

There is a synchronizer in constant velocity joint to equalize the two shaft speed.

Joints named Bendix-Weise, Bendix-Tracta are constant velocity joints.

Correct

1/1 Points

5

Regarding the functions of the propeller shaft and drive shaft, which of the following statements is not true?

These shafts are often used to transmit torque between two assemblies on the same housing (or frame).

These shafts transmit the torque between two assemblies with rotation relative to each other.

These shafts transmit the torque between the two assemblies with a large transmission angle.

These shafts transmit the torque between two assemblies with sliding motion relative to each other.

Correct

1/1 Points

6

Regarding the Cardan universal joint, which of the following statements is correct?

It is a torque transmission joint with different velocities of the two shafts of the same joint.

It is a torque transmission joint with different angular velocities of the two shafts of the same joint.

It is a torque transmission joints with different instantaneous angular velocities of the two shafts of the same joint.

Usually used on FF vehicles.

Correct

1/1 Points

7

Regarding the Cardan universal joint, which of the following statements is correct?

It is a torque transmission joint with the same velocities of the two shafts of the same joint.

It is a torque transmission joint with the same angular velocities of the two shafts of the same joint.

It is a torque transmission joints with the same instantaneous angular velocities of the two shafts of the same joint.

Usually used on FR vehicles.

Correct

1/1 Points

8

Regarding the hole for the needle bearing on the yokes of the Cardan universal joint, which of the following statements is correct?

The main purpose of large hole machining on yokes is to install needle ball bearings.

The main purpose of large hole machining on yokes is to assembly the cross shaft.

The main purpose of large hole machining on yokes is for installation snap ring easily.

The main purpose of large hole machining on yokes is to lighten the yokes.

Correct

1/1 Points

9

Regarding the spider in the tripod constant velocity joint, which of the following statements is correct?

The spider is threaded for fixation with driving yoke.

The spider is splined inside so that it can be slide relatively with driving yoke in operation.

The spider has construction that can be removed from the driving yoke so that when necessary, the rubber covering over the joints can be replaced.

The balls are fixed on the spider.

Correct

1/1 Points

10

Regarding the boot (rubber) covering outside the constant velocity joints, which of the following statements is correct?

The boot only has the role of blocking dust and dirt under the vehicle to protect joints.

The boot only has the role of preventing water from entering the joints.

The boot only has the role of keeping the amount of grease inside.

The boot has all the above roles and also has to work in the conditions of bending, torsion, and heat, so it requires to be made from good rubber material.

Go back to thank you page



This content is created by the owner of the form. The data you submit will be sent to the form owner. Microsoft is not responsible for the privacy or security practices of its customers, including those of this form owner. Never give out your password.

Microsoft Forms | AI-Powered surveys, quizzes and pollsCreate my own form

[Privacy and cookies](#) | [Terms of use](#)