

Chapter 6 Final gear, differential and axle shaft - Posttest

19:48


Chapter 6 Final gear, differential and axle shaft - Posttest

Hi, Pham. When you submit this form, the owner will see your name and email address.

1

Which of the following selections is the final gear in the figure?

(1 Point)



Single reduction bevel gear type final gear x

Single reduction spur (cylindrical) gear type final gear


Double reduction center type final gear

Double reduction side type final gear

2

Which of the following selections is the final gear in the figure?

(1 Point)



Single reduction bevel gear type final gear

Single reduction spur gear type final gear x


Double reduction center type final gear

Double reduction side type final gear

3

Which of the following selections is the final gear in the figure?

(1 Point)



Single reduction bevel gear type final gear

Single reduction spur gear type final gear


Double reduction center type final gear x

Double reduction side type final gear

4

Which of the following selections is the final gear in the figure?

(1 Point)



Single reduction bevel gear type final gear

Single reduction spur gear type final gear

Double reduction center type final gear

Double reduction side type final gear x

5

Where is the hypoid gear in the following figures?

(1 Point)

<https://hive.forms.usercontent.microsoft/images/06f1b89f-07e8-464f-b408-ec1b45703f31/46b30eca-1ac8-47e1-9b51-de26daa35e5b/T2RGU7YR8BCE88H52L346PJGBY/82b3a9f3-d2ae-4f42-835a-dbd0bc25527>

Figure a

Figure b x

Figure c

No figures at all.

6

Regarding the advantages of the hypoid gear, which of the following statements is not true?

(1 Point)

Has a higher gear ratio and contact ratio than a spiral bevel gear of the same size.

Minimize noise level at high speed.

Can help lower the vehicle's center of gravity while keeping the ground clearance.

Low cost. x

7

Regarding the disadvantages of the hypoid gear, which of the following statements is not true?

(1 Point)

Complicated manufacturing, requiring high assembly accuracy.

The longitudinal sliding along the tooth length in the meshing area increase.


Requires special lubricating oil

Does not help lower the vehicle's center of gravity. x

8

Through the layout of bearings, it is possible to evaluate which final gear in the figure has the greatest torque transmission capacity?

(1 Point)



Left figure

Middle figure

Right figure x

Both middle and right figure

9

Regarding the final gear, which of the following statements is not true?

(1 Point)

The pinion gear of the FR vehicle is usually arranged in cantilever beam type.

Pairs of two tapered roller bearings are usually arranged in an O letter-shape for better rigidity of the shaft. x

The double reduction final gear is designed for a large gear ratio with little impact on ground clearance.

The double reduction final gear has center type and side type.

10

Regarding the functions of differential, which of the following statements is not true?

(1 Point)

The differential is used to transmit torque to the drive wheels.

The differential is used to distribute torque to the drive wheels.

The differential is used to change the torque before it is transmitted to the drive wheels. x

The differential ensures that the drive wheels can rotate at different speeds.

11

Find the incorrect sentence in the following sentences? Bevel gear type final gears for FR vehicles are usually constructed to:

(1 Point)

Be able to adjust the preload of bearing.

Be able to adjust the backlash between pinion gear and ring gear.


Be able to adjust the vehicle's ground clearance. x

Be able to adjust the tooth contact pattern.

12

The figure show the construction of differential, choose the name for numbered part in the following table?

(5 Points)



	Pinion shaft	Differential pinion	Side gear	Differential case	Thrust washer
1	☐	☐	☐	☒	☐
2	☐	☐	☐	☐	☒
3	☐	☐	☒	☐	☐
4	☐	☒	☐	☐	☐
8	☒	☐	☐	☐	☐

13

In the final gear and differential unit, which of the following part meshinng with the ring gear?

(1 Point)

Planetary gear.

Differential case.

Side gear.

Pinion gear. x

14

In the final gear and differential unit of FR vehicle, which of the following part meshinng with the pinion gear?

(1 Point)

Haft shaft.

Side gear.

Ring gear. x

Differential case.

15

Which the following part constructed the final gear and differential of the FR vehicle, is directly related to the speed distribution operation.

(1 Point)

Driven gear (ring gear).

Final gear housing.

Side gear. x

Driving gear (pinion gear).

16

Talking about full floating rear axle shaft, which of the following sentences is incorrect?

(1 Point)

Normally, used for heavy trucks and buses.

Its construction make vehicle can support heavy load.


Rear axle shaft can be removed from axle housing without disassembly wheel.

Rear axle shaft both transmits torque to the drive wheels and support the load of vehicle. x

17

The following figure shows differential construction with locking differential, find the incorrect statement in the following sentences?

(1 Point)



When the one side drive wheel is spined, the differential must be locking differential.

Locking operation is possible when the wheels have come to a complete stop.

When locking, the driver act the differential lever, the lock shift lerver 3 push the sliding sleeve 5 into the teething ring 6 to lock the differential.

There is usually no locking differential indicator on the dashboard, so remember to unlock it after use. x

18

Choose a proper name for the axle shaft in figure a, b, c?

(3 Points)




Figure a

No floating axle shaft	Semi floating axle shaft (1/2 load)	Semi floating axle shaft (3/4 load)	Full floating axle shaft
Load increasing axle shaft			

Figure b

No floating axle shaft	Semi floating axle shaft (1/2 load)	Semi floating axle shaft (3/4 load)	Full floating axle shaft
Load increasing axle shaft			

Figure c

No floating axle shaft	Semi floating axle shaft (1/2 load)	Semi floating axle shaft (3/4 load)	Full floating axle shaft
Load increasing axle shaft			

19

Talking about semi floating axle shaft, which of the following sentences is correct?

(1 Point)

Normally, used for heavy trucks and buses.

In terms of construction, it is possible to make the vehicle withstand a bigger load than the fully floating axle shaft.

There is only one supporting bearing between the axle shaft and the axle housing. x

Axle shaft transmits torque to the drive wheel and support only a part of the vehicle's load.

20

Talking about full floating axle shaft, which of the following sentences is incorrect?

(1 Point)

Normally, used for heavy trucks and buses.

In terms of construction, it is possible to make the vehicle withstand a bigger load than other axle shaft.

The axle shaft can be pulled out without jacking up the axle or removing the wheels.

The end of axle shaft mounted with the hub has one supporting bearing. x

Submit



This content is created by the owner of the form. The data you submit will be sent to the form owner. Microsoft is not responsible for the privacy or security practices of its customers, including those of this form owner. Never give out your password.

Microsoft Forms | AI-Powered surveys, quizzes and pollsCreate my own form

[Privacy and cookies](#) | [Terms of use](#)