

INSTRUMENTS

- (7x) violins
- (4x) double bass
- (1x) clarinet
- (2x) flute
- (1x) electric bass
- (1x) drums
- (1x) keyboard
- (3x) horns
- (2x) trumpets
- (3x) trombone
- (1x) voice

MICROPHONES		
INSTRUMENT TYPE	MICROPHONE	CONNECTION TO D-RACK
VIOLINS	(7x) DPA 4099 core Violin	mini XLR + phantom adapter + XLR
DOUBLE BASS	(4x) KNA Pickups DB-1 Double Bass Pickup + (4x) Radial Engineering Pro 48 active DI Box	jack + DI Box + XLR
CLARINET	(1x) DPA 4099 Core Trumpet / Brass	mini XLR + phantom adapter + XLR
FLUTES	(2x) DPA 4099 Core Trumpet / Brass	mini XLR + phantom adapter + XLR
ELECTRIC BASS	(1x) Radial Engineering Pro 48 active DI Box	jack + DI Box + XLR
VOICE	(1x) Shure SM58	XLR
DRUMS	(1x) AKG D 112 MKII (for kick) + (1x) Shure SM57 (for snare) + (1x) Sennheiser e604 (for toms) + (1x) Rode NT5 (for overheads)	XLR
KEYBOARD	(1x) Radial Engineering Pro D2 passive Stereo DI Box	stereo jack + DI Box + (2x) XLR
TROMBONE	(3x) AKG C 519 ML	mini XLR + phantom adapter + XLR
HORNS	(3x) AKG C 519 ML	mini XLR + phantom adapter + XLR
TRUMPETS	(2x) AKG C 519 ML	mini XLR + phantom adapter + XLR

CONSOLE

CONSOLE SIGNAL CABLES

- optical fiber (from D-Rack to console)

DIGICO SD9	
CONNECTORS	The SD9's 8 mic inputs, 8 line outs, 4 mono AES/EBU, 1 MADI port, and two dedicated D-Rack Ports. Optical fiber connector: OpticalCon
D-RACK	D-Rack with 32-inputs and 8 outputs (extendable to 16). A second D-Rack can be connected for a total of 72 mic inputs.
DIMENSIONS	878mm (w) x 785mm (d) x 262mm (h)
WEIGHT	36kg (105kg with optional flightcase)
POWER	208W



Recommended installation: 1x unity around 20m from stage in the audience + D-Rack on stage

Recommended cable configuration: D-Rack receiving all mic lines on stage, sending optical fiber to console