

Week-8 Practical Student Records Application using Spring Boot and MongoDB [V. Siri Chandana , 2520090198]

To develop a Student Records REST API using Spring Boot, MongoDB, JWT Authentication, CRUD Operations, and Input Validation.

Spring Boot Application Running Successfully

```
2026-09-30T18:42:32.479+05:30 INFO 12212 --- [student-records]
[main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tom
cat started on port 8080 (http) with context path '/'
2026-09-30T18:42:32.486+05:30 INFO 12212 --- [student-records]
[main] c.e.s.StudentRecordsApplication : Sta
rted StudentRecordsApplication in 4.066 seconds (process running
for 4.735)
```

Registering the user:

```
PS C:\WINDOWS\system32> cd "C:\Users\DELL\OneDrive\Documents\S
DB&DBD\Practical\student-records\student-records"
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\
student-records> Invoke-RestMethod -Uri "http://localhost:8080/auth/register"
-Method POST -ContentType "application/json" -Body '{"username":"siri
chandana","email":"2520090198@klh.edu.in","password":"secret123"}'

message
-----
registered successfully
```

User Login and JWT Token Generation:

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> Invoke-RestMethod -Uri "http://localhost
:8080/auth/register" -Method POST -ContentType "application/json"
-Body '{"username":"siri chandana","email":"2520090198@klh.edu.in",
"password":"secret123"}'

message
-----
registered successfully
```

Saving the JWT Token:

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> $token = "eyJhbGciOiJIUzI1NiJ9.eyJzdWIi
OiJwcm15YW5rYSIsIm1hdCI6MTc5MDc..."
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> $headers = @{
>>     Authorization = "Bearer $token"
>> }

```

GET All Students Records:

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> Invoke-RestMethod -Uri "http://localhost:
8080/students/6ab0d6e94bd72bb2efd336e4" -Method GET -Headers $headers

id      : 6ab0d6e94bd72bb2efd336e4
name     : siri chandana
age      : 19
course   : CSIT
email    : 2520090198@klh.edu.in

```

Student Record Updated Successfully:

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> Invoke-RestMethod -Uri "http://localhost
:8080/auth/register" -Method POST -ContentType "application/json"
-Body '{"username":"siri chandana","email":"2520090198@klh.edu.in",
"password":"secret123"}'

message
-----
registered successfully

```

Test Validation: Student Input Validation and Error Handling

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students" -Method POST -Headers $headers -ContentType "application/json" -Body '{"name":"","age":10,"course":"","email":"wrong-email"}'
Invoke-RestMethod : The remote server returned an error: (400) Bad Request.
At line:1 char:1
+ Invoke-RestMethod -Uri "http://localhost:8080/students" -Method POST ...
+ ~~~~~
+ CategoryInfo          : InvalidOperation: (System.Net.HttpWebRequest:HttpWebRequest) [Invoke-RestMethod], WebException
+ FullyQualifiedErrorId : WebCmdletWebResponseException,Microsoft.PowerShell.Commands.InvokeRestMethodCommand

```

Student Records Stored in MongoDB

```

test> use student_records
switched to db student_records
student_records> show collections
students
users
student_records> db.students.find().pretty()
[
  {
    _id: ObjectId('6ab0d6e94bd72bb2efd336e4'),
    name: 'siri chandana',
    age: 19,
    course: 'CSIT',
    email: '2520090198@klh.edu.in',
    _class: 'com.example.student_records.entity.Student'
  }
]
student_records> |

```

Delete the student record

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students/6ab0d6e94bd72bb2efd336e4" -Method DELETE -Headers $headers

```

Output on PowerShell 1: [Student Record Deleted Successfully]

```
2026-09-30T20:41:01.852+05:30 INFO 14660 --- [student-records]
[nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Com
pleted initialization in 2 ms
JWT VALID
JWT VALID
```

Student data deletion verification

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students" -Method GET -Headers $headers
```

MongoDB Records After Deletion

```
test> use student_records
switched to db student_records
student_records> db.students.find().pretty()

student_records> exit
```

Folder Structure:

Week-8_Practical_Student_Records/

```
|
|
| └─ students-records
|
| └─ pom.xml
|
| └─ mvnw
|
| └─ mvnw.cmd
|
| └─ .mvn/
|
| └─ src/
|   | └─ main/
|   |   | └─ java/
|   |   |   | └─ com/
|   |   |   |   | └─ example/
|   |   |   |   |   | └─ student_records/
|   |   |   |   |   |   | └─ StudentRecordsApplication.java
|   |   |   |   |   |   |   | └─ controller/
|   |   |   |   |   |   |   |   | └─ dto/
|   |   |   |   |   |   |   |   |   | └─ entity/
```

```

| | | | └─ exception/
| | | | └─ repository/

| | | | └─ security/

| | | | └─ service/

| | | |

| | | └─ resources/

| | └─ application.properties

| |

| └─ target/

```

Codes:

1. Main Application

□ StudentRecordsApplication.java

```

package com.example.student_records;

import org.springframework.boot.SpringApplication; import
org.springframework.boot.autoconfigure.SpringBootApplication;
@SpringBootApplication public class
StudentRecordsApplication {

    public static void main(String[] args) {
        SpringApplication.run(StudentRecordsApplication.class, args);
    }

}

```

2. Entity

□ Student.java

```

package com.example.student_records.entity;

import org.springframework.data.annotation.Id;
import org.springframework.data.mongodb.core.mapping.Document;
@Document(collection="students") public
class Student {

```

@Id

```

        private String id;
        private String name;
private Integer age;
private String course;
private String email;
        public String getId() {
return id;
    }
    public void setId(String
id) {
        this.id = id;
    }
    public String
getName() {
        return
name;
    }
    public void setName(String
name) {
        this.name = name;
    }
    public Integer
getAge() {
        return age;
    }
    public void setAge(Integer
age) {
        this.age = age;
    }
    public String getCourse() {
return course;
    }
    public void setCourse(String
course) {
        this.course = course;
    }
    public String
getEmail() {
        return
email;
    }
    public void setEmail(String
email) {
        this.email = email;
    }
}

```

□ User.java

```

package com.example.student_records.entity;
import org.springframework.data.annotation.Id; import
org.springframework.data.mongodb.core.index.Indexed; import
org.springframework.data.mongodb.core.mapping.Document;

@Document(collection = "users") public
class User {
    @Id
    private String id;

    @Indexed(unique = true)
private String username;
    private String password;

```

```

        public String getId() {
return id;
        }
        public void setId(String
id) {
            this.id = id;
        }
        public String
getUsername() {
            return
username;
        }
        public void setUsername(String username) {
this.username = username;
        }
        public String
getPassword() {
            return
password;
        }
        public void setPassword(String password) {
this.password = password;
        }
    }
}

```

3. DTO

```

□ StudentRequest.java
package com.example.student_records.dto;
import jakarta.validation.constraints.Email;
import jakarta.validation.constraints.Min;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.NotNull;
public class StudentRequest {

    @NotBlank(message = "name is required")
private String name;

    @NotNull(message = "age is required")
    @Min(value = 16, message = "age must be at least 16")
private Integer age;

    @NotBlank(message = "course is required")
private String course;

    @NotBlank(message = "email is required")
    @Email(message = "a valid email is required")
private
String email;
    public String getName() {
return name;
    }
}

```

```
    }    public void setName(String
name) {    this.name = name;
    }
    public Integer getAge() {
return age;
    }    public void setAge(Integer
age) {    this.age = age;
    }    public String
getCourse() {    return
course;
    }    public void setCourse(String
course) {    this.course = course;
    }    public String
getEmail() {
```

```

        return email;
    }
    public void setEmail(String
email) {        this.email = email;
    }
}

```

□ RegisterRequest.java

```

package com.example.student_records.dto;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.Size;
public class RegisterRequest {

    @NotBlank    private
String username;

    @NotBlank
    @Size(min = 6, message = "password must be at least 6 characters")
private String password;
    public String getUsername() {
return username;
    }
    public void setUsername(String
username) {        this.username = username;
    }
    public String
getPassword() {        return
password;
    }
    public void setPassword(String
password) {        this.password = password;
    }
}

```

□ LoginRequest.java package

```

com.example.student_records.dto; import
jakarta.validation.constraints.NotBlank;

public class LoginRequest {

    @NotBlank    private
String username;

```

```

    @NotBlank    private
String password;

    public String getUsername() {
return username;
    }
    public void setUsername(String
username) {        this.username = username;
    }
    public String
getPassword() {        return
password;
    }
    public void setPassword(String
password) {        this.password = password;
    }
}

```

4. Repository

- StudentRepository.java

```

package com.example.student_records.repository;

import com.example.student_records.entity.Student; import
org.springframework.data.mongodb.repository.MongoRepository;
    public interface StudentRepository extends MongoRepository<Student,
String>
{
}

```

- UserRepository.java

```

package com.example.student_records.repository;
    import com.example.student_records.entity.User;
import org.springframework.data.mongodb.repository.MongoRepository;
    import java.util.Optional;
public interface
UserRepository extends
MongoRepository<User,
String> {
    Optional<User> findByUsername(String username); }

```

5. Service

□ StudentService.java

```
package com.example.student_records.service;

import com.example.student_records.dto.StudentRequest; import
com.example.student_records.entity.Student; import
com.example.student_records.repository.StudentRepository; import
org.springframework.stereotype.Service;

import java.util.List;
import java.util.Optional;

@Service public class
StudentService {

    private final StudentRepository repository;

    public StudentService(StudentRepository repository) {
this.repository = repository;
    }

    public Student
create(StudentRequest r) {

        Student s = new Student();

        apply(s, r);

        return repository.save(s);
    }

    public List<Student>
getAll() {
        return
repository.findAll();
    }

    public Optional<Student> getById(String
id) {
        return repository.findById(id);
    }

    public Optional<Student> update(String id, StudentRequest r) {
```

```

        return repository.findById(id).map(s -> {
            apply(s, r);
            return repository.save(s);
        });
    }
    public boolean delete(String
id) {
        if (!repository.existsById(id)) {
            return false;
        }
        repository.deleteById(id);
        return true;
    }
    private void apply(Student s,
StudentRequest r) {
        s.setName(r.getName());
        s.setAge(r.getAge());
        s.setCourse(r.getCourse());
        s.setEmail(r.getEmail());
    }
}

```

6. Controller

□ StudentController.java

```

package com.example.student_records.controller;

import com.example.student_records.dto.StudentRequest;
import com.example.student_records.entity.Student; import
com.example.student_records.service.StudentService;

import jakarta.validation.Valid;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;
import java.util.List;

@RestController
@RequestMapping("/students")
public class StudentController {
    private final StudentService service;

    public StudentController(StudentService service) {
        this.service = service;
    }
}

```

```

    }

    @PostMapping      public
    ResponseEntity<Student> create(
        @Valid @RequestBody StudentRequest r) {
        return ResponseEntity
            .status(201)
            .body(service.create(r));
    }

    @GetMapping      public
    List<Student> getAll() {
    return service.getAll();
    }

    @GetMapping("/{id}")      public
    ResponseEntity<Student> getById(
        @PathVariable String id) {
        return service.getById(id)
            .map(ResponseEntity::ok)
            .orElse(ResponseEntity.notFound().build());
    }

    @PutMapping("/{id}")
    public ResponseEntity<Student> update(
        @PathVariable String id,
        @Valid @RequestBody StudentRequest r) {
        return service.update(id, r)
            .map(ResponseEntity::ok)
            .orElse(ResponseEntity.notFound().build());
    }

    @DeleteMapping("/{id}")      public
    ResponseEntity<Void> delete(
        @PathVariable String id) {
        return service.delete(id)
            ? ResponseEntity.noContent().build()
            : ResponseEntity.notFound().build();
    }
}

```

□ AuthController.java

```
package com.example.student_records.controller;

import com.example.student_records.dto.LoginRequest; import
com.example.student_records.dto.RegisterRequest; import
com.example.student_records.entity.User; import
com.example.student_records.repository.UserRepository; import
com.example.student_records.security.JwtUtil;
import jakarta.validation.Valid;
import org.springframework.http.ResponseEntity;
import org.springframework.security.authentication.AuthenticationManager;
import
org.springframework.security.authentication.UsernamePasswordAuthenticationT
oken; import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.web.bind.annotation.*;
import java.util.Map;

@RestController
@RequestMapping("/auth") public
class AuthController {

    private final UserRepository users;
    private final PasswordEncoder encoder;
    private final AuthenticationManager manager;
    private final JwtUtil jwt;

    public AuthController(
        UserRepository users,
        PasswordEncoder encoder,
        AuthenticationManager manager,
        JwtUtil jwt) {

        this.users = users;
        this.encoder = encoder;
        this.manager = manager;        this.jwt
        = jwt;
    }

    @PostMapping("/register")
    public ResponseEntity<?> register(
        @Valid @RequestBody RegisterRequest r) {
        if (users.findByUsername(r.getUsername()).isPresent()) {
            return ResponseEntity
                .badRequest()
                .body(Map.of(
                    "error",
```

```

        "username already taken"
    ));
}

User user = new User();
user.setUsername(r.getUsername());
user.setPassword(
encoder.encode(r.getPassword())
);
users.save(user);
return ResponseEntity
.status(201)
    .body(Map.of(
        "message",
        "registered successfully"
    ));
}

@PostMapping("/login")
public ResponseEntity<?> login(
    @Valid @RequestBody LoginRequest r) {

    manager.authenticate(
        UsernamePasswordAuthenticationToken(
            r.getUsername(),
            r.getPassword()
        )
    );
    return ResponseEntity.ok(
        Map.of(
            "token",

```

```

        jwt.generateToken(r.getUsername())
    )
    );
}
}

```

7. Security

□ SecurityConfig.java

```

package com.example.student_records.security;

import org.springframework.context.annotation.Bean; import
org.springframework.context.annotation.Configuration;
import org.springframework.security.authentication.AuthenticationManager;
import
org.springframework.security.config.annotation.authentication.configuration
.AuthenticationConfiguration;
import
org.springframework.security.config.annotation.web.builders.HttpSecurity;
import org.springframework.security.config.http.SessionCreationPolicy;
import org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder;
import org.springframework.security.crypto.password.PasswordEncoder;
import org.springframework.security.web.SecurityFilterChain;
import
org.springframework.security.web.authentication.UsernamePasswordAuthenticat
ionFilter;

```

@Configuration

```

public class SecurityConfig {

    private final JwtAuthFilter jwtAuthFilter;

    public SecurityConfig(JwtAuthFilter jwtAuthFilter) {
this.jwtAuthFilter = jwtAuthFilter;
    }

    @Bean    public PasswordEncoder
passwordEncoder() {        return new
BCryptPasswordEncoder();
    }

    @Bean
    public AuthenticationManager authenticationManager(
AuthenticationConfiguration        configuration)
throws Exception {
        return configuration.getAuthenticationManager();
    }
}

```

```

    }
    @Bean
    public SecurityFilterChain filterChain(
        HttpSecurity http) throws Exception
    {
        return http
            .csrf(csrf -> csrf.disable())
            .sessionManagement(session ->
session.sessionCreationPolicy(
                SessionCreationPolicy.STATELESS
            )
        )

        .authorizeHttpRequests(auth ->
auth
            .requestMatchers("/auth/**")
            .permitAll()

            .anyRequest()
            .authenticated()
        )

        .addFilterBefore(
jwtAuthFilter,
            UsernamePasswordAuthenticationFilter.class
        )

        .build();
    }
}

```

□ JwtUtil.java

```

package com.example.student_records.security;

import io.jsonwebtoken.*;
import io.jsonwebtoken.security.Keys;
import org.springframework.beans.factory.annotation.Value;
import org.springframework.stereotype.Component;
import javax.crypto.SecretKey; import
java.nio.charset.StandardCharsets; import
java.util.Date;

```

```

@Component public
class JwtUtil {

    @Value("${jwt.secret}")
    private String secret;

    @Value("${jwt.expiration-ms}")
    private long expirationMs;

    private SecretKey key() {
        return Keys.hmacShaKeyFor(
secret.getBytes(StandardCharsets.UTF_8)
        );
    }

    public String generateToken(String
username) {

        Date now = new Date();
        return Jwts.builder()
.setSubject(username)
.setIssuedAt(now)
.setExpiration(
+ expirationMs)
        )
        .signWith(key(), SignatureAlgorithm.HS256)
        .compact();
    }

    public String extractUsername(String
token) {

        return Jwts.parserBuilder()
.setSigningKey(key())
        .build()
        .parseClaimsJws(token)
        .getBody()
        .getSubject();
    }

    public boolean isValid(String
token) {

```

```

        try {

            Jwts.parserBuilder()
                .setSigningKey(key())
                .build()
                .parseClaimsJws(token);
            return true;

        } catch (JwtException | IllegalArgumentException e) {
            return false;
        }
    }
}

```

□ JwtAuthFilter.java

```

package com.example.student_records.security;
import jakarta.servlet.*;
import jakarta.servlet.http.*;
import
org.springframework.security.authentication.UsernamePasswordAuthenticationToken;
import
org.springframework.security.core.context.SecurityContextHolder;
import
org.springframework.security.core.userdetails.UserDetailsService;
import
org.springframework.security.web.authentication.WebAuthenticationDetailsSource;
import org.springframework.stereotype.Component;
import org.springframework.web.filter.OncePerRequestFilter;
import java.io.IOException;

@Component public class JwtAuthFilter extends
OncePerRequestFilter {

    private final JwtUtil jwtUtil;
    private final UserDetailsService userDetailsService;

    public JwtAuthFilter(
        JwtUtil jwtUtil,
        UserDetailsService userDetailsService) {
        this.jwtUtil = jwtUtil;
        this.userDetailsService =
userDetailsService;
    }
}

```

```

@Override
protected void doFilterInternal(
HttpServletRequest request,
        HttpServletResponse response,
FilterChain chain) throws
ServletException, IOException {
    String header = request.getHeader("Authorization");
    if (header != null && header.startsWith("Bearer ")) {
        String token = header.substring(7);
        if (jwtUtil.isValid(token)) {

            System.out.println("JWT VALID");
            String username =
jwtUtil.extractUsername(token);
            var details =
userService.loadUserByUsername(username);
            var authentication = new
UsernamePasswordAuthenticationToken(
details, null,
details.getAuthorities()
        );
            authentication.setDetails(
                new WebAuthenticationDetailsSource()
                    .buildDetails(request)
            );

            SecurityContextHolder
                .getContext()
                .setAuthentication(authentication);
        } else {

            System.out.println("JWT INVALID");
        }
    }

    chain.doFilter(request, response);
}
}

```

□ CustomUserDetailsService.java

```
package com.example.student_records.security;
```

```

import com.example.student_records.repository.UserRepository;
import org.springframework.security.core.userdetails.*;
import org.springframework.stereotype.Service;
@Service public class CustomUserDetailsService implements
UserDetailsService {
    private final UserRepository userRepository;
    public CustomUserDetailsService(UserRepository userRepository) {
this.userRepository = userRepository;
    }

    @Override    public UserDetails
loadUserByUsername(String username)                throws
UsernameNotFoundException {
        var user = userRepository
            .findByUsername(username)                .orElseThrow(()
->                new UsernameNotFoundException("User not
found"));

        return User.withUsername(user.getUsername())
            .password(user.getPassword())
            .authorities("USER")
            .build();
    }
}

```

8. Exception Handling

□ GlobalExceptionHandler.java

```

package com.example.student_records.exception;

import org.springframework.http.ResponseEntity; import
org.springframework.web.bind.MethodArgumentNotValidException;

```

```

import org.springframework.web.bind.annotation.ExceptionHandler; import
org.springframework.web.bind.annotation.RestControllerAdvice;
import java.util.HashMap;
import java.util.Map;
@RestControllerAdvice public class
GlobalExceptionHandler {

    @ExceptionHandler(MethodArgumentNotValidException.class)
    public ResponseEntity<Map<String, Object>> handleValidation(
        MethodArgumentNotValidException ex) {

        Map<String, String> errors = new HashMap<>();
        ex.getBindingResult()
            .getFieldErrors()
            .forEach(error ->
                errors.put(
                    error.getField(),
                    error.getDefaultMessage()
                )
            );

        Map<String, Object> body = new HashMap<>();
        body.put("error", "VALIDATION_ERROR");
        body.put("details", errors);
        return ResponseEntity.badRequest().body(body);
    }
}

```

9. Configuration application.properties

```

spring.application.name=student-records
spring.data.mongodb.uri=mongodb://localhost:27017/student_records

jwt.secret=replace-this-with-a-long-random-secret-at-least-32-characters

jwt.expiration-ms=3600000
server.port=8080

```

10. Maven Configuration

□ pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">

    <modelVersion>4.0.0</modelVersion>

    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.5.6</version>
        <relativePath/>
    </parent>

    <groupId>com.example</groupId>
    <artifactId>student-records</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>student-records</name>
    <description>Student Records Application</description>
    <properties>
        <java.version>17</java.version>
    </properties>

    <dependencies>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-data-mongodb</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-validation</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-security</artifactId>
        </dependency>

    </dependencies>

</project>
```

```
<dependency>
  <groupId>io.jsonwebtoken</groupId>
  <artifactId>jjwt-api</artifactId>
  <version>0.11.5</version>
</dependency>

<dependency>
  <groupId>io.jsonwebtoken</groupId>
  <artifactId>jjwt-impl</artifactId>
  <version>0.11.5</version>
  <scope>runtime</scope>
</dependency>

<dependency>
  <groupId>io.jsonwebtoken</groupId>
  <artifactId>jjwt-jackson</artifactId>
  <version>0.11.5</version>
  <scope>runtime</scope>
</dependency>

<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-test</artifactId>
  <scope>test</scope>
</dependency>

</dependencies>

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
    </plugin>
  </plugins>
</build>
</project>
```