

WEEK-9

[V. Siri Chandana , 2520090198]

BOOKFLOW LIBRARY SYSTEM

Transactional Microservice using Spring Boot, Spring Data JPA and PostgreSQL

To develop a transactional BookFlow Library microservice using Spring Boot, Spring Data JPA and PostgreSQL for managing book inventory and borrowing orders, with FastAPI Gateway integration.

Database – bookflow creation in Postgresql

```
postgres=# CREATE DATABASE bookflow;
CREATE DATABASE
postgres=# \c bookflow
You are now connected to database "bookflow" as user "postgres".
bookflow=# \dt
Did not find any tables.
```

Tables Inserted


```
bookflow=# \dt
List of tables
Schema | Name      | Type  | Owner
-----+-----+-----+-----
public | inventory | table | postgres
public | orders    | table | postgres
(2 rows)
```

Initial Inventory Data in PostgreSQL

```
bookflow=# INSERT INTO inventory
bookflow-# (book_id, total_stock, available_stock)
bookflow-# VALUES
bookflow-# (101, 5, 5),
bookflow-# (102, 3, 3),
bookflow-# (103, 2, 0);
INSERT 0 3
bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock
-----+-----+-----
    101  |                5 |          5
    102  |                3 |          3
    103  |                0 |          2
(3 rows)
```

GET Inventory for Book 101

```
2026-10-01T12:02:30.250+05:30 INFO 23396 --- [demo] [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 1 ms
Hibernate:
    select
        i1_0.book_id,
        i1_0.available_stock,
        i1_0.total_stock
    from
        inventory i1_0
    where
        i1_0.book_id=?
```



localhost:8080/inventory/101

Pretty print ☒

```
{
  "bookId": 101,
  "totalStock": 5,
  "availableStock": 5
}
```

Successful Book Borrowing — POST /orders

POST http://localhost:8080/orders

Docs Params Authorization Headers 8 Body Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ G

```
1 {
2   "userId": 501,
3   "bookId": 101
4 }
```

Body Cookies Headers 5 Test Results

{ } JSON Preview Visualize

```
1 {
2   "id": 1,
3   "userId": 501,
4   "bookId": 101,
5   "status": "BORROWED"
6 }
```

GET /inventory/101 — Inventory After Book Borrowing

```
Hibernate:
select
  i1_0.book_id,
  i1_0.available_stock,
  i1_0.total_stock
from
  inventory i1_0
where
  i1_0.book_id=?
```

< > ↺ ⓘ localhost:8080/inventory/101

Pretty print ☒

```
{
  "bookId": 101,
  "totalStock": 5,
  "availableStock": 4
}
```

PostgreSQL Database — Inventory and Order Records After Borrowing

```
bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock
-----+-----+-----
      101 |              5 |          5
      102 |              3 |          3
      103 |              0 |          2
(3 rows)

bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock
-----+-----+-----
      102 |              3 |          3
      103 |              0 |          2
      101 |              4 |          5
(3 rows)

bookflow=# SELECT * FROM orders;
 id | book_id | status  | user_id
----+-----+-----+-----
   1 |     101 | BORROWED |      501
(1 row)
```

POST /orders — Out-of-Stock Book Returns 409 Conflict

KAMTAM PRIYANKA's Workspace

POST http://localhost:8080/orders


Body

```
{
  "userId": 502,
  "bookId": 103
}
```

Book out of stock

JSON

```
{
  "message": "Book 103 is out of stock",
  "status": 409,
  "error": "OUT_OF_STOCK"
}
```



PostgreSQL — Final Inventory and Order Records

```
bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock 
-----+-----+-----
    102  |               3 |           3
    103  |               0 |           2
    101  |               3 |           5
(3 rows)
```

```
bookflow=# SELECT * FROM orders;
 id | book_id | status  | user_id 
----+-----+-----+-----
  1 |    101 | BORROWED |    501
  2 |    101 | BORROWED |    501
(2 rows)
```

Folder Structure: bookflow-transaction/

|

```
├─ pom.xml
|
└─ src/
    └─ main/
        └─ java/
            └─ com/
                └─ bookflow/
                    └─ transaction/
                        └─ BookflowTransactionApplication.java
                        └─ controller/
                            └─ OrderController.java
                            └─ InventoryController.java
                        └─ entity/
                            └─ Inventory.java
                            └─ Order.java
                        └─ repository/
                            └─ InventoryRepository.java
                            └─ OrderRepository.java
                        └─ service/
                            └─ InventoryService.java
                            └─ OrderService.java
                        └─ dto/
                            └─ OrderRequest.java
```

```

|      |
|      └─ exception/
|          └─ BookOutOfStockException.java
|          └─ GlobalExceptionHandler.java
|
└─ resources/
└─ application.yml

```

Codes:

□ pom.xml

```

<?xml version="1.0" encoding="UTF-8"?> <project
xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">

    <modelVersion>4.0.0</modelVersion>

    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.5.5</version>
        <relativePath/>
    </parent>

    <groupId>com.bookflow</groupId>
    <artifactId>bookflow-transaction</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>bookflow-transaction</name>
    <description>BookFlow Transactional Microservice</description>
    <properties>
        <java.version>17</java.version>
    </properties>

    <dependencies>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>

```

```
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-data-jpa</artifactId>
</dependency>

<dependency>
  <groupId>org.postgresql</groupId>
  <artifactId>postgresql</artifactId>
  <scope>runtime</scope>
</dependency>

<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-validation</artifactId>
</dependency>

<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-test</artifactId>
  <scope>test</scope>
</dependency>

</dependencies>

<build>
  <plugins>
    <plugin>
```

```

    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-maven-plugin</artifactId>
    <configuration>
        <mainClass>com.bookflow.transaction.BookflowTransactionApplication<
/ma inClass>
    </configuration>
</plugin>
    </plugins>
</build>

</project>

```

□ application.yml

```

spring:
datasource:
    url: jdbc:postgresql://localhost:5432/bookflow
username: postgres    password: UR_PASSWORD
    jpa:
hibernate:
    ddl-auto: update
show-sql: true
properties:
hibernate:
    format_sql: true
server:
port: 8080

```

- BookflowTransactionApplication.java

```
package com.bookflow.transaction;
```

```

import org.springframework.boot.SpringApplication; import
org.springframework.boot.autoconfigure.SpringBootApplication;
@SpringBootApplication public class
BookflowTransactionApplication {

    public static void main(String[] args) {
        SpringApplication.run(BookflowTransactionApplication.class, args);
    } }

```

- Inventory.java

```

package com.bookflow.transaction.entity;

import jakarta.persistence.Entity; import
jakarta.persistence.Id; import
jakarta.persistence.Table; import
jakarta.validation.constraints.Min;

@Entity
@Table(name = "inventory") public
class Inventory {

    @Id    private Long
bookId;

    @Min(value = 0, message = "Total stock cannot be negative")
private Integer totalStock;

    @Min(value = 0, message = "Available stock cannot be negative")
private Integer availableStock;

    public Inventory() {
    }    public Inventory(Long bookId, Integer totalStock, Integer
availableStock)
{
    this.bookId = bookId;
this.totalStock = totalStock;
this.availableStock = availableStock;
}
    public Long getBookId() {
return bookId;
    }    public void setBookId(Long
bookId) {    this.bookId = bookId;
    }    public Integer
getTotalStock() {    return
totalStock;
    }    public void setTotalStock(Integer
totalStock) {    this.totalStock = totalStock;
    }

    public Integer getAvailableStock() {
return availableStock;
    }    public void setAvailableStock(Integer
availableStock) {    this.availableStock = availableStock;
    } }

```

□ Order.java

```

package com.bookflow.transaction.entity;

```

```
import jakarta.persistence.Entity; import
jakarta.persistence.GeneratedValue; import
jakarta.persistence.GenerationType; import
jakarta.persistence.Id; import
jakarta.persistence.Table;
```

```
@Entity
```

```
@Table(name = "orders") public
class Order {
```

```
    @Id
```

```
    @GeneratedValue(strategy = GenerationType.IDENTITY)
```

```
private Long id;
```

```
    private Long userId;
```

```
private Long bookId;
```

```
private String status;
```

```
    public Order() {
```

```
    }
```

```
    public Order(Long userId, Long bookId, String status) {
```

```
this.userId = userId;        this.bookId = bookId;
```

```
this.status = status;
```

```
    }
```

```
    public Long getId() {
```

```
return id;
```

```
    }
```

```
    public void setId(Long
```

```
id) {        this.id = id;
```

```
    }
```

```

        public Long getUserId() {
            return userId;
        }
        public void setUserId(Long
userId) {            this.userId = userId;
        }
        public Long
getBookId() {            return
bookId;
        }
        public void setBookId(Long
bookId) {            this.bookId = bookId;
        }
        public String
getStatus() {            return
status;
        }
        public void setStatus(String
status) {            this.status = status;
        }
    }
}

```

- InventoryRepository.java

```

package com.bookflow.transaction.repository;

import com.bookflow.transaction.entity.Inventory;
import org.springframework.data.jpa.repository.JpaRepository;

public interface InventoryRepository extends JpaRepository<Inventory, Long> {
}

```

- OrderRepository.java

```

package com.bookflow.transaction.repository;

import com.bookflow.transaction.entity.Order; import
org.springframework.data.jpa.repository.JpaRepository;

public interface OrderRepository extends JpaRepository<Order, Long> {
}

```

- OrderRequest.java

```

package com.bookflow.transaction.dto;

import jakarta.validation.constraints.NotNull;

public class OrderRequest {

```

```

@NotNull
private Long userId;

@NotNull
private Long bookId;
public Long getUserId() {
return userId;
}
public void setUserId(Long
userId) {
this.userId = userId;
}
public Long
getBookId() {
return
bookId;
}
public void setBookId(Long
bookId) {
this.bookId = bookId;
} }

```

□ InventoryService.java

```

package com.bookflow.transaction.service;

import com.bookflow.transaction.entity.Inventory; import
com.bookflow.transaction.repository.InventoryRepository; import
org.springframework.stereotype.Service;
@Service public class
InventoryService {

    private final InventoryRepository inventoryRepository;
    public InventoryService(InventoryRepository inventoryRepository) {
this.inventoryRepository = inventoryRepository;
    }

    public Inventory getInventory(Long bookId) {
        return inventoryRepository.findById(bookId)
            .orElseThrow(() -> new RuntimeException("Book not found"));
    }
}

```

□ OrderService.java

```

package com.bookflow.transaction.service;

import com.bookflow.transaction.dto.OrderRequest; import
com.bookflow.transaction.entity.Inventory; import
com.bookflow.transaction.entity.Order; import

```

```

com.bookflow.transaction.exception.BookOutOfStockException; import
com.bookflow.transaction.repository.InventoryRepository; import
com.bookflow.transaction.repository.OrderRepository; import
org.springframework.stereotype.Service; import
org.springframework.transaction.annotation.Transactional;

@Service public class
OrderService {

    private final InventoryRepository inventoryRepository;
    private final OrderRepository orderRepository;

    public OrderService(
        InventoryRepository inventoryRepository,
        OrderRepository orderRepository) {
        this.inventoryRepository
        = inventoryRepository;
        this.orderRepository =
        orderRepository;
    }

    @Transactional
    public Order borrowBook(OrderRequest request) {

        Inventory inventory =
        inventoryRepository.findById(request.getBookId())
            .orElseThrow(() -> new RuntimeException("Book not found"));

        if (inventory.getAvailableStock() <= 0) {
            throw new BookOutOfStockException(
                "Book " + request.getBookId() + " is out of stock");
        }
        inventory.setAvailableStock(
        inventory.getAvailableStock() - 1);
        inventoryRepository.save(inventory);
    }
}

```

```

        Order order = new Order(
request.getUserId(),
request.getBookId(),
        "BORROWED");
        return orderRepository.save(order);
    } }

```

□ InventoryController.java

```

package com.bookflow.transaction.controller;

import com.bookflow.transaction.entity.Inventory; import
com.bookflow.transaction.service.InventoryService; import
org.springframework.web.bind.annotation.*;

@RestController
@RequestMapping("/inventory") public
class InventoryController {
    private final InventoryService inventoryService;
    public InventoryController(InventoryService inventoryService) {
this.inventoryService = inventoryService;
    }

    @GetMapping("/{bookId}")    public Inventory
getInventory(@PathVariable Long bookId) {        return
inventoryService.getInventory(bookId);
    } }

```

□ OrderController.java

```

package com.bookflow.transaction.controller;

import com.bookflow.transaction.dto.OrderRequest;
import com.bookflow.transaction.entity.Order; import
com.bookflow.transaction.service.OrderService; import
jakarta.validation.Valid; import
org.springframework.http.HttpStatus; import
org.springframework.web.bind.annotation.*;

@RestController
@RequestMapping("/orders") public
class OrderController {
    private final OrderService
orderService;

```

```

    public OrderController(OrderService orderService) {
this.orderService = orderService;
    }

    @PostMapping
    @ResponseStatus(HttpStatus.CREATED)    public Order
borrowBook(@Valid @RequestBody OrderRequest request) {        return
orderService.borrowBook(request);
    } }

```

- BookOutOfStockException.java

```

package com.bookflow.transaction.exception;

public class BookOutOfStockException extends RuntimeException {
    public BookOutOfStockException(String message) {
super(message);
    } }

```

- GlobalExceptionHandler.java

```

package com.bookflow.transaction.exception;

import org.springframework.http.HttpStatus;
import org.springframework.web.bind.annotation.*;

import java.util.Map;

@RestControllerAdvice public class
GlobalExceptionHandler {

    @ExceptionHandler(BookOutOfStockException.class)
    @ResponseStatus(HttpStatus.CONFLICT)
    public Map<String, Object> handleOutOfStock(
        BookOutOfStockException ex) {
        return Map.of(
            "status", 409,
            "error", "OUT_OF_STOCK",
            "message", ex.getMessage()
        );
    }
}

```

□ gateway.py — FastAPI gateway

```
from fastapi import FastAPI
import httpx app =
FastAPI()
```

```
SPRING_SERVICE = "http://localhost:8080"
```

```
@app.post("/gateway/orders") async def
create_order(order: dict):    async with
httpx.AsyncClient() as client:
response = await client.post(
f"{SPRING_SERVICE}/orders",
json=order    )    return
response.json()
```